

Part Number: 6307UE



Security & Sound, #18-9c, BC, CMP

Product Description

Security & Sound Cable, Plenum-CMP 9-18 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material No. of Conductors 18 7x26 BC - Bare Copper 9 Conductor Count: 9 Conductor Size: 18 AWG

Insulation

Material	Material Trade Name	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.009 in

Color Chart



Outer Shield Material



Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.262 in	0.015 in	Yes

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 6.5 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor
30 pF/ft
Shielding: Unshielded

Current

Max. Recommended Current [A] 3.5 Amps per conductor @ 25°C A

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

Operating Temp Range:	0°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	64.1 lbs/1000ft
Max Recommended Pulling Tension:	201.6 lbs
Min Bend Radius/Minor Axis:	2.6 in

Standards

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262 Plenum Flame Test (UL910)
CSA Flammability:	FT6
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N): Yes	
-------------------	--

Part Number

Non-Plenum Number:	5307UE	

Variants

Item #	Color Footn
6307UE 8771000	Natural C
Footnote:	

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.