



AW5500C

Industrial Wireless Access Point

User's Manual



v.1.1
May 2017

Important Announcement

The information contained in this document is the property of Atop Technologies, Inc., and is supplied for the sole purpose of operation and maintenance of Atop Technologies, Inc. products. No part of this publication is to be used for any other purposes, and it is not to be reproduced, copied, disclosed, transmitted, stored in a retrieval system, or translated into any human or computer language, in any form, by any means, in whole or in part, without the prior explicit written consent of Atop Technologies, Inc., offenders will be liable for damages. All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Disclaimer

We have checked the contents of this manual for agreement with the hardware and software described. Since deviations cannot be precluded entirely, we cannot guarantee full agreement. However, the data in this manual is reviewed regularly and any necessary corrections included in subsequent editions. Suggestions for improvement are welcome. All other product names referenced herein are registered trademarks of their respective companies.

Published by

Atop Technologies, Inc.

2F, No. 146, Sec. 1, Tung-Hsing Rd.

Jubei, Hsinchu 30261

Taiwan, R.O.C.

Tel: 886-3-5508137

Fax: 886-3-5508131

www.atop.com.tw

www.atoponline.com

Copyright © 2017 Atop Technologies, Inc. All rights reserved. Technical data is subject to change. All other product names referenced herein are registered trademarks of their own respective companies.

Contents

1	Preface	1
2	Introduction.....	5
2.1	Product Overview.....	5
2.2	Features	6
3	Getting Started.....	7
3.1	Inside the Package	7
3.2	Front & Power Panels	8
3.3	First Time Installation	10
3.4	Finding the Device	11
3.5	Factory Default Settings.....	13
4	Web Console Configuration	17
4.1	Overview Information	17
4.2	User Interface Overview	17
4.3	Secure Wireless Network	19
4.4	Wireless Settings	19
4.4.1	Wizard.....	20
4.4.2	Basic Settings	20
4.4.3	Security Settings	28
4.4.4	WPS Settings.....	34
4.4.5	WDS Settings.....	35
4.4.6	Advanced Settings	36
4.4.7	Wireless Scheduler Settings.....	38
4.5	Network Settings	41
4.6	SNMP Settings.....	42
4.7	Email Settings.....	44
4.8	DHCP Server	45
4.9	Firewall & Filtering	47
4.9.1	Wired MAC Filtering.....	48
4.9.2	Wireless MAC Filtering	49
4.9.3	Ethernet Type Filtering.....	50
4.9.4	IP Filtering.....	51

4.9.5	Management List	52
4.10	System Log	53
4.10.1	Syslog	53
4.10.2	Event Log	54
4.11	System Setup.....	55
4.11.1	Admin Settings.....	55
4.11.2	Date/Time Settings	56
4.11.3	Alert Event	57
4.11.4	Firmware Upgrade	58
4.11.5	Backup & Restore Configuration	59
4.12	System Status.....	60
4.12.1	System Information	60
4.12.2	Site Monitor	61
4.12.3	Wireless Client Table	63
4.12.4	Traffic Log & Statistics	64
4.12.5	DHCP Status.....	65
4.12.6	Ping.....	66
4.13	Reboot and Restore Default Settings	67
5	Operation Modes	68
5.1	Regular AP Mode.....	68
5.2	WDS Bridge Mode	71
5.3	AP Client Mode	75
6	Applications	77
6.1	Basic Access Point Setup	77
6.2	Basic WDS Setup	78
6.3	Coverage Range Extender Setup	79
6.4	AP Client Setup	80
6.5	P2P Button (External Physical WPS button)	81
7	Specifications	84
7.1	Hardware Specifications	84
7.2	Software Specifications.....	94
7.3	LED Indicators	95

8	Emergency System Recovery	97
9	Warranty	99

1 Preface

Purpose of the Manual

This manual supports you during the installation and configuring of the AW5500C Industrial Wireless Access Point only, as well as it explains some technical options available with the mentioned product. As such, it contains some advanced network management knowledge, instructions, examples, guidelines and general theories designed to help users manage this device and its corresponding software; a background in general theory is a must when reading it. Please refer to the Glossary for technical terms and abbreviations (if any).

Who Should Use This User Manual

This manual is to be used by qualified network personnel or support technicians who are familiar with network operations; it might be useful for system programmers or network planners as well. This manual also provides helpful and handy information for first time users. For any related problems please contact your local distributor, should they be unable to assist you, please redirect your inquiries via www.atop.com.tw or www.atoponline.com

Supported Platform

This manual is designed for the AW5500C Industrial Wireless Access Point and that model only.

Warranty Period

We provide a **5 year limited warranty** for AW5500C Industrial Wireless Access Point.

Manufacturers Federal Communication Commission Declaration of Conformity Statement

Model: AW5500C

NOTE: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. This device and its antenna(s) must not be co-located or operating in conjunction with any other antenna or transmitter.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

For product available in the USA/Canada market, only channel 1~11 can be operated. Selection of other channels is not possible.

FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator & your body.

European Community, Switzerland, Norway, Iceland, and Liechtenstein

Model: AW5500C

Declaration of Conformity with regard to the R&TTE Directive 1999/5/EC

This equipment is in compliance with the essential requirements and other relevant provisions of 1999/5/EC.

The following standards were applied:

EMC	EN 301.489-1 v1.4.1; EN 301.489-17 v1.2.1
Health & Safety	EN60950-1: 2001; EN 50385: 2002
Radio	EN 300 328 v 1.7.1; EN 301.893 v 1.5.1

The conformity assessment procedure referred to in Article 10.4 and Annex III of Directive 1999/5/EC has been followed.

Note: This equipment is intended to be used in all EU and EFTA countries. Outdoor use may be restricted to certain frequencies and/or may require a license for operation. For more details, contact Atop Technical Support.

European Union

This system has been evaluated for RF exposure for humans in reference to the ICNIRP (International Commission on Non-Ionizing Radiation Protection) limits. The evaluation was based on the EN 50385 Product Standard to Demonstrate Compliance of Radio Base stations and Fixed Terminals for Wireless Telecommunications Systems with basic restrictions or reference levels related to Human Exposure to Radio Frequency Electromagnetic Fields from 300 MHz to 40 GHz. The minimum separation distance from the antenna to a general bystander is 20 cm (7.9 inches).

UL Notice for Power supplier

The AW5500C series products are intended to be supplied by a Listed Power Unit marked with a "LPS" (Limited Power Source), or "Class 2" and output rate of 9~48 VDC, 1.0 A minimum, or use the recommended power supply listed in "Optional Accessories".

Caution

Beginning from here there will be extreme caution exercised.



Never install or work on electrical cabling during periods of lightning activity.
Never connect or disconnect power when hazardous gases are present



WARNING: Disconnect the power and allow to cool 5 minutes before touching.

2 Introduction

2.1 Product Overview

The **AW5500C Wireless Access Point** series is our new line of wireless products designed to provide a wireless connectivity to clients or mobile stations creating a complete solution for your industrial wireless networking.

As an example, you can connect serial devices to our **Wireless Serial Device Server** and connect these two to a **Wireless Access Point** device; this example illustrates how to connect serial devices to a local area network or a backbone network, Figure 2.1. The **AW5500C** series provide several functionalities to support mobile and wireless networking.



Figure 2.1

2.2 Features

AW5500C is our latest addition to our Industrial Wireless products; its small size but powerful architecture makes it a perfect choice for industrial/manufacturing needs in which size is a decisive factor. It rewards our customers with superb connectivity. Among its many characteristics, we could mention:

- Stream input/output with maximum link speed of 300 Mbps and throughput of 100 Mbps (environment dependent).
- Wireless Isolation to enhance security between wireless clients.
- Different modes of operation:
 - Regular AP
 - WDS Bridge
 - AP Client

3 Getting Started

3.1 Inside the Package

Inside the product purchased you will find the following items:

Table 3.1

Item	Quantity	Description
AW5500C	1	Industrial Wireless Access Point
Antenna	1	3~5 dBi antenna
Terminal Block	1	3-pin lockable terminal block
Mounting Kit	1	DIN-Rail kit, already mounted on the device's back plate
Documentation + CD (Utilities)	1	Inside the CD you will find: <ul style="list-style-type: none">● User's Manual● Installation Guide● Device Management Utility © Utility

Note: Please notify your sales representative if any of the above items is missing or damaged in any form upon delivery. If your sales representative is unable to satisfy your enquiries, please contact us directly.

3.2 Front & Power Panels

The Front (Figure 3.1), and Power panels (Figure 3.2), are as follow:



Figure 3.1



Figure 3.2

The Rear panel (where you can mount the device on a rail or to the wall), looks as in Figure 3.3, a simple mounting instruction is given on Figure 3.4. For more information on hardware installation, please refer to the product's installation Guide.



Figure 3.3




Figure 3.4

3.3 First Time Installation

Before installing the device, please adhere to all safety procedures described below, Atop will not be held liable for any damages to property or personal injuries resulting from the installation or overall use of the device. **Do not attempt to manipulate the product in any way if unsure of the steps described here, in such cases please contact your dealer immediately.**

- Prepare the necessary cables, DC adapter, power cord, LAN cable, etc.: do not connect the unit yet.
- Install the antenna to the SMA connectors.
- Proceed then to plug the power source to the unit, starting from the ground and then the terminal block.
- Place the device in the desired location and connect it to the LAN via an Ethernet cable with a RJ45 connector.
- Connect your computer to the LAN network. Default configurations will be addressed later on Sections.

Note: remember to please consult your Hardware Installation Guide when attempting an installation. Also, please follow all safe procedures when doing so.

3.4 Finding the Device

As soon as the device is connected to the network, the user can search for its IP settings using **Device Management Utility** ©, (utility that comes in the CD); as noted in

Figure 3.5 below, important information such as the IP, MAC address, etc is going to be displayed.

No.	Caution	Model	IP Address	MAC Address	Host Name	Kernel
1		DT4500W	0.0.0.0	00:00:00:00:00:00		V2.22
2		SE5404D-S5	10.0.0.82	00:60:E9:07:AC:02	0060E9-07AC02	V3.22
3		SE5302-10	10.0.5.10	00:60:E9:01:BB:7C	yyyyyyyyyyyyyyyyyy	V1.1
4		SE5404D-Sis	10.0.50.8	00:60:E9:07:AB:CA	0060E9-07ABCA	V4.12
5		SE5404D	10.0.50.111	00:60:E9:07:AC:08	0060E9-07AC08	V4.12
6		AW5500C	10.0.50.200	00:60:E9:0F:2C:C2	0060E90F2CC2	V3.12
7		SE5002-55	10.0.63.219	00:60:E9:0C:DE:00	name	V2.70
8		SE5016	10.0.154.61	00:60:E9:05:6F:76		V1.18
9		SW5502-TB	10.0.159.100	00:60:E9:0B:4E:B8	atop^_^	V2.17
10		DT4500W	10.0.161.120	00:60:E9:01:10:93		V2.22
11		DT4500W	10.0.161.140	00:60:E9:01:10:90		V2.22
12		DT4000	10.0.166.102	00:60:E9:08:F6:4F	0060E9:08F64F	V1.2
13		EH7506-2SFP	10.0.176.50	00:60:E9:10:00:00	EH7506-2SFP	V2.15
14		RH7528	10.0.177.16	00:60:E9:AB:CD:00	RH7528	V1.21
15		SW5502	10.0.177.123	00:60:E9:5A:4B:3C	0060E95A4B3C	V2.51
16		IN126STa	10.0.189.11	00:60:E9:1B:55:EA	P*6STa^ I	V9.3
17		SE5901-DB9	10.0.189.98	00:60:E9:10:7A:B4	0060E9107AB4	V0.1
18		GW231A	10.0.210.2	00:60:E9:00:17:0B		V2.18
19		AW5500	10.1.195.253	00:60:E9:0A:C4:E5	0060E9-0AC4E5	V2.23
20		DT4500W	10.2.1.77	00:60:E9:01:10:91		V2.22
21		AW5500	140.115.16.1	00:60:E9:AA:AA:AA	0060E9AAAAAA	V2.24
22		SE5901	172.16.1.59	00:60:E9:13:EA:64	0060E913EA64	V0.3
23		SW5502	192.168.1.1	00:60:E9:5A:4B:3D	0060E95A4B3C	V2.51
24		SW5502-TB	192.168.1.10	00:60:E9:0B:4E:B9	atop^_^	V2.17
25		SE1908	192.168.2.1	00:60:E9:12:42:CB		V2.18

Figure 3.5

If the device's name is double-clicked or the Internet Explorer logo is clicked, **Device Management Utility** would open the Web UI of AW5500C using the system default browser. A window will pop-out that will prompt you to enter username and password (see [Factory Default Settings](#) for more information), proceed then to click “OK”, Figure 3.6. If credentials are entered correctly, the Web UI can then be accessed.




Figure 3.6

3.5 Factory Default Settings

Upon arrival, the device will be set as Regular AP, the rest of the settings are as follow:

Table 3.2

Mode	Regular AP	WDS Bridge	AP Client
Wireless			
Basic Settings			
AP Enabled	AP1		N.A.
SSID	AW5500C		
SSID Broadcast	Enabled		
Wireless Mode	802.11b/g/n		
Channel	1 (Automatic Channel Selection enabled)		
Bandwidth	Auto 20/40 MHz		
Security Settings			
Security Mode	Disabled	N.A.	N.A.
WPS Settings			
WPS	Disabled	N.A.	
WPS BUTTON			
PIN Number			
Advanced Settings			
Regulatory Domain	US (United States)		
Tx Power	100%		
Short GI	Enabled		
WMM	Enabled		
WPA Group Rekey Interval	600		
STP	Disabled		
Forward Delay	4 Seconds		
Fast Handoff	Disabled		N.A.
Wireless Isolation	Disabled		N.A.
20/40 MHz Coexistence	Enabled	N.A.	N.A.
P2P Button	Enabled		
Scheduler Settings			
Number	1	N.A.	N.A.

Name	OPEN	N.A	N.A
Status	Disabled	N.A	N.A
SSID	AW5500C	N.A	N.A
Day(s)	OPEN	N.A	N.A
Time(hour :minute)	OPEN	N.A	N.A
Network Settings			
LAN & WLAN Interfaces			
DHCP	Disabled		
Gratuitous ARP	Disabled		
Manual Settings			
IP Address	10.0.50.200		
Subnet Mask	255.255.0.0		
Default Gateway	10.0.0.254		
Preferred DNS	168.95.1.1		
Alternate DNS	Blank		
SNMP Settings			
System Contact	"Contact"		
System Location	"Location"		
Read Community	None (SNMP disabled)		
Write Community			
SNMP Trap Server	0.0.0.0		
Email Settings			
Sender	Blank		
Receiver			
SMTP Server			
Authentication	Disabled		
User name	Blank		
Password			
DHCP Server			
DHCP	Disabled (unchecked)		
From IP Address	None (if above unchecked)		
To IP Address			
Netmask			
Lease Time (minutes)			

Static Connection		
Firewall & Filtering (a total of 64 entries available per option)		
Wired MAC Filtering	Disabled MAC Filtering	N.A.
· Access Control List	None (if above checked)	
Wireless MAC Filtering	Disabled	
· Access Control List	None (if above checked)	
Ether Type Filtering	Disabled	
· Ethernet Type Filtering List	None (if above checked)	
IP Filtering	Disabled	
· IP Filtering List	None (if above checked)	
Management List	Disabled	
Log Settings		
Enable Log Event to Flash	Disabled	
Log Level	2: (LOG_CRIT)	
Enable Syslog Server	Disabled	
IP Address	0.0.0.0	
Syslog Server Service Port	514	
Event Log	"example"	
System Setup		
Username	admin	
Default Password	default	
New Password	NULL (Blank)	
Repeat new password		
Web Mode	HTTP	
Device name	Device's MAC Address	
NTP	Unchecked	
NTP Server	None (if above unchecked)	
Time Zone		
Daylight Saving Time Settings	Unchecked	
Start Date	None (if above unchecked)	
End Date	None (if above unchecked)	
Offset	None (if above unchecked)	
Manual Time Settings	2006/1/1 00:00	
Alert Event	All Items unchecked	

Firmware Upgrade	Path directed to Desktop	
Backup & Restore Configuration		
System Status		
System Information	As Shown	
Site Monitor	Default table according to connection	
Wireless client table		N.A.
Traffic Log & Statistics		
DHCP Status	No DHCP entry	
Ping	Blank	

4 Web Console Configuration

4.1 Overview Information

AW5500C is an Industrial Wireless solution for applications in harsh environments. The AW5500C is tough enough, expected to operate at temperatures ranging from -10°C~60°C. The ease of installation makes it attractive as it uses a DIN-Rail for fixing itself to virtually any surface in your workplace. Reliability is a key factor when wireless solutions are needed, that is why AW5500C's size makes it ideal for small places when considering its positioning without affecting real-time, control and overall performance.

4.2 User Interface Overview

AW5500C series' Web Configuration is designed into three different modes for ease of use to suit customer needs. The Web Configuration appears as follows, Figure 4.1




Figure 4.1



On the left side, a menu-tree appears with all the modes and options available, while on the right side of your screen the contents of each mode/option will be displayed in a graphical state. Since each Mode of operation is different, the content will differ, for more information on each selection please refer to each option's Section throughout the manual.

- Operation Mode
- Wizard
- Wireless
 - Basic Settings
 - Security Settings
 - WPS Settings
 - Advanced Settings
 - Scheduler Settings
- Network Settings
 - LAN & WLAN Interfaces
 - SNMP Settings
 - E-mail Settings
 - DHCP Server
- Firewall & Filtering
 - Wired MAC Filtering
 - Wireless MAC Filtering
 - Ethernet Type Filtering
 - IP Filtering
 - Management List
- Log Settings
 - System Log Settings
 - Event Log
- System Setup
 - Admin Settings
 - Date/Time Settings
 - Alert Event
 - Firmware Upgrade
 - Backup & Restore
 - Configuration
- System Status
 - System Information
 - Site Monitor
 - Wireless Client Table
 - Traffic Log & Statistics
 - DHCP Status
 - Ping
- Reboot

Figure 4.2

In general, there will be three buttons which will be present at the end of almost each configuration:

Table 4.1

Button	Function
	Saves the current configuration input on the page only, the configuration itself will not be applied to the device. We recommend users to use this button before the configuration process is completed and then press "Apply" at the last step.
	Save and apply the current configuration input on the page. On some pages, the device may need to reboot, we strongly advice to save the device's settings before reboot.
	Cancel the current configuration input and shows the original settings.

4.3 Secure Wireless Network

AW5500C is designed to provide you security support when building a network. We recommend using WPA2-PSK with AES as a minimum when securing your network; also remember to set it at 802.11n for a full speed performance. For more information on this and more please read [Security Settings](#).

4.4 Wireless Settings

Wireless Settings includes the basic Wi-Fi settings and wireless security. There are however, some concepts to be mentioned before going one step forward on the wireless settings. As you know, 802.11 is a set of standards for WLAN communication at the 2.4, 3.6 and 5 GHz frequencies. The AW5500C works only with the 2.4GHz. It follows the below mentioned standards:

- **802.11b**; the first of the standards to be created; an 11 Mbps (4~5 Mbps net throughput), 2.4 GHz signaling standard. Although it performs much better than traditional dial-up networking, its performance is still significantly less than 802.11a and other, newer standards.

- **802.11g**; very similar to 802.11b, the main difference being that it is done in a maximum raw data rate of 54 Mbps (20 Mbps net throughput), at the same 2.4 GHz bandwidth
- **802.11n**; Improves the amount of bandwidth utilized by using multiple wireless signals and antennas (MIMO technology) instead of one. Link speed on a 2x2 solution is 300 Mbps on our models

4.4.1 Wizard

AW5500C comes with a Quick Setup **Wizard** that will guide you through most of the common settings. You might find it suffice to follow the wizard and setup the Access Point without the need to proceed with this manual, (again, this is only applicable for the most basic setups in each mode).

4.4.2 Basic Settings

To set up a wireless network, several parameters are needed as shown in Figure 4.7. Link Speed can be optimized up to 154 Mbps by choosing 802.11 b/g/n; Below there is a table which shows **Basic Settings** for the device, Table 4.2 .

Table 4.2

Caption	Default
AP Enabled(AP1)	Enabled
AP Enabled (AP2)	Disabled
AP Enabled (AP3)	Disabled
SSID	AW5500C
SSID Broadcast	Enabled
Wireless Mode	802.11b/g/n
Channel	1 (Automatic Channel Selection box checked)
Bandwidth	Auto 20/40 MHz


The basic settings are explained in detail below:

- **AP Enabled:** AW5500C supports up to three multiple SSIDs (AP1, AP2, and AP3).AP1 must be enabled before you can proceed to AP2 and AP3. AP2 and AP3's settings are only shown when they are enabled. When all three APs are disabled, wireless radio would turn off completely.
- **SSID:** specifies the device's wireless network name that other wireless devices should

use in order to associate with this AP. Each AP (AP1, AP2, and AP3) can have their own SSID for better wireless network management. You can use the **“Scan network”** function to learn about the different SSIDs and channel numbers in the device’s surroundings, please be patient as this process might take as long as 10 seconds as shown below. Once it has finished scanning, names and basic properties of neighboring networks will be shown as in Figure 4.4. When no neighbors have been found the answer is as follows Figure 4.5. Keep in mind that the SSID should be unique unless wireless roaming is required.



Figure 4.3



The screenshot shows a web browser window titled "# Wireless Network - Windows Internet Explorer". The address bar contains the URL "http://10.0.160.9/neighbor_ap.asp?neborpge=1". The main content area displays a table with the following columns: SSID, MAC Address, T, Mode, Channel, Authentication, Encryption, Mbps, and Signal%. Below the table, there is a legend for 'T' and 'Channel', and two buttons: 'Refresh' and 'Close'.

SSID	MAC Address	T	Mode	Channel	Authentication	Encryption	Mbps	Signal%
banmu02	8c:4d: :00	Infra	b/g	1	OPEN	WEP	54	56
banmu01	00:26: :f3	Infra	b/g/n	2,6	WPA-PSK	TKIP	300	34
dlink-canon	00:24: :a2	Infra	b/g/n	3,7	OPEN	WEP	300	32
iptime	00:0e: :f6	Infra	b/g	6	WPA-PSK	TKIP	54	40
Atop_Public	00:24: :f0	Infra	b/g	9	OPEN	WEP	54	42
	68:92: :09	Infra	b/g	11	WPA-PSK	TKIP	54	37
Ruckus-2825	68:92: :49	Infra	b/g	11	WPA2-PSK	AES	54	36
4F	00:1f: :e2	Infra	b/g/n	11	OPEN	WEP	144	38

T is Topology (Infra = Infrastructure, Adhoc)
Channel is listed as Primary Channel, Secondary Channel

Figure 4.4





Figure 4.5

- **SSID Broadcast:** allow any wireless client to search for this access point presence, it is enabled by default. When the **SSID Broadcast** is disabled, wireless clients need to manually input the SSID in their wireless client configuration, increasing network security to prevent an access from unsolicited clients.
- **Wireless Mode:** 802.11b, 802.11b/g, 802.11b/g/n are available. We suggest leaving this option to 802.11b/g/n for AW5500C to sense the best available mode
- **Channel:** Select "Automatic Channel Select" to let the device automatically assign the best available channel number. When setting the channels manually, bear in mind that channels 1, 6, and 11 are the non-overlapping channels for 2.4 GHz Figure 4.6. Again, you can use "Scan network" to see which channels are already occupied.
- **Bandwidth:** when 40 MHz is used, AW5500C will double the channel width to 40 MHz as


compared to the standard 20 MHz to transmit its data; this is not recommended for 802.11b/g/n since it will leave only one non-overlapping channel for other APs. HT40 (40 MHz), is recommended for 802.11a/n because it offers a wider frequency range and it is easier for AW5500C to find empty channels as well.

Non-Overlapping Channels for 2.4 GHz WLAN

802.11b (DSSS) channel width 22 MHz



802.11g/n (OFDM) 20 MHz ch. width – 16.25 MHz used by sub-carriers



802.11n (OFDM) 40 MHz ch. width – 33.75 MHz used by sub-carriers




Figure 4.6

Wireless > Basic Settings AW5500C

Basic Settings

AP Enabled	<input checked="" type="checkbox"/> AP1	<input checked="" type="checkbox"/> AP2	<input checked="" type="checkbox"/> AP3
AP1 Settings			
SSID	<input type="text" value="AW5500C"/>	<input type="button" value="scan network"/>	
SSID Broadcast	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled		
Wireless Mode	<input type="text" value="802.11b/g/n"/> ▼		
BandWidth	<input type="text" value="Auto 20/40 MHz"/> ▼		
Channel	<input type="text" value="1"/> ▼	<input checked="" type="checkbox"/> Automatic Channel Selection	
AP2 Settings			
SSID	<input type="text" value="AW5500C_2"/>		
SSID Broadcast	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled		
AP3 Settings			
SSID	<input type="text" value="AW5500C_3"/>		
SSID Broadcast	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled		

Figure 4.7

Table 4.3

2.4 GHz Primary channel	20 MHz	40MHz upper			40 MHz lower		
	Blocks	2 nd ch.	Center	Blocks	2 nd ch.	Center	Blocks
1	1-3	5	3	1-7	Not Available		
2	1-4	6	4	1-8			
3	1-5	7	5	1-9			
4	2-6	8	6	2-10			
5	3-7	9	7	3-11	1	3	1-7
6	4-8	10	8	4-12	2	4	1-8
7	5-9	11	9	5-13	3	5	1-9
8	6-10	12	10	6-13	4	6	2-10
9	7-11	13	11	7-13	5	7	3-11
10	8-12	Not Available			6	8	4-12
11	9-13				7	9	5-13
12	10-13				8	10	6-13
13	11-13				9	11	7-13

Table 4.4

5 GHz Primary channel	40MHz upper	40 MHz lower
	2 nd channel	2 nd channel
36	40	-
40	-	36
44	48	-
48	-	44
60	64	-
64	-	60
149	153	-
153	-	149
157	161	-
161	-	157

Table 4.5

MCS index	Spatial streams	Modulation type	Data rate (Mbit/sec)			
			20 MHz channel		40 MHz channel	
			800 ns GI	400 ns GI	800 ns GI	400 ns GI
0	1	BPSK	6.50	7.20	13.50	15.00
1	1	QPSK	13.00	14.40	27.00	30.00
2	1	QPSK	19.50	21.70	40.50	45.00
3	1	16-QAM	26.00	28.90	54.00	60.00
4	1	16-QAM	39.00	43.30	81.00	90.00
5	1	64-QAM	52.00	57.80	108.00	120.00
6	1	64-QAM	58.50	65.00	121.50	135.00
7	1	64-QAM	65.00	72.20	135.00	150.00
8	2	BPSK	13.00	14.40	27.00	30.00
9	2	QPSK	26.00	28.90	54.00	60.00
10	2	QPSK	39.00	43.30	81.00	90.00
11	2	16-QAM	52.00	57.80	108.00	120.00
12	2	16-QAM	78.00	86.70	162.00	180.00
13	2	64-QAM	104.00	115.60	216.00	240.00
14	2	64-QAM	117.00	130.00	243.00	270.00
15	2	64-QAM	130.00	144.40	270.00	300.00

4.4.3 Security Settings

These settings provide an overall network security (according to the user's needs), by default Wireless Security is Disabled, Figure 4.8. Each AP (SSID) can have its own wireless security. For example, you can create a temporary SSID with OPEN security for guest access. Note that WEP will not be available if you have enabled more than one AP (SSID).

The screenshot shows a web-based configuration interface for the AW5500C access point. At the top, a green header bar contains the text 'Wireless > Security Settings' on the left and 'AW5500C' on the right. Below the header, the main content area is titled 'Security Settings'. It contains three configuration fields: 'AP1 Security Mode' with a dropdown menu showing 'WPA-PSK', 'Encryption Type' with a dropdown menu showing 'TKIP', and 'PassPhrase' with a text input field containing '11111111'. At the bottom of the configuration area, there are three buttons: 'Save Settings', 'Apply', and 'Cancel'.

Figure 4.8

A number of Security Settings are available for you:

- **WEP 64/128-bit Hex:** stands for **Wired Equivalent Privacy**. Which is a moderately weak security algorithm, and although it implies security in a wired connection, it is weaker than **WPA** protocols. It is not recommended unless a really large network is being administered. Up to 4 different hexadecimal or ASCII keys can be entered in this section, Figure 4.9




Figure 4.9

- **WPA-PSK:** stands for **Wi-Fi Protected Access**. Uses a passphrase generated and entered by the user; this passphrase can be between 8 and 63 characters long. We strongly recommend not to take a passphrase already in use within the network (nor use a variation of personal information publicly available), since this can compromise network's security, Figure 4.10.




Figure 4.10

- **WPA2-PSK:** stands for **Wi-Fi Protected Access II**. This is a highly recommended setting for the average user. You can select the encryption mode one of the following: TKIP (**T**emporal **K**ey **I**ntegrity **P**rotocol), or AES (**A**dvanced **E**ncryption **S**tandard). Less prone to be hacked than the above one, Figure 4.11.




Figure 4.11

- **WPA2 (RADIUS):** designed for enterprise networks, it requires a RADIUS (Remote Authentication Dial In User Service), authentication server. Although possessing a more complicated setup, security is optimized since passwords are not transmitted between the NAS (Network Authentication Server) and RADIUS, Figure 4.12.

Wireless > Security Settings AW5500C

Security Settings

AP1 Security Mode

Encryption Type:

IP Address:

Port: (1812 is recommended.)

Shared Secret:

Figure 4.12

- **Disabled:** no security settings are being used in the current device (comes as factory default), Figure 4.13. **This option is highly discouraged since authentication as well as encryption is not performed in this mode.**




Figure 4.13

4.4.4 WPS Settings

This option is available only when AW5500C is running in the **Regular AP** mode. **WPS** stands for **Wi-Fi Protected Setup**, **PBC** stands for **Push Button Configuration**. WPS needs to be enabled before you can **Start WPS PBC**. To use this feature, first trigger the WPS process in AW5500C by pressing the **WPS PBC** button and click on the **WPS PBC** button on SW5500C's UI or other WPS methods designated by a WPS compatible device, Figure 4.14. After the **Start WPS PBC** button is pressed, **WPS** would be triggered and the AW5500C will wait for 120 seconds for a WPS compatible device to associate with it automatically.




Figure 4.14

Note that since AW5500C only supports the “**Configured**” mode of WPS, the following wireless settings need to be set manually before the device would enter the WPS state:

Table 4.6

Operation Mode		Regular AP
Basic Settings	SSID	User Define
	Wireless Mode	User Define
Security Settings	Authentication	WPA-PSK or WPA2-PSK
	Encryption	TKIP or AES
	Passphrase	User Define

*Again, TKIP is not covered in the 802.11n standard and the wireless rate would be limited to 54 Mbps.

4.4.5 WDS Settings

This option is available only when AW5500C is running in the **WDS Bridge** mode and AW5500C is configured as a **WDS Hybrid** or a **WDS Station**, three different encryption types are available, WEP/TKIP/AES. The configuration is relatively simple and straightforward; enter the Second MAC of the adjacent AW5500C, the adjacent AW5500C could be a **Root AP** or a **Hybrid**, Figure 4.15

The screenshot shows the WDS Settings configuration interface. At the top, a green header bar contains 'Wireless > WDS Settings' on the left and 'AW5500' on the right. Below the header, the main content area is titled 'WDS Settings'. It features an 'Encryption Type' dropdown menu currently set to 'NONE'. Underneath is a table with a blue header row labeled 'WDS Settings'. The table has two columns: 'Root/Hybrid AP' and 'MAC:'. The 'MAC:' column contains six empty input boxes for entering a MAC address, followed by a 'scan network' button. At the bottom of the form are three buttons: 'Save Settings', 'Apply', and 'Cancel'.

Figure 4.15

Note that the **Encryption Type** here would also be used by the wireless clients connecting to AW5500C if you are a **WDS Root** or **WDS Hybrid**. When TKIP or CCMP (AES) is selected, AW5500C would use **WPA2-PSK** authentication for the connecting wireless clients.

4.4.6 Advanced Settings

Provide details on wireless parameters for performance tuning. Changes in this section may affect overall performance, so caution is recommended, if you are not clear of what you are doing please refrain from altering them, Figure 4.16.




Figure 4.16

- **Regulatory Domain** defines the different parameters for antenna gain, transmit power, channel selection, and so on that must be followed in different geographic areas. The default setting is US(FCC 5_FCCA)
- **TX Power** is AW5500C's **T**ransmission **P**ower. The transmission power can be reduced to prevent wireless interference to other wireless networks.
- **Short GI** is recommended to leave it as enabled to maximize the throughput.
- **WMM** or **W**ireless **M**ultimedia **E**xtension, which is recommended to leave as enabled in order to comply with 802.11n standards and achieve link speeds higher than 54 Mbps.
- **WPA Group ReKey Interval**, WPA automatically changes secret keys after certain

period of time, which all devices on the wireless network share. Constantly rekeying the group key protects your network against intrusion.

- **STP** or Spanning Tree Protocol, please enable this option if STP is enabled in your network to prevent network loops. When disabled, AW5500C will not forward STP BPDUs. **Forward Delay** time in which the interface takes to converge from blocking stage to forwarding state. This option only shows in the **AP Client** mode.
- **Maximum Signal Distance** is used to determine how fast a wireless signal should be timed out. If AW5500C is equipped with an outdoor antenna to reach further distances, increase this value accordingly.
- **Fast Handoff** is the Atop proprietary protocol to speed up roaming between AW5500Cs. Enable to allow AW5500C to share its neighboring AW5500C information to SW550X to further reduce its roaming time.
- **Wireless Isolation** creates a firewall between wireless clients connected to this AP. The isolation can be enabled to prevent data traffic flowing between clients to increase client security and to prevent unnecessary traffic between clients.
- **20/40 MHz Coexistence** allows AW5500C working in 40MHz to fall back to 20MHz when there are 20MHz only clients in the wireless network. The AP will also fall back to 20MHz when the channel within the +-40MHz frequency range has been occupied.
- **P2P Button** is used to enable or disable the function of Push Button at the front panel of AW5500C. Default setting is "Enable".

4.4.7 Wireless Scheduler Settings

This function allows you to setup a wireless schedule and disables SSIDs according to the time in a day when necessary. You can have up to 10 rules.

Wireless > Scheduler Settings
AW5500C

Scheduler Settings

Number	<input checked="" type="radio"/> 1 <input type="radio"/> 2 <input type="radio"/> 3 <input type="radio"/> 4 <input type="radio"/> 5 <input type="radio"/> 6 <input type="radio"/> 7 <input type="radio"/> 8 <input type="radio"/> 9 <input type="radio"/> 10
Name	<input type="text"/>
Status	<input type="radio"/> Enabled <input checked="" type="radio"/> Disabled
SSID	AW5500C ▼
Day(s)	<input type="checkbox"/> Sun <input type="checkbox"/> Mon <input type="checkbox"/> Tue <input type="checkbox"/> Wed <input type="checkbox"/> Thu <input type="checkbox"/> Fri <input type="checkbox"/> Sat
Time (hour:minute)	00 ▼ : 00 ▼ - 00 ▼ : 00 ▼

No.	Name	SSID	Day(s)	Start	Stop	Status
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						

Figure 4.17

- **Number:** select from 1 to 10.
- **Name:** give this rule a name, so it is easier to remember.
- **Status:** enable or disable this rule.
- **SSID:** select the SSID which this rule applies to.
- **Days(s):** select the days of the week when this rule should be effective.
- **Time (hour:minute):** select the time of the day when this rule should be effective. If you want this rule to run for the whole day, set 00:00 – 00:00.

Scheduler Usage Tutorial:

Let's say there are two sites that are covered by the AP and they have different working hours. The office would normally work from 8am to 6pm and the production line should run 24 hours. Both sites will shut down on weekends Figure 4.18.

Steps

- Enable **AP2** in the Wireless Basic Settings. Set **AP1** to use SSID AW_Production and **AP2** to use **SSID** AW_Office. Configure other wireless settings when necessary.
- Go to Wireless Scheduler Settings and select **Rule 1**. Give this rule a name (Production Line), change its status to **Enabled**, select the **SSID** (AW_Production), check the days (Monday ~ Friday), and set 00:00 – 00:00 for **Time**. In case you have done something wrong and would like to discard the changes, press the **Cancel** button. Click the **Add/Modify** button to add this rule or overwrite an existing rule.
- Select **Rule 2**. Give this rule a name (Office), change its status to **Enabled**, select the **SSID** (AW_Office), check the days (Monday ~ Friday), and set the **Time** range to 8:00-18:00. Click the **Add/Modify** button to add this rule or overwrite an existing rule.
- In case there are other rules present in the table, you can select that rule and press the **Remove** button so it would clear.
- Click the **Apply** button to make the new scheduler rules effective.

Note that under this scenario, the wireless function (radio) would be turned off completely on Saturdays and Sundays.

Wireless > Scheduler Settings
AW5500C

Scheduler Settings

Number	<input checked="" type="radio"/> 1 <input type="radio"/> 2 <input type="radio"/> 3 <input type="radio"/> 4 <input type="radio"/> 5 <input type="radio"/> 6 <input type="radio"/> 7 <input type="radio"/> 8 <input type="radio"/> 9 <input type="radio"/> 10
Name	<input type="text" value="Production Line"/>
Status	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled
SSID	<input type="text" value="AW5500C"/>
Day(s)	<input type="checkbox"/> Sun <input checked="" type="checkbox"/> Mon <input checked="" type="checkbox"/> Tue <input checked="" type="checkbox"/> Wed <input checked="" type="checkbox"/> Thu <input checked="" type="checkbox"/> Fri <input type="checkbox"/> Sat
Time (hour:minute)	<input type="text" value="08"/> : <input type="text" value="00"/> - <input type="text" value="18"/> : <input type="text" value="00"/>

No.	Name	SSID	Day(s)	Start	Stop	Status
1	Production Line	AW5500C	Mon, Tue, Wed, Thu, Fri	08:00	18:00	Enable
2						
3						
4						
5						
6						
7						
8						
9						
10						

Figure 4.18

4.5 Network Settings

AW5500C will get an IP address from a DHCP server connected on the LAN interface, just check **“Obtain an IP Address Automatically”** for it, Figure 4.19, or enter the values manually if known, Figure 4.20.

Network Settings > LAN & WLAN Interfaces AW5500C

LAN & WLAN Interfaces

DHCP	<input checked="" type="checkbox"/> Obtain an IP Address Automatically.
Gratuitous ARP	Disabled ▾ 5 minutes
Manual Settings	
IP Address	10.0.50.200
Subnet Mask	255.255.0.0
Default Gateway	10.0.50.1
DNS Server	
Preferred DNS	168.95.1.1
Alternate DNS	

Save Settings Apply Cancel

Figure 4.19

Network Settings > LAN & WLAN Interfaces AW5500C

LAN & WLAN Interfaces

DHCP	<input type="checkbox"/> Obtain an IP Address Automatically.
Gratuitous ARP	Disabled ▾ 5 minutes
Manual Settings	
IP Address	10.0.50.200
Subnet Mask	255.255.0.0
Default Gateway	10.0.50.1
DNS Server	
Preferred DNS	168.95.1.1
Alternate DNS	

Save Settings Apply Cancel

Figure 4.20

Gratuitous ARP enables to periodically send out an ARP response automatically to announce that AW5500C is in the network. The frequency in minutes could be set in the nearby box.

4.6 SNMP Settings

The SNMP is used by network management software to monitor devices in a network to retrieve network status information and to configure network parameters. The SNMP Settings shows the configuration of this device so it can be viewed or edited by third-party SNMP software as shown below, Figure 4.21.

SNMP Settings AW5500C

SNMP (Simple Network Management Protocol)

The *SNMP* is used in network management systems to monitor network-attached devices for conditions that require administrative attention.

Basic Data Objects	
System Contact	Contact
System Location	Location

SNMP	<input type="checkbox"/> Enabled
Read Community	public
Write Community	private

SNMP Trap Server	
A trap is an unsolicited message sent by an SNMP agent to an SNMP management system.	
SNMP Trap Server	0.0.0.0

Apply Cancel

Figure 4.21

AW5500C provides two SNMP fields, which are “**System Contact**”, usually used to specify the device’s contact information in case of emergency; and “**System Location**”, usually used to specify the device location.

If you wish to make the device information available for public viewing/editing, **Enable** the SNMP function. Fill in the passphrase for the “**Read Community**”, the group that is allowed to read the device information and fill in the passphrase for the “**Write Community**”, the group that is allowed to read/modify the device information. By default AW5500C comes in **public** for **Read Community** and **private** for **Write Community**. In case the device raises an alert due to any unexpected incident, a message will be dispatched to a SNMP trap server. Specify the **IP Address** of the **SNMP Trap Server** designed to collect all alert messages; any changes made will take effect after the device is restarted.

4.7 Email Settings

In case the device raises an alert and/or warning message, it will send an email to the administrator's mailbox. **Email Settings** allows you to set up the device to be able to send an email. To set up the email sending, you need to put a **"Sender"** email address which will be the **"From"** on the email. Then, you fill in **"Receiver"** email address to which the email is sent. You can send the email to several recipients using Semicolon (;) to separate each email address. Next step is to set the **Email Server**. First, you fill in the **IP address** of a **Mail Server** in your local network. If the **Mail Server** needs a user authentication, you need to enable **"SMTP server authentication required"**, and fill in **Username** and **Password**. Please contact your network administrator for **Mail Server IP address** and the **Username** and **Password**, Figure 4.22. You can click on **"Send Test Mail"** to verify your mail settings.

E-mail Settings AW5500C

SMTP Server & Client (Simple Mail Transfer Protocol)

E-mail Address Settings	
Sender	<input type="text"/>
Receiver	<input type="text"/>
Use a semicolon (;) for each e-mail address.	

E-mail Server	
SMTP Server	<input type="text"/>
Authentication	<input type="checkbox"/> SMTP server authentication required. <input type="checkbox"/> Enable TLS/SSL.
User name	<input type="text"/>
Password	<input type="password"/>

Figure 4.22

4.8 DHCP Server

If there is no workstation or server to act as the DHCP Server and assign IP addresses to each client automatically, AW5500C can serve as the DHCP Server to statically or dynamically assign an IP address to any network device. To enable such functionality, check **Enabled** to enable the DHCP Server in AW5500C; proceed then to fill in the **IP Address Range** including the **“From IP Address”** and **“To IP Address”**, fill in the IP address’ **Netmask** (or **Subnet Mask**). **“Lease Time”** is the duration in minutes that an assigned IP Address will belong to that device; once expired, the IP address will be recycled. A maximum of 21600 minutes is set by default.

You can also assign a static IP address to a network device, meaning that the network device would always get the same Static IP Address from the DHCP server. To statically assign an IP address, check on the small box in front of each line, and then fill in the **Host Name** and/or the **MAC Address** that you want to assign a static **IP Address** to. When DHCP is enabled, up to 32 different static IP/MAC can be set, Figure 4.23.

DHCP ServerAW5500C

DHCP Server Settings

The DHCP Server is used to distribute the dynamic/static IP addresses settings to the requested client. [DHCP Client List](#)

DHCP	<input type="checkbox"/> Enabled																																			
IP Address Range																																				
From IP Address	<input type="text"/>																																			
To IP Address	<input type="text"/>																																			
Netmask	<input type="text"/>																																			
Lease Time(seconds)	21600																																			
Static Connection																																				
<table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th style="width: 10%;"></th><th style="width: 25%;">Host Name</th><th style="width: 25%;">IP Address</th><th style="width: 25%;">MAC</th><th style="width: 15%;">Status</th></tr></thead><tbody><tr><td><input type="checkbox"/></td><td><input type="text"/></td><td><input type="text"/></td><td><input type="text"/></td><td></td></tr><tr><td><input type="checkbox"/></td><td><input type="text"/></td><td><input type="text"/></td><td><input type="text"/></td><td></td></tr></tbody></table>			Host Name	IP Address	MAC	Status	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
	Host Name	IP Address	MAC	Status																																
<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>																																	
<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>																																	
<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>																																	
<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>																																	
<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>																																	
<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>																																	

Page 1/6

◀▶Save Settings Apply Cancel

Figure 4.23

For a look at the current DHCP client table, just click where it says “**DHCP client list**”, if no clients are present there would be a message specifying so Figure 4.24

System Status > DHCP Status

DHCP Client List

Host Name	MAC Address	IP Address	Lease Time
No DHCP entry.			

Figure 4.24

4.9 Firewall & Filtering

The following section deals with configuration for the network's **firewall** as well as its **packet filtering**. Available criteria for packet filtering are based on MAC address (Wired or Wireless), Ethernet packet, and IP address. These filtering methods provide security, preventing unauthorized or malicious packets an entrance to your network.

Data packets will be filtered (classified) as either "**allowed packets**" or "**denied packets**"; the "**allowed packets**" mode is more commonly known as the "whitelist" and the "**denied packets**" mode is known as the blacklist. We highly encourage you to be extremely careful on this section as data that doesn't fit into any of those criteria will be discarded with the potential outcome of letting the AW5500C as inaccessible if not configured properly. If the latter happens, you will need to reset the device back to its default by any of the methods described in [Reboot and Restore Default Settings](#)

4.9.1 Wired MAC Filtering

When connected to the LAN/Ethernet interface, filtering can be done using this option. The setting is simple, intuitive and straight-forward; just choose whether to **Allow** or **Deny packets** and proceed to fill in the blanks with the corresponding MAC addresses. Up to 64 different MAC addresses can be set for allowing as well as for denying packets, Figure 4.25; as a default, **Wired MAC Filtering** is disabled. For changes to take effect, press **Apply**, for saving those changes just press **Save Settings**.




Figure 4.25

4.9.2 Wireless MAC Filtering

Packet filtering in a Wireless environment can be done in an analogous way as the Wired MAC Filtering. In the same way, connection is ensured by allowing or denying packets according to their respective MAC addresses; again, a maximum of 64 different MAC addresses are available as an option, Figure 4.26.




Figure 4.26

4.9.3 Ethernet Type Filtering

Ethernet Type Filtering is done according to the packets' **Ethernet type**, also known as Layer 3 filtering. As in the two previous sections, there is a maximum of 64 entries for packets' specification. Enabling is simple (packets are set as disabled by default, Figure 4.27), checking the packet's **Ethertype** box (located to the left of it, first column). **Ethertype** numbering usually starts with 0x□□□□, in which □□□□ corresponds to a hexadecimal number, e.g., 0xF0F0 which is to filter NETBUI type messages or 0x8035 for RARP type messages; Figure 4.27.




Figure 4.27

4.9.4 IP Filtering

IP Filtering, as its name implies, is for filtering on the IP protocol, also known as Layer 4 filtering. Continuing its simple design, IP address is added on the Source and Destination Address fields. Each filter only provides a one-way filtering, to create a 2-way filtering you need to add another entry that has the source and destination address reversed. The filters should be active once the checkbox in the first column is checked. A total of 64 different entries can be added to the list, Figure 4.28.




Figure 4.28

4.9.5 Management List

The **Management List** is used to filter the MAC address that has access to the Web management interface. When enabled, only the MAC addresses entered in the Access Control List below has access to the Web UI.




Figure 4.29

4.10 System Log

4.10.1 Syslog

The Syslog function is turned on by default and cannot be turned off. It is used to log system events and report to an external Syslog server if necessary.

Log Settings > System Log Settings AW5500C

System Log Settings

Enable Log Event to Flash	<input type="checkbox"/> Enabled
Log Level	2: (LOG_CRIT) ▼
Enable Syslog Server	<input type="checkbox"/> Enabled
IP Address	0.0.0.0
Syslog Server Service Port	514 (1~65535, default=514)

Figure 4.30

- **Enable Log Event to Flash:** this would write log events to the local flash, otherwise the logs would be cleared when the device restarts because they are stored in the RAM by default.
- **Log Level:** 2 (we only allow logging at this level).
- **Enable Syslog Server:** enabling this option would allow you to send Syslog events to a remote Syslog server.
- **Syslog Server IP:** Please specify the remote Syslog Server IP.
- **Syslog Server Service Port:** Please specify the remote Syslog Server Port.

4.10.2 Event Log

Display the current event log stored in the device.

Event Log

Index	Date	Time	Startup Time	Level	Event
1/4	2006.01.02	22:30:29	00d02h45m34s	error	syslog: Authentication Failure (Web console)
2/4	2006.01.02	22:30:27	00d02h45m32s	error	syslog: Authentication Failure (Web console)
3/4	2006.01.02	22:30:25	00d02h45m31s	error	syslog: Authentication Failure (Web console)
4/4	2006.01.02	22:30:09	00d02h45m15s	error	syslog: Authentication Failure (Web console)

Last Page Next Page
Show All Events Clear All Events
Save To File

Figure 4.31

Click on “**Last Page**” to go to the last page. Click on “**Next Page**” to go to the next page. Click on “**Show All Event**” to show all events in one page. Click on “**Clear All Event**” to clear the events stored in the device. Click on “**Save To File**” to save all the events to a file locally. Click on “**Last Page**” to go to the last page. Click on “**Next Page**” to go to the next page. Click on “**Show All Event**” to show all events in one page. Click on “**Clear All Event**” to clear the events stored in the device. Click on “**Save To File**” to save all the events to a file locally.

4.11 System Setup

The following section describes some critical settings for the AW5500C; take care when changing the values here as they will greatly influence your network performance.

4.11.1 Admin Settings

The AW5500C allows User and password management, the user's default is as "admin" and the password "default". The Device name entry can be changed as well; to set/change their value just follows the steps filling in the corresponding blanks and choose **Apply** in the end, Figure 4.32.

There are two ways to access AW5500C's Web UI. One is Hypertext Transfer Protocol (**HTTP**) and the other is Hypertext Transfer Protocol Secure (**HTTPS**). For enhanced security, it is recommended to use the encrypted HTTPS protocol. Note that HTTP uses the 80 port while HTTPS uses the 443 port.

System Setup > Admin Settings AW5500C

Admin Settings

User & Password	
User name	admin
Old password	
New password	
Repeat new password	

Web mode	
Web mode	<input checked="" type="radio"/> HTTP <input type="radio"/> HTTPS

Device Name	
Device Name	0060E90F2CC2

Apply Cancel

Figure 4.32

4.11.2 Date/Time Settings

Date and time can be set manually, or using **Network Time Protocol (NTP)** to automatically synchronizes with a Time Server. For auto-synching check the box below **NTP Server Settings “Obtain date/time automatically”** proceeding then to fill the IP address or host name for it if a hostname is entered, the DNS server must be configured properly; a Time Zone can be selected as well, Figure 4.33.

System Setup > Date/Time Settings
AW5500C

Date/Time Settings

The NTP (Network Time Protocol) is used to synchronize the date/time from the NTP server.

Current Date/Time	
2 / Jan / 2006 16:51:56	
NTP Server Settings	
NTP	<input type="checkbox"/> Obtain date/time automatically
NTP Server	<input type="text" value="pool.ntp.org"/>
Time Zone	<input type="text" value="(GMT) Greenwich Mean Time: Dublin, Edinburgh, Lisbon, London"/>
Daylight Saving Time Settings	
<input type="checkbox"/> Enable Daylight Saving Time	
Start Date	<input type="text" value="--"/> / <input type="text" value="--"/> / <input type="text" value="Sun"/> / <input type="text" value="00"/> (Month / Week / Date / Hour)
End Date	<input type="text" value="--"/> / <input type="text" value="--"/> / <input type="text" value="Sun"/> / <input type="text" value="00"/> (Month / Week / Date / Hour)
Offset	<input type="text" value="0"/>
Manual Time Settings	
Date	<input type="text" value="02"/> / <input type="text" value="Jan"/> / <input type="text" value="2006"/>
Time	<input type="text" value="16"/> : <input type="text" value="51"/> : <input type="text" value="33"/> (HH : MM : SS)

Figure 4.33

4.11.3 Alert Event

There are five events that will trigger the alarm; these alerts are useful for security control or security monitoring, Figure 4.34

- **Cold Start**, when there is a power interruption.
- **Warm Start**, when the device resets.
- **Authentication Failure**, when an incorrect username or password is entered.
- **IP Address Changed**, when the device's IP is changed.
- **Password Changed**, when the administrator password is changed.

Any of the five events would trigger an alert. When enabled, an email alert would be sent to the designated address in the E-Mail Settings. A Trap alert would be sent to the designated Trap server in the SNMP Settings.

See [“Email Settings” section](#), to specify the email addresses to which the alert message is sent. See [“SNMP Settings” section](#) to specify a SNMP trap server.

Event	E-mail Alert	Trap Alert
Cold Start	<input type="checkbox"/>	<input type="checkbox"/>
Warm Start	<input type="checkbox"/>	<input type="checkbox"/>
Authentication Failure	<input checked="" type="checkbox"/>	<input type="checkbox"/>
IP Address Changed	<input type="checkbox"/>	<input type="checkbox"/>
Password Changed	<input type="checkbox"/>	<input type="checkbox"/>

Apply Cancel

Figure 4.34

4.11.4 Firmware Upgrade

Updated firmware is provided by our company from time to time (for more information visit our News & Events webpage), to fix bugs and optimize performance. It is very important that the device must **NOT be turned off or powered off during the firmware upgrading, (please be patient as this whole process might take up to 7 minutes)**. Before upgrading the firmware, please make sure that the device has a reliable power source that will not be powered off or restarted during the upgrading process. To upgrade a new firmware, once downloaded, copy the new firmware file to your computer, and then click “**Browse**” to find the new firmware file, then click “**Upload**”. The program will show the upload status, please wait until the uploading process is finished (the amount of time varies depending on the equipment used); the device will then proceed to restart itself (Figure 4.35)




Figure 4.35

Note: if the firmware upgrade process fails and the device becomes unreachable, follow the TFTP Recovery procedure on the Appendix.

4.11.5 Backup & Restore Configuration

Once all the configurations are set and the device is working properly, you may want to back up your configuration. Backup can be used when the new firmware is uploaded and it is reset to a factory default settings, it is done to prevent accidental loading of incompatible old settings. The backup file could also be used to efficiently deploy multiple AW5500Cs of similar settings by uploading the settings to the devices.

To backup your configuration, click “**Backup**”, and a pop-up dialog is prompted for saving the backup file on your computer. It is important **NOT to modify the saved configuration file by any editor. Any modification to the file may corrupt the file, and it may not be used for restore.** Please contact our authorized distributors for more information on this subject.

To restore the configuration backup, click “**Browse**” to locate the backup file, and then click “**Upload**” to upload the configuration backup file to the device. Once, the backup file is successfully uploaded; the device will restart, the time needed for this process may vary on the equipment used, Figure 4.36.




Figure 4.36

4.12 System Status

Overall AW5500C's info as well as network (and very possibly neighbors') information will be available when browsing this section.

4.12.1 System Information

This section illustrates AW5500C's overall information, Figure 4.37




Figure 4.37

4.12.2 Site Monitor

Site Monitor allows users to view the other wireless networks in the neighborhood, it also provides information on other access points such as SSID, Channel, the RSSI (**R**eceived **S**ignal **S**trength Indicator), Security and Link Speed of other access points. It can be helpful when setting SSID and Channel for this device to avoid SSID name and Channel conflict and prevent unexpected errors or degraded performance.

Please bear in mind that it will take some time (approximately 10 seconds), for this option to gather information of the surrounding wireless networks, Figure 4.38~ Figure 4.39

Show Waiting



Figure 4.38

System Status > Site Monitor *AW5500C*

Neighbor Wireless Network

SSID	Mode	Channel	Authentication	Encryption	Mbps	Signal%
HTC Portable Hotspot 9FB3	b/g/n	1	WPA2-PSK	AES	72	92
Dlink_Tudoo	b/g/n	1	WPA-PSK	TKIP/AES	150	4
AW55XX	b/g/n	6	OPEN	NONE	300	95
Ruckus-2825	b/g	6	WPA2-PSK	TKIP/AES	54	53
SAMSUNG GT-I8750_9967	b/g/n	6	WPA2-PSK	AES	72	2
Banmu-Bravo	b/g/n	6	OPEN	NONE	130	0
AW5300	b/g	1	OPEN	NONE	54	1

Figure 4.39

4.12.3 Wireless Client Table

On this table you may be able to see all the Wireless and WDS device connected to this AW5500C, Figure 4.40.

System Status > Wireless Client Table AW5500C

Associated wireless client


MAC Address	*AID	Channel	Tx Rate	*RSSI	Idle	Tx Seq	Rx Seq
No associated wireless client.							

*AID: Association ID.
*RSSI: Signal strength of the last received packet.

Figure 4.40

4.12.4 Traffic Log & Statistics

Traffic Log & Statistics shows wireless network and status information; “Refresh Rate” can be changed to automatically reload/update the page, the default being a “no refresh” option, but it can be done manually by clicking on Refresh. Be careful when setting this value because it will increase CPU load on the device, Figure 4.41



System Status > Traffic Log & Statistics AW5500C

Traffic Log & Statistics

Refresh Rate :

recv eol interrupts:	218
global txmit timeout interrupts:	68
carrier sense timeout interrupts:	34
tx management frames:	1977
tx failed 'cuz too many retries:	1148
tx frames with no ack marked:	134
tx frames with short preamble:	143
total number of bytes received:	35449581
total number of bytes transmitted:	212446
rssl of last ack[ctl, ch0]:	23
rx rssi from histogram [combined]:	8
rssl of last rcv[ctl, ch0]:	8
beacons transmitted:	54651
periodic calibrations:	80264

Antenna profile:

switched default/rx antenna	1	
[0] tx	1050 rx	39
[1] tx	0 rx	166345

Figure 4.41

4.12.5 DHCP Status

AW5500C could distribute IP addresses using the DHCP protocol; a list of clients currently receiving an IP can be accessed by choosing the DHCP Status option. DHCP Client's **MAC Address** as well as its **IP addresses**, **Host Name**, and **Lease Time** will be shown in this list
Figure 4.42




Figure 4.42

4.12.6 Ping

Use the Ping function to determine whether AW5500C can reach the gateway or other devices in the network or not. This process takes around 20 seconds. Figure 4.43 represents a successful ping while Figure 4.44 means that the connecting device is not reachable.




Figure 4.43




Figure 4.44

4.13 Reboot and Restore Default Settings

To manually reboot the device, you may click on “Reboot”, after which the device will restart. If a factory default setting is needed, tick the “Reset” checkbox, and then click on Reboot, Figure 4.45. Also, you could use the button located on the Front panel, close to the LAN Port; it is conveniently labeled as Reset. Just insert the tip of a paper clip and hold it long enough until the device produce a long beep, release the button and wait for the device to restart.




Figure 4.45

5 Operation Modes

5.1 Regular AP Mode

Regular AP mode's welcome screen is as shown below, Figure 5.1.




Figure 5.1

Regular AP mode which is the factory default and the first option on the screen, allows wireless clients to connect to a network, relaying data between the wired and wireless devices in the network. It allows multiple wireless clients to access the network through AW5500C's Ethernet interface (physical/wired connection). Its corresponding complete menu-tree is as follows in Figure 5.2

- Operation Mode
- Wizard
- Wireless
 - Basic Settings
 - Security Settings
 - WPS Settings
 - Advanced Settings
 - Scheduler Settings
- Network Settings
 - LAN & WLAN Interfaces
 - SNMP Settings
 - E-mail Settings
 - DHCP Server
- Firewall & Filtering
 - Wired MAC Filtering
 - Wireless MAC Filtering
 - Ether Type Filtering
 - IP Filtering
 - Wireless Client Isolation
 - Management List
- Log Settings
 - System Log Settings
 - Event Log
- System Setup
 - Admin Settings
 - Date/Time Settings
 - Alert Event
 - Firmware Upgrade
 - Backup & Restore
 - Configuration
- System Status
 - System Information
 - Site Monitor
 - Wireless client table
 - Traffic Log & Statistics
 - DHCP Status
 - Ping
- Reboot

Figure 5.2

Steps for a quick setting for the AW5500C as a Regular AP are:

- On operation mode choose **“Regular AP”** (if the device is not in factory default).
- Go to **Wireless** → **Basic Settings**; here you can change the **Network Name** (SSID) to your preferred name, you might want to first click on **“Scan network”** to find whether there are neighbors with a name matching yours (this is done for preventing any conflict over networks).
- At this point you may decide to change other settings such as the **Wireless Mode** and whether to have **Automatic Channel Selection**.
- Next go to **Security Settings**, and on **Security Mode** choose which security protocol will be used in the network. We strongly recommend not leaving this section as disabled.
- On **LAN & WLAN Interfaces**, enter the **IP Address, Subnet Mask, Default Gateway,** and **DNS servers** used (if any), according to your network configuration.
- Click **“Apply”**, and wait for the changes to take effect. You may also want to **Save Settings** afterwards just in case you need these configurations in the future.

5.2 WDS Bridge Mode

On this mode multiple AW5500C can bridge together to create a **Wireless Distribution System**. Under this mode, the device uses its second MAC address as its wireless interface instead of the first one. The following details the WDS structure; there are three roles that AW5500C can play in a WDS network:

- **Root AP (or Root)**
- **Hybrid (or Parent)**
- **Station (or Child)**

Please keep in mind that there should be one and only one Root AP in the WDS network.

Hybrids can connect to a **Root AP** or connect with each other and **Stations** can connect with either a **Root AP** or a **Hybrid**. Connecting multiple WDS nodes to a **Root AP** or a **Hybrid** is allowed as well. Please take a look at the following tree structure, Figure 5.3




Figure 5.3

Note: it is possible to setup a Hybrid (Parent) without a Station (Child). The difference between a Hybrid and a Station is that the Station does not allow wireless clients to associate to it.

For AW5500C quick steps to work as in WDS Mode, the procedure is as follows:

- On operation mode choose **“WDS Bridge”**.
- Go to **Wireless** → **Basic Settings**; on **WDS Mode** you can choose whether to use the AW5500C as a **Root AP**, **Hybrid**, or **Station**. Also as before, you can change the **Network Name** (SSID) to your preferred name; you might want to first click on **“Scan network”** to find whether there are neighbors with a name matching yours (this is done for preventing any conflict over networks). From here three different configurations are therefore possible:
 - **When on Root mode**
 - ◆ **SSID Broadcast** can be disabled here for an additional level of security.
 - ◆ On **Wireless Mode**, we recommend using **802.11 a/n** since it is not as crowded as **802.11 b/g/n**; however this is only possible if it is supported by your wireless client. **Channel and transmission rate** can be chosen automatically by the AW5500C, however feel free to change them to the settings that work for you.
 - ◆ On **WDS Settings** → **Encryption Type**, do not leave this option as NONE, non-existent encryption will result in an easy target for undesired access to your network.
 - ◆ On **Root AP**, the **MAC address** is to be left empty; again the Local Area network fields should be entered with their corresponding values for the network being configured.
 - ◆ Save and apply the settings for them to take effect.
 - **When on Hybrid mode**
 - ◆ Please remember that the SSID here should be the same as the Root AP. This also means roaming is possible between APs.
 - ◆ On **WDS Settings** → **Root AP**, the **MAC address** entered should be the **Root/Hybrid’s (Parent’s) Second MAC address** that is directly above this **Hybrid AP**. It might not be the **Root AP’s MAC address** if the WDS setup has a multilayer architecture.
 - ◆ Save and apply the settings for them to take effect.

- **When on Station mode**
 - ◆ SSID is not present here as there is no AP function
 - ◆ On **WDS Settings** → **Root AP**, the **MAC address** entered should be the **Root/Hybrid's (Parent's)** Second MAC address that is directly above the Station AP. It might not be the **Root AP's** MAC address if the WDS setup has a multi-layer.
 - ◆ Save and apply the settings for them to take effect.



Figure 5.4

Its corresponding menu-tree has slight differences compared to Regular AP, Figure 5.5.

- Operation Mode**
- Wizard**
- Wireless**
 - Basic Settings
 - WDS Settings
 - Advanced Settings
- Network Settings**
 - Local Area Network
- SNMP Settings**
- E-mail Settings**
- DHCP Server**
- Firewall & Filtering**
 - Wired MAC Filtering
 - Wireless MAC Filtering
 - Ether Type Filtering
 - IP Filtering
 - Wireless Client Isolation
 - Management List
- Log Settings**
 - System Log Settings
 - Event Log
- System Setup**
 - Admin Settings
 - Date/Time Settings
 - Alert Event
 - Firmware Upgrade
 - Backup & Restore
 - Configuration
- System Status**
 - System Information
 - Site Monitor
 - Wireless client table
 - Traffic Log & Statistics
 - DHCP Status
 - Ping
- Reboot**

Figure 5.5

5.3 AP Client Mode

This mode allows your AW5500C to connect to an AP. Ethernet clients connected to AW5500C over the Ethernet interface are allowed to access the network through AW5500C's wireless interface. Under this mode, the device uses its second MAC address as its wireless interface instead of the first one.




Figure 5.6

Remember that your AW5500C can function as both a **Regular AP** and as an **AP Client** (the latter connected to the first one).

Supposing we already have the network physically installed, the steps for configuring your AW5500C as an **AP Client** are as follows.

- On **Operation Mode** choose **AP Client**.
- Click on **“Save Settings”**, go then to **Mobile Station** under the **Wireless** section and click on **“Scan network”** to choose an **SSID**.
- A window/tab will pop out; in that new window/tab, there will be the names of the surrounding Wireless Networks. Choose the one that you already designated as your **Regular AP** by selecting its corresponding SSID.
- Click **“Connect”**, this will make you close the pop-out window/tab, and leave you with

the settings selected on the previous page.

- Enter the **WEP key** or the **WPA passphrase** if necessary.
- Scroll to the end of the page and press **“Apply”**, please wait for some time for the changes to apply.
- Then proceed to go to **System Information**, on the **AP Client** Information you can confirm your AW5500C is connected to the Network selected if the status field displays a signal percentage instead of disconnected. Also, you may also double check the wireless connection status inside the client table of the connected **AP**.




Figure 5.7

6 Applications

6.1 Basic Access Point Setup

The following figure illustrates a standard **Access Point** serving multiple wireless clients **within its signal coverage**




Figure 6.1

For more information on how to configure your AW5500C as an **Access Point** please refer to [Regular AP Mode](#)

Note: wireless coverage is dependent on the environment.

6.2 Basic WDS Setup

The following figure illustrates two sites with some considerable distance apart. Ethernet cabling is impossible to the adjacent site. The adjacent site has both wireless clients and Ethernet clients. Note that if the **Access Point** function is not required at the adjacent site (no wireless clients), **WDS Hybrid** can be changed to **WDS Station**.




Figure 6.2

For more information on how to configure your AW5500C for this topology, please refer to [WDS Bridge Mode](#)

Note: wireless coverage is dependent on the environment.

6.3 Coverage Range Extender Setup

Extending from the above scenario, if the distance needs to be further extended, it is always possible to add more AW5500C (in **WDS Hybrid** mode) in between the existing one. The **WDS MAC address** of the newly added AW5500C (in **WDS Hybrid** mode) should be **MAC address** of the AW5500C that it is directly connecting to, not the **MAC address** of the AW5500C in **WDS Root** mode. Note that AW5500C in **WDS Station** mode does not allow both wireless client and AW5500C (in **WDS Hybrid** mode) to connect in. Normally it should be the last AW5500C in the wireless topology if utilized.




Figure 6.3

For more information on how to configure your AW5500C for this topology, please refer to [WDS Bridge Mode](#)

Note: wireless coverage is dependent on the environment.

6.4 AP Client Setup

If AW5500C is being added to a wireless network where **Access Points** (AP1) from other vendors already existed, AW5500C could be set to AP Client mode to connect to that AP1 and bridge the Ethernet clients to AP1. This setup is similar to Scenario #2, except that WDS is not used. This is because WDS from different vendors might not be compatible.



Figure 6.4

For more information on how to configure your AW5500C for this topology, please refer to [AP Client Mode](#).

Note: wireless coverage is dependent on the environment.

6.5 P2P Button (External Physical WPS button)

AW5500C has an external physical WPS button – P2P Button, which can build the connection directly between two AW5500C. So that user’s manual setting steps can be decreased.

1. You have to tick this option to enable P2P button working. This option can be found in webpage, under Wireless, Advanced Settings label. The default setting is enabled.




Figure 6.5

2. To establish connection succeeds, all device IP address and subnet mask setting should be correct. Users can use **Device Management Utility** to setup.




Figure 6.6

3. AW5500C can be assigned to different mode by pressing P2P button; the following table shows the timing relationship.

Table

Pressing seconds	1~3(s)	4~7(s)	8~(s)
Working mode	Restart connection	Regular AP	AP client

4. AW5500C can make WI-FI connection just by pressing P2P button. To set AP mode, press P2P button for 4~7 seconds. To set as AP client, press over 8 seconds. If user wants the AP connect to other clients, just press 1~3 seconds to restart connection.

5. Users can check connection situation by LED status. The follow table represents the meaning of LED color.

Table 6.1

	LED State		
Color	Off	Blinking	On
Orange	P2P is not enabled.	P2P is connecting at AP mode	Device's P2P mode is enabled in AP mode.
Green	P2P is not enabled.	P2P is connection at Client mode	Device's P2P mode is enabled in AP client mode.

※ Limitation

- After pressing P2P button, the whole pairing sequence time is 120 seconds, which means user has to set both device in 120 seconds or pairing will be failed.
- WDS protocol doesn't support making multi AP to AP client link in the same time, pairing two or more devices in the same time might cause pairing failed.
- The pairing time might be influenced by environmental complexity.

7 Specifications

7.1 Hardware Specifications

The device's appearance is as follows, Figure 7.1.



Figure 7.1

- **Ethernet:** IEEE 802.3 10 BASE-T, 802.3U 100BASE-TX, 802.3ab 1000 BASE-T

Power Requirements

- **Input Voltage:** 9VDC-48VDC
- **Input Current:** (9VDC) 0.65 A
- **Power Consumption:** Approx. 5.85 W
- **Reverse Polarity Protection*:** Yes
- **Connection:** 3-pin Lockable, terminal block on top.

Note*: we strongly advice against this practice.

Physical Characteristics

- **Housing:** IP50 protection, metal case.
- **Weight:** 500 g
- **Dimensions:** 47 * 110 * 90 mm
- **Installation:** DIN-Rail, wall mount (optional kit)

Environmental Limits

- **Operating Temperature:** -10°C~60°C (14°F~140°F)
- **Storage Temperature:** -40°C~85°C (-40°F~185°F)
- **Ambient Relative Humidity:** 5~95% RH, (non-condensing)

Wireless Specifications

- **PCI-e Module:** Atheros AR9382
- **Tx/Rx:** 1T1R MIMO (1 x 1 with MCS 0-7)
- **Wireless Standard Conformance:** 802.11b, 802.11g, 802.11n
- **Antenna:** 3/5 dBi antenna design, SMA(R) Female connector

Frequency Range

Table 7.1

Country/Region	2.4 GHz	5 GHz
Unites States (FCC)	2412-2462 (20 MHz)	5180-5240, 5745-5825 (20 MHz)
	2422-2452 (40 MHz)	5190-5230, 5755-5795(40MHz)
Europe (ETSI)	2412-2472 (20 MHz)	5180-5240(20MHz)
	2422-2462 (40 MHz)	5190-5230(40MHz)
Taiwan (NCC)	2412-2462 (20 MHz)	5320,5745-5825(20MHz)
	2422-2452 (40 MHz)	5310-5310, 5755-5795(40MHz)
China (CCC)	2412-2472 (20 MHz)	5745-5825(20MHz)
	2422-2462 (40 MHz)	5755-5795(40MHz)

Data Rate

Table 7.2

802.11b		1, 2, 5.5 and 11 Mbps
802.11g		6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n	20 MHz	1Nss: 65Mbps @ 800GI, 72.2Mbps @ 400GI (Max.)
		2Nss: 130Mbps @ 800GI, 144.4Mbps @ 400GI (Max.)
	40 MHz	1Nss: 135Mbps @ 800GI, 150Mbps @ 400GI (Max.)
		2Nss: 270Mbps @ 800GI, 300Mbps @ 400GI (Max.)

Output Power

Table 7.3

802.11b		+14dBm
802.11g		+17dBm @ 6, 9, 12, 18, 24Mbps +17dBm @ 36Mbps +16dBm @ 48Mbps +16dBm @ 54Mbps
802.11n	2.4GHz/HT20	+16dBm @ MCS 0/8 +16dBm @ MCS 1/9 +16dBm @ MCS 2/10 +16dBm @ MCS 3/11 +16dBm @ MCS 4/12 +16dBm @ MCS 5/13 +16dBm @ MCS 6/14 +15dBm @ MCS 7/15
	2.4GHz/HT40	+15dBm @ MCS 0/8 +15dBm @ MCS 1/9 +15dBm @ MCS 2/10 +15dBm @ MCS 3/11 +15dBm @ MCS 4/12 +15dBm @ MCS 5/13 +15dBm @ MCS 6/14 +14dBm @ MCS 7/15

	5GHz/HT20	<p>+15dBm @ MCS 0/8,</p> <p>+15dBm @ MCS 1/9</p> <p>+15dBm @ MCS 2/10</p> <p>+15dBm @ MCS 3/11</p> <p>+15dBm @ MCS 4/12</p> <p>+11 - 14dBm @ MCS 5/13</p> <p>+9 - 12dBm @ MCS 6/14</p> <p>+7 - 10dBm @ MCS 7/15</p>
	5GHz/HT40	<p>+14dBm @ MCS 0/8,</p> <p>+14dBm @ MCS 1/9</p> <p>+14dBm @ MCS 2/10</p> <p>+14dBm @ MCS 3/11</p> <p>+14dBm @ MCS 4/12</p> <p>+10– 13dBm @ MCS 5/13</p> <p>+8 – 11dBm @ MCS 6/14</p> <p>+6 – 9dBm @ MCS 7/15</p>

*Note: please bear in mind that this is the raw output power for the RF module; note that the device has been tested with one 3 dbi @2.4GHz.

Receiver Sensitivity

Table 7.4

	Data Rate	IEEE Spec (1Rx dBm)	Typical/Maximum (2Rx dBm)
802.11b	1M	Not specified	-98/-85
	5.5M	Not specified	-98/-85
	11M	Not specified	-94/-85
802.11g	6M	-82	-96/-85
	9M	-81	-96/-84
	12M	-79	-95/-82
	18M	-77	-93/-80
	24M	-74	-90/-77
	36M	-70	-87/-73
	48M	-66	-83/-69
	54M	s-65	-82/-68
802.11n HT20	MCS0	-82	-94/-85
	MCS1	-79	-92/-82
	MCS2	-77	-90/-80
	MCS3	-74	-87/-77
	MCS4	-70	-84/-73
	MCS5	-66	-79/-69
	MCS6	-65	-78/-68
	MCS7	-64	-76/-67

802.11n HT40	MCS0	-79	-92/-82
	MCS1	-76	-90/-79
	MCS2	-74	-87/-77
	MCS3	-71	-84/-74
	MCS4	-67	-80/-70
	MCS5	-63	-76/-66
	MCS6	-62	-74/-65
	MCS7	-61	-72/-64
802.11b/g/n HT20	MCS0	-82	-95/-85
	MCS1	-79	-94/-82
	MCS2	-77	-92/-80
	MCS3	-74	-89/-77
	MCS4	-70	-86/-73
	MCS5	-66	-82/-69
	MCS6	-65	-80/-68
	MCS7	-64	-78/-67
802.11b/g/n HT40	MCS0	-79	-92/-82
	MCS1	-76	-92/-79
	MCS2	-74	-89/-77
	MCS3	-71	-86/-74
	MCS4	-67	-83/-70
	MCS5	-63	-77/-66
	MCS6	-62	-76/-65

	MCS7	-61	-75/-64
--	------	-----	---------

Operation Distance

Table 7.5

Standard	Outdoor	Indoor
802.11b	150m @ 11Mbps	30m @ 11Mbps
	300m @ 1Mbps	100m @ 1Mbps
802.11g	50m @ 54Mbps	30m @ 54Mbps
	300m @ 6Mbps	100m @ 6Mbps
802.11n	30m @ 300Mbps	20m @ 300Mbps
	30m @ 130Mbps	20m @ 130Mbps
	250m @ 6.5Mbps	100m @ 6.5Mbps

Security

- 64-bit and 128-bit WEP encryption
- 802.1x authentication
- AES and TKIP, WPA/WPA2

Others

- **Reset Button:** Yes
- **P2P Button:** Yes

Regulatory requirements

- **EMC:** EN 301489-1: 2008, EN301489-17: 2009 (Class A), FCC 15B (Class A), CNS 13438
- **Radio:** FCC 15C 15.247, FCC 15E 15.407, EN 301893: 2008, EN 300328: 2006, NCC LP00002
- **EMF:** EN 62311: 2008, EN 50385: 2002,
- **Safety:** UL60950-1, EN60950-1, CNS 14336
- **Shock:** IEC 60068-2-27
- **Freefall:** IEC 60068-2-32
- **Vibration:** IEC 60068-2-6
- **MTB*F:** 20 years
- **RoHS:** Yes
- **Maritime:** N/A
- **Hazardous location:** IEC 62368-1

Table 7.6

Test	Item		Value	Level
IEC 61000-4-2	ESD	Contact Discharge	±8KV	4
		Air Discharge	±15KV	4
IEC 61000-4-3	RS	Radiated(Enclosure)	10(V/m)	3
IEC 61000-4-4	EFT	AC Power Port	±2.0 KV	3
		LAN Port	±2.0 KV	4
		COM Port	±2.0 KV	4
IEC 61000-4-5	Surge	AC Power Port	Line-to-Line±1.0 KV	3
		AC Power Port	Line-to-Earth±2.0 KV	3
		LAN Port	Line-to-Earth±2.0 KV	3
		COM Port	Line-to-Earth±2.0 KV	3
IEC 61000-4-6	CS	Conducted(Enclosure)	10 V rms	3
IEC 61000-4-8	PFMF	(Enclosure)	10(A/m)	3
IEC 61000-4-11	DIP	AC Power Port	-	-

Note: Above certifications are subject to change depending on product's final destination. DC Ports are tested through a power adaptor available in the accessories kit.

7.2 Software Specifications

Table 7.7

Configuration	<ul style="list-style-type: none"> ■ Browser (IE8+, Firefox 6+, and Chrome 13+) ■ Telnet ■ Device Management Utility © (Windows utility)
Protocol	<ul style="list-style-type: none"> ■ ICMP ■ DNS ■ HTTP ■ TCP ■ SNMP ■ HTTPS ■ RADIUS ■ UDP ■ NTP ■ IPv4 ■ Syslog ■ DHCP ■ SMTP ■ 802.1x
Alert Events	<ul style="list-style-type: none"> ■ E-mail ■ SNMP Trap
Radio OFF	Yes
Other	<ul style="list-style-type: none"> ■ Multiple SSID ■ Wireless Scheduler ■ Config Import / Export from Web ■ Firmware upgrade through Web or Device Management Utility © ■ Site Monitor / Site Survey ■ Wireless Isolation ■ Firewall/Filtering (Wired / Wireless MAC Filtering, Ethernet Type Filtering, IP Filtering, Management List)

7.3 LED Indicators

Table 7.8

Name	Color	Status	Description
Regular AP Mode	Green	On	The Access Point (AP) function is enabled and has more than one wireless client connected.
		Blinking	The AP function is enabled and does not have any wireless client connected.
		Off	The Access Point (AP) function is disabled.
WDS Bridge Mode	Yellow	On	The WDS Bridge function is enabled and the WDS is connected successfully.
		Blinking	The WDS Bridge function is enabled and the WDS is not connected successfully.
		Off	The WDS Bridge function is disabled.
AP Client Mode	Red	On	The AP Client function is enabled and connected to the remote AP successfully
		Blinking	The AP Client function is enabled but not connected to the remote AP
		Off	The AP Client function is disabled.
P2P	Orange	On	Device's WPS mode is enabled in AP mode.
		Blinking	WPS is connecting at Soft AP mode
		Off	WPS connection failed.
	Green	On	Device's WPS P2P mode is enabled in AP client mode.
		Blinking	WPS is connecting at client mode
		Off	WPS connection failed.
Locate	Green	Blinking	The AP is being located
		Off	The AP is not being located
LAN	Orange	Blinking	Data is transmitting on Ethernet
		On	Ethernet is connected on 100Mbps

		Off	Ethernet is disconnected on 100Mbps
	Green	Blinking	Data is transmitting on Ethernet
		On	Ethernet is connected on 10Mbps
		Off	Ethernet is disconnected on 10Mbps
WLAN	Green	On	Wireless Radio is enabled
		Blinking	Wireless Radio is enabled and data is transmitting
		Off	Wireless Radio is disabled (Mode LEDs should also disable)
RUN	Green	Off	System is not powered on
		Blinking Steadily	AP firmware is running normally
		Blinking Rapidly	AP firmware is not running

8 Emergency System Recovery

If your device becomes inaccessible and the management utility cannot find your device, please use the following procedure to recover your device over TFTP.

System Recovery Procedures

System recovery is based on the TFTP Client embedded in the device. It can recover the device from a bad firmware or other unknown reasons that corrupted the firmware image inside the flash. Follow the procedures below to force AW5500C to download a valid firmware from the TFTP Server to recover its Operating System.

Default Settings

TFTP Server	10.0.50.201
TFTP Server Subnet Mask	255.255.0.0
Name of firmware Image*	firmware.dld

*This firmware image can be obtained from Atop's website.

- If the device is beeping continuously after power up, the bootloader is damaged and there is no way to recover it; please contact directly Atop RMA for further solutions.
- Obtain and setup a **TFTP server** on your **PC**. Make sure that the **PC's network settings** are set properly according to the default above.
- Rename the firmware image that you obtained from our website to firmware.dld and place it in the TFTP Server's root directory. For Solarwinds TFTP Server, it is usually **C:\TFTP-Root**.
- Make sure that the device is powered OFF and the Ethernet cable is plugged in.
- Press and hold the reset to default pin under LAN Port then power ON the device. If the bootloader is still functioning, you will hear one long beep followed by two shorter beeps.

- Release the reset pin after you hear seven consecutive short beeps. You should see that the device requested files from your TFTP Server. Please wait until the device shows up on the management utility. This process could take five more minutes or more.

Important Note

You can download free TFTP Servers from the following locations:

Solarwinds TFTP Server	http://www.solarwinds.com/products/freetools/free_tftp_server.aspx
Note: for Solarwinds, please remember to Start the TFTP Server Service, the default is Stop.	
TFTPD32 TFTP Server	http://tftpd32.jounin.net/tftpd32.html

9 Warranty

Limited Warranty Conditions

Products supplied by us are covered in this warranty for undesired performance or defects resulting from shipping, or any other event deemed to be the result of Atop Technologies' mishandling. The warranty does not cover however, equipment which has been damaged due to accident, misuse, abuse, such as:

- Use of incorrect power supply, connectors, or maintenance procedures
- Use of accessories not sanctioned by us
- Improper or insufficient ventilation
- Improper or unauthorized repair
- Replacement with unauthorized parts
- Failure to follow Our operating Instructions
- Fire, flood, "Act of God", or any other contingencies beyond our control.

RMA and Shipping Reimbursement

- Customers must always obtain an authorized "RMA" number from us before shipping the goods to be repaired.
- When in normal use, a sold product shall be replaced with a new one within 3 months upon purchase. The shipping cost from the customer to us will be reimbursed.
- After 3 months and still within the warranty period, it is up to us whether to replace the unit with a new one; normally, as long as a product is under warranty, all parts and labor are free of charge to the customers.
- After the warranty period, the customer shall cover the cost for parts and labor.
- Three months after purchase, the shipping cost from you to us will not be reimbursed, but the shipping costs from us to the customer will be paid by us.

Limited Liability

Atop Technologies Inc., shall not be held responsible for any consequential losses from using our products.

Warranty

Atop Technologies Inc., gives a 5 years max for Wireless Access Point products.