

# Control box - FL RUGGED BOX OMNI-1 - 2701430

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



IP65 control box set for constructing wireless systems for industrial applications, incl. three 2.4/5 GHz omnidirectional antennas that can be directly screwed on, with DIN rail, plugs, and screw connections, without devices

## Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	1640.0 GRM
Custom tariff number	85177011
Country of origin	Germany

#### Technical data

#### **Dimensions**

Width	174 mm
Height	254 mm
Depth	137 mm

#### Ambient conditions

Degree of protection	IP66
Wireless set	Control box (with bore holes incl. sealing plugs, screw connections, and DIN rail), 3 omnidirectional antennas incl. antenna cable and RJ45 plug for field assembly

#### General

Housing material	polycarbonate



## Control box - FL RUGGED BOX OMNI-1 - 2701430

## Articles in set

Antenna - ANT-OMNI-2459-02 - 2701408



Omnidirectional antenna, 2.4 GHz/5 GHz, 2.5/5 dBi gain, linear vertical polarization, opening angle 2.4 GHz h/v 360°/30°, 5 GHz h/v 360°/16°, N (male), IP68; matching cable with panel feed-through Order No. 2701402

#### Antenna cable - RAD-PIG-EF316-N-RSMA - 2701402



Adapter cable, pigtail 50 cm, N (female) -> RSMA (male), insertion loss 0.75 dB at 2.4 GHz; 1.25 dB at 5 GHz, impedance 50 Ohm;

## Classifications

## eCl@ss

eCl@ss 4.0	27240409
eCl@ss 4.1	24010504
eCl@ss 5.0	19030112
eCl@ss 5.1	27242208
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208
eCl@ss 8.0	27242208

## **ETIM**

ETIM 3.0	EC001423
ETIM 4.0	EC001423
ETIM 5.0	EC001423

#### **UNSPSC**

UNSPSC 6.01	43172710
UNSPSC 7.0901	43223108
UNSPSC 11	43172710
UNSPSC 12.01	43223108
UNSPSC 13.2	43223108



## Control box - FL RUGGED BOX OMNI-1 - 2701430

## Accessories

Accessories

Mounting material

Mounting material - FL RUGGED BOX POLE SET - 2701205



Set for mast mounting of the FL RUGGED BOX housing, incl. screw clamps for masts up to 89 mm #

#### WLAN Ethernet device

Wireless module - FL WLAN 5100 - 2700718



WLAN access point, client, WLAN 802.11 a, b, g, n, frequency 2.4 GHz, 5 GHz, IP20, connections: Combicon for 10 ... 36 V DC, 2x RJ45 for LAN, central cluster management, WBM, 802.11i: WPA2, WPA-PSK, TKIP, AES, connections for 3 antennas (MIMO technology)

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com