APPLICA	BLE STAN	DARD										
OPERATING TEMPERATURE		= RANGE -35°C TO +85°C (NOTES 1)		TES 1)	STORAGE TEMPERATURE RAN				-10°C TO +60°C			
RATING VOLTAGE		30V AC			APPLICABLE CONNECTOR				BM14* (**) -24DP-0. 4V (**)			
L	CURRENT	0. 3A										
SPECIFICATIONS												
	EM		TEST METHOD				RE	QUII	REMENTS	QT	АТ	
CONSTR	RUCTION											
GENERAL EX	AMINATION	CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.					Х	
MARKING		CONFIRMED VISUALLY.								X	X	
	IC CHARA									_		
CONTACTE	RESISTANCE	20mV AC OR LESS 1khz,1m A .				200mΩ MAX.					_	
INSULATION RESISTANCE		100V DC.				50MΩ MIN.					_	
VOLTAGE PROOF		100V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.					X	<u> </u>	
MECHAN	NICAL CHA	I RACTI	FRISTICS									
MECHANIC			S INSERTIONS AND EXTRA	ACTIONS	S.	① CON	NTACT RE	SIST	TANCE: 200mΩ MAX.	Τ		
OPERATION						② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	_	
COUN	T D	ESCRIPTI	ON OF REVISIONS		DESIG	NED			CHECKED	DA	TE	
REMARKS NOTE1: INCL	UDE THE TEMP	ERATURE RISING BY CURRENT					APPROVED		KH. IKEDA	11. 07. 04		
							CHECKED DESIGNED		AR. TAKAHASHI SH. HOSODA	11. 07. 04 11. 07. 01		
Unless oth	erwise specif	ied, refer	ed, refer to JIS C 5402 and IEC 60512					DRAWN YN. SAKAMOTO		11.0		
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWING NO.			ELC4-331561		,, 01		
HS.	SI	PECIFI	CATION SHEET		PART			BM1	4JB-24DS-0. 4V (5			
11.7		HIROSE ELECTRIC CO., LTD.			CODE NO. CL684-8227-2-55		-8227-2-55	Δ	1/1			
	1					000E 140. 0E0						