



**Series: Internal Antenna** 

**Description: 5GHz PCB antenna** 

**PART NUMBER: W3919XXXX** 



## Features:

- 4900-5925 MHz
- Size 15.9 X 7.6 X 0.45 mm
- Efficiency > 60%
- VSWR < 2</li>
- Nominal impedance 50  $\Omega$
- Cable and connector can be customized


## **Applications:**

- WiFi 5GHz
- DSRC
- ISM band 5GHz radios
- IoT, M2M

All dimensions are in mm / inches

Issue: 1714

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34<sup>th</sup> St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4<sup>th</sup> Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



#### **TECHNICAL DATA SHEET**

**Description: 5GHz PCB antenna** 

**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

## This document covers all product variants of the following product family:

W3919B0050 50mm 1.13mm OD cable U.FL compatible connector

W3919B0100 100mm 1.13mm OD cable U.FL compatible connector

Issue: 1714

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:





**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

## **ELECTRICAL SPECIFICATIONS**

Frequency 4900-5925 MHz

Nominal Impedance 50  $\Omega$ 

VSWR <2

Gain 3 dBi +/- 1 dB

Efficiency 60 %

Radiation Pattern Omni

Polarization Linear

Power withstanding 2 W

Connector U.FL compatible connector

Cable type 1.13mm coaxial cable black

Cable length Optional

# (\*) All RF parameters measured on 2mm thick PC plate



#### **TECHNICAL DATA SHEET**

**Description: 5GHz PCB antenna** 

**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

## **MECHANICAL SPECIFICATIONS**

Radiator material FR4 PCB

Color Black

Adhesive 3M467

Thickness(with adhesive, no liner) 0.45 mm

PCB size(L X W X T) 15.9 X 7.6 X 0.45 mm

## **ENVIRONMENTAL SPECIFICATIONS**

Operating temperature

-40/+85 ° C








**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

## **MECHANICAL DRAWING**








**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

### **CHARTS**

## (\*) All RF parameters measured on 2mm thick PC plate

## Return Loss










**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

## **CHARTS**

# (\*) All RF parameters measured on 2mm thick PC plate



Issue: 1714

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



**Series: Internal Antenna** 

PART NUMBER: W3919XXXX

### **CHARTS**

Ζ Typical free space radiation pattern WIFI 5GHz (\*) All RF parameters measured on 2mm thick PC plate XY Plane 0 5 30 330 Avg (dBi) = -2.93Peak (dBi) = 1.86 -10 Avg - 3 (deg) = 13060 -15 300 5500MHz -20 Avg (dBi) = -2.93Peak (dBi) = 1.75 Rower (dBm) -25 Avg - 3 (deg) = 115-30 5925MHz 90 -35 Avg (dBi) = -2.92Peak (dBi) = 2.81Avg - 3 (deg) = 65120 240

Issue: 1714



4900MHz

5925MHz

5500MHz

210

180

150

Phi Angle



**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

## **CHARTS**

Typical free space radiation pattern WIFI 5GHz (\*) All RF parameters measured on 2mm thick PC plate **ZX Plane** 0 30 330 Avg (dBi) = 0.01Peak (dBi) = 3.29Avg -3 (deg) = 82. 60 -15 300 5500MHz -20 Avg (dBi) = -0.54Peak (dBi) = 3.37 -25 Rower (dBm) Avg - 3 (deg) = 75-30 5925MHz 90 35 Avg (dBi) = -1.06Peak (dBi) = 3.04Avg -3 (deg) = 62. 120 240 150 210 4900MHz 5500MHz

Issue: 1714

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



5925MHz

Theta Angle (°)

180




**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

## **CHARTS**

Typical free space radiation pattern WIFI 5GHz

(\*) All RF parameters measured on 2mm thick PC plate



Issue: 1714

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION







**Series: Internal Antenna** 

**PART NUMBER: W3919XXXX** 

## **PACKAGING**

10PCS/PE bag 10 PE bag/foam bag 50 foam bag/ carton box

Total 5000PCS/Carton box



