## Customer Information Sheet DRAWING No.: M80-620XXXX IF IN DOUBT - ASK NOT TO SCALE ALL DIMENSIONS IN mm SHEET 2 OF 2 THIRD ANGLE PROJECTION ORDER CODE: M80-620XXXX 2.00 x No. OF WAYS PER ROW + 3.55 MAX SECTION TOTAL No. OF WAYS -- 2.00 04. 06. 08. 10. 12. 14. 16. 18. 20. 26. 34. 44 FINISH: -**OBSOLETE** 5.60 MAX 22 = GOLD + TIN/LEAD 42 = GOLD + 100% TIN 45 = GOLDSPECIFICATIONS: MATERIAL: 0.38 MAX MOULDING = POLYAMIDE 46 UL94V-0, BLACK CONTACTS = PHOSPHOR BRONZE (7.0)LATCHES = BERYLLIUM COPPER FINISH: CONTACTS: RECOMMENDED 22 = 0.75 m GOLD ON CONTACT AREA. PCB LAYOUT 3 Ou 90/10 TIN/LEAD ON TAILS $\emptyset$ 0.50 TYP $\rightarrow$ 6.15 MAX 42 = 0.75 m GOLD ON CONTACT AREA 3.0 u 100% TIN ON TAILS .00 x No. OF 45 = 0.75µ GOLD **PITCHES** Ø0.80 MAX TYP ELECTRICAL: CURRENT RATING (25°C) = 3.0A MAX. 2.00 CURRENT RATING (85°C) = 2.2A MAX. WORKING VOLTAGE = 120V AC/DC VOLTAGE PROOF = 360V AC/DC CONTACT RESISTANCE (INITIAL) = 20 m $\Omega$ MAX. CONTACT RESISTANCE (AFTER CONDITIONING) = 25 m $\Omega$ MAX. INSULATION RESISTANCE 10.09.09 10478 (INITIAL) = 1000 $M\Omega$ MIN. INSULATION RESISTANCE DATE C/NOTE NAME ISS — 2.00 TYP (AFTER CONDITIONING) = 100 MO MIN. APPROVED: C.PENROSE 4.75 MECHANICAL: 2.00 x No.0F Ø 0.90 MIN TYP DURABILITY = 500 OPERATIONS CHECKED: R. ADDE PITCHES PER ROW ENVIRONMENTAL: STRAIN RELIEF STRAP HOLES TEMPERATURE RANGE =-55°C TO +125°C DRAWN: I. SANDY PACKING: CUSTOMER REF.: NOTES: FOR COMPLETE SPECIFICATION, SEE COMPONENT I. 2-OFF STRAIN RELIEF STRAPS SPECIFICATION COOSXX (LATEST ISSUE) ASSEMBLY DRG: M80-0780006 ARE INCLUDED WITH FACH CONNECTOR. DATAMATE DIL THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE **TOLERANCES** MATERIAL: TITLE: HORIZONTAL PC TAIL PLUG MATTER SET OUT HEREON ARE X. = ±1mm SEE ABOVE CONFIDENTIAL AND COPYRIGHT $X.X = \pm 0.25 mm$ ASSEMBLY - UNLATCHED PROPERTY OF THE HARWIN $X.XX = \pm 0.10$ mm GROUP AND MUST NOT BE HARWLN USA HARWIN Europe (UK) HARWIN Asia DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, $X.XXX = \pm 0.01$ mm DRAWING NUMBER: SHT FINISH: SEE ABOVE TEL: 603 893 5376 TEL: 023 9231 4545 TEL: +65 6 779 4909 TENDERING OR FOR ANY ANGLES = ±5° M80-620XXXX FAX: 603 893 5396 FAX: 023 9231 4590 FAX: +65 6 779 3868 OTHER PURPOSE WITHOUT mm<sup>2</sup> S/AREA: mis@harwin.co.uk mis@harwin.com.sq mis@harwin.com THEIR WRITTEN PERMISSION UNLESS STATED