

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

LOC

DIST

REVISIONS

© COPYRIGHT 20

ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
	E	REVISED AND REDRAWN PER E.O. A5916	4-10-87	JN	JA
	F	REVISED PER E.O. P21133	9-29-11	IG	RDR
	G	REVISED PER E.O. P21366	6-4-12	IG	RDR
	G2	REVISED PER ECO-13-010849	6-13-13	JA	IG

4. FOR "PERFORMANCE AND APPLICATION CHARACTERISTICS OF SOLID/STAMPED AND FORMED CONTACTS AND WIRES," SEE ENVELOPE DRAWING 0425-015-0000. THIS PLUG USES SOCKET CONTACTS ONLY.

3. DELETED.

2. THIS CONNECTOR SERIES WILL ACCOMMODATE THE FOLLOWING WIRE INSULATION DIAMETERS:

CONTACT SIZE	MINIMUM O.D.	MAXIMUM O.D.
16	.100 [2.54]	.150 [3.81]

1. CONSULT FACTORY FOR ELECTRICAL AND MATERIAL SPECIFICATIONS.

8. DELETED.

7. MATERIAL: SHELL: PLASTIC; SEAL: RUBBER

△ 6 OVERALL DIMENSION DOES NOT INCLUDE RUBBER GROMMET.

5. THIS PLUG MATES WITH HD10-5-16P*-**** AND HD14-5-16P*-**** RECEPTACLES (* = SEAL TYPE, **** = ALL MODIFICATIONS).

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 12 JUN 2013 JAIME C. APOSTOL		 TE Connectivity	
DIMENSIONS: INCHES [mm]		TOLERANCES UNLESS OTHERWISE SPECIFIED:			
		0 PLC ±		NAME PLUG CONNECTOR ARR. 5-16	
		1 PLC ±		COLOR: GRAY, HD10 SERIES	
MATERIAL		2 PLC ±		DRAWING NO	
		3 PLC ±.025 [.64]		RESTRICTED TO	
FINISH		4 PLC ±		SIZE	
		ANGLES ± ±0°30'0"		CAGE CODE	
WEIGHT		20.35g		DRAWING NO	
CUSTOMER DRAWING		SCALE 2.5		SHEET 1 OF 1	
		REV G2			

1470-19 (3/11)