APPLICA	BLE STAN	DARD										
OPERATING TEMPERATUR		RE RANGE	-35°C TO 85°C(NOTE 1)		ТЕМ		JRE RANGE		-10°C TO 60°C			
RATING	VOLTAGE		1 001/40			LICABLE INECTOR			BM14C(0.8)-24DS-0	4V (>	**)	
	CURRENT		0. 3A									
	•		SPECI	FICA	ATIOI	NS						
	ГЕМ	TEST METHOD				REQUIREMENTS QT A						
	RUCTION	VICIALLY AND DV MEACUDING INCTRUMENT				AGGORDING TO DRAWING						
MARKING	EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.			ACCORDING TO DRAWING.				X	X		
		CTERISTICS								1^	1^	
						100mΩ MAX.				X	Ι_	
INSULATION RESISTANCE		100V DC.			50MΩ MIN.				X	<u> </u>		
VOLTAGE PROOF		100V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.				X	 		
MECHA	NICAL CHA	RACTI	ERISTICS							1 ^	<u> </u>	
MECHANICAL OPERATION		10TIMES INSERTIONS AND EXTRACTIONS.				 CONTACT RESISTANCE: 100mΩ MAX. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 				X	-	
VIBRATION		FREQUENCY 10 TO 55 TO 10 Hz,APPROX 5min, SINGLE AMPLITUDE 0.75 mm,10CYCLES, FOR 3 DIRECTIONS.				NO ELECTRICAL DISCONTINUITY OF 1 µs. NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				Х	-	
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				Х	-	
ENVIRO	NMENTAL	CHAR	ACTERISTICS									
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → +85°C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHANBER : WITHIN 2-3 min)				① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.					-	
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.			 CONTACT RESISTANCE: 100mΩ MAX. INSULATION RESISTANCE: 25MΩ MIN. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 				X	-		
SULPHUR DIIOXIDE		EXPOSED IN 25 PPM FOR 96h,25°C,75%. (REFER TO JIS C 60068)							Х	_		
COUN	IT D	ESCRIPTI	CRIPTION OF REVISIONS DESI		DESIG	3NED			CHECKED	DA	ATE	
REMARKS						A D D D D D D D D D D D D D D D D D D D	, I	W. 1165		10.0=		
	UDE THE TEMP	ERATURE RISING BY CURRENT				APPROV CHECK	-			12. 25 12. 25		
					DESIGNED		-	TR. YUNOK I	10. 12. 25			
	·	ied, refer to JIS C 5402 and IEC 60512.				DRAWN		N			12. 25	
		t AT:Assurance Test X:Applicable Test				RAWING NO.			ELC4-324416-01			
HS.		PECIFICATION SHEET			PART NO.		BM14C (0. 8) -24DP-0. 4			_	ı	
L HIR		ROSE ELECTRIC CO., LTD.			CODE NO.		CL	CL684-8026-0-51 🔼			1/1	