SPI	ECIFICATION CO	SCD 55A0144				
ïtle	FOUR CONDUCTOR CABLE GENERAL PUF	, UNSHIELDED, UN RPOSE, 600 VOLT	IJACKETED,	Date 2-12-16	Revision E	
	This specification sh	eet forms a part of th	he latest issue of Raychem S	pecification 55A.		
со	MPONENT WIRES - 55A0114		RUCTION DETAILS			
		CONDUCTOR	OUTSIDE DIAMETER	MAXIMUM		

PART NUMBER <u>1</u> /	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)
	( - )	NOMINAL	MAXIMUM	( ,
55A0144-30-*	30	.058	.071	2.7
55A0144-28-*	28	.065	.079	3.7
55A0144-26-*	26	.077	.093	5.7
55A0144-24-*	24	.090	.106	8.2
55A0144-22-*	22	.104	.123	11.8
55A0144-20-*	20	.121	.142	18.0
55A0144-18-*	18	.145	.169	26.5
55A0144-16-*	16	.165	.191	33.9

## CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C Maximum continuous conductor temperature VOLTAGE RATING: 600 volts (rms) at sea level DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz INSULATION FLAWS: Spark Test, 5.7 kV (rms) at 3 kHz Impulse Dielectric Test, 8.0 kV (peak) 1/ PART NUMBER:

The "\*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors. Colors shown do not necessarily reflect the sequence of manufacturing.

Example: AWG 22, black, brown, red, and orange component wires: 55A0144-22-0/1/2/3

NOTE: Nominal values are for information only. Nominal values are not requirements.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.							
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902" MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.							
Page 1 of 1	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.		Raychem Wire & Cable				
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL		501 Oakside Avenue Redwood City, CA 94063-3800				
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.	connectivity	Phone: 1-800-227-8816 Fax: 1-650-361-6297				