molex
one company › a world of innovation

This document was generated on 04/08/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 15166-0352

Status: Active

Overview: Premo-Flex™ FFC and Etched Polyimide Jumpers

Description: 0.50mm Pitch Premo-Flex™ FFC Jumper, Opposite Side Contacts (Type D), 32 Circuits, 0.203m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating

Series

image - Reference only

Documents:

Drawing (PDF)
Product Specification PS-15166-001 (PDF)
Packaging Specification PK-15166-001 (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	Cable
Series	15166
Comments	Contacts on opposite sides, Type D
Crimp Quality Equipment	Yes
Overview	Premo-Flex™ FFC and Etched Polyimide Jumpers
Product Name	Premo-Flex™FFC Jumper
UPC	884982848504

Physical

Cable Length	0.203m
Circuits (Loaded)	32
Circuits (maximum)	32
Net Weight	1.000/g
Packaging Type	Bag
Pitch - Termination Interface	0.50mm
Temperature Range - Operating	-40°C to +105°C
Wire Size AWG	N/A
Wire/Cable Type	Flat Flex Cable

Electrical

Current - Maximum per Contact	0.5A
Voltage - Maximum	60V AC

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-15166-001
Product Specification	PS-15166-001
Sales Drawing	SD-15166-001

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
15166Series

Use With
www.molex.com/product/ffcfpc_th.html

This document was generated on 04/08/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION