

# PRODUCT DATASHEET CA10929\_BOOM-W

### **BOOM-W**

~55° wide beam. Assembly with 0.4 mm thick installation tape.

### **TECHNICAL SPECIFICATIONS:**

Dimensions 22.2 mm Height 13.7 mm

Fastening tape
Colour metal

Box size 480 x 280 x 300 mm

Box weight 4.4 kg

Quantity in Box 1680 pcs

ROHS compliant yes (1)



#### **MATERIAL SPECIFICATIONS:**

Component	Туре	Material	Colour
BOOM-MC-W	Reflector	PC	metal
TINA-TAPE3	Tape	PU tape	black

# PRODUCT DATASHEET CA10929\_BOOM-W

### PHOTOMETRIC DATA (MEASURED):

### CREE 💠

LED MC-E

FWHM 54.0°

Efficiency %

Peak intensity 1.160 cd/lm

Required components:

### CREE \$


LED XR-E

FWHM 56.0° Efficiency 91 %

Peak intensity 1.300 cd/lm

Required components:







## PRODUCT DATASHEET CA10929 BOOM-W

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

www.ledil.com/ where\_to\_buy