Micro-Fit* TPA Cable Assemblies



Standard Micro-Fit* TPA Cable Assemblies deliver an off-the-shelf solution with a variety of cable lengths and a 3.00mm-pitch connector with a 5.0A maximum current rating to facilitate both prototyping and global production

Features and Advantages UL 1061 discrete wires Ready to use in electronic Multi-color cable configurations with appliance applications. Micro-Fit* TPA Receptacles available off the shelf Provide ease of design, Designed to support development and production prototyping and production programs. Multi-color cables ensure correct connection Micro-Fit* TPA Receptacles' 5.0A current rating and Assembled in ISO/TS16949-3.00mm pitch certified facilities Delivers a high-density, lower Ensures high quality. Meets

Applications

terminal back-out

Consumer / Home Appliance

power connection. Reduces

Harness manufacturers

Appliances

Data / Computing

Harness manufacturers

Desktops

Workstations

Power supplies

Uninterruptible Power Supply (UPS)

Telecommunications / Networking

Harness manufacturers

Servers

Routers

Switches

Automotive / Commercial Vehicle

Harness manufacturers

Non-sealed applications

Inside devices



Meets 2011/65/EU RoHS Compliance Decreases engineering time and resources

Workstation



Refrigerator



standards

current automotive industry

Servers

^{*}Micro-Fit is a trademark of Molex, LLC in the United States and may be registered in certain jurisdictions.

Micro-Fit* TPA Cable Assemblies



Specifications

REFERENCE INFORMATION

Connector UL File No.: E29179 CSA File No.: LR19980

Mates With:

Micro-Fit* 3.0 Connectors Use With: Micro-Fit* Headers Designed In: Millimeters

RoHS: Yes Halogen Free: No Glow Wire Compliant: No **ELECTRICAL**

Voltage (max.): 600V Current (max.):5.0

MECHANICAL

Contact Insertion Force (max.): 14.7N per contact Contact Retention to Housing (min.): 24.5N Mating Force (max.): 8N per circuit

Durability (max.):typically 30 cycles, refer to product

specifications

PHYSICAL

Housing: Nylon

Operating Temperature: -40 to +105°C

Ordering Information

Series No.	Product	Circuits	Lengths (m)
<u>45132</u>	Off-the-Shelf Micro-Fit* TPA Discrete Wire Cable Assemblies	4, 6, 8	1.0, 1.5, 3.0

Custom Product	Description
Contact Molex	Micro-Fit* TPA Discrete Wire Cable Assembly Custom lengths and other options

^{*}Micro-Fit is a trademark of Molex, LLC in the United States and may be registered in certain jurisdictions.