C&K

product details.



C&K

Image may be representation. See specifications for

7205T1PCQE

Part Number:

Manufacturer/Brand: Product description

Datasheets: RoHs Status Stock Condition

Ship From Shipment Way 7205T1PCQE

C&K

SWITCH TOGGLE DPDT 5A 120V

7205T1PCQE.pdf

Lead free / RoHS Compliant 7738 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER MANUFACTURER C&K DESCRIPTION SWITCH TOGGLE DPDT 5A 120V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 7738 pcs DATA SHEET 7738 pcs DATA SHEET VOLTAGE RATING - DC VOLTAGE RATING - AC 120V TERMINATION STYLE PC Pin SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING Bulk OPERATING TEMPERATURE 730°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1.LLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR 1.LLUMINATION PEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD		Specifications of 7205T1PCQE	
MANUFACTURER DESCRIPTION SWITCH TOGGLE DPDT 5A 120V LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 7738 pcs DATA SHEET DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 120V TERMINATION STYLE PC Pin SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia Bulk OPERATING TEMPERATURE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS COMPILIANT INGRESS PROTECTION 1. LLUMINATION VOLTAGE (NOMINAL) 1. LLUMINATION TYPE, COLOR 1. LLUMINATION PEATURES EDOXY Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD		Specifications of 720311FCQL	
DESCRIPTION SWITCH TOGGLE DPDT SA 120V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant 7738 pcs DATA SHEET ₹ 7205T1PCQE.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 120V TERMINATION STYLE PC Pin SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD free STATUS / ROHS STATUS LEAD free STATUS / ROHS COMPLIANT INGRESS PROTECTION 1. LLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR 1. LLUMINATION FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD	PART NUMBER	7205T1PCQE	
LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 7738 pcs DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 120V TERMINATION STYLE PC Pin SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD free STATUS / ROHS STATUS LEAD free STATUS / ROHS COMMINAL) ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION FEATURES EPOXY Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD	MANUFACTURER	C&K	
QUANTITY AVAILABLE DATA SHEET DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 120V TERMINATION STYLE PC PIN SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS COMMINAL) ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD	DESCRIPTION	SWITCH TOGGLE DPDT 5A 120V	
DATA SHEET DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 120V TERMINATION STYLE PC Pin SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS COMMINAL) ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
VOLTAGE RATING - DC VOLTAGE RATING - AC 120V TERMINATION STYLE PC PIN SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING SA (AC/DC) CIRCUIT DPDT BUSHING THREAD	QUANTITY AVAILABLE	7738 pcs	
VOLTAGE RATING - AC TERMINATION STYLE PC PIN SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING DERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAd Free / ROHS Compliant INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR JILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING SA (AC/DC) CIRCUIT DPDT BUSHING THREAD	DATA SHEET	7205T1PCQE.pdf	
TERMINATION STYLE SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION PEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING CIRCUIT DPDT BUSHING THREAD	VOLTAGE RATING - DC	28V	
SWITCH FUNCTION Mom-Off-Mom SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION TOGGLE SWItch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD 15/32-32	VOLTAGE RATING - AC	120V	
SERIES 7000 PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING BUIK OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES EDOXY Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION TOggle Switch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD 15/32-32	TERMINATION STYLE	PC Pin	
PANEL CUTOUT DIMENSIONS Circular - 11.91mm Dia PACKAGING Bulk OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING SA (AC/DC) CIRCUIT DPDT BUSHING THREAD	SWITCH FUNCTION	Mom-Off-Mom	
PACKAGING OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT BUSHING THREAD 15/32-32	SERIES	7000	
OPERATING TEMPERATURE -30°C ~ 85°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING SA (AC/DC) CIRCUIT DPDT BUSHING THREAD	PANEL CUTOUT DIMENSIONS	Circular - 11.91mm Dia	
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING CIRCUIT DPDT BUSHING THREAD	PACKAGING	Bulk	
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING SA (AC/DC) CIRCUIT DPDT BUSHING THREAD	OPERATING TEMPERATURE	-30°C ~ 85°C	
LEAD FREE STATUS / ROHS STATUS INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING SA (AC/DC) CIRCUIT DPDT BUSHING THREAD Lead free / RoHS Compliant - CHARLED COMPLIANT TOGGLE AND COMPLIANT Lead free / RoHS Compliant - CHARLED COMPLIANT TOGGLE Switch DPDT Panel Mount DPDT BUSHING THREAD	MOUNTING TYPE	Panel Mount	
INGRESS PROTECTION - ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD 15/32-32	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)	
ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD 15/32-32	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
ILLUMINATION TYPE, COLOR-ILLUMINATIONNon-IlluminatedFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch DPDT Panel MountCURRENT RATING5A (AC/DC)CIRCUITDPDTBUSHING THREAD15/32-32	INGRESS PROTECTION	-	
ILLUMINATIONNon-IlluminatedFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch DPDT Panel MountCURRENT RATING5A (AC/DC)CIRCUITDPDTBUSHING THREAD15/32-32	ILLUMINATION VOLTAGE (NOMINAL)	-	
FEATURESEpoxy Sealed TerminalsELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch DPDT Panel MountCURRENT RATING5A (AC/DC)CIRCUITDPDTBUSHING THREAD15/32-32	ILLUMINATION TYPE, COLOR	-	
ELECTRICAL LIFE 40,000 Cycles DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD 15/32-32	ILLUMINATION	Non-Illuminated	
DETAILED DESCRIPTION Toggle Switch DPDT Panel Mount 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD 15/32-32	FEATURES	Epoxy Sealed Terminals	
CURRENT RATING 5A (AC/DC) CIRCUIT DPDT BUSHING THREAD 15/32-32	ELECTRICAL LIFE	40,000 Cycles	
CIRCUIT DPDT BUSHING THREAD 15/32-32	DETAILED DESCRIPTION	Toggle Switch DPDT Panel Mount	
BUSHING THREAD 15/32-32	CURRENT RATING	5A (AC/DC)	
,	CIRCUIT	DPDT	
ACTUATOR TYPE Anti-Rotation	BUSHING THREAD	15/32-32	
AND THE PARTY OF T	ACTUATOR TYPE	Anti-Rotation	
ACTUATOR MATERIAL Brass, Chrome Plated	ACTUATOR MATERIAL	Brass, Chrome Plated	

Related Tags

12.37mm

C&K 7205T1PCQE	7205T1PCQE Distributor	7205T1PCQE Supplier
7205T1PCQE Price	7205T1PCQE Pictures	7205T1PCQE Image
7205T1PCQE PDF Datasheet	7205T1PCQE Download Datasheet	7205T1PCQE Datasheet
7205T1PCQE Stock	Buy 7205T1PCQE	Buy C&K 7205T1PCQE
C&K 7205T1PCQE	C&K Supplier	C&K Distributor
C&K 7205T1PCQE	C&K Components 7205T1PCQE	

Related Products



ACTUATOR LENGTH

7205T1CWZ3QE Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V In stock: 7797 pcs

RFQ



7205T1PV31QE

Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V In stock: 6065 pcs

RFQ



7205T1PZGE

Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V In stock: 6555 pcs

RFQ

7205T1PZ3QE

Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V In stock: 6940 pcs

RFQ



7205T1CWZQI

Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V In stock: 6371 pcs

RFQ

7205T1CWZBE

Manufacturers: C&K Description: SWITCH TOGGLE DPDT 0.4VA 20V

In stock: 7857 pcs

RFQ



7205T1PZQE Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V

In stock: 6389 pcs

RFQ



7205T1CWZGE Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V

In stock: 7669 pcs

RFQ



7205T1CWCQI Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V In stock: 6588 pcs

RFQ



7205T1CWZQE Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V

In stock: 6668 pcs **RFQ**



7205T1PZQI Manufacturers: C&K

Description: SWITCH TOGGLE DPDT 5A 120V In stock: 6676 pcs

RFQ



7205T1PZBE

Manufacturers: C&K Description: SWITCH TOGGLE DPDT 0.4VA 20V

In stock: 6874 pcs

RFQ



Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong











