Grayhill





Grayhill, Inc.

### 44M45-02B08S

Part Number:

Manufacturer/Brand:

Product description Datasheets:

Stock Condition Ship From

Shipment Way

RoHs Status

44M45-02B08S

Grayhill, Inc.

SWITCH ROTARY 85 DEG;C, 45 DEG 2

**K** RoHS Compliant 1149 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

PART NUMBER  44M45-02808S  MANUPACTURER  Grayhill, Inc.  DESCRIPTION  SWITCH ROTARY 85 DEG;C, 45 DEG 2  LEAD FREE STATUS / ROHS STATUS  ROHS Compiliant  QUANTITY AVAILABLE  DATA SHEET  VOLTAGE RATING - DC  28V  VOLTAGE RATING - DC  VOLTAGE RATING - DC  SOIder Lug  SERIES  44  ROHS Compiliant  PANEL CUTOUT DIMENSIONS  OPERATING FORCE  5.761 ~ 83g/fm  NUMBER OF POLES PER DECX  MUMBER OF POLES PER DECX  MUMBER OF POLES PER DECX  MUMBER OF DEGS  MUUNTING TYPE  Panel Mount  INDEX STOPS  Fixed  FEATURES  -  DETAILED DESCRIPTION  ROTARY SWIRCH 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL  -  CURRENT RATING  SA (AC), 1A (DC)  CONTACT TIMING  SHORT MINES  CONTACT TIMING  SHORT MINES  ACTUATOR LENGTH  1.10mm  ACTUATOR LENGTH  1.110mm		Sr	pecifications of 44M45-02B08S
MANUFACTURER         Grayhill, Inc.           DESCRIPTION         SWITCH ROTARY 85 DEG;C, 45 DEG 2           LEAD FREE STATUS / ROHS STATUS         RoHS Compliant           QUANTITY AVAILABLE         1149 pcs           DATA SHEET         VOLTAGE RATING - DC           VOLTAGE RATING - AC         115V           TERMINATION STYLE         Solder Lug           SERIES         44           ROHS STATUS         ROHS Compliant           PANEL CUTOUT DIMENSIONS         -           OPERATING FORCE         5.761 ~ 83gfm           NUMBER OF POSITIONS         8           NUMBER OF POEIS PER DECK         1           NUMBER OF DECKS         -           MOUNTING TYPE         Panel Mount           INDEX STOPS         Fixed           FEATURES         -           DETAILED DESCRIPTION         Rotary Switch 8 Position SP8T SA (AC), 1A (DC) 115VAC Panel Mount           DETAILED DESCRIPTION         Rotary Switch 8 Position SP8T SA (AC), 1A (DC) 115VAC Panel Mount           CURRENT RATING         SA (AC), 1A (DC)           CONTACT THINING         Shorting (MBB)           CONTACT THINING         Shorting (MBB)           CONTACT THINING         Shorting (MBB)           CONTACT THINING         Shorting (MBB)     <		3	Declifications of 44M45-02D005
DESCRIPTION SWITCH ROTARY 85 DEG;C, 45 DEG 2  LEAD FREE STATUS / ROHS STATUS ROHS Compliant  QUANTITY AVAILABLE 1149 pcs  DATA SHEET  VOLTAGE RATING - DC 28V  VOLTAGE RATING - AC 115V  TERMINATION STYLE Solder Lug  SERIES 44  ROHS CAMPILIANS ROHS COMPLIANS  ROHS COMPLIANT  PANEL CUTOUT DIMENSIONS - ROHS COMPLIANT  NUMBER OF POSITIONS 8  NUMBER OF POSITIONS 8  NUMBER OF POSITIONS 8  NUMBER OF DECKS - ROHE Mount  INDEX STOPS Fixed  FEATURES - Panel Mount  INDEX STOPS Fixed  FEATURES - CONTACT THINING SHOTION ROTARY SWITCH 8 Position SPRT SA (AC), 1A (DC) 115VAC Panel Mount  CONTACT THINING SHOTION SHOTION SHOTION (MBB)  CONTACT THROW 45°  ACTUATOR TYPE FIREDOX  PRINT PATHON (MBC)  CIRCUIT PER DECK SPRT  ANGLE OF THROW 45°  FIRED SHOTION (MBC)  CIRCUIT PER DECK SPRT  ANGLE OF THROW 45°		PART NUMBER	44M45-02B08S
LEAD FREE STATUS / ROHS STATUS     RoHS Compilant       QUANTITY AVAILABLE     1149 pcs       DATA SHEET     28V       VOLTAGE RATING - DC     28V       VOLTAGE RATING - AC     115V       TERMINATION STYLE     Solder Lug       SERIES     44       ROHS STATUS     ROHS Compliant       PANEL CUTOUT DIMENSIONS     -       OPERATING FORCE     5.761 ~ 83gfm       NUMBER OF POSITIONS     8       NUMBER OF POLES PER DECK     1       NUMBER OF DECKS     -       MOUNTING TYPE     Panel Mount       INDEX STOPS     Fixed       FEATURES     -       DETAILED DESCRIPTION     Rotary Switch 8 Position SP8T 5A (AC), IA (DC) 115VAC Panel Mount       DETAILED DESCRIPTION     Rotary Switch 8 Position SP8T 5A (AC), IA (DC) 115VAC Panel Mount       CORTACT TIMING     5A (AC), IA (DC)       CONTACT TIMING     Shorting (MBB)       CONTACT TIMING     Shorting (MBB)       CONTACT FINISH     -       CIRCUIT PER DECK     SP8T       ANGLE OF THROW     45°       ACTUATOR TYPE     Flatted (6.35mm Dia)		MANUFACTURER	Grayhill, Inc.
QUANTITY AVAILABLE DATA SHEET  VOLTAGE RATING - DC 28V  VOLTAGE RATING - AC 115V  TERMINATION STYLE Solder Lug  SERIES 44  ROHS STATUS ROHS COMPIBANK  PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm  NUMBER OF POSITIONS 8  NUMBER OF POLES PER DECK 1  NUMBER OF DECKS - MOUNTING TYPE Panel Mount  INDEX STOPS Fixed  FEATURES - DETAILED DESCRIPTION RORAY SWItch & Position SPRT 5A (AC), 1A (DC) 115VAC Panel Mount  CURRENT RATING CONTACT TIMING Shorting (MBB)  CONTACT TIMING SONG CONTACT TIMING CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 45° RATCUATOR TYPE Flatted (6.35mm Dia)		DESCRIPTION	SWITCH ROTARY 85 DEG;C, 45 DEG 2
DATA SHEET  VOLTAGE RATING - DC  28V  VOLTAGE RATING - AC  115V  TERMINATION STYLE  Solder Lug  SERIES  44  ROHS STATUS  ROHS COMPIANT  PANEL CUTOUT DIMENSIONS  - OPERATING FORCE  5.761 ~ 83gfm  NUMBER OF POSITIONS  8  NUMBER OF POSITIONS  8  NUMBER OF POLES PER DECK  1  NUMBER OF DECKS  - MOUNTING TYPE  Panel Mount  INDEX STOPS  Fixed  FEATURES  - DETAILED DESCRIPTION  ROTAGY SWIRCH 8 POSITION SPRT 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL  CURRENT RATING  CONTACT TIMING  Shorting (MBB)  CONTACT TIMING  SIVER Alloy  CONTACT FINISH  - CIRCUIT PER DECK  ANGLE OF THROW  45°  Flatted (6.35mm Dia)		LEAD FREE STATUS / ROHS STATUS	RoHS Compliant
VOLTAGE RATING - DC       28V         VOLTAGE RATING - AC       115V         TERMINATION STYLE       Solder Lug         SERIES       44         ROHS STATUS       ROHS Compliant         PANEL CUTOUT DIMENSIONS       -         OPERATING FORCE       5.761 ~ 83gfm         NUMBER OF POSITIONS       8         NUMBER OF POLES PER DECX       1         NUMBER OF DECKS       -         MOUNTING TYPE       Panel Mount         INDEX STOPS       Fixed         FEATURES       -         DETAILED DESCRIPTION       Rotary Switch 8 Position SP8T SA (AC), 1A (DC) 115VAC Panel Mount         DETHIND PANEL       -         CURRENT RATING       SA (AC), 1A (DC)         CONTACT TIMING       Shorting (MBB)         CONTACT TIMISH       -         CIRCUIT PER DECK       SP8T         ANGLE OF THROW       45°         ACTUATOR TYPE       Flatted (6.35mm Dia)		QUANTITY AVAILABLE	1149 pcs
VOLTAGE RATING - AC     115V       TERNINATION STYLE     Solder Lug       SERIES     44       ROHS STATUS     ROHS Compilant       PANEL CUTOUT DIMENSIONS     -       OPERATING FORCE     5.761 ~ 83gfm       NUMBER OF POSITIONS     8       NUMBER OF POLES PER DECK     1       NUMBER OF DECKS     -       MOUNTING TYPE     Panel Mount       INDEX STOPS     Fixed       FEATURES     -       DETAILED DESCRIPTION     Rotary Switch 8 Position SP8T SA (AC), 1A (DC) 115VAC Panel Mount       DEPTH BEHIND PANEL     -       CURRENT RATING     SA (AC), 1A (DC)       CONTACT TIMING     Shorting (MBB)       CONTACT TIMISH     -       CIRCUIT PER DECK     SP8T       ANGLE OF THROW     45°       ACTUATOR TYPE     Flatted (6.35mm Dia)		DATA SHEET	
TERMINATION STYLE  SERIES  44  ROHS STATUS  ROHS Compliant  PANEL CUTOUT DIMENSIONS  - OPERATING FORCE  5.761 ~ 83gfm  NUMBER OF POSITIONS  8  NUMBER OF POLES PER DECK  1  NUMBER OF DECKS  - MOUNTING TYPE  Panel Mount  INDEX STOPS  Fixed  FEATURES  - DETAILED DESCRIPTION  Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL  - CURRENT RATING  CONTACT TIMING  Shorting (MBB)  CONTACT FINISH  - CIRCUIT PER DECK  ANGLE OF THROW  45°  Flated (6.35mm Dia)		VOLTAGE RATING - DC	28V
SERIES 44  ROHS STATUS ROHS Compliant  PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm  NUMBER OF POSITIONS 8  NUMBER OF POLES PER DECK 1  NUMBER OF DECKS - MOUNTING TYPE Panel Mount INDEX STOPS Fixed  FEATURES - DETAILED DESCRIPTION Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL - CURRENT RATING 5A (AC), 1A (DC)  CONTACT TIMING Shorting (MBB)  CONTACT FINISH - CIRCUIT PER DECK SP8T  ANGLE OF THROW 45°  Flatted (6.35mm Dia)		VOLTAGE RATING - AC	115V
ROHS STATUS  ROHS COMPILIANT  PANEL CUTOUT DIMENSIONS  - OPERATING FORCE  5.761 ~ 83gfm  NUMBER OF POSITIONS  8 NUMBER OF POLES PER DECK  1 NUMBER OF DECKS  - MOUNTING TYPE  Panel Mount  INDEX STOPS  Fixed  FEATURES  - DETAILED DESCRIPTION  ROTATY SWITCH 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL  - CURRENT RATING  5A (AC), 1A (DC)  CONTACT TIMING  CONTACT TIMING  CONTACT FINISH  - CURCUIT PER DECK  SP8T  ANGLE OF THROW  45°  Flatted (6.35mm Dia)		TERMINATION STYLE	Solder Lug
PANEL CUTOUT DIMENSIONS  OPERATING FORCE  5.761 ~ 83gfm  NUMBER OF POSITIONS  8  NUMBER OF POLES PER DECK  1  NUMBER OF DECKS  - MOUNTING TYPE  Panel Mount  INDEX STOPS  Fixed  FEATURES  - DETAILED DESCRIPTION  ROTAGY Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  CURRENT RATING  CONTACT TIMING  CONTACT TIMING  CONTACT FINISH  CIRCUIT PER DECK  ANGLE OF THROW  45°  Fatted (6.35mm Dia)		SERIES	44
OPERATING FORCE       5.761 ~ 83gfm         NUMBER OF POSITIONS       8         NUMBER OF POLES PER DECK       1         NUMBER OF DECKS       -         MOUNTING TYPE       Panel Mount         INDEX STOPS       Fixed         FEATURES       -         DETAILED DESCRIPTION       Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount         DEPTH BEHIND PANEL       -         CURRENT RATING       SA (AC), 1A (DC)         CONTACT TIMING       Shorting (MBB)         CONTACT MATERIAL       Silver Alloy         CONTACT FINISH       -         CIRCUIT PER DECK       SP8T         ANGLE OF THROW       45°         ACTUATOR TYPE       Flatted (6.35mm Dia)		ROHS STATUS	RoHS Compliant
NUMBER OF POSITIONS  8  NUMBER OF POLES PER DECK  1  NUMBER OF DECKS  -  MOUNTING TYPE  Panel Mount  INDEX STOPS  Fixed  FEATURES  -  DETAILED DESCRIPTION  Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  CURRENT RATING  CONTACT TIMING  Shorting (MBB)  CONTACT TIMING  Silver Alloy  CONTACT FINISH  -  CIRCUIT PER DECK  SP8T  ANGLE OF THROW  ACTUATOR TYPE  Flatted (6.35mm Dia)		PANEL CUTOUT DIMENSIONS	
NUMBER OF POLES PER DECK       1         NUMBER OF DECKS       -         MOUNTING TYPE       Panel Mount         INDEX STOPS       Fixed         FEATURES       -         DETAILED DESCRIPTION       Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount         DEPTH BEHIND PANEL       -         CURRENT RATING       5A (AC), 1A (DC)         CONTACT TIMING       Shorting (MBB)         CONTACT MATERIAL       Silver Alloy         CONTACT FINISH       -         CIRCUIT PER DECK       SP8T         ANGLE OF THROW       45°         ACTUATOR TYPE       Flatted (6.35mm Dia)		OPERATING FORCE	5.761 ~ 83gfm
NUMBER OF DECKS  MOUNTING TYPE Panel Mount  INDEX STOPS Fixed  FEATURES - DETAILED DESCRIPTION Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL - CURRENT RATING SA (AC), 1A (DC)  CONTACT TIMING Shorting (MBB)  CONTACT TIMISH - CIRCUIT PER DECK ANGLE OF THROW 45°  ACTUATOR TYPE Flatted (6.35mm Dia)		NUMBER OF POSITIONS	8
MOUNTING TYPE Panel Mount  INDEX STOPS Fixed  FEATURES -  DETAILED DESCRIPTION Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL -  CURRENT RATING 5A (AC), 1A (DC)  CONTACT TIMING Shorting (MBB)  CONTACT MATERIAL Silver Alloy  CONTACT FINISH -  CIRCUIT PER DECK SP8T  ANGLE OF THROW 45°  ACTUATOR TYPE Flatted (6.35mm Dia)		NUMBER OF POLES PER DECK	1
INDEX STOPS FEATURES - DETAILED DESCRIPTION Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL - CURRENT RATING SA (AC), 1A (DC)  CONTACT TIMING Shorting (MBB)  CONTACT MATERIAL Silver Alloy  CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW 45°  Flatted (6.35mm Dia)		NUMBER OF DECKS	-
FEATURES  DETAILED DESCRIPTION  Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount  DEPTH BEHIND PANEL  CURRENT RATING  5A (AC), 1A (DC)  CONTACT TIMING  Shorting (MBB)  CONTACT MATERIAL  Silver Alloy  CONTACT FINISH  -  CIRCUIT PER DECK  ANGLE OF THROW  45°  Flatted (6.35mm Dia)		MOUNTING TYPE	Panel Mount
DETAILED DESCRIPTION  Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount		INDEX STOPS	Fixed
DEPTH BEHIND PANEL  CURRENT RATING  5A (AC), 1A (DC)  CONTACT TIMING  Shorting (MBB)  CONTACT MATERIAL  Silver Alloy  CONTACT FINISH  -  CIRCUIT PER DECK  SP8T  ANGLE OF THROW  45°  Flatted (6.35mm Dia)		FEATURES	-
CURRENT RATING  5A (AC), 1A (DC)  CONTACT TIMING  Shorting (MBB)  CONTACT MATERIAL  Silver Alloy  CONTACT FINISH  -  CIRCUIT PER DECK  SP8T  ANGLE OF THROW  45°  ACTUATOR TYPE  Flatted (6.35mm Dia)		DETAILED DESCRIPTION	Rotary Switch 8 Position SP8T 5A (AC), 1A (DC) 115VAC Panel Mount
CONTACT TIMING  CONTACT MATERIAL  Silver Alloy  CONTACT FINISH  -  CIRCUIT PER DECK  SP8T  ANGLE OF THROW  45°  ACTUATOR TYPE  Flatted (6.35mm Dia)		DEPTH BEHIND PANEL	-
CONTACT MATERIAL  CONTACT FINISH  CIRCUIT PER DECK  ANGLE OF THROW  ACTUATOR TYPE  Silver Alloy  -  Silver Alloy  -  Hatted (6.35mm Dia)		CURRENT RATING	5A (AC), 1A (DC)
CONTACT FINISH  CIRCUIT PER DECK  SP8T  ANGLE OF THROW  ACTUATOR TYPE  Flatted (6.35mm Dia)		CONTACT TIMING	Shorting (MBB)
CIRCUIT PER DECK  ANGLE OF THROW  45°  ACTUATOR TYPE  Flatted (6.35mm Dia)		CONTACT MATERIAL	Silver Alloy
ANGLE OF THROW 45°  ACTUATOR TYPE Flatted (6.35mm Dia)		CONTACT FINISH	-
ACTUATOR TYPE Flatted (6.35mm Dia)		CIRCUIT PER DECK	SP8T
		ANGLE OF THROW	45°
ACTUATOR LENGTH 11.10mm		ACTUATOR TYPE	Flatted (6.35mm Dia)
		ACTUATOR LENGTH	11.10mm

# **Related Tags**

Grayhill, Inc. 44M45-02B08S	44M45-02B08S Distributor	44M45-02B08S Supplier
44M45-02B08S Price	44M45-02B08S Pictures	44M45-02B08S Image
44M45-02B08S PDF Datasheet	44M45-02B08S Download Datasheet	44M45-02B08S Datasheet
44M45-02B08S Stock	Buy 44M45-02B08S	Buy Grayhill, Inc. 44M45-02B08S
Grayhill, Inc. 44M45-02B08S	Grayhill, Inc. Supplier	Grayhill, Inc. Distributor
Grayhill, Inc. 44M45-02B08S	Grayhill Inc. 44M45-02B08S	

# **Related Products**



Manufacturers: Grayhill, Inc.

44M45-02-2-03N

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 2 In stock: 1090 pcs

**RFQ** 

Grayhill

Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 2 In stock: 974 pcs

**RFQ** 

44M45-02-4-02N



## 44M45-03-1-02N

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 45 DEG 2 DECK,

In stock: 1424 pcs

**RFQ** 



#### 44M45-03-1-03N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 3

In stock: 1344 pcs **RFQ** 



#### 44M45-03-1-05S Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 3 In stock: 1031 pcs

**RFQ** 



#### 44M45-02B08N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 2 In stock: 1436 pcs

RFQ



#### 44M45-02-2-03S Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 2 In stock: 1375 pcs

**RFQ** 



#### 44M45-03-1-04N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 3 In stock: 1323 pcs

**RFQ** 



#### 44M45-03-1-05N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 3 In stock: 1328 pcs

**RFQ** 



#### 44M45-03-1-03S Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 3 In stock: 1187 pcs

**RFQ** 



#### Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 2

44M45-02-2-04N

In stock: 1220 pcs

**RFQ** 



44M45-02-3-02N

In stock: 1360 pcs

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 2

**RFQ** 















