

Honeywell

**Honeywell Sensing and** 

**Productivity Solutions** 

Datasheets:

RoHs Status

Ship From

Stock Condition

Shipment Way

Part Number: Manufacturer/Brand: Product description

**HSCSAAN015PD2A3** 

HSCSAAN015PD2A3

Honeywell Sensing and Productivity Solutions

SENSOR PRES 15PSI DIFF 3.3V SIP 1.HSCSAAN015PD2A3.pdf

2.HSCSAAN015PD2A3.pdf 3.HSCSAAN015PD2A3.pdf

4.HSCSAAN015PD2A3.pdf

5.HSCSAAN015PD2A3.pdf Lead free / RoHS Compliant

3099 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

Specifications of HSCSAAN015PD2A3

MANUFACTURER  DESCRIPTION  SENSOR PRES 15PSI DIFF 3.3V SIP  LEAD FREE STATUS / ROHS STATUS  PRESSURE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  PRESSURE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  PRESSURE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  PRESSURE STATUS / ROHS STATUS  PRESSURE STATUS / ROHS STATUS  PRESSURE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  PRESSURE STATUS / ROHS COmpliant  FEATURES  OPERATING DESCRIPTION  PRESSURE STATUS / ROHS COmpliant  FEATURES  OPERATING PREPSSURE  ###################################	PART NUMBER	HSCSAAN015PD2A3
LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  3099 pcs  11 LHSCSAAN015PD2A3.pdf  12 LHSCSAAN015PD2A3.pdf  13 LHSCSAAN015PD2A3.pdf  14 LHSCSAAN015PD2A3.pdf  15 LHSCSAAN015PD2A3.pdf  16 LHSCSAAN015PD2A3.pdf  17 LHSCSAAN015PD2A3.pdf  18 LHSCSA	MANUFACTURER	Honeywell Sensing and Productivity Solutions
QUANTITY AVAILABLE  3099 pcs  1.HSCSAAN015PD2A3.pdf 2.HSCSAAN015PD2A3.pdf 3.HSCSAAN015PD2A3.pdf 3.HSCSAAN015PD2A3.pdf 3.HSCSAAN015PD2A3.pdf 3.HSCSAAN015PD2A3.pdf 3.HSCSAAN015PD2A3.pdf 3.HSCSAAN015PD2A3.pdf 3.V ~ 3.6 V  VOLTAGE - SUPPLY  7. SUPPLIER DEVICE PACKAGE  4.SIP  SERIES  TruStability® HSC  PRESSURE TYPE  Differential  PORT STYLE  Barbed  PORT STYLE  Barbed  PORT SIZE  Male - 0.19" (4.93mm) Tube, Dual  PACKAGE / CASE  0.1PUT TYPE  1.2 b  OPERATING TEMPERATURE  -20"C ~ 85"C  OPERATING TEMPERATURE  DIFFERUNCE  DEVICE SENSITIVITY LEVEL (MSL)  MAXIMUM PRESSURE  ±60 PSI (±113.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  MAXIMUM PRESSURE  ±60 PSI (±113.69 kPa)  LEAD FREE STATUS / ROHS STATUS  LEAd free / ROHS Compilant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR ±15 PSI (±103.42 kPa)  PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4.51P, PRESSURE SENSOR + 155 PSI (±103.42 kPa) Differentia	DESCRIPTION	SENSOR PRES 15PSI DIFF 3.3V SIP
DATA SHEET	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DATA SHEET  2 J.HSCSAAN015PD2A3.pdf  4 J.HSCSAAN015PD2A3.pdf  5 J.HSCSA	QUANTITY AVAILABLE	3099 pcs
TERMINATION STYLE  SUPPLIER DEVICE PACKAGE  4-SIP  SERIES  TruStability® HSC  PRESSURE TYPE  Differential  PORT STYLE  Barbed  PORT SIZE  Male - 0.19" (4.93mm) Tube, Dual  PACKAGE / CASE  4-SIP, Dual Ports, Opposite Sides  OUTPUT TYPE  1°C  OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	DATA SHEET	2.HSCSAAN015PD2A3.pdf  3.HSCSAAN015PD2A3.pdf  4.HSCSAAN015PD2A3.pdf
SUPPLIER DEVICE PACKAGE  SERIES  TruStability® HSC  PRESSURE TYPE  Differential  PORT STYLE  Barbed  PORT SIZE  Male - 0.19" (4.93mm) Tube, Dual  PACKAGE / CASE  OUTPUT TYPE  I²C  OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	VOLTAGE - SUPPLY	3 V ~ 3.6 V
TruStability® HSC  PRESSURE TYPE  Differential  PORT STYLE  Barbed  PORT SIZE  Male - 0.19" (4.93mm) Tube, Dual  PACKAGE / CASE  4-SIP, Dual Ports, Opposite Sides  OUTPUT TYPE  12C  OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	TERMINATION STYLE	PC Pin
PRESSURE TYPE  Differential  PORT STYLE  Barbed  PORT SIZE  Male - 0.19" (4.93mm) Tube, Dual  PACKAGE / CASE  4-SIP, Dual Ports, Opposite Sides  OUTPUT TYPE  12C  OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	SUPPLIER DEVICE PACKAGE	4-SIP
PORT STYLE  Barbed  PORT SIZE  Male - 0.19" (4.93mm) Tube, Dual  PACKAGE / CASE  4-SIP, Dual Ports, Opposite Sides  OUTPUT TYPE  I²C  OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	SERIES	TruStability® HSC
PORT SIZE  Male - 0.19" (4.93mm) Tube, Dual  PACKAGE / CASE  4-SIP, Dual Ports, Opposite Sides  OUTPUT TYPE  I²C  OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	PRESSURE TYPE	Differential
PACKAGE / CASE  4-SIP, Dual Ports, Opposite Sides  OUTPUT TYPE  I²C  OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	PORT STYLE	Barbed
OUTPUT TYPE  OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  Amplified Output, Temperature Compensated  DETAILED DESCRIPTION  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	PORT SIZE	Male - 0.19" (4.93mm) Tube, Dual
OUTPUT  12 b  OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	PACKAGE / CASE	4-SIP, Dual Ports, Opposite Sides
OPERATING TEMPERATURE  -20°C ~ 85°C  OPERATING PRESSURE  ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  MAXIMUM PRESSURE  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	OUTPUT TYPE	I <sup>2</sup> C
OPERATING PRESSURE ±15 PSI (±103.42 kPa)  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MAXIMUM PRESSURE ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant  FEATURES Amplified Output, Temperature Compensated  DETAILED DESCRIPTION Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	OUTPUT	12 b
MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	OPERATING TEMPERATURE	-20°C ~ 85°C
MAXIMUM PRESSURE ±60 PSI (±413.69 kPa)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	OPERATING PRESSURE	±15 PSI (±103.42 kPa)
LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURES  Amplified Output, Temperature Compensated  Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	MAXIMUM PRESSURE	±60 PSI (±413.69 kPa)
Pressure Sensor ±15 PSI (±103.42 kPa) Differential Male - 0.19" (4.93mm) Tube, Dual 12 b 4-SIP,	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
	FEATURES	Amplified Output, Temperature Compensated
	DETAILED DESCRIPTION	

# **Related Tags**

±0.25%

Honeywell Sensing and Productivity Solutions HSCSAAN015PD2A3	HSCSAAN015PD2A3 Distributor	HSCSAAN015PD2A3 Supplier
HSCSAAN015PD2A3 Price	HSCSAAN015PD2A3 Pictures	HSCSAAN015PD2A3 Image
HSCSAAN015PD2A3 PDF Datasheet	HSCSAAN015PD2A3 Download Datasheet	HSCSAAN015PD2A3 Datasheet
HSCSAAN015PD2A3 Stock	Buy HSCSAAN015PD2A3	Buy Honeywell Sensing and Productivity Solutions HSCSAAN015PD2A3
Honeywell Sensing and Productivity Solutions HSCSAAN015PD2A3	Honeywell Sensing and Productivity Solutions Supplier	Honeywell Sensing and Productivity Solutions Distributor
Honeywell Sensing and Productivity Solutions HSCSAAN015PD2A3	HONEYWELL HSCSAAN015PD2A3	Honeywell Sensing and Control EMEA HSCSAAN015PD2A3

# **Related Products**



HSCSAAN015PD2A3

**ACCURACY** 

# **HSCSAAN015PDAA3**

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR PRES 15PSI DIFF 3.3V SIP In stock: 3089 pcs

**RFQ** 

Honeywell Sensing and Productivity Solutions T&M



### **HSCSAAN010NDAA3** Manufacturers: Honeywell Sensing and Productivity Solutions

Description: BRD MNT PRESSURE SENSORS In stock: 2503 pcs

**RFQ** 



#### **HSCSAAN010NG2A3** Manufacturers: Honeywell Sensing and Productivity Solutions

Description: BRD MNT PRESSURE SENSORS In stock: 7057 pcs

**RFQ** 



#### **HSCSAAN600MDAA5** Manufacturers: Honeywell Sensing and Productivity Solutions

Description: BRD MNT PRESSURE SENSORS In stock: 3257 pcs

**RFQ** 



#### **HSCSAAN010NDAA5** Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR PRESS DIFF 10" H2O 4SIP In stock: 1664 pcs

**RFQ** 



#### **HSCSAAN005PDAA3** Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR PRES 5PSI DIFF 3.3V SIP In stock: 3074 pcs

**RFQ** 



### **HSCSAAN020NG2A3** Manufacturers: Honeywell Sensing and Productivity Solutions

Description: BRD MNT PRESSURE SENSORS In stock: 5652 pcs

**RFQ** 



#### HSCSAAN030PG2A3 Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR PRES 30PSI GAUG 3.3V SIP

In stock: 3850 pcs **RFQ** 



### Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR PRES 5PSI GAUG 5V SIP

**HSCSAAN005PGAA5** 

In stock: 3988 pcs **RFQ** 



#### **HSCSAAN160MDAA5** Manufacturers: Honeywell Sensing and Productivity Solutions

Description: BRD MNT PRESSURE SENSORS In stock: 3080 pcs


**RFQ** 





**HSCSAAN010MGAA5** Manufacturers: Honeywell Sensing and Productivity Solutions

**RFQ** 





Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR PRES 15PSI DIFF 5V SIP In stock: 3898 pcs

**RFQ** 









