## N/A Product description Image may be representation. See specifications for product details.

## WTB4-3P3161S02

Part Number:

Manufacturer/Brand:

Datasheets: Stock Condition

Ship From

Shipment Way

WTB4-3P3161S02

N/A

LINE SPOT BGS PNP PGTL

DHL/Fedex/TNT/UPS/EMS

386 pcs stock

Hong Kong

**REQUEST FOR QUOTATION** 

MANUFACTURER  MANUFACTURER  N/A  DESCRIPTION  LINE SPOT BGS PNP PGTL  LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  386 pcs  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  W4-3  SENSING METHOD  Proximity  SENSING DISTANCE  0.394" (10mm)  RESPONSE TIME  200µS  OUTPUT CONFIGURATION  NPN - Dark-ON/Light-ON  OTHER NAMES  1029261  OPERATING TEMPERATURE  -10°C ~ 50°C (TA)  LIGHT SOURCE  Red (650nm)  INGRESS PROTECTION  IP67, IP69K  CONNECTION METHOD  Cable with Connector  CABLE LENGTH  3.937" (100.00mm)  Adjustable, Potentiometer		Specifications of WTB4-3P3161S02
MANUFACTURER  DESCRIPTION  LINE SPOT BGS PNP PGTL  LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  386 pcs  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  W4-3  SENSING METHOD  Proximity  SENSING DISTANCE  0.394" (10mm)  RESPONSE TIME  0UTPUT CONFIGURATION  NPN - Dark-ON/Light-ON  OTHER NAMES  1029261  OPERATING TEMPERATURE  -10°C ~ 50°C (TA)  LIGHT SOURCE  Red (650nm)  INGRESS PROTECTION  IP67, IP69K  CONNECTION METHOD  CABLE LENGTH  3.937" (100.00mm)		
DESCRIPTION  LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  386 pcs  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  W4-3  SENSING METHOD  Proximity  SENSING DISTANCE  0.394" (10mm)  RESPONSE TIME  200µS  OUTPUT CONFIGURATION  NPN - Dark-ON/Light-ON  OTHER NAMES  1029261  OPERATING TEMPERATURE  -10°C ~ 50°C (TA)  LIGHT SOURCE  Red (650nm)  INGRESS PROTECTION  IP67, IP69K  CONNECTION METHOD  Cable with Connector  CABLE LENGTH  3.937" (100.00mm)		
QUANTITY AVAILABLE 386 pcs  DATA SHEET  VOLTAGE - SUPPLY 10 V ~ 30 V  SERIES W4-3  SENSING METHOD Proximity  SENSING DISTANCE 0.394" (10mm)  RESPONSE TIME 200µS  OUTPUT CONFIGURATION NPN - Dark-ON/Light-ON  OTHER NAMES 1029261  OPERATING TEMPERATURE -10°C ~ 50°C (TA)  LIGHT SOURCE Red (650nm)  INGRESS PROTECTION IP67, IP69K  CONNECTION METHOD Cable with Connector  CABLE LENGTH 3.937" (100.00mm)	MANUFACTURER	N/A
QUANTITY AVAILABLE  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  W4-3  SENSING METHOD  Proximity  SENSING DISTANCE  0.394" (10mm)  RESPONSE TIME  200µS  OUTPUT CONFIGURATION  NPN - Dark-ON/Light-ON  OTHER NAMES  1029261  OPERATING TEMPERATURE  -10°C ~ 50°C (TA)  LIGHT SOURCE  Red (650nm)  INGRESS PROTECTION  IP67, IP69K  CONNECTION METHOD  CABLE LENGTH  3.937" (100.00mm)	DESCRIPTION	LINE SPOT BGS PNP PGTL
DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  W4-3  SENSING METHOD  Proximity  SENSING DISTANCE  0.394" (10mm)  RESPONSE TIME  200µs  OUTPUT CONFIGURATION  NPN - Dark-ON/Light-ON  OTHER NAMES  1029261  OPERATING TEMPERATURE  -10°C ~ 50°C (TA)  LIGHT SOURCE  Red (650nm)  INGRESS PROTECTION  IP67, IP69K  CONNECTION METHOD  CABLE LENGTH  3.937" (100.00mm)	LEAD FREE STATUS / ROHS STATUS	
VOLTAGE - SUPPLY10 V ~ 30 VSERIESW4-3SENSING METHODProximitySENSING DISTANCE0.394" (10mm)RESPONSE TIME200μsOUTPUT CONFIGURATIONNPN - Dark-ON/Light-ONOTHER NAMES1029261OPERATING TEMPERATURE-10°C ~ 50°C (TA)LIGHT SOURCERed (650nm)INGRESS PROTECTIONIP67, IP69KCONNECTION METHODCable with ConnectorCABLE LENGTH3.937" (100.00mm)	QUANTITY AVAILABLE	386 pcs
SERIES W4-3  SENSING METHOD Proximity  SENSING DISTANCE 0.394" (10mm)  RESPONSE TIME 200µs  OUTPUT CONFIGURATION NPN - Dark-ON/Light-ON  OTHER NAMES 1029261  OPERATING TEMPERATURE -10°C ~ 50°C (TA)  LIGHT SOURCE Red (650nm)  INGRESS PROTECTION IP67, IP69K  CONNECTION METHOD Cable with Connector  CABLE LENGTH 3.937" (100.00mm)	DATA SHEET	
SENSING METHOD  SENSING DISTANCE  0.394" (10mm)  RESPONSE TIME  200µS  OUTPUT CONFIGURATION  NPN - Dark-ON/Light-ON  OTHER NAMES  1029261  OPERATING TEMPERATURE  -10°C ~ 50°C (TA)  LIGHT SOURCE  INGRESS PROTECTION  IP67, IP69K  CONNECTION METHOD  CABLE LENGTH  3.937" (100.00mm)	VOLTAGE - SUPPLY	10 V ~ 30 V
SENSING DISTANCE 0.394" (10mm)  RESPONSE TIME 200µS  OUTPUT CONFIGURATION NPN - Dark-ON/Light-ON  OTHER NAMES 1029261  OPERATING TEMPERATURE -10°C ~ 50°C (TA)  LIGHT SOURCE Red (650nm)  INGRESS PROTECTION IP67, IP69K  CONNECTION METHOD Cable with Connector  CABLE LENGTH 3.937" (100.00mm)	SERIES	W4-3
RESPONSE TIME200μsOUTPUT CONFIGURATIONNPN - Dark-ON/Light-ONOTHER NAMES1029261OPERATING TEMPERATURE-10°C ~ 50°C (TA)LIGHT SOURCERed (650nm)INGRESS PROTECTIONIP67, IP69KCONNECTION METHODCable with ConnectorCABLE LENGTH3.937" (100.00mm)	SENSING METHOD	Proximity
OUTPUT CONFIGURATION  NPN - Dark-ON/Light-ON  1029261  OPERATING TEMPERATURE  -10°C ~ 50°C (TA)  LIGHT SOURCE  Red (650nm)  INGRESS PROTECTION  IP67, IP69K  CONNECTION METHOD  Cable with Connector  CABLE LENGTH  3.937" (100.00mm)	SENSING DISTANCE	0.394" (10mm)
OTHER NAMES  1029261  OPERATING TEMPERATURE  -10°C ~ 50°C (TA)  LIGHT SOURCE  Red (650nm)  INGRESS PROTECTION  IP67, IP69K  CONNECTION METHOD  Cable with Connector  CABLE LENGTH  3.937" (100.00mm)	RESPONSE TIME	200μs
OPERATING TEMPERATURE -10°C ~ 50°C (TA)  LIGHT SOURCE Red (650nm)  INGRESS PROTECTION IP67, IP69K  CONNECTION METHOD Cable with Connector  CABLE LENGTH 3.937" (100.00mm)	OUTPUT CONFIGURATION	NPN - Dark-ON/Light-ON
LIGHT SOURCE Red (650nm)  INGRESS PROTECTION IP67, IP69K  CONNECTION METHOD Cable with Connector  CABLE LENGTH 3.937" (100.00mm)	OTHER NAMES	1029261
INGRESS PROTECTION IP67, IP69K  CONNECTION METHOD Cable with Connector  CABLE LENGTH 3.937" (100.00mm)	OPERATING TEMPERATURE	-10°C ~ 50°C (TA)
CONNECTION METHOD  Cable with Connector  3.937" (100.00mm)	LIGHT SOURCE	Red (650nm)
CABLE LENGTH 3.937" (100.00mm)	INGRESS PROTECTION	IP67, IP69K
	CONNECTION METHOD	Cable with Connector
ADJUSTMENT TYPE Adjustable, Potentiometer	CABLE LENGTH	3.937" (100.00mm)
	ADJUSTMENT TYPE	Adjustable, Potentiometer

**Related Tags** 

WTB4-3P3161S02	Supplier	Distributor
WTB4-3P3161S02 Stock	Buy WTB4-3P3161S02	Buy WTB4-3P3161S02
WTB4-3P3161S02 PDF Datasheet	WTB4-3P3161S02 Download Datasheet	WTB4-3P3161S02 Datasheet
WTB4-3P3161S02 Price	WTB4-3P3161S02 Pictures	WTB4-3P3161S02 Image
WTB4-3P3161S02	WTB4-3P3161S02 Distributor	WTB4-3P3161S02 Supplier

**Related Products** 

