# **infinity-electronic**

| <ul> <li>Part Number:</li> <li>Manufacturer/Brand:</li> <li>Product description</li> <li>Datasheets:</li> <li>Stock Condition</li> <li>Ship From</li> <li>Shipment Way</li> </ul> REOUEST FOR OUOTATION | WTB12-3P2433T01      |
|---|----------------------|
| <ul> <li>Product description</li> <li>Datasheets:</li> <li>Stock Condition</li> <li>Ship From</li> <li>Shipment Way</li> </ul>  | Part Number:         |
| Datasheets:<br>Stock Condition<br>Ship From<br>Shipment Way   | Manufacturer/Brand:  |
| Stock Condition<br>Ship From<br>Shipment Way  | Product description  |
| Ship From<br>Shipment Way   | Datasheets:          |
| Shipment Way  | Stock Condition      |
|   | Ship From            |
|   | Shipment Way         |
|   | REQUEST FOR QUOTATIO |

# T01

| Number:          |
|------------------|
| ufacturer/Brand: |
| luct description |
| sheets:          |
| k Condition      |
| From             |
| ment Way         |

### WTB12-3P2433T01

N/A PNP LO/DO M12 4-PN PLG

365 pcs stock Hong Kong DHL/Fedex/TNT/UPS/EMS

### Specifications of WTB12-3P2433T01

| PART NUMBER                    | WTB12-3P2433T01                 |
|--------------------------------|---------------------------------|
| MANUFACTURER                   | N/A                             |
| DESCRIPTION                    | PNP LO/DO M12 4-PN PLG          |
| LEAD FREE STATUS / ROHS STATUS |                                 |
| QUANTITY AVAILABLE             | 365 pcs                         |
| DATA SHEET                     |                                 |
| VOLTAGE - SUPPLY               | 10 V ~ 30 V                     |
| SERIES                         | W12 Teflon                      |
| SENSING METHOD                 | Proximity                       |
| SENSING DISTANCE               | 0.787" ~ 13.780" (20mm ~ 350mm) |
| RESPONSE TIME                  | 330µs                           |
| OUTPUT CONFIGURATION           | PNP                             |
| OTHER NAMES                    | 1048278                         |
| OPERATING TEMPERATURE          | -40°C ~ 60°C (TA)               |
| LIGHT SOURCE                   | Red (640nm)                     |
| INGRESS PROTECTION             | IP66, IP67, IP69K               |
| CONNECTION METHOD              | Connector, M12                  |
| CABLE LENGTH                   | -                               |
| ADJUSTMENT TYPE                | Adjustable                      |

## **Related Tags**

| WTB12-3P2433T01               | WTB12-3P2433T01 Distributor        | WTB12-3P2433T01 Supplier  |
|-------------------------------|------------------------------------|---------------------------|
| WTB12-3P2433T01 Price         | WTB12-3P2433T01 Pictures           | WTB12-3P2433T01 Image     |
| WTB12-3P2433T01 PDF Datasheet | WTB12-3P2433T01 Download Datasheet | WTB12-3P2433T01 Datasheet |
| WTB12-3P2433T01 Stock         | Buy WTB12-3P2433T01                | Buy WTB12-3P2433T01       |
| WTB12-3P2433T01               | Supplier                           | Distributor               |

### **Related Products**



