N/A Image may be representation. See specifications for product details.

IMB08-02BNPVC0S

Part Number:

Manufacturer/Brand:

Product description Datasheets: Stock Condition

Ship From Shipment Way IMB08-02BNPVC0S

N/A

SEN PROX FLSH NPN COMP M12

1462 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER IMBO8-02BNPVCOS MANUFACTURER N/A DESCRIPTION SEN PROX FLSH NPN COMP M12 LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 1462 pcs DATA SHEET VOLTAGE - SUPPLY 10 V ~ 30 V TERMINATION STYLE Connector SHIELDING Shielded SERIES - SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE CYINDER, Threaded - MB OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY INDICATOR LED DETAILED DESCRIPTION Inductive Proximity Sensor 0.079" (2mm) IP68, IP69K Cylinder, Threaded - MB		Specifications of IMB08-02BNPVC0S
MANUFACTURER DESCRIPTION SEN PROX FLSH NPN COMP M12 LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 1462 pcs DATA SHEET VOLTAGE - SUPPLY 10 V ~ 30 V TERMINATION STYLE Connector SHIELDING SHIELDING SENISC SENISC SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE CYLINDER, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES OUTPUT TYPE OTHER NAMES OPACTOR OF THE SHIELD AND AND AND AND AND AND AND AND AND AN		
DESCRIPTION SEN PROX FLSH NPN COMP M12 LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE DATA SHEET VOLTAGE - SUPPLY 10 V ~ 30 V TERMINATION STYLE Connector SHIELDING Shielded SERIES - SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES OPERATING TEMPERATURE A-0°C ~ 100°C (TA) MATERIAL - BODY INDICATOR LED	PART NUMBER	IMB08-02BNPVC0S
QUANTITY AVAILABLE DATA SHEET VOLTAGE - SUPPLY 10 V ~ 30 V TERMINATION STYLE SHIELDING Shielded SERIES - SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY AkHz PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE *40°C ~ 100°C (TA) MATERIAL - BODY INGRESS PROTECTION IP68, IP69K INDICATOR	MANUFACTURER	N/A
QUANTITY AVAILABLE DATA SHEET VOLTAGE - SUPPLY 10 V ~ 30 V TERMINATION STYLE Connector SHIELDING Shielded SERIES - SENSOR TYPE Inductive SENSING DISTANCE Q.0.79" (2mm) RESPONSE FREQUENCY PACKAGE / CASE OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES OUTPUT TYPE OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY INDICATOR INDICATOR LED	DESCRIPTION	SEN PROX FLSH NPN COMP M12
DATA SHEET VOLTAGE - SUPPLY 10 V ~ 30 V TERMINATION STYLE Connector SHIELDING Shielded SERIES - SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE MATERIAL - BODY INGRESS PROTECTION IP68, IP69K INDICATOR	LEAD FREE STATUS / ROHS STATUS	
VOLTAGE - SUPPLY TERMINATION STYLE Connector SHIELDING Shielded SERIES - SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE MATERIAL - BODY INGRESS PROTECTION IP68, IP69K INDICATOR	QUANTITY AVAILABLE	1462 pcs
TERMINATION STYLE Connector Shielded SERIES - SENSOR TYPE Inductive SENSING DISTANCE RESPONSE FREQUENCY PACKAGE / CASE OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES OUTPUT TYPE OPERATING TEMPERATURE MATERIAL - BODY INGRESS PROTECTION IP68, IP69K INDICATOR CHAMBES Connector Inductive Induct	DATA SHEET	
SHIELDING SERIES - SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY INGRESS PROTECTION IP68, IP69K INDICATOR SENSING INDICATOR Shielded - Shielded - Shielded - 1nductive 1ndu	VOLTAGE - SUPPLY	10 V ~ 30 V
SERIES - Inductive SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY Plastic INGRESS PROTECTION IP68, IP69K INDICATOR	TERMINATION STYLE	Connector
SENSOR TYPE Inductive SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY Plastic INGRESS PROTECTION IP68, IP69K INDICATOR LED	SHIELDING	Shielded
SENSING DISTANCE 0.079" (2mm) RESPONSE FREQUENCY 4kHz PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY Plastic INGRESS PROTECTION IP68, IP69K INDICATOR LED	SERIES	-
RESPONSE FREQUENCY AkHz PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE Ado C ~ 100°C (TA) MATERIAL - BODY INGRESS PROTECTION IP68, IP69K INDICATOR	SENSOR TYPE	Inductive
PACKAGE / CASE Cylinder, Threaded - M8 OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY Plastic INGRESS PROTECTION IP68, IP69K INDICATOR LED	SENSING DISTANCE	0.079" (2mm)
OUTPUT TYPE NPN-NC/NO, 4-Wire OTHER NAMES 1074352 OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY Plastic INGRESS PROTECTION IP68, IP69K INDICATOR	RESPONSE FREQUENCY	4kHz
OTHER NAMES 1074352 OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY INGRESS PROTECTION IP68, IP69K INDICATOR LED	PACKAGE / CASE	Cylinder, Threaded - M8
OPERATING TEMPERATURE -40°C ~ 100°C (TA) MATERIAL - BODY Plastic INGRESS PROTECTION IP68, IP69K INDICATOR LED	OUTPUT TYPE	NPN-NC/NO, 4-Wire
MATERIAL - BODY INGRESS PROTECTION IP68, IP69K INDICATOR LED	OTHER NAMES	1074352
INGRESS PROTECTION IP68, IP69K INDICATOR LED	OPERATING TEMPERATURE	-40°C ~ 100°C (TA)
INDICATOR LED	MATERIAL - BODY	Plastic
	INGRESS PROTECTION	IP68, IP69K
DETAILED DESCRIPTION Inductive Proximity Sensor 0.079" (2mm) IP68, IP69K Cylinder, Threaded - M8	INDICATOR	LED
	DETAILED DESCRIPTION	Inductive Proximity Sensor 0.079" (2mm) IP68, IP69K Cylinder, Threaded - M8

Related Tags

IMB08-02BNPVC0S	IMB08-02BNPVC0S Distributor	IMB08-02BNPVC0S Supplier
IMB08-02BNPVC0S Price	IMB08-02BNPVC0S Pictures	IMB08-02BNPVC0S Image
IMB08-02BNPVC0S PDF Datasheet	IMB08-02BNPVC0S Download Datasheet	IMB08-02BNPVC0S Datasheet
IMB08-02BNPVC0S Stock	Buy IMB08-02BNPVC0S	Buy IMB08-02BNPVC0S
IMB08-02BNPVC0S	Supplier	Distributor

Related Products



cial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong

Address: 1