SDA04H0SB Details PDF

product details.





SDA04H0SB

Part Number:
Manufacturer/Brand:
Product description
Datasheets:
RoHs Status
Stock Condition
Ship From
Shipment Way

C&K SWITCH SLIDE DIP SPST 25MA 24V SDA04H0SB.pdf Lead free / RoHS Compliant 59960 pcs stock Hong Kong DHL/Fedex/TNT/UPS/EMS

SDA04H0SB

REQUEST FOR QUOTATION

Specifications of SDA04H0SB

MANUFACTURERCakDESCRIPTIONSWITCH SLIDE DIP SPST 25MA 24VLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantQUANTITY AVAILABLES960 pcsDATA SHEFTSWICHASES, pdfWASHABLEVoVOLTAGE RATINGVaVDCSTREINTION STYLESWICHASE, pdfSTREINTION STYLESWICHASE, pdfPICHAUIOW (2.54mm), FullPICHAUIOW (2.54mm), FullPICHASUDAHOSEOTHER NAMESSUDAHOSEOTHER NAMESSUDAHOSESUDAHOSESUDAHOSESUDAHOSESUDAHOSESUDAHOSESUDAH		
DESCRIPTIONSWITCH SLUE DUP SPST 25MA 24VLEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantQUANTITY AVAILABLES960 psDATA SHEETSA04HIDSB.pdfWASHAREVerVOLTAGE RATINGQUANTITY AVAILABLEVOLTAGE RATINGQUI WingSREESGON (2.54mm), FullPRICHADING STYLESUD (2.54mm), FullPACKAGINGTubeOTHER NAMESSOD (2.54mm), FullPACKAGINGVICTAGE RATINGOTHER NAMESSUD (2.54mm), FullPACKAGINGSUD (2.54mm), FullPACKAGINGVer C & 85°COTHER NAMESGUP (2.54mm), FullNUMERE OF POSITIONS4MOUTTING TEMPERATURENOW C & 85°CNUMERE OF POSITIONSL (Unlimited)MECHANICAL LIFEJOO CyclesLEAD FREE STATUS / ROHS STATUSL (Merimeta)HEIGH TABOVE BOARD175° (4.45mm)FEATURESSINAFEATURESSINAFEATURESSINAFEATURESSINAFEATURESSINAFEATURESSINAFEATURESSINAFEATURESSINAFEATURESSINACONTACT FINSHGelCONTACT FINSHGUPGONTACT FINSHSINAGONTACT FINSHSINAGONTACT FINSHSINAGONTACT FINSHSINAGONTACT FINSHSINAGONTACT FINSHSINAGONTACT FINSHSINAGONTACT FINSHSINAGONTACT FINSHSINA <td>PART NUMBER</td> <td>SDA04H0SB</td>	PART NUMBER	SDA04H0SB
LEAD FREE STATUS / ROHS STATUSLead free / RohS ComplentQUANTTY AVALABLES950 psDATA SHEETS0A01H03B.pdfWASHABLEYesVOLTAGE RATING24VDCSERIESSDAPTCHGul WingSERIESS0A01H03B.pdfOTHER MARESS0A0240000000000000000000000000000000000	MANUFACTURER	C&K
QUANTITY AVAILABLE59960 psDATA SHEET© SOA0H40S8.pdfWASHABLEVesVILTAGE RATING24VDCTERMINATION STYLEGul WingSERLESSDAPITCH0.100° (2.54mm), FuilPACKAGINGTubeOTHER NAMES"SSA04H6SS"OTHER NAMES40°C ~ 85°CNUMERC OF POSITIONS4MOUNTING TYPESuface MountMOUNTING TYPE1 (Unlimited)MOUNTING TYPE1 (Unlimited)MOUNTING TYPE1 (Unlimited)MOUNTING TYPE1 (Unlimited)MOUNTING TYPE1 (Unlimited)MEGANICAL LIFE1 (Strace MountMEGANICAL LIFE1 (Strace MountELENGTHAL LIFE1 (Strace MountELENTRICAL LIFE1 (Strace MountELENTRICAL LIFE1 (Strace MountELENTRICAL LIFE1 (Strace Mount Strate)ELENTRICAL LIFE1 (Strate)ELENTRICAL LIFE1 (Strate)ELENTRICAL LIFE1 (Strate)ELENTRICAL LIFE1 (Strate)ELENTRICAL LIFE1 (Strate)CONTACT FINISH6 (Stra	DESCRIPTION	SWITCH SLIDE DIP SPST 25MA 24V
DATA SHERTSi S0AH06SB.pdfWASHABLEYesVOLTAGE PATINGAVDCYERMINATION STYLEGAI WingSERLESSDAPITCH0.100° (2.54mm), FullPACKAGINGTubeOTHER NAMESSGAOBH0GSBOTHER NAMES4.0°C & 8°COTHER NAMES4.0°C & 8°COTHER NAMESGUNNITING TYPEMUMEER OF POSITIONS4.0°C & 8°CMUTTING TYPESGAOBH0GSMUTTING TYPESUGAOBCMOUTTING TYPEJOO CyclesMECHANICOL LIFEJOO CyclesLENGTHJOO CyclesELEGTERICAL LIFEJOO CyclesELEGTERICAL LIFEJOS CyclesELEGTERICAL LIFEJOO CyclesDETALED DESCRIPTIONSINGHNESPENDESCRIPTIONCONTACT FINISHJOS VICH SPEN AUGU SIGNAGING JACLADIC 25MA 24MDCCONTACT FINISHGUACONTACT FINISHGUAPUNESUGIG/CPS)CONTACT FINISHGUAPUNESUGIG/CPS)CONTACT FINISHGUAPUNESUGIG/CPS)CONTACT FINISHGUAPUNESUGIG/CPS)CONTACT FINISHGUAPUNESUGIG/CPS)CONTACT FINISHGUAPUNESUGIG/CPS)CONTACT FINISHGUAPUNESUGIG/CPS)CONTACT FINISHGUAPUNESUGIG/CPS)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
washaale va washaale va voltrade hatting davoc texnination strue Gall Wing series Sola prod dovor strue prod dovor strue order dovor strue order dovor strue order dovor strue order strue dovor strue strue dovor strue strue dovor strue strue dovor strue strue dovo	QUANTITY AVAILABLE	59960 pcs
VOLTAGE RATING24VDCTERNINATION STYLEGIM WigSERIESSDAPTCH0.10° (2.54mm), FullPACAGINGTbeOrHER NAMESSDAOHMSBOTHER NAMESSOAOHMSBOPERATING TEMPERATURE4MUMEER OF POSITIONS4MUNDER FORSTRUTY LEVEL (MSL)0.101Imited)MUNTAGE SUNSTRYTY LEVEL (MSL)0.102 (SAGMANMUNTAGE SUNSTRYTY LEVEL (MSL)0.024 (SAGMANMURAGE ALT DE SANSTRYTY LEVEL (MSL)0.024 (SAGMANLEAD FREE STATUS / ROHS STATUS0.024 (SAGMANFEAT RATING0.024 (SAGMANELECTRI CAL LIFE0.024 (SAGMANFEAT RATING0.024 (SAGMANCURRENT RATING0.024 (SAGMANCURRENT RATING0.024 (SAGMANCURRENT RATINGSOACURRENT RATINGSOACONTACT FINISHGalCURTACT FINISHGAICONTACT FINISHGIMENCENSERCONTACT FINISHSIGE (SAGMAN)CONTACT FINISHSIGE (SAGMAN)CINITATERIALSIGE (SAGMAN)CINITATERIALSIGE (SAGMAN)CINITATERIALSIGE (SAGMAN)CINITATERIALSIGE (SAGMAN)CINITATERIALSIGE (SAGMAN)CINITATERIALSIGE (SAG	DATA SHEET	SDA04H0SB.pdf
TRYINATION STYLEGill WingSRESSOAPTCH0.10° (2.54mm, FullPACAGINGTobOTHER NAMESSDAMHOSEOPERATING TEMPERATURE-0°C - 8°CNUMBER OF POSITIONS4MOUTING TYPEOrde SouMOUTING TYPEUnimotionMOUTING SITURE SENSITIVITY LEVEL (MSL)UnimotionLENDARJOC / 2000LENDARJOC / 2000LENDARJOC / 2000LENDARUnimotionLENDARDJOC / 2000LENDARDJOC / 2000L	WASHABLE	Yes
SRIESSDAPITH0.00 (2.54m), FullPACKAGINGTokOTHER NAMESSDA0HDOSOTHER NAMES-00 CA SOCOPERATING TEMPERATURE-00 CA SOCNUMBER OF POSITIONS4MOUTING TYPEOrde MoutMOUTING TYPEJOI (JUINING)MICHANICAL LIFEJOI (JUINING)LENDA MADES BOARDJOI (JUINING)LENDA MOLADALJOI (JUINING)LENDA MOLADALJOI (JUINING)LEIGTA LIFEJOI (JUINING)LIFE TATURSJOI (JUINING)LIFE TATURS </td <td>VOLTAGE RATING</td> <td>24VDC</td>	VOLTAGE RATING	24VDC
PTCH0.10° (2.54mm), FullPACKAGINGTubePACKAGINGStandard Standard Stan	TERMINATION STYLE	Gull Wing
PACKAGINGTubeOTHER NAMESSADAHADSE CANORDSOPERATING TEMPERATURE40°C ~ 8°CNUMER OF POSITIONS4MOUNTING TYPESurface MountMOUNTING TYPE(Inlimited)MOUNTING TYPE1000 CyclesLENGTH040°C 48°CLENGTH040°C 48°CLENGTH ABOVE BOARD010°C 48°CLENGTH ALL DESCRIPTION090°C 48°CCURRENT RATING090°C 48°CCONTACT HATERIAL090°C 48°CCONTACT FINISH091°C 48°CCONTACT FINI	SERIES	SDA
oTHER NAMESSDAQHQOS SNAGGESOPERATING TEMPERATURE40°C A S°CNUMER OF POSITIONS4MOUNTING TYPESuface MountMOUNTING TYPE(Unlinted)MCGANAL LIFE100 CyclesLENGTH(Aff° (12.09m)LENGT RADOL STATUSCaffer ARDSC MountFIGHT ABOVE BOARD100 CyclesLENGTR SENSITIVIT LEVEL (MSL)100 CyclesLENGT RADOL STATUSCaffer ARDSC MountLENGT RADOL STATUSCaffer ARDSC MountLENGT RADOL STATUS100 CyclesELCTRICAL LIFE100 CyclesDETAILED DESCRIPTIONSinch Status Since Mount Sile (Standard) Actuator 25m A24DCCURRENT RATINGSinch Status Sile (Standard) Actuator 25m A24DCCONTACT FINISHGoldCONTACT FINISHSinch Sile (Standard) Actuator 25m A24DCCONTACT FINISHSile (Standard) Sile (Standard) Actuator 25m A24DCCONTACT FINISHSile (Standard) Sile (Standard) Actuator 25m A24DCCONTACT FINISHSile (Standard) Sile (Stan	PITCH	0.100" (2.54mm), Full
OTHER NAMESCKN6066OPERATING TEMPERATURE40°C ~ 8°CNUMBER OF POSITIONS4MOUNTING TYPESurface MountMOINTING TYPE(Unlimited)MCGANICAL LIFE1,000 CyclesLENGTH0.476° (12.09m)LENGT ABOVE BOARD1,000 CyclesLENGT ABOVE BOARD1,000 CyclesLENGT ABOVE BOARD0.476° (12.09m)ELEGT ABOVE BOARD1,000 CyclesELEGT ALLIFE0.175° (4.55m)ELEGT ALLIFE1,000 CyclesELEGTRICAL LIFE0.000 CyclesELECTRICAL LIFE0.000 CyclesELECTRICAL LIFE0.000 CyclesELECTRICAL LIFE0.000 CyclesCURRENT TATING0.000 CyclesCONTACT FINISH0.000 CyclesCURRENT CALL CY	PACKAGING	Tube
NUMBER OF POSITIONS4MOUNTING TYPESurface MountMOINTING TYPE(Indimediation of the second of	OTHER NAMES	
MOUNTING TYPESurface MountMOUNTING TYPE(Unlimited)MOISTURE SENSITIVITY LEVEL (MSL)(J00 CyclesMECHANICAL LIFE0476* (12.09mm)LENGTH6476* (PASCOmpliantLENGT ABOVE BOARD175* (4.45mm)FEATURES1700 CyclesELECTRICAL LIFE1000 CyclesELECTRICAL LIFE0100 CyclesCURRENT RATING050 CyclesCONTACT MATERIAL604CONTACT FINISH604CONTACT FINISH604BODY MATERIALPSIPAINE SUFFICEBODY MATERIAL6100 CyclesBODY MATERIAL	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL)i (Unimited)MOISTURE SENSITIVITY LEVEL (MSL)i (Unimited)MCHANICAL LIFEi.000 CyclesLENGTHi.207 (A.50mpliantLEAD FREE STATUS / ROHS STATUSi.207 (A.50mpliantHEIGHT ABOVE BOARDi.207 (A.50mpliant)FATURESi.200 CyclesELCTRICAL LIFEi.200 CyclesLECTRICAL LIFEi.200 CyclesCONTACT MATERIALi.200 CyclesCONTACT MATERIALi.200 CyclesCONTACT FINISHi.200 CyclesCONTA	NUMBER OF POSITIONS	4
MECHANICAL LIFE1,000 cyclesLINGTH0.476" (1.09mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEGHT ABOVE BOARD0.175" (4.45mm)FEATURESTape SalELECTRICAL LIFE0.000 cyclesDETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Side (Standard) Actuator 25mA 24VDCCURRENT RATINGSmallCONTACT FINISHGolCONTACT FINISHSpSTBODY MATERIALMich Spiling (Standard) Actuator 25mA 24VDCBODY MATERIALSig (Standard) Scandard)RUTUTO TYPESig (Standard) Scandard)	MOUNTING TYPE	Surface Mount
LENGTH0.476° (12.09mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.175° (4.45mm)FEATURESTape SealELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSomACONTACT FINISHGoldCONTACT FINISHSpsTBODY MATERIALPolypenyensuffice (PSPS)BODY MATERIALSig (Standard)BODY MATERIAL	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.15° (4.45mm)FEATURESTape SealELCTRICAL LIFE.000 CyclesDETAILED DESCRIPTIONDiswitch SPST 4 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSmallCONTACT MATERIALBerljium CooperCONTACT FINISH.000 CyclesBODY MATERIALPojpenselinge Surface Mount Slide (Standard) Actuator 25mA 24VDCBODY MATERIAL.000 CyclesBODY MATERIAL.000 Cycles	MECHANICAL LIFE	1,000 Cycles
HEIGHT ABOVE BOARD0.15" (4.5mm)FEATURESTap SalELECTRICAL LIFEJ00 CyclesDETAILED DESCRIPTIONDip Switch SPAT 4 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATINGSmACONTACT MATERIALBeylium CopperCONTACT FINISHGodBODY MATERIALPiphensenfielde (PSS)BODY MATERIALBiphensenfielde (PSS)Actuator YPEBiel (Standard)	LENGTH	0.476" (12.09mm)
FEATURESTape SealELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALBerylium CopperCONTACT FINISHGoldCRCUITSPSTBODY MATERIALPolypengengengengengengengengengengengengenge	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE1,00 CyclesDETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATING5mACONTACT MATERIALBeylium CopperCONTACT FINISHGodCIRCUITSPSTBODY MATERIALPolypenselinge (Standard)ACTUATOR TYPEBide (Standard)	HEIGHT ABOVE BOARD	0.175" (4.45mm)
DETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATING5mACONTACT MATERIALBerylium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolypensufide (PPS)ACTUATOR TYPESile (Standard)	FEATURES	Tape Seal
CURRENT RATING25mACONTACT MATERIALBeylium CopperCONTACT FINISHGoldCIRCUTSPSTBODY MATERIALPolypenselfiele (PSS)ACTUATOR TYPEBide (Standard)	ELECTRICAL LIFE	1,000 Cycles
CONTACT MATERIALBerylium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyhenylene Sulfide (PPS)ACTUATOR TYPESile (Standard)	DETAILED DESCRIPTION	Dip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC
CONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyhengengengengengengengengengengengengenge	CURRENT RATING	25mA
CIRCUITSPSTBODY MATERIALPolyphenylene Sulfide (PPS)ACTUATOR TYPESide (Standard)	CONTACT MATERIAL	Beryllium Copper
BODY MATERIAL Polyphenylene Sulfide (PPS) ACTUATOR TYPE Slide (Standard)	CONTACT FINISH	Gold
ACTUATOR TYPE Slide (Standard)	CIRCUIT	SPST
	BODY MATERIAL	Polyphenylene Sulfide (PPS)
ACTUATOR LEVEL Flush, Recessed	ACTUATOR TYPE	Slide (Standard)
	ACTUATOR LEVEL	Flush, Recessed

Related Tags

C&K SDA04H0SB	SDA04H0SB Distributor	SDA04H0SB Supplier
SDA04H0SB Price	SDA04H0SB Pictures	SDA04H0SB Image
SDA04H0SB PDF Datasheet	SDA04H0SB Download Datasheet	SDA04H0SB Datasheet
SDA04H0SB Stock	Buy SDA04H0SB	Buy C&K SDA04H0SB
C&K SDA04H0SB	C&K Supplier	C&K Distributor
C&K SDA04H0SB	C&K Components SDA04H0SB	

Related Products



SDA04H1KD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 4356 pcs

RFQ



SDA04H0B

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 79908 pcs

RFQ

SDA03H1SKD



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 5305 pcs

RFQ

C&K

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 6081 pcs

RFQ



SDA03H1SBD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 57615 pcs



SDA04H0SBD

SDA04H0SKD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 57702 pcs

RFQ



SDA04H0SBR

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 43171 pcs

RFQ

RFQ

SDA04H0K



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 5125 pcs

RFQ

SDA04H0KD



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 6750 pcs

RFQ



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 3994 pcs

RFQ



SDA04H1BD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 90375 pcs

RFQ



SDA04H0BD

SDA04H0SK

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 90256 pcs

RFQ

Copyright © 2020 Reliable Distributor of Electronic Components

E-mail: Info@infinity-electronic.com

Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong

