N/A Image may be representation. See specifications for product details.

TPS2350PWG4

Part Number:

Manufacturer/Brand:

Product description Datasheets:

RoHs Status Stock Condition

Ship From

Shipment Way

TPS2350PWG4

N/A

IC MANAGER POWER HOTSWAP 14TSSOP

Lead free / RoHS Compliant

25519 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER TPS2350PWG4 MANUFACTURER N/A DESCRIPTION IC MANAGER POWER HOTSWAP 14TSSOP LEAD FREE STATUS / ROHS STATUS LEAD FREE FREE ROHS COmpliant LINTERNAL SWITCH(S) NO FEATURE SINS STATUS / FLITTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION HOT SWAP CONTROLLES A CHAPLE OF CHAPLE SOP CURRENT - OUTPUT (MXX) BASE PART NUMBER A TRS250 APPLICATIONS LABOR STATUS LEAD FREE STATUS / MORE STATUS / PG. RAMP, UV DETAILED DESCRIPTION HOT SWAP CONTROLLES A CHAPLE A CHAPLE A CHAPLE OF CHAPLE SOP CURRENT - OUTPUT (MXX) BASE PART NUMBER A TRS250		Specifications of TPS2350PWG4
MANUFACTURER N/A DESCRIPTION IC MANAGER POWER HOTSWAP 14TSSOP LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 25519 pcs DATA SHEET **** VOLTAGE - SUPPLY -80 V ~ -12 V TYPE Hot Swap Controller SUPPLIER DEVICE PACKAGE 14-TSSOP SERIES - PROGRAMMABLE FEATURES Current Limit, Fault Timeout, OVP, Slew Rate, UVLO PACKAGING Tube PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF CHANNELS 3 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LEAD FREE STATUS / ROHS STATUS Auto Retry FEATURES Auto Retry FEATURE PINS FLT, FLTTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) - BASE PART NUMBER TPS2350		
DESCRIPTION IC MANAGER POWER HOTSWAP 14TSSOP LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 25519 pcs DATAS SHEET VOLTAGE - SUPPLY 480 V ~ 12 V TYPE Hot Swap Controller SUPPLIER DEVICE PACKAGE 14-TSSOP SERIES - PROGRAMMABLE FEATURES Current Limit, Fault Timeout, OVP, Siew Rate, UVLO PACKAGING Tube PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF CHANNELS 3 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INTERNAL SWITCH(S) No FEATURE PINS Auto Retry FEATURE PINS AUTO RAMP, UV DETAILED DESCRIPTION HOLS Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) - BOSSON TESSSO	PART NUMBER	TPS2350PWG4
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 25519 pc DATA SHEET ************************************	MANUFACTURER	N/A
QUANTITY AVAILABLE 25519 pcs DATA SHEET 180 V ~ -12 V VOLTAGE - SUPPLY 480 V ~ -12 V TYPE Hot Swap Controller SUPPLIER DEVICE PACKAGE 14-TSSOP SERIES - PROGRAMMABLE FEATURES Current Limit, Fault Timeout, OVP, Slew Rate, UVLO PACKAGING Tube PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF CHANNELS 3 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INTERNAL SWITCH(S) No FEATURES Auto Retry FEATURE PINS /FLT, FLITTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTP UT (MAX) - BSE PART NUMBER TPS2350	DESCRIPTION	IC MANAGER POWER HOTSWAP 14TSSOP
DATA SHEET VOLTAGE - SUPPLY -80 V ~ -12 V TYPE Hot Swap Controller SUPPLIER DEVICE PACKAGE 14-TSSOP SERIES - PROGRAMMABLE FEATURES Current Limit, Fault Timeout, OVP, Slew Rate, UVLO PACKAGING Tube PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF CHANNELS 3 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INTERNAL SWITCH(S) No FEATURE PINS Auto Retry FEATURE PINS /FLT, FLTTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) - BSE PART NUMBER TPS2350	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE - SUPPLY TYPE Hot Swap Controller SUPPLIER DEVICE PACKAGE 14-TSSOP SERIES PROGRAMMABLE FEATURES CURRENT LIMIT, Fault Timeout, OVP, Slew Rate, UVLO PACKAGING Tube PACKAGING PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE A0°C ~ 85°C NUMBER OF CHANNELS MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS INTERNAL SWITCH(S) NO FEATURES Auto Retry FEATURE PINS FEATURE PINS DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) TPS2350	QUANTITY AVAILABLE	25519 pcs
TYPE SUPPLIER DEVICE PACKAGE SUPPLIER DEVICE PACKAGE 14-TSSOP SERIES - PROGRAMMABLE FEATURES CUrrent Limit, Fault Timeout, OVP, Slew Rate, UVLO PACKAGING Tube PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE A0°C ~ 85°C NUMBER OF CHANNELS SURface Mount MOUNTING TYPE SURface Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INTERNAL SWITCH(S) FEATURES AUto Retry FEATURE PINS FEATURE PINS FEATURE PINS CURRENT - OUTPUT (MAX) BASE PART NUMBER TPS2350 TPS2350	DATA SHEET	
SUPPLIER DEVICE PACKAGE SERIES CURRENT SOUR SERIES PROGRAMMABLE FEATURES CURRENT LIMIT, Fault Timeout, OVP, Slew Rate, UVLO PACKAGING Tube PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF CHANNELS MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INTERNAL SWITCH(S) No FEATURES Auto Retry FEATURES AUto Retry FEATURE PINS /FLT, FLTTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) TPS2350	VOLTAGE - SUPPLY	-80 V ~ -12 V
SERIES PROGRAMMABLE FEATURES Current Limit, Fault Timeout, OVP, Slew Rate, UVLO PACKAGING Tube PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE A0°C ~ 85°C NUMBER OF CHANNELS MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS INTERNAL SWITCH(S) FATURES AUTO RETURN FEATURE PINS FEATURE PINS DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) BASE PART NUMBER TPS2350	TYPE	Hot Swap Controller
PROGRAMMABLE FEATURES Current Limit, Fault Timeout, OVP, Slew Rate, UVLO PACKAGING Tube PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF CHANNELS Surface Mount MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INTERNAL SWITCH(S) No FEATURES Auto Retry FEATURE PINS DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) BASE PART NUMBER TPS2350	SUPPLIER DEVICE PACKAGE	14-TSSOP
PACKAGING PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE A0°C ~ 85°C NUMBER OF CHANNELS SURface Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS INTERNAL SWITCH(S) NO FEATURES FEATURES FEATURE PINS FEATURE PINS CURRENT- OUTPUT (MAX) BASE PART NUMBER TUBE TUBE 14-TSSOP (0.173", 4.40mm Width) A0°C ~ 85°C A0°C ~ 80°C A0°C ~ 85°C A0°C ~ 85°C A0°C ~ 80°C A0°C	SERIES	-
PACKAGE / CASE 14-TSSOP (0.173", 4.40mm Width) OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF CHANNELS SURFACE Mount MOUNTING TYPE Surface Mount (1 (Unlimited) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INTERNAL SWITCH(S) NO FEATURES Auto Retry FEATURE PINS FEATURE PINS DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) BASE PART NUMBER 14-TSSOP (0.173", 4.40mm Width) 3-40°C ~ 85°C 40°C ~ 85°C 10 (Intimited) 10 (Intimited) 10 (Intimited) 10 (Intimited) 11 (Intimited) 12 (Intimited) 13 (Intimited) 14 (Intimited) 15 (Intimited) 16 (Intimited) 17 (Intimited) 18 (Intimited) 18 (Intimited) 18 (Intimited) 19 (Intimited) 19 (Intimited) 10 (Intimited) 10 (Intimited) 10 (Intimited) 10 (Intimited) 11 (Intimited) 11 (Intimited) 12 (Intimited) 13 (Intimited) 14 (Intimited) 15 (Intimited) 16 (Intimited) 17 (Intimited) 18 (Intimited) 18 (Intimited) 19 (Intimited) 10 (Intimited) 10 (Intimited) 10 (Intimited) 10 (Intimited) 10 (Intimited) 10 (Intimited) 11 (Intimited) 11 (Intimited) 12 (Intimited) 13 (Intimited) 14 (Intimited) 15 (Intimited) 16 (Intimited) 16 (Intimited) 17 (Intimited) 18 (Int	PROGRAMMABLE FEATURES	Current Limit, Fault Timeout, OVP, Slew Rate, UVLO
OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF CHANNELS 3 MOUNTING TYPE SURFACE MOUNT MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INTERNAL SWITCH(S) No FEATURES Auto Retry FEATURE PINS /FLT, FLTTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) TPS2350	PACKAGING	Tube
NUMBER OF CHANNELS3MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINTERNAL SWITCH(S)NoFEATURESAuto RetryFEATURE PINS/FLT, FLTTIM, OV, PG, RAMP, UVDETAILED DESCRIPTIONHot Swap Controller 3 Channel -48V 14-TSSOPCURRENT - OUTPUT (MAX)-BASE PART NUMBERTPS2350	PACKAGE / CASE	14-TSSOP (0.173", 4.40mm Width)
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS No FEATURES Auto Retry FEATURE PINS FEATURE PINS CURRENT - OUTPUT (MAX) BASE PART NUMBER Surface Mount 1 (Unlimited) Lead free / RoHS Compliant No Auto Retry FILT, FLTTIM, OV, PG, RAMP, UV THOS Wasp Controller 3 Channel -48V 14-TSSOP TPS2350 TPS2350	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INTERNAL SWITCH(S) No FEATURES Auto Retry FEATURE PINS /FLT, FLTTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) BASE PART NUMBER I (Unlimited) Lead free / ROHS Compliant No No TEXTURE PINS FEATURE PINS TEXTURE PINS TEXTUR	NUMBER OF CHANNELS	3
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINTERNAL SWITCH(S)NoFEATURESAuto RetryFEATURE PINS/FLT, FLTTIM, OV, PG, RAMP, UVDETAILED DESCRIPTIONHot Swap Controller 3 Channel -48V 14-TSSOPCURRENT - OUTPUT (MAX)-BASE PART NUMBERTPS2350	MOUNTING TYPE	Surface Mount
INTERNAL SWITCH(S) REATURES Auto Retry FEATURE PINS FEATURE PINS DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) BASE PART NUMBER TPS2350	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURE PINS /FLT, FLTTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) - BASE PART NUMBER TPS2350	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
FEATURE PINS PLT, FLTTIM, OV, PG, RAMP, UV DETAILED DESCRIPTION CURRENT - OUTPUT (MAX) BASE PART NUMBER TPS2350	INTERNAL SWITCH(S)	No
DETAILED DESCRIPTION Hot Swap Controller 3 Channel -48V 14-TSSOP CURRENT - OUTPUT (MAX) - BASE PART NUMBER TPS2350	FEATURES	Auto Retry
CURRENT - OUTPUT (MAX) - BASE PART NUMBER TPS2350	FEATURE PINS	/FLT, FLTTIM, OV, PG, RAMP, UV
BASE PART NUMBER TPS2350	DETAILED DESCRIPTION	Hot Swap Controller 3 Channel -48V 14-TSSOP
	CURRENT - OUTPUT (MAX)	-
APPLICATIONS -48V	BASE PART NUMBER	TPS2350
	APPLICATIONS	-48V

TPS2350PWG4 Dietributor

Related Tags

TPS2350PWG4	TPS2350PWG4 Distributor	TPS2350PWG4 Supplier
TPS2350PWG4 Price	TPS2350PWG4 Pictures	TPS2350PWG4 Image
TPS2350PWG4 PDF Datasheet	TPS2350PWG4 Download Datasheet	TPS2350PWG4 Datasheet
TPS2350PWG4 Stock	Buy TPS2350PWG4	Buy TPS2350PWG4
TPS2350PWG4	Supplier	Distributor

Related Products

