SD04H1SB Details PDF





Image may be representation. See specifications for product details.

SD04H1SB

Part Number:
Manufacturer/Brand:
Product description
Datasheets:
RoHs Status
Stock Condition
Ship From
Shipment Way

SD04H1SB C&K SWITCH SLIDE DIP SPST 100MA 25V SD04H1SB.pdf Lead free / RoHS Compliant 75022 pcs stock Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION


Specifications of SD04H1SB

NAMIJACTURER Eak DESCRIPTION SWITCH SLIDE DIS PSET 100MA 25V LEAD FREE STATUS / ROHS STATUS Ead free / ROHS Compliant QUANTITY AVAILABLE SWOOLAGE COmpliant QUANTITY AVAILABLE SWOOLAGE COmpliant VICHAGE RATING SWOOLAGE COMPLIANCE VICHAGE RATING TOME PARTATURE AUGY COMPLIANCE		
DESCRIPTIONSINTCH SLIDE DIPS NOM 25VLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantQUANTIY AVAILABLES022 pcsDATA SHEETSINDHISE pdfWASHABLEVSVOLTAGE RATINGSVCSERIESOIL 000 (2.54 mm, PullPTCH0.100° (2.54 mm, PullPARCAGINGSOUHISE pdfOTHER MANESSOUHISE pdfOTHER ANDESSOUHISE pdfOTHER ANDESSOUHISE pdfOTHER ANDESSOUHISE pdfOTHER ANDESSOUHISE pdfOTHER ANDES FOR STATUSAUG CASCHINGMUMERE OF POSITIONS400 CASCHINGMOUTING TYPE RATUREAUG CASCHINGMOUTING TYPE RATURECON CASCHINGMOUTING TYPE RATURESOUNCHING SUM CASCHING SUM CASCHING SUM CASCHINGMOUTING TYPE RATURECON CASCHINGMOUTING TYPE RATURECON CASCHINGMOUTING TYPE RATURESOUNCHING SUM CASCHING SUM CASCHING SUM CASCHINGRECHANICAL LIFECON CASCHING SUM CASCHIN	PART NUMBER	SD04H1SB
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantQUANTTY AVAILABLE5024 pcsDATA SHEETSOMHISB pdfWASHABLEVSVOLTAGE RATINGSINOCTERMINATION STYLEGII WingSERESDPTCH0.00° (2.54m), PullPACKAGINGVOLTAGE RATINGOTHER NAMESSOMHISB SCH SINOSOTHER NAMESSOMHISB SCH SINOSONDUTING TEMPERATURESOMSCH SCH SCH SINOSNUMERTAL LIFESONG SCH SCH SINOS SUFFICIENTICALISEIEGT RADVE SOARDISING SCH SCH SINOS SUFFICIENTICALISEIEGT RADVE SOARDSONG SCH SCH SINOS SUFFICIENTICALISE SCH SINOS SUFFICIENTICALISEIEGT RADVE SOARDSONG SCH SCH SINOS SUFFICIENTICALISE SCH SINOS SUFFICIENTICALISEIEGT RATINGSONG SCH SINOS SUFFICIENTICALISE SCH SINOS SUFFICIENTICALISEIEGT RATINGSONG SCH SINOS SUFFICIENTICALISE SCH SINOS SUFFICIENTICALISE SCH SINOS SUFFICIENTICALISEIEGT RATINGSONG SCH SINOS SUFFICIENTICALISE SCH SINOS SUFFICIENTICALISE SCH SINOS SU		
QUANTIY AVAILABLE502 pcsDATA SHEET© 5004H1SB.pdfVACTAGE RATINGVSVOLTAGE RATINGGNUSTRISSOFITHIOI (° 2.4 mm, FullPITCHIOI (° 2.4 mm, FullPACAGINGVBOTHER NAMES- 600 × 650 × 600	DESCRIPTION	SWITCH SLIDE DIP SPST 100MA 25V
DATA SHEETSci04H1S8,pdfWASHABLEYoVICTAGE RATINGSVCYOLTAGE RATINGGUI WINGSERIESSDPITCHD10° (2.54mm), FullPACKAGINGTbeOTHER NAMESSONH152OTHER NAMES40° C > SPCOTHER NAMES40° C > SPCNUMBER OF POSITIONS4MOUTING TYPESURGINGMOUTING TYPE(Ulninked)MOUTING TYPE2000 CyclesLEIGT HA GOVE BOARDJOS (ASSM)EIGT HA GOVE BOARDJOS (ASSM)EIGT RATUS C NON STATUSSON STATUS FUNGLEIGT RATUS C NON STATUSSON STATUS FUNGCARENT RATUNGSON STATUS FUNGCARENT RATUNGSON STATUS FUNGCARENT RATUNGSON STATUS FUNGCARENT RATUNGSON STATUS FUNG STATUSCARENT RATUSSON STATUS FUNG STATUSCARENT RATUNGSON STATUS FUNG STATUSCARENT RATUNGSON STATUS FUNG SUTATUS FUNG SUTATUS FUNG SUTATUS FUNG SUTATUS FUNG SUTATUS FUNG SUTATUS FUNG SUTATUSCARENT RATUNGSON STATUS FUNG SUTATUSCUNTACT FINISHGUICUNTACT FINISHSON SATURESCUNTACT FINISHSON SATURESCUNTACT FINISHSON SATURESCUNTACT FINISHSON SATURESCUNTACT FINISHSON SATURESCUNTACT FINISHSON SATURESCUNTACT FINISHSON SATURES<	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
WSHABLEYesVOTAGE PATINGSVDCTEMINATION STYLEGIU MIGSREESSOPACAGINGIOO (2.54mm), FUIPACAGINGSVORTAGEOTHER NAMESSVORTAGEOTHER NAMESSVORTAGEOTHER NAMESSVORTAGEOTHER NAMESSVORTAGEOTHER NAMESSVORTAGEOTHER NAMESSVORTAGEOTHER NAMESSVORTAGEOTHER NAMESSVORTAGEOTHER NAMESSVORTAGEMUMERE OF DISTIONSAMUMERE OF DISTIONSSVORTAGEMUNTER STINTTY LEVEL (MSL)SVORTAGEMUSTURE STATUST FORSSVORTAGEMECHANDCA LIFESVORTAGELIFTA ADAVE BOARDSVORTAGEFATURESSVORTAGEFATURESSVORTAGEDISTINT STATUSSVORTAGEGURANTATINGSVORTAGECONTACT FINISHGUACONTACT FINISHSVITCONTACT	QUANTITY AVAILABLE	75022 pcs
VOLTAGE RATING2NOCTERNINATION STYLEGIN WIGSERIESSOPITCH0.00° (2.54mm) FullPACKAGINGTWOPERATINGSOOPERATING TEMPERATURE-00° COPERATING TEMPERATURE-00° CMUNDERO F POSITIONS4MOUNTING TYPESURSAGINGMOUNTING TYPEJUNG VOLGEMICHANALLIFEJON CYClesLIGHT ALLOY E DARDAJON CYClesLIGHTA LIFEJON CYClesLIGHT ALLOY E DARDAJON CYClesLIGHT ALLOY E DARDAJON CYClesLIGHT ALLOY E DARDAJON CYClesLIGTALLIFEJON CYClesLIGTALLIFEJON CYClesLIGTALLIFEJON CYClesLIGTALLIFEJON CYClesLIGTALLIFEJON CYClesCONTACT MATERIALGONCONTACT FINISHGINCONTACT FINISHGINCONTACT FINISHSIGCONTACT FINISHSIGNAMIC (PAN)CONTAREIALASIGNAMIC (PAN)CONTAREIALASIGNAMIC (PAN)CONTAREIALASIGNAMIC (PAN)CONTAREIALASIGNAMIC (PAN)CONTAREIALASIGNAMIC (PAN)CONTAREIALASIGNAMIC (PAN)CIALDA TENELSIGNAMIC (PAN)CIALDA TENELSIGNAMIC (PAN)	DATA SHEET	DI SD04H1SB.pdf
TRMINATION STYLEGul WingSRIESS0PTCH0.00° (.34mm, FullPACAGINGToeortHER NAMES0.00° (.34mm, FullOTHER NAMES0.00° (.34mm, FullOPERATING TEMPERATURE0.00° (.30°	WASHABLE	Yes
S PITCH 0.00° (2.54m), Full PACKAGING Tube ortHER NAMES 50°04H158 OPERATING TEMPERATURE 40°C ~ 85°C NUMEER OF POSITIONS 4 MOUTING TYPE Garde Mount MOUTING TYPE (Inlinited) MOUTING TYPE 2000 Cycles ILGATAR AEXONE 2000 Cycles ILGATAR AEXONE 2000 Cycles ILGAT RAEXONE BOARD 2000 Cycles ILGATAR AEXONE BOARD 2000 Cycles ILGATAR AEXONE BOARD 2000 Cycles ILGATAR ATINS 2000 Cycles ILGATAR ATINS 2000 Cycles ILGATAR ATINS 2000 Cycles ILGATARATINS 2000 Cycles ILGATAR ATINS 2000 Cycles ILGATARATINS 2000 Cycles ILGATARATINS 2000 Cycles ILGATARATEXILA 2000 Cycles ILGATATATINS 2000 Cycles <tr< td=""><td>VOLTAGE RATING</td><td>25VDC</td></tr<>	VOLTAGE RATING	25VDC
PTCH0.00°(2.4mm, FullPACKAGINGTuGOTHER NAMESSKN0HISSOTHER NAMES40°C ~ 85°CNUMBER OF POSITIONS4MOUNTING TYPESKN0HISGMOUNTING TYPE(10Imited)MOSTURE SENSITIVITY LEVEL (MSL)(10Imited)MECHANICAL LIFE0.00 CyclesLENGTH(16CTAGNDE)LEAD FREATING SAMUS(16CTAGNDE)LEAD FREATING SAMUS(16CTAGNDE)LEAD FREATING NG(16CTAGNDE)LEAD FREATING NG(16CTAGNDE)LEATING(16CTAGNDE)LEATING(16CTAGNDE)CIATURA <td>TERMINATION STYLE</td> <td>Gull Wing</td>	TERMINATION STYLE	Gull Wing
PACKAGINGTubeorter NAMESS004H1SB S004H1SB S004H1SBorter NAMES-40° ~ 85°CNUMBER OF POSITIONS4MOUNTING TYPESuface MountMOUNTING TYPE(Minited)MOLTAL LIFE200 CyclesLENGTHCaffer AGNC MountHEGHAN LIFESuface MountLENGTHSuface MountLIGNTA MATERIALSuface MountCONTACT FINISHSuface MountCONTACT FINISHSuface MountBOY MATERIALSuface MountLIGNTATERIALSuface MountSuface Mo	SERIES	SD
ofHer NAMESSD04H1SB SN04H12OPERATING TEMPERATURE4MC ~ 8S°CNUMBER OF POSITIONS4MOUNTING TYPESarae MontaMOUNTING TYPE(Julinide)MCGALALLIFEJ00 CyclesLENGTHCAS*C MONTALENGTHCAS*C MONTAHEIGHT ABOVE BOARDJ00 CyclesELERTRIAL IFEJ00 CyclesLEIGTRIAL IFEJ00 CyclesLEIGTRIAL IFEJ00 CyclesELERTRIAL IFEJ00 CyclesELERTRIAL IFEJ00 CyclesELERTRIAL IFEJ00 CyclesELERTRIAL IFEJ00 CyclesCURRENT RATINGJ00 CyclesCURRENT RATINGJ00 CyclesCURRENT RATINGJ00 CyclesCURRENT RATINGJ00 CyclesCURRENT RATINGJ00 CyclesCURRENT RATINGGMICMORENTERATURENTONCONACT FINISHGuldCONACT FINISHSPEBODY MATERIALSPECONTARTRIALSPENDATIONENTIONCONTARTRIALSPENDATIONENTIONCONTARTRIALSPENDATIONENTIONCONTARTRIALSPENDATIONENTIONCONTARTRIALSPENDATIONENTI	PITCH	0.100" (2.54mm), Full
OTHER MARIESCKN6117OPERATING TEMPERATURE40°C ~ 85°CNUMBER OF POSITIONS4MOUNTING TYPESuface MountMOINTING TYPE(Iulimited)MCISTURE SENSITIVITY LEVEL (MSL)(Julimited)LENGTH2,000 CyclesLENGTHLead Free / ROHS CompliantLENGTH0.80°C (ASS°)LEAD FREE STATUS / ROHS STATUSLead Free / ROHS CompliantHEIGHT ABOVE BOARD1.80° (4.57m)ELECTRICAL LIFE2,000 CyclesELECTRICAL LIFE0.900 CyclesELECTRICAL LIFE0.900 CyclesELECTRICAL LIFE0.900 CyclesCURRENT RATING0.900 CyclesCURRENT RATING0.900 CyclesCURRENT RATING0.900 CyclesCURRENT RATING0.900 CyclesCURRENT RATING0.900 CyclesCONTACT FINISHGoldCONTACT FINISHGoldBODY MATERIAL0.901 CyclesBODY MATERIALSibit Cycles (PAR)BODY MATERIALSibit Cycles (PAR)Sibit Contact TYPESibit Cycles (PAR)	PACKAGING	Tube
NUMBER OF POSITIONS4NUMBER OF POSITIONSSuface MontMOUNTING TYPESuface MontMOSTURE SENSITIVITY LEVEL (MSL)(Iulimita)MECHANICAL LIFEOBO QdeLENGTHGaffer ABONELEAD FREE STATUS / ROMS STATUSGaffer ABONEHEIGHT ABOVE BOARDSIB (Stringmentantic)FEATURESTape SalELECTRICAL LIFEJON QdeCURRENT RATINGOBO VIGACURRENT RATINGGioland CompanyCONTACT FINISHGulCONTACT FINISHGulCRUTTSPTFODY MATERIALSiphthamine (PAN)ROM MATERIALSiph	OTHER NAMES	
MOUNTING TYPESurface MountMOUNTING TYPE(ulimited)MOISTURE SENSITIVT LEVEL (MSL)(ulimited)MECHANICAL LIFE2000 CyclesLENGTH(LaST (MSL))LEAD FREE STATUS / ROHS STATUS(alf ref / ROHS CompliantHEIGHT ABOVE BOARD(Bol (MSL))FEATURES300 CyclesELECTRICAL LIFE(Don Cycles)CURRENT RATING(Bolk (MSL))CURRENT RATING(Bolk (MSL))CURRENT RATING(Bolk (MSL))CONTACT FINISHGoldCONTACT FINISHSold (MSL))CONTACT FINISH(Sig Mande) (PASL)ROM MATERIALSig Mande) (P	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL)i (Unimited)MOISTURE SENSITIVITY LEVEL (MSL)i (Dimited)MCHANICAL LIFEi (Dimited)LENGTHi (A5% (1.63mm)LEAD FREE STATUS / ROHS STATUSi (Baf re/ RoHS CompliantHEIGHT ABOVE BOARDi (Baf (4.57mm)FATURESi (Dimited)ELCTRICAL LIFEi (Dimited)DETAILED DESCRIPTIONi (Dimited)CURRENT RATINGi (Dimited)CONTACT MATERIALi (Dimited)CONTACT FINISHi (Dimited)CONTACT FINISHi (Dimited)CONTACT RATINGi (Dimited)CONTACT MATERIALi (Dimited)BODY MATERIALi (Dimited)BOD	NUMBER OF POSITIONS	4
MECHANICAL LIFE2,000 CyclesLENGTH0.458° (11.63 mm)LEAD FREE STATUS / ROHS STATUSLed free / ROHS CompliantHEIGHT ABOVE BOARD0.80° (4.57 mm)FATURESTape SealELECTRICAL LIFE0.000 CyclesCURRENT RATING100mACONTACT MATERIALBeylium CopperCONTACT FINISHGodCONTACT FINISHSPSTBODY MATERIALPiphthamide (PAPA)ACUATOR TAPESpiphthamide (PAPA)	MOUNTING TYPE	Surface Mount
LindLENGTH6458° (11.63m)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.80° (4.57m)FATURESTape SealELECTRICAL LIFE0.000 CyclesDETAILED DESCRIPTIONDis Wich SPST 4 Position Surface Mount Slide (Standard) Actuator 100mA 25VDCCURRENT RATING0.000 CyclesCONTACT MATERIALBerlium CopperCONTACT FINISHGoldBODY MATERIALSPSTBODY MATERIALDisyltanaide (PPA)ACTUATO TYPESie (Standard)	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.180° (4.57mm)FEATURESTape SealELECTRICAL LIFE0.000 CyclesDETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 100mA 25VDCCURRENT RATING0.000 CyclesCONTACT MATERIALBerylium CooperCONTACT FINISHGoldCONTACT FINISHPSTBODY MATERIALPolyphthamide (PPA)ACUATOR TYPEBie (Standard)	MECHANICAL LIFE	2,000 Cycles
HEIGHT ABOVE BOARD0.80° (4.57mm)FEATURESTape SealELCTRICAL LIFE0.000 CyclesDETAILED DESCRIPTIONDis Wich SPST 4 Position Surface Mount Slide (Standard) Actuator 100mA 25VDCCURRENT RATING00mACONTACT FINISHGoldCROUTSPSTBODY MATERIALPolyhthalmide (PPA)ACTUATOR YPESile (Standard)	LENGTH	0.458" (11.63mm)
FEATURESTape SealELECTRICAL LIFE2,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 100mA 25VDCCURRENT RATING100mACONTACT MATERIALBerylium CopperCONTACT FINISHGldCIRCUITSPSTBODY MATERIALPolynthalamide (PPA)ACTUATOR YPESile (Standard)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE2,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 100mA 25VDCCURRENT RATING10mACONTACT MATERIALBeylium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyphtalamide (PPA)ACTUATOR TYPEBid (Standard)	HEIGHT ABOVE BOARD	0.180" (4.57mm)
DETAILED DESCRIPTIONDip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 100mA 25VDCCURRENT RATING100mACONTACT MATERIALBerylium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyhtlamide (PAA)ACTUATOR TYPESide (Standard)	FEATURES	Tape Seal
CURRENT RATING100mACONTACT MATERIALBerylium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyhthalmide (PPA)ACTUATOR TYPESide (Standard)	ELECTRICAL LIFE	2,000 Cycles
CONTACT MATERIALBerylium CopperCONTACT FINISHGoldCIRCUITSPSBODY MATERIALPolynthalamide (PPA)ACTUATOR TYPESide (Standard)	DETAILED DESCRIPTION	Dip Switch SPST 4 Position Surface Mount Slide (Standard) Actuator 100mA 25VDC
CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphthalmide (PPA) ACTUATOR TYPE Side (Standard)	CURRENT RATING	100mA
CIRCUITSPSTBODY MATERIALPolyphthalamide (PPA)ACTUATOR TYPESide (Standard)	CONTACT MATERIAL	Beryllium Copper
BODY MATERIAL Polyphthalamide (PPA) ACTUATOR TYPE Slide (Standard)	CONTACT FINISH	Gold
ACTUATOR TYPE Slide (Standard)	CIRCUIT	SPST
	BODY MATERIAL	Polyphthalamide (PPA)
ACTUATOR LEVEL Raised	ACTUATOR TYPE	Slide (Standard)
	ACTUATOR LEVEL	Raised

Related Tags

C&K SD04H1SB	SD04H1SB Distributor	SD04H1SB Supplier
SD04H1SB Price	SD04H1SB Pictures	SD04H1SB Image
SD04H1SB PDF Datasheet	SD04H1SB Download Datasheet	SD04H1SB Datasheet
SD04H1SB Stock	Buy SD04H1SB	Buy C&K SD04H1SB
C&K SD04H1SB	C&K Supplier	C&K Distributor
C&K SD04H1SB	C&K Components SD04H1SB	

Related Products



SD04H0SBD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 49547 pcs

RFQ



SD04H0SK

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 5922 pcs

RFQ



SD04H1BD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 58894 pcs

RFQ



SD04H1SBR

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 71266 pcs

RFQ

SD05-01FTG



Manufacturers: Hamlin / Littelfuse Description: TVS DIODE 5V 16.8V SOD323 In stock: 747781 pcs



SD04H0SBR

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 76299 pcs

RFQ

SD05.TCT

Manufacturers: Semtech Description: TVS DIODE 5V 14.5V SOD323 In stock: 106083 pcs

RFQ

RFQ

SD04H1B Manufacturer

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 60754 pcs

RFQ

SD05-7 Manufacturers: Diodes Incorporated Description: TVS DIODE 5V 14.5V SOD323 Manufacturers: Micro Commercial Components (MCC) In stock: 275246 pcs Description: 5V,ESD PROTECTION DEVICES,SOD-32 In stock: 1091892 pcs In stock: 1091892 pcs



SD04H0SB1R

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 64724 pcs

RFQ



Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 100MA 25V In stock: 5229 pcs

RFQ

SD04H1SK

Copyright © 2020 Reliable Distributor of Electronic Components

E-mail: Info@infinity-electronic.com

0.10

Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong

