Grayhill



Grayhill, Inc.

44HG30-04-4-02N

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way 44HG30-04-4-02N

Grayhill, Inc.

SWITCH ROTARY 125 DEG;C, LOW LEV

RoHS Compliant 418 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER 44H630-044-02N MANUFACTURER Grayhill. Inc. DESCRIPTION SWITCH ROTARY 125 DEG;C, LOW LEV LEAD FREE STATUS / ROHS STATUS ROHS COMPilant QUANTITY AVAILABLE 418 pcs DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - DC 115V TERRIHATION STYLE SOIGHT MUST ACCOUNTED THE STATUS ROHS COMPILANT ACCOUNTED THE STATUS ROHS COMPILANT ACCOUNTED THE STATUS ROHS ACCOUNTED THE STATUS ROHS ACCOUNTED THE STATUS ACCOUNTED THE SOIGHT MUST ACCOUNTED THE STATUS ACCOUNTED		Sne	ecifications of 44HG30-04-4-02N
MANUFACTURER DESCRIPTION SWITCH ROTARY 125 DEG/C, LOW LEV LEAD FREE STATUS / ROHS STATUS ROHS Compliant QUANTITY AVAILABLE 418 pcs DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE SORIES 44 ROHS STATUS ROHS STATUS ROHS COMPLIANT PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83g/m NUMBER OF POLES PER DECK 4 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 4 NUMBER OF DECKS 4 NUMBER OF DECKS 5-FAITURS PANEL ROHS STATUS PANEL ROHS STATUS 1NDEX STOPS FIXED FEATURES - CETAILED DESCRIPTION ROTARY DETAILED DESCRIPTION ROTARY DETAILED DESCRIPTION ROTARY DETAILED DESCRIPTION ROTARY CURRENT RATING 1A (AC/DC) CONTACT THINING NON-Shorting (B8M) CONTACT THINING CONTACT FINISH - CURCUIT PER DECK 4 ROLL STOPS FIXED CONTACT FINISH - CURCUIT PER DECK 4 ROLL STOPS FIXED CONTACT FINISH - CURCUIT PER DECK 4 ROLL STOPS FIXED			ichications of Throsport Toziv
DESCRIPTION SWITCH ROTARY 125 DEG;C, LOW LEV LEAD FREE STATUS / ROHS STATUS ROHS Compliant QUANTITY AVAILABLE 418 pcs DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS COMPLIANT STATUS ROHS STATUS ROHS COMPLIANT ROHS ROHS COMPLIANT ROHS ROHS COMPLIANT ROHS ROHS COMPLIANT ROHS ROHS ROHS ROHS ROHS ROHS ROHS ROHS		PART NUMBER	44HG30-04-4-02N
LEAD FREE STATUS / ROHS STATUS RoHS Compilant QUANTITY AVAILABLE 418 pcs DATA SHEET 28V VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS Compilant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PEDECK 4 NUMBER OF DECKS 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT IA (AC/DC) 115VAC Panel Mount DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT IA (AC/DC) 115VAC Panel Mount CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Silver Alloy CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		MANUFACTURER	Grayhill, Inc.
QUANTITY AVAILABLE 418 pcs DATA SHEET VOLTAGE RATING - DC VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS Compilant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF POLES PER DECK 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTAGE Solition 4PDT 1A (AC/DC) 115VAC Panel Mount DETHIED DESCRIPTION ROTAGE Solition 4PDT 1A (AC/DC) 115VAC Panel Mount CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		DESCRIPTION	SWITCH ROTARY 125 DEG;C, LOW LEV
DATA SHEET VOLTAGE RATING - DC 28W VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS COMPliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 MUMBER OF DECKS 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTAGY SWItch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount CURRENT RATING CURRENT RATING CONTACT TIMING NOn-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK APDT ANGLE OF THROW 30° Flatted (6.35mm Dia)		LEAD FREE STATUS / ROHS STATUS	RoHS Compliant
VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS Compilant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount DETH BEHIND PANEL 52.40mm CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		QUANTITY AVAILABLE	418 pcs
VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS Compilant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount DETH BEHIND PANEL 52.40mm CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		DATA SHEET	
TERMINATION STYLE SERIES 44 ROHS STATUS ROHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF POLES PER DECK 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° Rotary Smm Dia)		VOLTAGE RATING - DC	28V
SERIES 44 ROHS STATUS ROHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 52.40mm CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		VOLTAGE RATING - AC	115V
ROHS STATUS ROHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POSITIONS 2 NUMBER OF DECKS 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTARY Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount CURRENT RATING CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT FINISH CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		TERMINATION STYLE	Solder Lug
PANEL CUTOUT DIMENSIONS OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES DETAILED DESCRIPTION ROTARY Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount CURRENT RATING CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH CURCUIT PER DECK APDT ANGLE OF THROW 30° Flatted (6.35mm Dia)		SERIES	44
OPERATING FORCE NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTARY SWITCH 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount CURRENT RATING CURRENT RATING CONTACT TIMING NOn-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 30° Flatted (6.35mm Dia)		ROHS STATUS	RoHS Compliant
NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 4 NUMBER OF DECKS 4 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° Flatted (6.35mm Dia)		PANEL CUTOUT DIMENSIONS	-
NUMBER OF POLES PER DECK NUMBER OF DECKS MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTAGY Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING LA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)		OPERATING FORCE	5.761 ~ 83gfm
NUMBER OF DECKS4MOUNTING TYPEPanel MountINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel MountDEPTH BEHIND PANEL52.40mmCURRENT RATING1A (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALSilver AlloyCONTACT FINISH-CIRCUIT PER DECK4PDTANGLE OF THROW30°ACTUATOR TYPEFlatted (6.35mm Dia)		NUMBER OF POSITIONS	2
MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 52.40mm CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE FIAITED.		NUMBER OF POLES PER DECK	4
INDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel MountDEPTH BEHIND PANEL52.40mmCURRENT RATING1A (AC/DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALSilver AlloyCONTACT FINISH-CIRCUIT PER DECK4PDTANGLE OF THROW30°ACTUATOR TYPEFlatted (6.35mm Dia)		NUMBER OF DECKS	4
FEATURES DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		MOUNTING TYPE	Panel Mount
DETAILED DESCRIPTION Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 52.40mm CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		INDEX STOPS	Fixed
DEPTH BEHIND PANEL CURRENT RATING 1A (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 30° ACTUATOR TYPE 52.40mm 4AC/DC) ANGLE OF THROW 52.40mm 52.40mm 52.40mm 52.40mm 6BM) ACTUATOR TYPE 52.40mm 52.40mm 6BM) ACTUATOR TYPE 53.40mm 6BM) ACTUATOR TYPE 54.40mm 6BM) ACTUATOR TYPE 6BM 6BM 6BM 6BM 6BM 6BM 6BM 6B		FEATURES	-
CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE 1A (AC/DC) Non-Shorting (BBM) Silver Alloy 4PDT 4PDT ACTUATOR TYPE Flatted (6.35mm Dia)		DETAILED DESCRIPTION	Rotary Switch 2 Position 4PDT 1A (AC/DC) 115VAC Panel Mount
CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		DEPTH BEHIND PANEL	52.40mm
CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Silver Alloy - 4PDT 30° Flatted (6.35mm Dia)		CURRENT RATING	1A (AC/DC)
CONTACT FINISH		CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECK 4PDT ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		CONTACT MATERIAL	Silver Alloy
ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)		CONTACT FINISH	-
ACTUATOR TYPE Flatted (6.35mm Dia)		CIRCUIT PER DECK	4PDT
		ANGLE OF THROW	30°
ACTUATOR LENGTH 11.10mm		ACTUATOR TYPE	Flatted (6.35mm Dia)
		ACTUATOR LENGTH	11.10mm

Related Tags

Grayhill, Inc. 44HG30-04-4-02N	44HG30-04-4-02N Distributor	44HG30-04-4-02N Supplier
44HG30-04-4-02N Price	44HG30-04-4-02N Pictures	44HG30-04-4-02N Image
44HG30-04-4-02N PDF Datasheet	44HG30-04-4-02N Download Datasheet	44HG30-04-4-02N Datasheet
44HG30-04-4-02N Stock	Buy 44HG30-04-4-02N	Buy Grayhill, Inc. 44HG30-04-4-02N
Grayhill, Inc. 44HG30-04-4-02N	Grayhill, Inc. Supplier	Grayhill, Inc. Distributor
Grayhill, Inc. 44HG30-04-4-02N	Grayhill Inc. 44HG30-04-4-02N	

Related Products



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 125 DEG;C, LOW LEV

44HG30-01-1-02S

In stock: 1677 pcs

RFQ

Grayhill

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 125 DEG;C, LOW LEV

44HG45-01-1-05N

In stock: 1136 pcs

RFQ



44HG45-04-1-07N

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 125 DEG;C, LOW LEV

In stock: 579 pcs

RFQ



44HG45-01-1-02N

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 125 DEG;C, LOW LEV

In stock: 1091 pcs **RFQ**



44HG30-05-4-03N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 125 DEG;C, LOW LEV In stock: 322 pcs

RFQ



44HG45-02-1-08N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 125 DEG;C, LOW LEV In stock: 756 pcs

RFQ



Grayhill

44HG30-01-1-05N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 125 DEG;C, LOW LEV In stock: 1539 pcs

RFQ




44HG45-01-2-03S Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 125 DEG;C, LOW LEV In stock: 1182 pcs

RFQ

44HG30-03-1-05N



In stock: 1016 pcs

RFQ



Grayhill

44HG30-02B12N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 125 DEG;C, LOW LEV In stock: 896 pcs

RFQ



44HG30-02-1-12N Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY LOW LEVEL RATING,

In stock: 758 pcs

RFQ



In stock: 1434 pcs

44HG30-01-1-03N

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 125 DEG;C, LOW LEV

RFQ



Copyright © 2020 Reliable Distributor of Electronic Components

