



S1AW-WL

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way S1AW-WL

NKK Switches

MEDIUM CAPACITY STANDARD SIZE TO

S1AW-WL.pdf

Lead free / RoHS Compliant

6798 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for

product details.

PART NUMBER SLAW-WL MANUFACTURER NICK SWITCHES DESCRIPTION MEDIUM CAPACITY STANDARD SIZE TO Lead FREE STATUS / ROHS STATUS Load free / ROHS Compliant QUANTITY AVAILABLE 6798 ps DATA SHEET VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 125V TERMINATION STYLE Wire Leads SWITCH FUNCTION On-Off SERIES S PAMEL CUTOUT DIMENSIONS CITCAIAT - 12.50mm Dia Bulk OTHER NAMES 360-3675 COPEATING TEMPERATURE -30°C - 70°C MOUNTING TEMPERATURE -30°C - 70°C MOUNTING TYPE Pand Mount NOISTURE SENSITIVITY LEVEL (NSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION PYPE, COLOR ILLUMINATION Non-Illuminatiod FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Penel Mount CURRENT RATING 154 (AC), 20A (DC) CIRCUIT SPST EUSHING THREAD M12 x 1 ACTUATOR LENGTH ACTUATOR LENGT		Specifications of S1AW-WL
MANUFACTURER NKK Switches DESCRIPTION MEDIUM CAPACITY STANDARD SIZE TO LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 6798 pcs DATA SHEET DATA SHEET OULTAGE RATING - DC VOLTAGE RATING - DC VOLTAGE RATING - AC 125V TERMINATION STYLE Wire Leads SWITCH FUNCTION On-Off SERIES S PANEL CUTOUT DIMENSIONS Circular - 12.50mm Dia Bulk OTHER NAMES 300-3675 OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOUSTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION 1967 - Dust Tight, Waterproof ILLUMINATION TYPE, COLOR 1.LUMINATION TYPE, COLOR 1.LUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION 1986 - Switch SPST Panel Mount CURRENT RATING 154 (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR MATERIAL Brass, Chrome Plated		
DESCRIPTION MEDIUM CAPACITY STANDARD SIZE TO LEAD FREE STATUS / ROHS STATUS DATA SHEET STAN-WIL-pdf VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 125V TERMINATION STYLE Wire Leads SWITCH PUNCTION On-Off SERIES S PANEL CUTOUT DIMENSIONS Circular - 12.50mm Dia PACKAGING DHA OTHER NAMES 360-3675 OPERATING TEMPERATURE 30° ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITUTYT LEVEL (MSL) Lead Free STATUS / ROHS STATUS LUMINATION \ POPULATION P67 - Dust Tight, Waterproof LLUMINATION TYPE, COLOR - LLUMINATION TYPE, COLOR - LLUMINATION TYPE, COLOR - LLUMINATION TYPE ACACUMENT AND	PART NUMBER	S1AW-WL
LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 6798 pcs DATA SHEET DATA SHEET DATA SHEET VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 125V TERMINATION STYLE WIRE Leads SWITCH FUNCTION On-Off SERIES S PANEL CUTOUT DIMENSIONS Circular - 12.50mm Dia Bulk OPERATING TYPE MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS	MANUFACTURER	NKK Switches
QUANTITY AVAILABLE 6798 pcs DATA SHEET	DESCRIPTION	MEDIUM CAPACITY STANDARD SIZE TO
DATA SHEET	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 125V TERMINATION STYLE Wire Leads SWITCH FUNCTION On-Off SERIES S PANEL CUTOUT DIMENSIONS Circular - 12,50mm Dia PACKAGING Bulk OTHER NAMES 360-3675 OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / NOHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1P67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR TYPE Standard Round	QUANTITY AVAILABLE	6798 pcs
VOLTAGE RATING - AC TERMINATION STYLE Wire Leads SWITCH FUNCTION On-Off SERIES S PANEL CUTOUT DIMENSIONS Circular - 12,50mm Dia PACKAGING Bulk OTHER NAMES 360-3675 OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEad free / RoHS Compliant INGRESS PROTECTION IJP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION TOGGIE SWItch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD ACTUATOR MATERIAL Brass, Chrome Plated	DATA SHEET	S1AW-WL.pdf
TERMINATION STYLE SWITCH FUNCTION On-Off SERIES S PANEL CUTOUT DIMENSIONS Circular - 12,59mm Dia PACKAGING Bulk OTHER NAMES 360-3675 OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING LISA (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD ALTUATOR MATERIAL Brass, Chrome Plated	VOLTAGE RATING - DC	30V
SWITCH FUNCTION SERIES S PANEL CUTOUT DIMENSIONS Circular - 12.50mm Dia BACKAGING Bulk OTHER NAMES 360-3675 OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant IINGRESS PROTECTION IP67 - Dust Tight, Waterproof IILLUMINATION VOLTAGE (NOMINAL) - IILLUMINATION TYPE, COLOR - IILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	VOLTAGE RATING - AC	125V
SERIES S PANEL CUTOUT DIMENSIONS Circular - 12.50mm Dia PACKAGING Bulk OTHER NAMES 360-3675 OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION TOGGLE SWitch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR MATERIAL Brass, Chrome Plated	TERMINATION STYLE	Wire Leads
PANEL CUTOUT DIMENSIONS Circular - 12.50mm Dia Bulk OTHER NAMES 360-3675 OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR MATERIAL Brass, Chrome Plated	SWITCH FUNCTION	On-Off
PACKAGING OTHER NAMES 360-3675 OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION TOggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	SERIES	S
OTHER NAMES OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	PANEL CUTOUT DIMENSIONS	Circular - 12.50mm Dia
OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	PACKAGING	Bulk
MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION TOggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	OTHER NAMES	360-3675
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	OPERATING TEMPERATURE	-30°C ~ 70°C
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	MOUNTING TYPE	Panel Mount
INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL PAGE ACTUATOR MATERIAL	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	INGRESS PROTECTION	IP67 - Dust Tight, Waterproof
ILLUMINATION Non-Illuminated FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	ILLUMINATION VOLTAGE (NOMINAL)	-
FEATURES - ELECTRICAL LIFE 25,000 Cycles DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	ILLUMINATION TYPE, COLOR	-
ELECTRICAL LIFE25,000 CyclesDETAILED DESCRIPTIONToggle Switch SPST Panel MountCURRENT RATING15A (AC), 20A (DC)CIRCUITSPSTBUSHING THREADM12 x 1ACTUATOR TYPEStandard RoundACTUATOR MATERIALBrass, Chrome Plated	ILLUMINATION	Non-Illuminated
DETAILED DESCRIPTION Toggle Switch SPST Panel Mount CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	FEATURES	-
CURRENT RATING 15A (AC), 20A (DC) CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	ELECTRICAL LIFE	25,000 Cycles
CIRCUIT SPST BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	DETAILED DESCRIPTION	Toggle Switch SPST Panel Mount
BUSHING THREAD M12 x 1 ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	CURRENT RATING	15A (AC), 20A (DC)
ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	CIRCUIT	SPST
ACTUATOR MATERIAL Brass, Chrome Plated	BUSHING THREAD	M12 x 1
	ACTUATOR TYPE	Standard Round
ACTUATOR LENGTH 17.50mm	ACTUATOR MATERIAL	Brass, Chrome Plated
	ACTUATOR LENGTH	17.50mm

Related Tags

NKK Switches S1AW-WL	S1AW-WL Distributor	S1AW-WL Supplier
S1AW-WL Price	S1AW-WL Pictures	S1AW-WL Image
S1AW-WL PDF Datasheet	S1AW-WL Download Datasheet	S1AW-WL Datasheet
S1AW-WL Stock	Buy S1AW-WL	Buy NKK Switches S1AW-WL
NKK Switches S1AW-WL	NKK Switches Supplier	NKK Switches Distributor
NKK Switches S1AW-WL		

Related Products



S1ALHMQG

Manufacturers: TSC (Taiwan Semiconductor) Description: DIODE GEN PURP 50V 1A SUB SMA

In stock: 1656906 pcs

RFQ



S1ALHRQG Manufacturers: TSC (Taiwan Semiconductor)

Description: DIODE GEN PURP 50V 1A SUB SMA In stock: 1957205 pcs

RFQ



S1ALHRVG

Manufacturers: TSC (Taiwan Semiconductor) Description: DIODE GEN PURP 50V 1A SUB SMA

In stock: 1608048 pcs

RFQ



S1AW

Manufacturers: NKK Switches Description: SWITCH TOGGLE SPST 15A 125V

In stock: 10730 pcs

RFQ



S1ALHMTG

Manufacturers: TSC (Taiwan Semiconductor) Description: DIODE GEN PURP 50V 1A SUB SMA In stock: 1671322 pcs

RFQ



S1ATR

Manufacturers: Sensitron Semiconductor / SMC Diode Solutions Description: DIODE GEN PURP 50V 1A SMA

In stock: 4895728 pcs

RFQ



S1ALHRUG Manufacturers: TSC (Taiwan Semiconductor)

Description: DIODE GEN PURP 50V 1A SUB SMA In stock: 1521668 pcs

RFQ



S1ALHR3G Manufacturers: TSC (Taiwan Semiconductor)

Description: DIODE GEN PURP 50V 1A SUB SMA In stock: 2358993 pcs

RFQ





Manufacturers: TSC (Taiwan Semiconductor)

S1ALHRFG

Description: DIODE GEN PURP 50V 1A SUB SMA In stock: 1594271 pcs

RFQ



S1ALHRTG Manufacturers: TSC (Taiwan Semiconductor)

Description: DIODE GEN PURP 50V 1A SUB SMA In stock: 1838525 pcs

RFQ



S1AWF

Manufacturers: NKK Switches

RFQ



Manufacturers: TSC (Taiwan Semiconductor)

Description: DIODE GEN PURP 50V 1A SUB SMA

S1ALHRHG

In stock: 1738456 pcs **RFQ**



Description: SWITCH TOGGLE SPST 15A 125V

In stock: 9902 pcs

Copyright © 2020 Reliable Distributor of Electronic Components











