

	Specifications of WTT12L-B2562
PART NUMBER	WTT12L-B2562
MANUFACTURER	N/A
DESCRIPTION	SEN PHT PNP/NPN 100-3800MM
LEAD FREE STATUS / ROHS STATUS	
QUANTITY AVAILABLE	295 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 30 V
SERIES	-
SENSING METHOD	-
SENSING DISTANCE	3.937" ~ 149.606" (100mm ~ 3.8m)
RESPONSE TIME	5ms
OUTPUT CONFIGURATION	NPN/PNP - Dark-ON/Light-ON - Selectable
OTHER NAMES	1882-1493
OPERATING TEMPERATURE	-35°C ~ 50°C
LIGHT SOURCE	Red Laser Diode (658nm)
INGRESS PROTECTION	IP67
CONNECTION METHOD	Connector, M12, 5POS
CABLE LENGTH	-
ADJUSTMENT TYPE	-

Related Tags

WTT12L-B2562	WTT12L-B2562 Distributor	WTT12L-B2562 Supplier
WTT12L-B2562 Price	WTT12L-B2562 Pictures	WTT12L-B2562 Image
WTT12L-B2562 PDF Datasheet	WTT12L-B2562 Download Datasheet	WTT12L-B2562 Datasheet
WTT12L-B2562 Stock	Buy WTT12L-B2562	Buy WTT12L-B2562
WTT12L-B2562	Supplier	Distributor

Related Products

