Grayhill





Grayhill, Inc.

71C301103N-1103N

Part Number: 71C301103N-1103N

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way

Grayhill, Inc.

71C301103N-1103N.pdf

SWITCH ROTARY 3POS 250MA 115V

Lead free / RoHS Compliant 2290 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER 7.1C301103N-1103N MANUFACTURER Grayhill, Inc. DESCRIPTION SWITCH ROTARY 3POS 250MA 115V LEAD FREE STATUS / ROHS STATUS LEAR free / ROHS Compliant QUANTITY AVAILABLE 2290 pcs DATA SHEET 7.1C301103N-1103N-pdf VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 115V TERMINATION STYLE 50lder Lug SERIES 7.1 PANEL CUTOUT DIMENSIONS . OTHER NAMES 7.1C30.188-188-189-10 ZYC30.188-189-10 ZYC30.188-		Specifications of 71C301103N-1103N
MANUFACTURER Gray-fill, Inc. DESCRIPTION SWITCH ROTARY 3POS 250MA 115V Lead FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 2290 pcs DATA SHEET 37L 2031103N-1103N.pdf VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SFRIES 71 PANEL CUTOUT DIMENSIONS TOHER NAMES 71C30-18B-18B		- Specifications of 71c301103N-1103N
DESCRIPTION SWITCH ROTARY 3POS 250MA 115V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 2290 pcs DATA SHEET 137C301103N-1103N-pdf VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 71 PANEL CUTOUT DIMENSIONS - TOTHER NAMES 71C30-188-188 TC30-188-188 NO 71C30183188 OTHER NAMES 71C30-188-188 NO 71C30183188 OTHER STATUS FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 3 NUMBER OF POSITIONS 3 NUMBER OF POSITIONS 3 NUMBER OF POSITIONS 1 NUMBER OF	PART NUMBER	71C301103N-1103N
LEAD FREE STATUS / ROHS STATUS Laad free / ROHS Compilant	MANUFACTURER	Grayhill, Inc.
QUANTITY AVAILABLE DATA SHEET DITIONAL STATE DATA SHEET VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 71 PANEL CUTOUT DIMENSIONS	DESCRIPTION	SWITCH ROTARY 3POS 250MA 115V
DATA SHEET VOLTAGE RATING - DC 30V VOLTAGE RATING - AC 115V TERMINATION STYLE SOIDER LUG SERIES 71 PANEL CUTOUT DIMENSIONS - TIC30-1BB-1BB 71:C30-1BB-1BB 71:C30-1BB-1BB-71 71:C30-1B	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - DC VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 71 PANEL CUTOUT DIMENSIONS - OTHER NAMES 71:30-18B-18B 71:230-18B-18B 71:230-18B-18B 71:230-18B-18B-ND 71:23018B188 OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 3 NUMBER OF POSITIONS 1 MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS FEATURES FIXED DETAILED DESCRIPTION ROTAGE AS SHOWN CONTACT HIMING CONTACT TIMING NON-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 30° ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	QUANTITY AVAILABLE	2290 pcs
VOLTAGE RATING - AC TERMINATION STYLE Solder Lug SERIES 71 PANEL CUTOUT DIMENSIONS - OTHER NAMES 71(30-1BB-1BB-1BB 71(30-1BB-1BB-ND) 71(30-1BB-1BB-ND 71(30-1BB-1B-ND 71(30-1BB-1B-ND 71(30-1BB-1B-ND 71(30-1BB-1B-ND 71(30-1BB-1B-ND 71(30-1BB-1B-ND 71(30-1BB-1B-ND 71(30-1BB-1B-ND	DATA SHEET	71C301103N-1103N.pdf
TERMINATION STYLE SERIES 71 PANEL CUTOUT DIMENSIONS - CTHER NAMES TIC30-1BB-1BB 71C30-1BB-1BB 71C30-1BB-1BB-ND 71C30-1B-1BB-1BD 71C30-1BB-1BB-ND 71C30-1BB-1BB-ND 71C30-1B-1BB-1B 71C30-1BB-1BB-ND 71C30-1B-	VOLTAGE RATING - DC	30V
FEATURES DEFAILED DESCRIPTION ROTAGE STATUS DEFAILED DESCRIPTION DEFAILED DESCRIPTION DEFAILED DESCRIPTION DEFAILED DESCRIPTION ROTAGE SPEN ROTAGE STATUS STATUS ROTAGE STATUS SPEN ROTAGE S	VOLTAGE RATING - AC	115V
PANEL CUTOUT DIMENSIONS - TIC30-18B-18B TIC30-18B-18B-ND	TERMINATION STYLE	Solder Lug
TIC3O-1BB-1BB TIC3O-1BB-1BB TIC3O-1BB-1BB TIC3O-1BB-1BB-ND TIC3O-1BB-1BB TIC3O-1BB-1BB-ND TIC3O-1BB-1BB ND TIC3O-1BB-1BB-ND TIC3O-1BB-1BB TIC3O-1BB-1BB-P TIC3O-1BB-1BB TIC3O-1BB-1BB-P TIC3O-1BB-1BB TIC3O-1BB-1BB TIC3O-1BB-1BB TIC3O-1BB-1BB TIC3O-1BB-1BB TIC3O-1BB-1B TIC3O	SERIES	71
OPERATING FORCE 2.880 ~ 23gfm NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 30° ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	PANEL CUTOUT DIMENSIONS	-
NUMBER OF POSITIONS NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTATY SWITCH 3 POSITION SP3T 250mA (AC/DC) 115VAC Panel Mount CURRENT RATING CURRENT RATING CONTACT TIMING NOn-Shorting (BBM) CONTACT FINISH CURCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE CONCENTRO CONCENTRO SP3T ANGLE OF THROW ACTUATOR TYPE CONCENTRO CON	OTHER NAMES	71C30-1BB-1BB-ND
NUMBER OF POLES PER DECK NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 35.94mm CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT TIMINSH CIRCUIT PER DECK ANGLE OF THROW 30° ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	OPERATING FORCE	2.880 ~ 23gfm
NUMBER OF DECKS MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 35.94mm CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	NUMBER OF POSITIONS	3
MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 35.94mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 30° ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	NUMBER OF POLES PER DECK	1
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE CONCENTION Lead free / ROHS Compliant Lead free / ROHS Compliant I (Unlimited) Lead free / ROHS Compliant Fixed Fixed - CONTACT SP3T 250mA (AC/DC) 115VAC Panel Mount S9-94mm 250mA (AC/DC) Non-Shorting (BBM) CONTACT TIMING CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	NUMBER OF DECKS	1
Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 35.94mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 30° ACTUATOR TYPE CONCENTRATIONS (S.177mm Dia, 6.35mm Dia)	MOUNTING TYPE	Panel Mount
INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 35.94mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 30° ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
PEATURES DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE PROBLE Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount 35.94mm 250mA (AC/DC) Non-Shorting (BBM) CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount DEPTH BEHIND PANEL 35.94mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 30° ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	INDEX STOPS	Fixed
DEPTH BEHIND PANEL CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 30° ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	FEATURES	-
CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE S250mA (AC/DC) Non-Shorting (BBM) Silver Alloy - CONTACT MATERIAL Silver Alloy - CONTACT FINISH CONTACT FIN	DETAILED DESCRIPTION	Rotary Switch 3 Position SP3T 250mA (AC/DC) 115VAC Panel Mount
CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE COncentric (3.17mm Dia, 6.35mm Dia)	DEPTH BEHIND PANEL	35.94mm
CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE Silver Alloy CONTACT Alloy CONTACT FINISH CONTACT	CURRENT RATING	250mA (AC/DC)
CONTACT FINISH CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE SP3T Concentric (3.17mm Dia, 6.35mm Dia)	CONTACT MATERIAL	Silver Alloy
ANGLE OF THROW 30° ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	CONTACT FINISH	-
ACTUATOR TYPE Concentric (3.17mm Dia, 6.35mm Dia)	CIRCUIT PER DECK	SP3T
	ANGLE OF THROW	30°
ACTUATOR LENGTH Q 53mm	ACTUATOR TYPE	Concentric (3.17mm Dia, 6.35mm Dia)
ACTOATOR LENGTH 9.33mm	ACTUATOR LENGTH	9.53mm

Related Tags

Grayhill, Inc. 71C301103N-1103N	71C301103N-1103N Distributor	71C301103N-1103N Supplier
71C301103N-1103N Price	71C301103N-1103N Pictures	71C301103N-1103N Image
71C301103N-1103N PDF Datasheet	71C301103N-1103N Download Datasheet	71C301103N-1103N Datasheet
71C301103N-1103N Stock	Buy 71C301103N-1103N	Buy Grayhill, Inc. 71C301103N-1103N
Grayhill, Inc. 71C301103N-1103N	Grayhill, Inc. Supplier	Grayhill, Inc. Distributor
Grayhill, Inc. 71C301103N-1103N	Grayhill Inc. 71C301103N-1103N	

Related Products




71C301105N-1112NC Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 5/12POS 250MA 115V

In stock: 1844 pcs

RFQ

Grayhill



71C301102N-1112NC

In stock: 2062 pcs

RFQ



71C301105N-1112SF Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 5/12POS 250MA 115V In stock: 2034 pcs

RFQ



71C301104N-1104N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 4POS 250MA 115V

In stock: 1902 pcs

RFQ



71C301103N-1102N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 3/2POS 250MA 115V In stock: 1784 pcs

RFQ



71C301104N-1112NC Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 4/12POS 250MA 115V In stock: 1941 pcs

RFQ



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 2POS 250MA 115V

71C301102N-1102S

In stock: 1859 pcs

RFQ



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 2POS 250MA 115V

71C301102N-1102N

In stock: 1802 pcs **RFQ**



71C301102N-1112NF Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 2/12POS 250MA 115V

In stock: 1812 pcs

RFQ



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 4/12POS 250MA 115V

71C301104N-1112NF

In stock: 1949 pcs

RFQ

71C30-2CR-2CE

In stock: 1435 pcs



71C301105N-1112NF Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 5/12POS 250MA 115V

In stock: 2185 pcs **RFQ**



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 6POS 250MA 115V

RFQ

