

IDEC

IDEC

RH2B-UTAC220-240V

Part Number:

Manufacturer/Brand:

Datasheets: RoHs Status

Product description

Stock Condition

Ship From Shipment Way RH2B-UTAC220-240V

IDEC

RELAY GEN PURPOSE DPDT 10A 240V

RH2B-UTAC220-240V.pdf

Lead free / RoHS Compliant

7077 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER R12B-UTAC22D-240V MANUFACTURER IDEC DESCRIPTION RELAY CEN PURPOSE DPDT 10A 240V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 7077 pcs BRIZB-UTAC22D-240V.pdf TURN ON VOLTAGE (MAX) 192 VAC TURN OF VOLTAGE (MIN) 72 VAC TURN OF VOLTAGE (MIN) 72 VAC TERMINATION STYLE Quick Connect - 0.187' (1.7mm) SWITCHING VOLTAGE X14 VAC SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coll Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT RATING (CURRENT) 10A CONTACT RATING (CURRENT) 10A CONTACT FORM DEPT (2 Form C) COLL VOLTAGE 240VAC COLL TYPE No. 128 KOhns COLL CURRENT 4.0mA		Specifications of RH2B-UTAC220-240V
MANUFACTURER DESCRIPTION RELAY GEN PURPOSE DPDT 10A 240V LEAD FREE STATUS / ROHS STATUS LEAD free F ROHS Compliant QUANTITY AVAILABLE 7077 pcs DATA SHEET TURN ON VOLTAGE (MAX) 192 VAC TURN OFF VOLTAGE (MIN) 72 VAC TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELEASE TIME 20ms RELEAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) COIL VOLTAGE 240VAC COIL TYPE No Latching COIL RESISTANCE 18.8 KOhms COIL POWER - COIL RESISTANCE 18.8 KOhms COIL POWER		Specifications of Rhab of Acade 2 to V
DESCRIPTION LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 7077 pcs DATA SHEET □ RH2B-UTAC220-240V.pdf TURN ON VOLTAGE (MAX) 192 VAC TURN OF VOLTAGE (MIN) 72 VAC TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING GTHER NAMES 1885-1523 OPERATING TEMPERATURE 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED ESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT HATRING (CURRENT) COLI VOLTAGE 240VAC COIL TYPE Non Latching COIL POWER - COLI POWER - COLI POWER AS HAHS COmpliant - COLI POWER - CO	PART NUMBER	RH2B-UTAC220-240V
LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 7077 pcs DATA SHEET EN RH2B-UTAC220-240V.pdf TURN ON VOLTAGE (MAX) 192 VAC TURN OFF VOLTAGE (MIN) 72 VAC TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING OTHER NAMES 1885-1523 OPERATING TEMPERATURE 20ms OPERATING TEMPERATURE 20ms OPERATING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant FEATURES DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coll Chassis Mount CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COLL YOLTAGE 240VAC COLL TYPE Non Latching COLL RESISTANCE 18.8 KOhms COLL POWER -	MANUFACTURER	IDEC
QUANTITY AVAILABLE 7077 pcs DATA SHEET 100 RA26-UTAC220-240V.pdf TURN ON VOLTAGE (MAX) 192 VAC TURN OFF VOLTAGE (MIN) 72 VAC TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE -25°C ~ 70°C OPERATING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compilant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coll Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL POWER -	DESCRIPTION	RELAY GEN PURPOSE DPDT 10A 240V
DATA SHEET TURN ON VOLTAGE (MAX) 192 VAC TURN OF VOLTAGE (MIN) 72 VAC TERMINATION STYLE Quick Connect - 0.187" (4,7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING DEPARTING TEMPERATURE 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / CURRENT) LOND CONTACT RATING (CURRENT) CONTACT MATERIAL SIIVER Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COLL YOLTAGE 240VAC COLL TYPE NON LEACHING NON LEACHING COLL RESISTANCE 18.8 KOhms COLL POWER -	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN ON VOLTAGE (MAX) 192 VAC TURN OFF VOLTAGE (MIN) 72 VAC TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING DYFRATING TEMPERATURE 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT MATERIAL SILVER COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER	QUANTITY AVAILABLE	7077 pcs
TURN OFF VOLTAGE (MIN) T2 VAC TERMINATION STYLE Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 kOhms COIL POWER	DATA SHEET	RH2B-UTAC220-240V.pdf
TERMINATION STYLE SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS LEAd free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) LOA CONTACT MATERIAL SIIVEr Cadmium Oxide (AgCdO) COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER - COIL POWER RH AM AM AM AM AM AM AM AM AM A	TURN ON VOLTAGE (MAX)	192 VAC
SERIES RH RELEASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER -	TURN OFF VOLTAGE (MIN)	72 VAC
RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER -	TERMINATION STYLE	Quick Connect - 0.187" (4.7mm)
RELASE TIME 20ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER -	SWITCHING VOLTAGE	240VAC, 30VDC - Max
RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER -	SERIES	RH
PACKAGING DIL PACKAGING Bulk OTHER NAMES 1885-1523 OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER	RELEASE TIME	20ms
OTHER NAMES OPERATING TEMPERATURE -25°C ~ 70°C OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER -	RELAY TYPE	General Purpose
OPERATING TEMPERATURE OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 kOhms COIL POWER -	PACKAGING	Bulk
OPERATE TIME 20ms MOUNTING TYPE Chassis Mount LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL POWER -	OTHER NAMES	1885-1523
MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 kOhms COIL POWER	OPERATING TEMPERATURE	-25°C ~ 70°C
LEAD FREE STATUS / ROHS STATUS FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER	OPERATE TIME	20ms
FEATURES DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER -	MOUNTING TYPE	Chassis Mount
DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount 10A CONTACT RATING (CURRENT) Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 KOhms COIL POWER -	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 kOhms COIL POWER -	FEATURES	-
CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 240VAC COIL TYPE Non Latching COIL RESISTANCE 18.8 kOhms COIL POWER -	DETAILED DESCRIPTION	General Purpose Relay DPDT (2 Form C) 240VAC Coil Chassis Mount
CONTACT FORM COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 18.8 kOhms COIL POWER -	CONTACT RATING (CURRENT)	10A
COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 18.8 kOhms COIL POWER -	CONTACT MATERIAL	Silver Cadmium Oxide (AgCdO)
COIL TYPE Non Latching COIL RESISTANCE 18.8 kOhms COIL POWER -	CONTACT FORM	DPDT (2 Form C)
COIL RESISTANCE 18.8 kOhms COIL POWER -	COIL VOLTAGE	240VAC
COIL POWER -	COIL TYPE	Non Latching
	COIL RESISTANCE	18.8 kOhms
COIL CURRENT 4.0mA	COIL POWER	-
	COIL CURRENT	4.0mA

Related Tags

IDEC RH2B-UTAC220-240V	RH2B-UTAC220-240V Distributor	RH2B-UTAC220-240V Supplier
RH2B-UTAC220-240V Price	RH2B-UTAC220-240V Pictures	RH2B-UTAC220-240V Image
RH2B-UTAC220-240V PDF Datasheet	RH2B-UTAC220-240V Download Datasheet	RH2B-UTAC220-240V Datasheet
RH2B-UTAC220-240V Stock	Buy RH2B-UTAC220-240V	Buy IDEC RH2B-UTAC220-240V
IDEC RH2B-UTAC220-240V	IDEC Supplier	IDEC Distributor
IDEC RH2B-UTAC220-240V		

Related Products



RH2V2-UDC12V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 12V In stock: 7852 pcs

RFQ



RH2B-UTDC24V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 24V

In stock: 8782 pcs

RFQ



RH2B-UTAC24V

Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 24V

In stock: 8297 pcs

RFQ



RH2B-ULCDC24V

Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: 6555 pcs

RFQ



RH2B-ULDC12V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 12V

In stock: 7529 pcs

RFQ



RH2B-ULD-DC24V

Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: 5044 pcs

RFQ



RH2V2-UDC100-110V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 110V

In stock: 7639 pcs **RFQ**



RH2B-UTDC12V

Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 12V

In stock: 8220 pcs **RFQ**



Manufacturers: IDEC

RH2B-ULCDC12V

Description: RELAY GEN PURPOSE DPDT 10A 12V In stock: 6156 pcs

RFQ



Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 120V

RH2V2-UAC110-120V

In stock: 7444 pcs

RFQ



Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 24V

RH2B-ULDC24V

In stock: 5844 pcs

RFQ



RH2B-UTAC110-120V Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 120V

In stock: 8451 pcs **RFQ**















