



	Specifications of CD74HC4052M
PART NUMBER	CD74HC4052M
MANUFACTURER	N/A
DESCRIPTION	IC MUX/DEMUX DUAL 4X1 16SOIC
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
QUANTITY AVAILABLE	127474 pcs
DATA SHEET	
VOLTAGE - SUPPLY, SINGLE (V+)	2 V ~ 6 V
VOLTAGE - SUPPLY, DUAL (V±)	±1 V ~ 5 V
SWITCH TIME (TON, TOFF) (MAX)	-
SWITCH CIRCUIT	SP4T
SUPPLIER DEVICE PACKAGE	16-SOIC
SERIES	-
PACKAGING	Tube
PACKAGE / CASE	16-SOIC (0.154", 3.90mm Width)
OTHER NAMES	296-9218-5
OPERATING TEMPERATURE	-55°C ~ 125°C (TA)
ON-STATE RESISTANCE (MAX)	130 Ohm
NUMBER OF CIRCUITS	2
MULTIPLEXER/DEMULTIPLEXER CIRCUIT	4:1
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION	2 Circuit IC Switch 4:1 130 Ohm 16-SOIC
CURRENT - LEAKAGE (IS(OFF)) (MAX)	200nA
CROSSTALK	-
CHARGE INJECTION	-
CHANNEL-TO-CHANNEL MATCHING (ΔRON)	5 Ohm
CHANNEL CAPACITANCE (CS(OFF), CD(OFF))	12pF
BASE PART NUMBER	74HC4052
-3DB BANDWIDTH	185MHz

Related Tags

CD74HC4052M	CD74HC4052M Distributor	CD74HC4052M Supplier
CD74HC4052M Price	CD74HC4052M Pictures	CD74HC4052M Image
CD74HC4052M PDF Datasheet	CD74HC4052M Download Datasheet	CD74HC4052M Datasheet
CD74HC4052M Stock	Buy CD74HC4052M	Buy CD74HC4052M
CD74HC4052M	Supplier	Distributor

