## N/A Image may be representation. See specifications for product details.

## **SN74HC367DG4**

Part Number:

Manufacturer/Brand:

Product description Datasheets:

RoHs Status Stock Condition

Ship From Shipment Way SN74HC367DG4

N/A

IC BUFFER NON-INVERT 6V 16SOIC

Lead free / RoHS Compliant 337877 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

PART NUMBER SN74HC367DG4  MANUFACTURER N/A  DESCRIPTION IC BUFFER NON-INVERT 6V 16SOIC  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  QUANTITY AVAILABLE 337877 pcs  DATA SHEET  VOLTAGE - SUPPLY 2 V ~ 6 V  SUPPLIER DEVICE PACKAGE 16-SOIC  SERIES 74HC  PACKAGING Tube PACKAGING Tube PACKAGING TUBE OPERATING TEMPERATURE 40°C & 85°C (TA)  NUMBER OF ELEMENTS 2  NUMBER OF ELEMENT 2, 4 (Hex)  MOUNTING TYPE SURface Mont  LOGIC TYPE Buffer, Non-Inverting LEAD FREE STATUS / ROHS STATUS  LEAd free / ROHS Compliant  INPUT TYPE -  DETAILED DESCRIPTION BUffer, Non-Inverting LEAD FREE STATUS / ROHS STATUS  BUffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW 7.8mA, 7.8mA  BASE PART NUMBER 7 4HC367		Specifications of SN74HC367DG4
MANUFACTURER  DESCRIPTION  IC BUFFER NON-INVERT 6V 16SOIC  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  QUANTITY AVAILABLE  337877 pcs  DATA SHEET  VOLTAGE - SUPPLY  2 V ~ 6 V  SUPPLIER DEVICE PACKAGE  16-SOIC  SERIES  74HC  PACKAGING  Tube  PACKAGING  16-SOIC (0.154", 3.90mm Width)  OUTPUT TYPE  3-State  OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF BLEMENTS  2, 4 (Hex)  MOUSTURE SENSITIVITY LEVEL (MSL)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Buffer / ROHS Compliant  INPUT TYPE  - DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA		
DESCRIPTION  IC BUFFER NON-INVERT 6V 16SOIC  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  337877 pcs  DATA SHEET  VOLTAGE - SUPPLY  2 V ~ 6 V  SUPPLIER DEVICE PACKAGE  16-SOIC  SERIES  74HC  PACKAGING  Tube  PACKAGE / CASE  16-SOIC (0.154", 3.90mm Width)  OUTPUT TYPE  3-State  OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF ELEMENTS  2 (Hex)  MOUNTING TYPE  Surface Mount  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS  LEAD free / ROHS Compliant  INPUT TYPE  - DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	PART NUMBER	SN74HC367DG4
LEAD FREE STATUS / ROHS STATUS     Lead free / ROHS Compliant       QUANTITY AVAILABLE     337877 pcs       DATA SHEET     VOLTAGE - SUPPLY     2 V ~ 6 V       SUPPLIER DEVICE PACKAGE     16-SOIC       SERIES     74HC       PACKAGING     Tube       PACKAGE / CASE     16-SOIC (0.154", 3.90mm Width)       OUTPUT TYPE     3-State       OPERATING TEMPERATURE     -40°C ~ 85°C (TA)       NUMBER OF BITS PER ELEMENT     2, 4 (Hex)       MOUNTING TYPE     Surface Mount       MOISTURE SENSITIVITY LEVEL (MSL)     1 (Unlimited)       LOGIC TYPE     Buffer, Non-Inverting       LEAD FREE STATUS / ROHS STATUS     Lead free / ROHS Compliant       INPUT TYPE     -       DETAILED DESCRIPTION     Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC       CURRENT - OUTPUT HIGH, LOW     7.8mA, 7.8mA	MANUFACTURER	N/A
QUANTITY AVAILABLE  DATA SHEET  VOLTAGE - SUPPLY  2 V ~ 6 V  SUPPLIER DEVICE PACKAGE  16-SOIC  SERIES  74HC  PACKAGING  Tube  PACKAGING  Tube  PACKAGE / CASE  16-SOIC (0.154*, 3.90mm Width)  OUTPUT TYPE  3-State  OPERATING TEMPERATURE  A0°C ~ 85°C (TA)  NUMBER OF BITS PER ELEMENT  AUMBER OF BITS PER ELEMENT  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	DESCRIPTION	IC BUFFER NON-INVERT 6V 16SOIC
DATA SHEET  VOLTAGE - SUPPLY  SUPPLIER DEVICE PACKAGE  16-SOIC  SERIES  74HC  PACKAGING  Tube  PACKAGE / CASE  16-SOIC (0.154", 3.90mm Width)  OUTPUT TYPE  3-State  OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF ELEMENTS  2, 4 (Hex)  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  INPUT TYPE  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE - SUPPLY  SUPPLIER DEVICE PACKAGE  16-SOIC  SERIES  74HC  PACKAGING  Tube  PACKAGE / CASE  16-SOIC (0.154", 3.90mm Width)  OUTPUT TYPE  3-State  OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF ELEMENTS  2  NUMBER OF BITS PER ELEMENT  2, 4 (Hex)  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  - DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	QUANTITY AVAILABLE	337877 pcs
SUPPLIER DEVICE PACKAGE  SERIES  74HC  PACKAGING  Tube  PACKAGE / CASE  16-SOIC (0.154", 3.90mm Width)  OUTPUT TYPE  3-State  OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF ELEMENTS  2  NUMBER OF BITS PER ELEMENT  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  LEAD free / ROHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	DATA SHEET	
SERIES 74HC PACKAGING Tube PACKAGE / CASE 16-SOIC (0.154", 3.90mm Width) OUTPUT TYPE 3-State OPERATING TEMPERATURE -40°C ~ 85°C (TA) NUMBER OF ELEMENTS 2, 4 (Hex) MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) LOGIC TYPE Buffer, Non-Inverting LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INPUT TYPE - DETAILED DESCRIPTION Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC CURRENT - OUTPUT HIGH, LOW 7.8mA, 7.8mA	VOLTAGE - SUPPLY	2 V ~ 6 V
PACKAGING Tube  PACKAGE / CASE  16-SOIC (0.154", 3.90mm Width)  OUTPUT TYPE  3-State  OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF ELEMENTS  2, 4 (Hex)  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	SUPPLIER DEVICE PACKAGE	16-SOIC
PACKAGE / CASE  16-SOIC (0.154", 3.90mm Width)  OUTPUT TYPE  3-State  OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF ELEMENTS  2  NUMBER OF BITS PER ELEMENT  2, 4 (Hex)  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW	SERIES	74HC
OUTPUT TYPE  3-State  OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF ELEMENTS  2  NUMBER OF BITS PER ELEMENT  2, 4 (Hex)  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW	PACKAGING	Tube
OPERATING TEMPERATURE  -40°C ~ 85°C (TA)  NUMBER OF ELEMENTS  2  NUMBER OF BITS PER ELEMENT  2, 4 (Hex)  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	PACKAGE / CASE	16-SOIC (0.154", 3.90mm Width)
NUMBER OF ELEMENTS  2 (Hex)  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	OUTPUT TYPE	3-State
NUMBER OF BITS PER ELEMENT  2, 4 (Hex)  MOUNTING TYPE  Surface Mount  MOISTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	OPERATING TEMPERATURE	-40°C ~ 85°C (TA)
MOUNTING TYPE  Surface Mount  1 (Unlimited)  LOGIC TYPE  Buffer, Non-Inverting  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	NUMBER OF ELEMENTS	2
MOISTURE SENSITIVITY LEVEL (MSL)  LOGIC TYPE  Buffer, Non-Inverting  Lead free / RoHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	NUMBER OF BITS PER ELEMENT	2, 4 (Hex)
LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	MOUNTING TYPE	Surface Mount
LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INPUT TYPE  -  DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
INPUT TYPE -  DETAILED DESCRIPTION Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW 7.8mA, 7.8mA	LOGIC TYPE	Buffer, Non-Inverting
DETAILED DESCRIPTION  Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC  CURRENT - OUTPUT HIGH, LOW  7.8mA, 7.8mA	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CURRENT - OUTPUT HIGH, LOW 7.8mA, 7.8mA	INPUT TYPE	-
	DETAILED DESCRIPTION	Buffer, Non-Inverting 2 Element 2, 4 (Hex) Bit per Element 3-State Output 16-SOIC
BASE PART NUMBER 74HC367	CURRENT - OUTPUT HIGH, LOW	7.8mA, 7.8mA
	BASE PART NUMBER	74HC367

## CN74HC367DC4 Dietributer

**Related Tags** 

SN74HC367DG4	SN74HC367DG4 Distributor	SN74HC367DG4 Supplier
SN74HC367DG4 Price	SN74HC367DG4 Pictures	SN74HC367DG4 Image
SN74HC367DG4 PDF Datasheet	SN74HC367DG4 Download Datasheet	SN74HC367DG4 Datasheet
SN74HC367DG4 Stock	Buy SN74HC367DG4	Buy SN74HC367DG4
SN74HC367DG4	Supplier	Distributor

