



Image may be representation. See specifications for

product details.

#### SBR424SD

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way SBR424SD

Cynergy3

RELAY REED SPST-NC 500MA 24V

SBR424SD.pdf

Lead free / RoHS Compliant

1796 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

PART NUMBER  SBR424SD  MANUFACTURER  Cynergy3  DESCRIPTION  RELAY REED SPST-NC 500MA 24V  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  QUANTITY AVAILABLE  1796 pcs  DATA SHEET  TURN ON VOLTAGE (MAX)  15 VDC  TURN ON VOLTAGE (MIN)  4 VDC  TERMINATION STYLE  PC Pin  SWITCHING VOLTAGE  20VAC, 20VDC - Max  SERIES  4  RELEASE TIME  0.5ms  PACKAGING  Bulk  OTHER NAMES  725-1186  SBR424SD-ND  OPERATING TEMPERATURE  40°C ~ 100°C  OPERATING TEMPERATURE  MOUNTING TYPE  Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD free FRATUS  EATURES  -  CONTACT RATING (CURRENT)  500mA  CONTACT MATERIAL  Rhodium (Rh)  COLI VOLTAGE  24VDC  COLI TYPE  Non Latching  COLI CYPE  Non Latching  COLI CYPE  Non Latching  COLI RESISTANCE  12 KOhms		Specifications of SBR424SD
MANUFACTURER  Cynergy3  DESCRIPTION  RELAY REED SPST-NC 500MA 24V  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  QUANTITY AVAILABLE  1796 pcs  DATA SHEET  DATA SHEET  TURN ON VOLTAGE (MAX)  15 VDC  TURN OFF VOLTAGE (MIN)  4 VDC  TERMINATION STYLE  PC PIN  SWITCHING VOLTAGE  20VAC, 20VDC - Max  SERIES  4  RELEASE TIME  0.5ms  PACKAGING  Bulk  OTHER NAMES  SPREAZESO-ND  OPERATING TEMPERATURE  -40°C ~ 100°C  OPERATE TIME  MOUNTING TYPE  MOUSTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS  Lead free / ROHS Compliant  FEATURES  -  CONTACT RATING (CURRENT)  500mA  CONTACT FORM  SPST-NC (1 Form B)  COIL VOLTAGE  24VDC  COL TYPE  Non Latching		
DESCRIPTION RELAY REED SPST-NC 500MA 24V  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  QUANTITY AVAILABLE 1796 pcs  DATA SHEET  DATA SHEET  DATA SHEET  DATA SHEET  DATA SHEET  TURN ON VOLTAGE (MAX) 15 VDC  TURN OFF VOLTAGE (MIN) 4 VDC  TERMINATION STYLE PC Pin  SWITCHING VOLTAGE 20VAC, 20VDC - Max  SERIES 4  RELEASE TIME 0.5ms  PACKAGING Bulk  OTHER NAMES 725-1186 58R4245D-ND  OPERATING TEMPERATURE 40°C ~ 100°C  OPERATING TEMPERATURE  MOUNTING TYPE Through Hole  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant  FEATURES  CONTACT RATING (CURRENT) 500mA  CONTACT MATERIAL Rhodium (Rh)  COIL VOLTAGE 24VDC  COIL TYPE NO LABACH STATUS 1796 pcs  Lead free / ROHS Compliant  PACKAGING SPST-NC (1 Form B)  COIL VOLTAGE 24VDC  COIL TYPE NO LABACH STATUS NO LABACH STATUS NO LABACH STATUS NO MA  COIL TYPE NO LABACH STATUS NO MA  COIL TYPE NO LABACH STATUS NO LABACH STATU	PART NUMBER	SBR424SD
LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  1796 pcs  DATA SHEET  TURN ON VOLTAGE (MAX)  15 VDC  TURN OF VOLTAGE (MIN)  4 VDC  TERMINATION STYLE  SWITCHING VOLTAGE  20VAC, 20VDC - Max  SERIES  4  RELEASE TIME  0.5ms  PACKAGING  Bulk  OTHER NAMES  SBR424SD-NID  OPERATING TEMPERATURE  40°C ~ 100°C  OPERATE TIME  MOUNTING TYPE  Through Hole  MOUSTURE SENSITIVITY LEVEL (MSL)  1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS	MANUFACTURER	Cynergy3
QUANTITY AVAILABLE DATA SHEET DATA SHEET DES SER424SD.pdf TURN ON VOLTAGE (MAX) 15 VDC TURN OFF VOLTAGE (MIN) 4 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 20VAC, 20VDC - Max SERIES 4 RELEASE TIME 0.5ms PACKAGING Bulk OTHER NAMES SER424SD-ND OPERATING TEMPERATURE -40°C ~ 100°C OPERATE TIME MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD free STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES - CONTACT RATING (CURRENT) 500mA CONTACT FORM SPST-NC (1 Form B) COIL VOLTAGE COIL TYPE NON LEACHING SENSITIVITY LEVEL (MSL) LIST FORM COIL TYPE NON LATERIAL REGULATION COIL TYPE NON LATERIAL NON LATERIA	DESCRIPTION	RELAY REED SPST-NC 500MA 24V
DATA SHEET  TURN ON VOLTAGE (MAX)  15 VDC  TURN OFF VOLTAGE (MIN)  4 VDC  TERMINATION STYLE  PC PIN  SWITCHING VOLTAGE  SERIES  4 VAC  RELEASE TIME  0.5ms  PACKAGING  DIVERNAMES  COFERATING TEMPERATURE  0.9C × 100°C  OPERATING TEMPERATURE  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  CONTACT RATING (CURRENT)  CONTACT RATING (CURRENT)  CONTACT FORM  CONTACT FORM  CONTACT FORM  CONTACT FORM  CONTACT FORM  COLL TYPE  NON LEACHING  15 VDC  15 VDC  15 VDC  15 VDC  16 VDC  16 VDC  17 VDC  1	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN ON VOLTAGE (MAX)         15 VDC           TURN OFF VOLTAGE (MIN)         4 VDC           TERMINATION STYLE         PC Pin           SWITCHING VOLTAGE         20VAC, 20VDC - Max           SERIES         4           RELEASE TIME         0.5ms           PACKAGING         Bulk           OTHER NAMES         SPR42450-ND           OPERATUR TEMPERATURE         40°C ~ 100°C           OPERATE TIME         1ms           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           EFATURES         500mA           CONTACT RATING (CURRENT)         500mA           CONTACT MATERIAL         Rhodium (Rh)           CONTACT FORM         SPST-NC (1 Form B)           COLI VOLTAGE         24VDC           COLI TYPE         Non Latching	QUANTITY AVAILABLE	1796 pcs
TURN OFF VOLTAGE (MIN)         4 VDC           TERMINATION STYLE         PC Pin           SWITCHING VOLTAGE         20VAC, 20VDC - Max           SERIES         4           RELEASE TIME         0.5ms           PACKAGING         Bulk           OTHER NAMES         255-1186           OPERATING TEMPERATURE         -40°C ~ 100°C           OPERATE TIME         1ms           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           FEATURES         -           CONTACT RATING (CURRENT)         500mA           CONTACT FORM         SPST-NC (1 Form B)           CONTACT FORM         524VDC           COLI TYPE         Non Latching	DATA SHEET	SBR424SD.pdf
PC PIN SWITCHING VOLTAGE SERIES 4 RELEASE TIME O.5ms  PACKAGING OTHER NAMES SRR4245D-ND OPERATING TEMPERATURE OPERATING TEMPERATURE  MOUNTING TYPE MOUSTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS CONTACT RATING (CURRENT) CONTACT PARTING (CURRENT) CONTACT FORM COLL TYPE  MOLECASE  PC PIN  4  4  4  4  4  4  4  4  4  4  4  4  4	TURN ON VOLTAGE (MAX)	15 VDC
SERIES 4 RELEASE TIME 0.5ms  PACKAGING BUIK  OTHER NAMES 725-1186 SBR4245D-ND  OPERATE TIME 1ms  MOUNTING TYPE 1nough Hole  MOISTURE SENSITIVITY LEVEL (MSL) 1(Unlimited)  LEAD FREE STATUS / ROHS STATUS 200MA  CONTACT RATING (CURRENT) 500MA  CONTACT RATING (CURRENT) 500MA  CONTACT PARTINE  CONTACT FORM 5PST-NC (1 Form B)  COIL VOLTAGE 500L TYPE 10.5ms 3 Minus 14.5ms 4.5ms 4.5ms 6.5ms 7.5ms 14.5ms 6.5ms 7.5ms 7.5ms 14.5ms 7.5ms 7.	TURN OFF VOLTAGE (MIN)	4 VDC
SERIES RELEASE TIME O.5ms PACKAGING Buk  OTHER NAMES OTHER NAMES OPERATING TEMPERATURE OPERATE TIME MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS CONTACT RATING (CURRENT) OOMA CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT FORM CONTACT FORM CONTACT FORM CONTACT FORM CONTACT FORM CONTACT SOR CONTAC	TERMINATION STYLE	PC Pin
RELEASE TIME 0.5ms  PACKAGING Bulk  OTHER NAMES 725-186 SRR4245D-ND  OPERATING TEMPERATURE -40°C ~ 100°C  OPERATING TYPE 1 Through Hole  MOISTURE SENSITIVITY LEVEL (MSL) 1(Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES .  CONTACT RATING (CURRENT) 500mA  CONTACT MATERIAL ROHS STATUS SPST-NC (1 Form B)  COIL VOLTAGE SOLUTION NO LAtching	SWITCHING VOLTAGE	20VAC, 20VDC - Max
PACKAGINGBulkOTHER NAMES725-1186 SBR424SD-NDOPERATING TEMPERATURE40°C ~ 100°COPERATE TIMEImsMOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantFEATURES-CONTACT RATING (CURRENT)500mACONTACT MATERIALRhodium (Rh)CONTACT FORMSPST-NC (1 Form B)COIL VOLTAGE24VDCCOIL TYPENon Latching	SERIES	4
OTHER NAMES725-1186 SBR4245D-NDOPERATING TEMPERATURE-40°C ~ 100°COPERATE TIME1msMOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantFEATURES-CONTACT RATING (CURRENT)500mACONTACT MATERIALRhodium (Rh)CONTACT FORMSPST-NC (1 Form B)COIL VOLTAGE24VDCCOIL TYPENon Latching	RELEASE TIME	0.5ms
SBR4245D-ND  OPERATING TEMPERATURE  OPERATE TIME  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  FEATURES  CONTACT RATING (CURRENT)  CONTACT FORM  CONTACT FORM  CONTACT FORM  COLI VOLTAGE  COLI TYPE  SBR4245D-ND  Image: A40°C ~ 100°C  A00°C ~ 100°C  Image: A40°C ~ 100°C  Im	PACKAGING	Bulk
DPERATE TIME Immounting TYPE Through Hole  MOUNTING TYPE Immounting TYPE Immou	OTHER NAMES	
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS  CONTACT RATING (CURRENT) CONTACT MATERIAL CONTACT MATERIAL CONTACT FORM CONTACT FORM COLI VOLTAGE COLI VOLTAGE NOIL LECHING NON LETCHING NON MOUNT MEMBER NON MOUNT MEMB	OPERATING TEMPERATURE	-40°C ~ 100°C
MOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantFEATURES-CONTACT RATING (CURRENT)500mACONTACT MATERIALRhodium (Rh)CONTACT FORMSPST-NC (1 Form B)COIL VOLTAGE24VDCCOIL TYPENon Latching	OPERATE TIME	1ms
LEAD FREE STATUS / ROHS STATUS  FEATURES  CONTACT RATING (CURRENT)  SOOMA  CONTACT MATERIAL  CONTACT FORM  SPST-NC (1 Form B)  COIL VOLTAGE  COIL TYPE  Non Latching	MOUNTING TYPE	Through Hole
FEATURES - CONTACT RATING (CURRENT) 500mA  CONTACT MATERIAL Rhodium (Rh)  CONTACT FORM SPST-NC (1 Form B)  COIL VOLTAGE 24VDC  COIL TYPE Non Latching	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
CONTACT RATING (CURRENT)  CONTACT MATERIAL  CONTACT FORM  COIL VOLTAGE  COIL TYPE  SOMA  CONTACT RATING (CURRENT)  COMA  Rhodium (Rh)  SPST-NC (1 Form B)  24VDC  Non Latching	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT MATERIAL  CONTACT FORM  SPST-NC (1 Form B)  COIL VOLTAGE  COIL TYPE  Non Latching	FEATURES	-
CONTACT FORM SPST-NC (1 Form B)  COIL VOLTAGE 24VDC  COIL TYPE Non Latching	CONTACT RATING (CURRENT)	500mA
COIL VOLTAGE 24VDC COIL TYPE Non Latching	CONTACT MATERIAL	Rhodium (Rh)
COIL TYPE Non Latching	CONTACT FORM	SPST-NC (1 Form B)
	COIL VOLTAGE	24VDC
COIL RESISTANCE 1.2 kOhms	COIL TYPE	Non Latching
	COIL RESISTANCE	1.2 kOhms
COIL POWER 480 mW	COIL POWER	480 mW
COIL CURRENT 20.0mA	COIL CURRENT	20.0mA

# **Related Tags**

Cynergy3 SBR424SD	SBR424SD Distributor	SBR424SD Supplier
SBR424SD Price	SBR424SD Pictures	SBR424SD Image
SBR424SD PDF Datasheet	SBR424SD Download Datasheet	SBR424SD Datasheet
SBR424SD Stock	Buy SBR424SD	Buy Cynergy3 SBR424SD
Cynergy3 SBR424SD	Cynergy3 Supplier	Cynergy3 Distributor
Cynergy3 SBR424SD	Cynergy 3 SBR424SD	

# **Related Products**

### **SBR40U45CT**

DIODES PERICOM INC.

Manufacturers: Diodes Incorporated Description: DIODE ARRAY SBR 45V 20A TO220AB

In stock: 29141 pcs

**RFQ** 



### **SBR5E45P5-13D**

Manufacturers: Diodes Incorporated Description: DIODE RECT SBR 45V 5A POWERDI5

In stock: 494624 pcs

**RFQ** 



# **SBR40U60CTB-13**

Manufacturers: Diodes Incorporated

Description: DIODE ARRAY SBR 60V 20A TO220AB In stock: 99387 pcs

**RFQ** 

# SBR412SD

Manufacturers: Cynergy3

Description: RELAY REED SPST-NC 500MA 12V In stock: 2459 pcs

**RFQ** 



# SBR4F

Manufacturers: Semtech

Description: BRIDGE RECT 1.5A 400V In stock: 1141 pcs

**RFQ** 



### SBR40U60CTE

Manufacturers: Diodes Incorporated Description: DIODE ARRAY SBR 60V 20A TO262

In stock: 38665 pcs

**RFQ** 



# **SBR5E45P5-7**

Manufacturers: Diodes Incorporated Description: DIODE RECT SBR 45V 5A POWERDI5

**RFQ** 



### SBR5E45P5-13

Manufacturers: Diodes Incorporated Description: DIODE RECT SBR 45V 5A POWERDI5 In stock: 516667 pcs

**RFQ** 



#### **SBR40U300CTB-13** Manufacturers: Diodes Incorporated

Description: DIODE ARRAY SBR 300V 20A D2PAK In stock: 31099 pcs

**RFQ** 



DIODES PERICOM INC.

#### **SBR40U60CT** Manufacturers: Diodes Incorporated

Description: DIODE ARRAY SBR 60V 20A TO220AB In stock: 30535 pcs

**RFQ** 



#### **SBR4U130LP-7** Manufacturers: Diodes Incorporated

Description: DIODE SBR 130V 4A 8DFN In stock: 287950 pcs

**RFQ** 



### SBR545D1-13

In stock: 143615 pcs

Manufacturers: Diodes Incorporated Description: DIODE SBR 45V 10A DPAK

**RFQ** 



Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong











