



Image may be representation. See specifications for product details.

SDA02H0BD

Part Number:

Manufacturer/Brand:

Product description

Datasheets: RoHs Status

Stock Condition Ship From

Shipment Way

SDA02H0BD

C&K

SWITCH SLIDE DIP SPST 25MA 24V

SDA02H0BD.pdf

Lead free / RoHS Compliant

99785 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER SDA02H0BD MANUFACTURER C8K DESCRIPTION SWITCH SLIDE DIP SPST 25MA 24V LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE P9785 pcs DATA SHEET WASHABLE No VOLTAGE RATING 24VDC TERRITNATION STYLE PC Pin SERIES SDA PITCH 0.100° (2.54mm), Full PACKAGING OTHER NAMES OTHER NAMES OTHER NAMES OTHER NAMES OTHER NAMES OTHER NAMES MOUNTING TYPE Through Hole MOISTURE SERISTIVITY LEVEL (MSL) I (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH D.278° (7.06mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP SWItch SPST 2 Position Through Hole Slide (Slanderd) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyptenylene Sulfide (PPS)		Specifications of SDA02H0BD
MANUFACTURER CCRK DESCRIPTION SWITCH SLIDE DIP SPST 25MA 24VV LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 97785 p.cs DATA SHEET SDA02H0BD.pdf WASHABLE NO VOLTAGE RATING 24VDC TERMINATION STYLE PC Pin SERIES SDA PTTCH 0.100° (2.54mm), Full PACKAGING TUBE OTHER NAMES *SDA02H0BD CXM6952 OPERATING TEMPERATURE -40°C × 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1.000 Cycles LENGTH LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.183° (4.65mm) FEATURES - LECTRICAL LIFE 1.000 Cycles DETAILED DESCRIPTION DIP SWITCH SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT FINISH Gold CIRCUIT SPST		Specifications of SDA02110DD
DESCRIPTION SWITCH SLIDE DIP SPST ZSMA 24V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 99785 pcs DATA SHEET SDA02H080.pdf WASHABLE NO VOLTAGE RATING 24VDC TERMINATION STYLE PC PIN SERIES SDA PITCH 0.100° (2.54mm), Full PACKAGING Tube OTHER NAMES *5DA02H08D CXN6052 OPERATING TEMPERATURE 4-0°C 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1.000 Cycles LENCTH 0.278° (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.183° (4.65mm) FEATURES - DETAILED ESCRIPTION DIP SWITCH SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL BEPyllium Coppeer CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT	PART NUMBER	SDA02H0BD
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 99785 pcs DATA SHEET 123 SDA02H08D.pdf WASHABLE No VOLTAGE RATING 24VDC TERMINATION STYLE PC Pin SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES "SDA02H0BD CKN6052 OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCU	MANUFACTURER	C&K
QUANTITY AVAILABLE 99785 pcs DATA SHEET WASHABLE NO VOLTAGE RATING 24VDC TERMINATION STYLE PC Pin SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES SDAOZHOBD, PC OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LEIGTH ABOVE BOARD 0.183" (4.65mm) FEATURES ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP SWItch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllism Copper CONTACT MATERIAL GOID CIRCUIT SPST	DESCRIPTION	SWITCH SLIDE DIP SPST 25MA 24V
DATA SHEET WASHABLE NO VOLTAGE RATING 24VDC TERMINATION STYLE PC PIN SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES OPERATING TEMPERATURE AGNOCKNOSS2 OPERATING TEMPERATURE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE MOUSTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP SWITCH SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL BEYIllium Copper CONTACT MATERIAL Gold CIRCUIT SPST	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
WASHABLE VOLTAGE RATING 24VDC TERRITINATION STYLE PC PIN SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING TUBE OTHER NAMES "SDA02H0BD CKN6052 OPERATING TEMPERATURE 440°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000 Cycles LENGTH D.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD D.183" (4.65mm) FEATURES ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 2 Position Through Hole Silde (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT MATERIAL Gold CIRCUIT SPST	QUANTITY AVAILABLE	99785 pcs
VOLTAGE RATING 24VDC TERMINATION STYLE PC PIN SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES "5DA02H0BD CKN6052 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIp Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	DATA SHEET	SDA02H0BD.pdf
FERMINATION STYLE SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING TUBE OTHER NAMES CNN6052 CNN6052 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE LODO Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant HEIGHT ABOVE BOARD D.183" (4.55mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 2 Position Through Hole (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT MATERIAL Gold CIRCUIT	WASHABLE	No
SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING TUBE OTHER NAMES "SDA02H0BD CKN6052 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles OPERATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP SWItch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	VOLTAGE RATING	24VDC
PITCH 0.100" (2.54mm), Full PACKAGING Tube Tube *SDA02H08D CKN6052 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Gold CIRCUIT SPST	TERMINATION STYLE	PC Pin
PACKAGING OTHER NAMES STOA02HOBD CKN6052 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIp Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Gold CIRCUIT SPST	SERIES	SDA
*SDA02H0BD CKN6052 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP SWItch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	PITCH	0.100" (2.54mm), Full
OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 2 MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 6.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	PACKAGING	Tube
NUMBER OF POSITIONS2MOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE1,000 CyclesLENGTH0.278" (7.06mm)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.183" (4.65mm)FEATURES-ELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITSPST	OTHER NAMES	
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	NUMBER OF POSITIONS	2
MECHANICAL LIFE 1,000 Cycles LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	MOUNTING TYPE	Through Hole
LENGTH 0.278" (7.06mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.183" (4.65mm)FEATURES-ELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITSPST	MECHANICAL LIFE	1,000 Cycles
HEIGHT ABOVE BOARD O.183" (4.65mm) FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	LENGTH	0.278" (7.06mm)
FEATURES - ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITSPST	HEIGHT ABOVE BOARD	0.183" (4.65mm)
DETAILED DESCRIPTION Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL CONTACT FINISH CIRCUIT Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC 25mA Beryllium Copper Gold SPST	FEATURES	-
CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST	ELECTRICAL LIFE	1,000 Cycles
CONTACT MATERIAL CONTACT FINISH CIRCUIT Beryllium Copper Gold SPST	DETAILED DESCRIPTION	Dip Switch SPST 2 Position Through Hole Slide (Standard) Actuator 25mA 24VDC
CONTACT FINISH Gold CIRCUIT SPST	CURRENT RATING	25mA
CIRCUIT SPST	CONTACT MATERIAL	Beryllium Copper
	CONTACT FINISH	Gold
BODY MATERIAL Polyphenylene Sulfide (PPS)	CIRCUIT	SPST
	BODY MATERIAL	Polyphenylene Sulfide (PPS)

Related Tags

Slide (Standard)

Flush, Recessed

C&K SDA02H0BD	SDA02H0BD Distributor	SDA02H0BD Supplier
SDA02H0BD Price	SDA02H0BD Pictures	SDA02H0BD Image
SDA02H0BD PDF Datasheet	SDA02H0BD Download Datasheet	SDA02H0BD Datasheet
SDA02H0BD Stock	Buy SDA02H0BD	Buy C&K SDA02H0BD
C&K SDA02H0BD	C&K Supplier	C&K Distributor
C&K SDA02H0BD	C&K Components SDA02H0BD	

Related Products



ACTUATOR TYPE

ACTUATOR LEVEL

SDA01H1BD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 86341 pcs

RFQ



SDA02H0K

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 5837 pcs

RFQ



SDA01H0BD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 70254 pcs


RFQ



SDA02H0KD

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 5659 pcs **RFQ**



SDA02H0B Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 81933 pcs

RFQ



SDA01H0SBR Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 120428 pcs

RFQ



SDA02H0SK Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 6914 pcs

RFQ



SDA01H0SB Manufacturers: C&K

In stock: 72832 pcs **RFQ**

Description: SWITCH SLIDE DIP SPST 25MA 24V



SDA02H0SB

Manufacturers: C&K Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 65795 pcs

RFQ



SDA01H1SBD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 83000 pcs **RFQ**



SDA02H0SBD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 57731 pcs


RFQ





SDA02H0SBR

In stock: 69167 pcs **RFQ**





E-mail: Info@infinity-electronic.com











