OMRON.



OMRO

ELECTRONIC COMPONE

Omron

G8P-1111P-US-DC5

Part Number:

Manufacturer/Brand: Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way G8P-1111P-US-DC5

Omron

RELAY GEN PURPOSE SPST 30A 5V

Lead free / RoHS Compliant 4598 pcs stock

DHL/Fedex/TNT/UPS/EMS

Hong Kong

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER GRP-1111P-US-DCS MANUFACTURER Omron DESCRIPTION RELAY GEN PURPOSE SPST 30A SV LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUARITITY AVAILABLE 4598 pcs DATA SHEET TURN ON YOLFAGE (MAX) 3.75 VDC TURN ON YOLFAGE (MAX) 3.75 VDC TURN ON YOLFAGE (MIN) 0.5 VDC TERMINATION STYLE PC Ph SWITCHING VOLTAGE (MIN) 10ms RELEASE TIME 10ms RELEASE TIME 10ms RELEASE TIME 250 CREWAR 10ms PACKAGING BURK OTHER NAMES 289111PUSDCS 2333 COPERATING TEMPERATURE -555°C -70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant EACH TYPE 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant EACH TREE STATUS / ROHS STATUS LEAD free / ROHS Compliant EACH TREE STATUS / ROHS STATUS LEAD free / ROHS Compliant EACH TREE STATUS / ROHS STATUS LEAD free / ROHS Compliant CONTACT RATING (QURRENT) 30A CONTACT RATING (QURRENT) 30A CONTACT FORM SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT FORM SPST-NO (1 Form A) SVDC Coil Through Hole COIL ROYSER 500 mW COIL ROSESTANCE 27 Ohms COIL ROSESTANCE 300 mW COIL LORRENT 185mA		
MANUFACTURER Ominon DESCRIPTION RELAY GEN PURPOSE SPST 30A 5V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 4598 pcs DATA. SHEET TURN OF VOLTAGE (MAX) TURN OF VOLTAGE (MIN) 0.5 VDC TURN OFF VOLTAGE (MIN) 0.5 VDC SWITCHING VOLTAGE 2509AC, 28VDC - Max SKIEIS G8P RELASE TIME 10ms RELASE TIME 10ms RELASE TIME 68P1111PUSDCS RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES G8P1111PUSDCS OPERATE TIME 15ms MOUNTING TYPE 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES 30 CONTACT RATING (CURRENT) 30A CONTACT PORM SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT FORM SPST-NO (1 Form A) COLL VOLTAGE SPST-NO (1 Form A) COLL VOLTAGE Non Latching		Specifications of G8P-1111P-US-DC5
MANUFACTURER Ominon DESCRIPTION RELAY GEN PURPOSE SPST 30A 5V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 4598 pcs DATA. SHEET TURN OF VOLTAGE (MAX) TURN OF VOLTAGE (MIN) 0.5 VDC TURN OFF VOLTAGE (MIN) 0.5 VDC SWITCHING VOLTAGE 2509AC, 28VDC - Max SKIEIS G8P RELASE TIME 10ms RELASE TIME 10ms RELASE TIME 68P1111PUSDCS RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES G8P1111PUSDCS OPERATE TIME 15ms MOUNTING TYPE 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES 30 CONTACT RATING (CURRENT) 30A CONTACT PORM SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT FORM SPST-NO (1 Form A) COLL VOLTAGE SPST-NO (1 Form A) COLL VOLTAGE Non Latching	DADT NI IMPED	COD 1111D LIC DCE
DESCRIPTION RELAY GEN PURPOSE SPST 30A SV LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 4598 pc DATA SHEET TURN ON VOLTAGE (MAX) 3.75 VDC TURN OFF VOLTAGE (MIN) 0.5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE GBP SERIES GBP SERIES GBP RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES GBP1111PUSDCS 2933 GBP1111PUSDCS 2933 GBP111PUSDCS 2934 TURN ON PURPOSE STATUS OPERATING TEMPERATURE 15m MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS General Purpose Relay SPST-NO (1 Form A) SVOC Coll Through Hole CONTACT RATING (CURRENT) GONE Purpose Relay SPST-NO (1 Form A) SVOC Coll Through Hole CONTACT FARTING (CURRENT) SPST-NO (1 Form A) COLL VOLTAGE SVOC COLL VOLTAGE SVOC COLL VOLTAGE SON Lakthing COLL VOLTAGE SON Lakthing </td <td></td> <td></td>		
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 4598 pcs DATA SHEET TURN ON VOLTAGE (MAX) TURN ON FOULTAGE (MIN) 3.75 VDC TURN ON FOULTAGE (MIN) 0.5 VDC TERMINATION STYLE PC PIn SWITCHING VOLTAGE 250VAC, 28VDC - Max SERIES GBP RELEASE TIME 10ms RELEASE TIME General Purpose PACKAGING Buk OTHER NAMES G8P1111PUSDCS OPERATURE 55°C ~ 70°C OPERATURE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant EFATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT RATURG (URRENT) 30A CONTACT FORM SPST-NO (1 Form A) CONTACT FORM SPST-NO (1 Form A) COLL VOLTAGE SVDC COLL VOLTAGE NON Latching COLL LYPE NON LAtching COLL RESISTANCE		
QUANTITY AVAILABLE 4588 pcs DATA SHEET 757 VDC TURN ON VOLTAGE (MAX) 3.75 VDC TURN OFF VOLTAGE (MIN) 0.5 VDC TERMINATION STYLE PC Pin SWITCHING VOLTAGE 250VAC, 28VDC - Max SERIES G8P RELASE TIME 10ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES G981111PSDCSC OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - CONTACT RATING (CURRENT) 30A CONTACT RATING (CURRENT) SOLIVE Cadmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COLI VOLTAGE SVDC COLI LYDE Non Latching COLI LYDE Non Latching COLI LYDE 900 mW		
DATA SHEET TURN ON VOLTAGE (MAX) 3.75 VDC TURN OFF VOLTAGE (MIN) 0.5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 250VAC, 28VDC - Max SERIES G8P RELASE TIME 10ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 58P111 PUSDCS OPERATING TEMPERATURE 55°C ~ 0°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - OPTACET RATING (CURRENT) 30A CONTACT RATING (CURRENT) 30A CONTACT FORM SPST-NO (1 Form A) CONTACT FORM SPST-NO (1 Form A) COLL VOLTAGE SPST-NO (1 Form A) COLL VOLTAGE Non Latching COLL TYPE Non Latching COLL RESISTANCE 900 mW		
TURN ON VOLTAGE (MIN) 3.75 VDC TURN OFF VOLTAGE (MIN) 0.5 VDC TERNINATION STYLE PC PIn SWITCHING VOLTAGE 250VAC, 28VDC - Max SERIES G8P RELASE TIME 10ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES G8P1111PUSDCS 2933 593 OPERATING TEMPERATURE 55°C ~ 70°C OPERATING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL SINEY CAdmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COLI VOLTAGE SVDC COLI VOLTAGE Non Latching COLI LYPE Non Latching COLI RESISTANCE 900 mW		4598 pcs
TURN OFF VOLTAGE (MIN) 0.5 VDC TERMINATION STYLE PC Pin SWITCHING VOLTAGE 250VAC, 28VDC - Max SERIES G8P RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES G8P1111PUSDCS 2933 OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL Silver Cadmium Oxide (AgcdO) CONTACT FORM SPST-NO (1 Form A) COLI VOLTAGE 5VDC COLI, VOLTAGE No. Latching COLI, LYPE No. Latching COLI, ESSISTANCE 27 Ohms COLI, POWER 900 mW		
FERMINATION STYLE SWITCHING VOLTAGE SERLES G8P RELEASE TIME 10ms RELAY TYPE General Purpose Bulk OTHER NAMES G8P1111PUSDCS 2933 OPERATING TEMPERATURE 55°C ~ 70°C OPERATE TIME MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS LEAd free / RoHS Compliant FEATURES DETAILED DESCRIPTION CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT FARMING CONTACT FORM CONTACT FORM COLL VOLTAGE COLL VOLTAGE COLL VOLTAGE COLL VOLTAGE COLL RESISTANCE COLL RESISTANCE COLL POWER 900 mW PC Pin General Purpose G8P2 G8P2 G8P3 G8P3 G8P3 G8P3 G8P3 G8P3 G8P4 G8P4		
SWITCHING VOLTAGE 250VAC, 28VDC - Max SERIES GBP RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 55°C ~ 70°C OPERATING TEMPERATURE 55°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COLL VOLTAGE VDC COLL VOLTAGE Non Latching COLL TYPE Non Latching COLL RESISTANCE 27 Ohms COLL POWER 900 mW		
SERIES GBP RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 55°C ~ 70°C OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COIL YOPE Non Latching COIL TYPE Non Latching COIL RESISTANCE 27 Ohms COIL POWER 900 mW		
RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 2931 OPERATING TEMPERATURE 55°C ~ 70°C OPERATING TEMPERATURE 15ms MOUNTING TYPE 15ms LEAD FREE STATUS / ROHS STATUS 6eneral Purpose Relay SPST-NO (1 Form A) 5VDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT PARTINAL CONTACT FORM 9FST-NO (1 Form A) 5VDC Coil Through Hole CONTACT FORM 5DSTATUS 5VDC 50C COIL TYPE 50DC 50DC COIL TYPE 70DC 50DC COIL TYPE 70DC 50DC COIL RESISTANCE 70 Non Latching COIL POWER 70DC 50DC	SWITCHING VOLTAGE	250VAC, 28VDC - Max
RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES G8P1111PUSDCS 2933 OPERATING TEMPERATURE 55°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE 15ms MOUNTING TYPE 15ms LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL SINEY CAdmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COIL YOLTAGE 5VDC COIL TYPE NO LAtching COIL RESISTANCE 27 Ohms COIL POWER 900 mW	SERIES	G8P
PACKAGING OTHER NAMES OTHER NAMES OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME OPERATE TIME Through Hole LEAD FREE STATUS / ROHS STATUS LEAd Free / ROHS Compliant FEATURES -CONTACT RATING (CURRENT) ONTACT RATING (CURRENT) ONTACT FORM ONTACT FORM ONTACT FORM ONTACT FORM ONTACT FORM ONTACT FORM ONTACT SOLU CONTACT MATERIAL CONTACT SOLU CONTACT MATERIAL CONTACT SOLU	RELEASE TIME	10ms
OTHER NAMES G8P1111PUSDCS 2933 OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 5VDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COIL YOLTAGE 5VDC COIL TYPE Non Latching COIL RESISTANCE 27 Ohms COIL POWER 900 mW	RELAY TYPE	General Purpose
2933 OPERATING TEMPERATURE -55°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) SVDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE SVDC COIL TYPE Non Latching COIL RESISTANCE 27 Ohms OU MW	PACKAGING	Bulk
DERATE TIME 15ms MOUNTING TYPE 17mough Hole LEAD FREE STATUS / ROHS STATUS 12ead free / ROHS Compliant FEATURES - CONTACT RATING (CURRENT) 20A	OTHER NAMES	
MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 5VDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE COIL VOLTAGE COIL VOLTAGE COIL TYPE Non Latching COIL POWER 900 mW	OPERATING TEMPERATURE	-55°C ~ 70°C
LEAD FREE STATUS / ROHS STATUS FEATURES DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 5VDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE SVDC COIL TYPE Non Latching COIL TYPE COIL POWER 900 mW	OPERATE TIME	15ms
FEATURES DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 5VDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 27 Ohms OIL POWER	MOUNTING TYPE	Through Hole
DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 5VDC Coil Through Hole CONTACT RATING (CURRENT) 30A CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE SVDC COIL TYPE Non Latching COIL RESISTANCE 27 Ohms COIL POWER 900 mW	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) SIVER Cadmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE COIL POWER 30A Silver Cadmium Oxide (AgCdO) SPST-NO (1 Form A) SPST-NO (1 For	FEATURES	-
CONTACT MATERIAL Silver Cadmium Oxide (AgCdO) CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE 5VDC COIL TYPE Non Latching COIL RESISTANCE 27 Ohms COIL POWER 900 mW	DETAILED DESCRIPTION	General Purpose Relay SPST-NO (1 Form A) 5VDC Coil Through Hole
CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE 5VDC COIL TYPE Non Latching COIL RESISTANCE 27 Ohms COIL POWER 900 mW	CONTACT RATING (CURRENT)	30A
COIL YOLTAGE COIL TYPE Non Latching COIL RESISTANCE 27 Ohms COIL POWER 900 mW	CONTACT MATERIAL	Silver Cadmium Oxide (AgCdO)
COIL TYPE Non Latching COIL RESISTANCE 27 Ohms COIL POWER 900 mW	CONTACT FORM	SPST-NO (1 Form A)
COIL RESISTANCE 27 Ohms COIL POWER 900 mW	COIL VOLTAGE	5VDC
COIL POWER 900 mW	COIL TYPE	Non Latching
	COIL RESISTANCE	27 Ohms
COIL CURRENT 185mA	COIL POWER	900 mW
	COIL CURRENT	185mA

Related Tags

Omron G8P-1111P-US-DC5	G8P-1111P-US-DC5 Distributor	G8P-1111P-US-DC5 Supplier
G8P-1111P-US-DC5 Price	G8P-1111P-US-DC5 Pictures	G8P-1111P-US-DC5 Image
G8P-1111P-US-DC5 PDF Datasheet	G8P-1111P-US-DC5 Download Datasheet	G8P-1111P-US-DC5 Datasheet
G8P-1111P-US-DC5 Stock	Buy G8P-1111P-US-DC5	Buy Omron G8P-1111P-US-DC5
Omron G8P-1111P-US-DC5	Omron Supplier	Omron Distributor
Omron G8P-1111P-US-DC5	Omron Electronics Inc-IA Div G8P-1111P-US-DC5	Omron Electronics Inc-EMC Div G8P-1111P-US-DC5
Omron Electronics LLC G8P-1111P-US-DC5		

Related Products



G8P-1114P-BI-US-DC24

Manufacturers: Omron Description: RELAY GEN PURPOSE SPST 30A 24V

In stock: 2948 pcs

RFQ



G8P-1111P-US-DC48 Manufacturers: Omron

Description: RELAY GEN PURPOSE SPST 30A 48V

In stock: 7049 pcs

RFQ



G8P-1A2T-F-FD DC12 Manufacturers: Omron

Description: RELAY GEN PURPOSE SPST 30A 12V

In stock: 4750 pcs **RFQ**



G8P-1A2T-F DC22 Manufacturers: Omron

Description: RELAY GEN PURPOSE SPST 30A 22V In stock: 3394 pcs

RFQ



Manufacturers: Laird Technologies - Antennas

G8P

Description: MOUNT MAGN 3/4" RG58A 12' UHFM In stock: 2722 pcs

RFQ



G8P-1111P-US-DC24 Manufacturers: Omron

Description: RELAY GEN PURPOSE SPST 30A 24V In stock: 5932 pcs

RFQ



G8P-1A2T-F DC110 Manufacturers: Omron Description: RELAY GEN PURPOSE SPST 30A 110V

In stock: 5013 pcs

RFQ



G8P-1A2T-F DC9 Manufacturers: Omron

Description: RELAY GEN PURPOSE SPST 30A 9V In stock: 4613 pcs

RFQ



Manufacturers: Omron

G8P-1A2T-F DC24

Description: RELAY GEN PURPOSE SPST 30A 24V

In stock: 6034 pcs **RFQ**

Manufacturers: Omron



G8P-1A2T-F DC48

Manufacturers: Omron Description: RELAY GEN PURPOSE SPST 30A 48V

In stock: 3451 pcs

RFQ



G8P-1114P-BI-US-DC12

Description: RELAY GEN PURPOSE SPST 30A 12V In stock: 5291 pcs

RFQ

Copyright © 2020 Reliable Distributor of Electronic Components



Manufacturers: Omron

G8P-1A2T-F DC12

Description: RELAY GEN PURPOSE SPST 30A 12V In stock: 2778 pcs

RFQ





E-mail: Info@infinity-electronic.com











