OHMITE



OHMIT

Ohmite

T504SE

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Ship From Shipment Way

Datasheets:

T504SE

Ohmite

SWITCH ROTARY 4POS 3A 120V

T504SE.pdf

Lead free / RoHS Compliant

DHL/Fedex/TNT/UPS/EMS

1227 pcs stock Hong Kong

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER TS04SE MANUFACTURER O'mine DESCRIPTION SWITCH ROTTARY 4POS 3A 120V LEAD FREE STATUS / ROYIS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 1227 pcs DATA SHEET 17504SE pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V STERRIS T-50 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES O'HTS04SE ND OPERATINA FORCE 4 NUMBER OF POLIES PER DECK 1 NUMBER OF POLIES PER DECK 1 MUMBER OF POLIES PER DECK 1 MUMBER OF SENSTITUTY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant MOSTURE SENSTITUTY LEVEL (MSL) 4 (Sample Mount DETAILES 5 (Sample Mount IDETAILED DESCRIPTION 4 (AC/DC) READ FREE STATUS / ROH STATUS 4 (AC/DC) CURRENT RATING 3 (AC/DC) CURRENT RATING 3 (AC/DC) CURRENT RATING 3 (AC/DC) CU		Specifications of T504SE
MANUFACTURER Ohmite DESCRIPTION SWITCH ROTARY 4POS 3A 120V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUARTITY AVAILABLE 1227 pc DATA SHEET STOSIASE, DELTA VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERNINATION STYLE Solder lug SERIES T-50 PARLE CUTOUT DIMENSIONS OHTSOASE-ND OPERATING FORCE 1 NUMBER OF POSITIONS 4 NUMBER OF POSITIONS 1 NUMBER OF DECKS 1 MOUNTION TYPE Ponel Mount MOUNTION TYPE Ponel Mount MOUNTION TYPE Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES Ponel Mount DET FLIE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES Ponel Mount ELEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant IDE THIS BEHIND PANEL 34,93mm CURRENT RATING 34,04C/QCD		
DESCRIPTION SWITCH ROTARRY 4POS 3A 120V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 1227 pcs DATA SHEET \$\frac{1}{2}\$ TSOHSE.pdf VOLTAGE RATING - DC \$\frac{1}{2}\$ TSOHSE.pdf VOLTAGE RATING - AC 120V CERMINATION STYLE Solder Lug SERIES T-50 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES Circular - 9.53mm Dia OPERATING FORCE - OPERATING FORCE 1 NUMBER OF POSITIONS 4 NUMBER OF POSITIONS 1 MOUNTING TYPE Panel Mount MOUNTING TYPE Panel Mount MOUNTING STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES Rotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount DET TAILED DESCRIPTION Rotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount CURRENT RATING Shorting (MBB) CONTACT TRING Shorting (MBB) CONTACT FINISH C CURL THROW AN	PART NUMBER	T504SE
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 1227 pcs DATA SHEET 20V VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERRINATION STYLE Solder Lug SERIES T-50 PANEL CUTOUT DIMENSIONS Ortcular - 9.53mm Dia OTHER NAMES OHTS04SE ND OPERATING FORCE - NUMBER OF POSITIONS 4 NUMBER OF POSITIONS 4 MOUNTING TYPE Panel Mount MOUNTING TYPE Panel Mount MOUNTING STATUS Lead free / RoHS Compliant MEDIE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES A CAPO DETAILED DESCRIPTION Rotary Switch 4 Postion SP4T 3A (AC/DC) 120VAC Panel Mount DET HE BLIND PANEL 34 (AC/DC) CONTACT HATTENIA Shorting (MBB) CONTACT FINISH - CONTACT FINISH - CONTACT FINISH - CILLIAGO THROW SP4	MANUFACTURER	Ohmite
QUANTITY AVAILABLE 1277 pes DATA SHEET 20 T5045E.pdf VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SERIES T-50 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT5045E.Pn.D OPERATING PORCE - NUMBER OF POSITIONS 4 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS Rotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34-93mm QUIRENT RATING Solver Miles CONTACT TIMING Solver Miles CONTACT TIMING Silver Alloy CONTACT FINISH - CONTACT FINISH - CONTACT FINISH - CONTACT FINISH - CHELD STATUS SOLVER	DESCRIPTION	SWITCH ROTARY 4POS 3A 120V
DATA SHEET TO SHEE PABE VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SERIES T-50 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OTHER NAMES OPERATING FORCE - NUMBER OF POSITIONS 4 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LEAD FREE STATUS / ROHS STATUS Rokel FEATURES Rokel FEATURES Rokel DEPTH BEHIND PANEL 34.93mm CURRENT RATING 36 (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CRUIT PER DECK SP4T ANGLE OF THROW 30° ALLIE OF THROW 50°	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - DC 20V VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SERIES T-50 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHTS045E-ND OPERATING FORCE - NUMBER OF POSITIONS 4 NUMBER OF POSITIONS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 MIDEX STOPS Fixed FEATURES 1 DETAILED DESCRIPTION Rotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34.93mm CURRENT RATING 34.04C/DC CONTACT TIMING Shorting (MBB) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CIRCULT PER DECK SMPT ANGLE OF THROW 30° ANGLE OF THROW 51 Stited (6.35mm Dia)	QUANTITY AVAILABLE	1227 pcs
VOLTAGE RATING - AC 120V TERMINATION STYLE Solder Lug SERIES T-50 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT5045E-MD OPERATING FORCE CHT5045E-MD NUMBER OF POSITIONS 4 NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES Fixed DETAILED DESCRIPTION Rotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34.93mm CURRENT RATING 34.04/DC) CONTACT TIMING Shorting (MBB) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CONTACT FINISH - CONTACT FINISH 30° CONTACT FINISW Shorting (MBB) CONTACT FINISW Shorting (MBB) CONTACT FINISW Shorting (MBB) CONTACT FINISW Shorti	DATA SHEET	T504SE.pdf
TERMINATION STYLE Solder Lug SERIES T-50 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT5045E OHT5045E-ND OPERATING FORCE - NUMBER OF POSITIONS 4 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES ROBARY SWIRCH A Position SP4T 3A (AC/DC) 12DVAC Panel Mount DETAILED DESCRIPTION Rotary Switch 4 Position SP4T 3A (AC/DC) 12DVAC Panel Mount CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CONTACT FINISH - <t< td=""><td>VOLTAGE RATING - DC</td><td>20V</td></t<>	VOLTAGE RATING - DC	20V
SERIES T-50 PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT504SE OHT504SE ND OPERATING FORCE - NUMBER OF POSITIONS 4 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotery Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount DETAILED DESCRIPTION 34 (AC/DC) CONTACT TIMING 34 (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT TIMING Silver Alloy CONTACT FINISH - CONTACT FINISH - CONTACT FINISH SP4T ANGLE OF THROW 30° ANGLE OF THROW 30° ANGLE OF THROW 510° ANGLE OF THROW 30°	VOLTAGE RATING - AC	120V
PANEL CUTOUT DIMENSIONS Circular - 9.53mm Dia OTHER NAMES OHT504SE OHT504SE-ND OPERATING FORCE - NUMBER OF POSITIONS 4 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) I (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rolary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount CURRENT RATING 34.93mm CONTACT TIMING Shoring (MBB) CONTACT TIMING Shoring (MBB) CONTACT FINISH - CURCULT PER DECK SP4T ANGLE OF THROW 50° ANGLE OF THROW Flatted (6.55mm Dia)	TERMINATION STYLE	Solder Lug
OTHER NAMES OTHER NAMES OPERATING FORCE OPERATING FORCE NUMBER OF POSITIONS 4 NUMBER OF POLES PER DECK INUMBER OF POLES PER DECK INUMBER OF DECKS INUMBER OF D	SERIES	T-50
OFFER TIMES OPERATING FORCE OPERATING FORCE OPERATING FORCE OPERATING FORCE OPERATING FORCE OPUBLISHER OF POSITIONS OPUBBER OF POELS PER DECK INUMBER OF POELS PER DECK INUMBER OF DECKS INDURING TYPE MOINTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) ILEAD FREE STATUS / ROHS STATUS INDEX STOPS FIXE FEATURES OFFIALLED DESCRIPTION ORATION DEPTH BEHIND PANEL OPETH BEHIND PANEL OUTGANT TIMING OUTGANT T	PANEL CUTOUT DIMENSIONS	Circular - 9.53mm Dia
NUMBER OF POSITIONS4NUMBER OF POLES PER DECK1NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel MountCURRENT RATING3A (AC/DC)CONTACT TIMINGShorting (MBB)CONTACT TIMINGSilver AlloyCONTACT FINISH-CIRCUIT PER DECKSP4TANGLE OF THROW30°ACTUATOR TYPEFlatted (6.35mm Dia)	OTHER NAMES	
NUMBER OF POLES PER DECK1NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel MountDEPTH BEHIND PANEL34.93mmCURRENT RATING34.(AC/DC)CONTACT TIMINGShorting (MBB)CONTACT TIMINGSilver AlloyCONTACT FINISH-CONTACT FINISH-CIRCUIT PER DECKSP4TANGLE OF THROW30°ANGLE OF THROWFlatted (6.35mm Dia)	OPERATING FORCE	-
NUMBER OF DECKS1MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel MountDEPTH BEHIND PANEL34.93mmCURRENT RATING34.(AC/DC)CONTACT TIMINGShorting (MBB)CONTACT TIMINGSilver AlloyCONTACT FINISH-CICRCUIT PER DECKSP4TANGLE OF THROW30°ANGLE OF THROWTelted (6.35mm Dia)	NUMBER OF POSITIONS	4
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS FEATURES FEATURES DETAILED DESCRIPTION ROTARY SWItch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING AN (AC/DC) CONTACT TIMING CONTACT TIMING CONTACT TIMING CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ANGLE OF THROW BIEND SILVER (6.35mm Dia)	NUMBER OF POLES PER DECK	1
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS INDEX STOPS FIXED FEATURES DETAILED DESCRIPTION DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ANGLE OF THROW ACTUATOR TYPE (Unlimited) (Unlimited) Lead free / RoHS Compliant Ead free	NUMBER OF DECKS	1
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel MountDEPTH BEHIND PANEL34.93mmCURRENT RATING34.(AC/DC)CONTACT TIMINGShorting (MBB)CONTACT TIMISHSilver AlloyCONTACT FINISH-CIRCUIT PER DECKSP4TANGLE OF THROW30°ACTUATOR TYPEFlatted (6.35mm Dia)	MOUNTING TYPE	Panel Mount
FEATURES - CATURES - CATUR	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURES DETAILED DESCRIPTION Rotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34.93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT FINISH CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Rotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount DEPTH BEHIND PANEL 34.93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Sliver Alloy CONTACT FINISH - CIRCUIT PER DECK SP4T ANGLE OF THROW 30° ACTUATOR TYPE FIRED SEARCH STATEMENT SPATE AND SPATE STATEMENT SPATE S	INDEX STOPS	Fixed
DEPTH BEHIND PANEL 34.93mm CURRENT RATING 3A (AC/DC) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CONTACT FINISH SP4T CIRCUIT PER DECK SP4T ANGLE OF THROW 30° ACTUATOR TYPE SHORT SP4T Flatted (6.35mm Dia)	FEATURES	-
CURRENT RATING ANACYDC) Shorting (MBB) CONTACT MATERIAL CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE BIANCE ACTUATOR TYPE ACTUATOR TYPE ANGLE OF THROW ANGLE OF THRO	DETAILED DESCRIPTION	Rotary Switch 4 Position SP4T 3A (AC/DC) 120VAC Panel Mount
CONTACT TIMING CONTACT MATERIAL CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Shorting (MBB) Silver Alloy CIVE Alloy Silver Alloy Alloy Flatted (6.35mm Dia)	DEPTH BEHIND PANEL	34.93mm
CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Silver Alloy	CURRENT RATING	3A (AC/DC)
CONTACT FINISH CIRCUIT PER DECK SP4T ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT TIMING	Shorting (MBB)
CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE SP4T SP4T SP4T ACTUATOR TYPE SP4T SP4T SP4T SP4T SP4T SP4T SP4T SP4T	CONTACT MATERIAL	Silver Alloy
ANGLE OF THROW 30° ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT FINISH	-
ACTUATOR TYPE Flatted (6.35mm Dia)	CIRCUIT PER DECK	SP4T
	ANGLE OF THROW	30°
ACTUATOR LENGTH 12.70mm	ACTUATOR TYPE	Flatted (6.35mm Dia)
	ACTUATOR LENGTH	12.70mm

Related Tags

	-	
Ohmite T504SE	T504SE Distributor	T504SE Supplier
T504SE Price	T504SE Pictures	T504SE Image
T504SE PDF Datasheet	T504SE Download Datasheet	T504SE Datasheet
T504SE Stock	Buy T504SE	Buy Ohmite T504SE
Ohmite T504SE	Ohmite Supplier	Ohmite Distributor
Ohmite T504SE	Ohmite Mfg. Co. T504SE	Ohmite Mfg. Co. T504SE

Related Products



OHMITE

Manufacturers: Ohmite Description: SWITCH ROTARY 5POS 3A 120V

In stock: 1055 pcs

RFQ



Manufacturers: Ohmite Description: SWITCH ROTARY 4POS 3A 120V

In stock: 932 pcs

RFQ

T503E



OHMITE

Manufacturers: Ohmite Description: SWITCH ROTARY 3POS 3A 120V

In stock: 1184 pcs

RFQ

OHMITE

T5039NLT Manufacturers: Pulse Electronics Corporation

Description: MODULE ISDN-S 1CT:2.5CT 30MH SMD In stock: 7024 pcs

RFQ

T505S

Manufacturers: Ohmite Description: SWITCH ROTARY 5POS 3A 120V

In stock: 3970 pcs

RFQ

OHMITE

T504E Manufacturers: Ohmite

Description: SWITCH ROTARY 4POS 3A 120V In stock: 1140 pcs

RFQ

T504 Manufacturers: Ohmite OHMITE

Description: SWITCH ROTARY 4POS 3A 120V In stock: 6690 pcs

RFQ

OHMITE

Manufacturers: Ohmite Description: SWITCH ROTARY 5POS 3A 120V

T505

In stock: 789 pcs

RFQ

Manufacturers: Ohmite OHMITE

T505E

Description: SWITCH ROTARY 5POS 3A 120V In stock: 974 pcs

RFQ

T50401500000G

Amphenol ANYTEK

Manufacturers: Anytek (Amphenol Anytek) Description: 350 TB WIR PRO 180D SOL

T50501500000G

In stock: 266476 pcs **RFQ**

Manufacturers: Anytek (Amphenol Anytek)

Amphenol ANYTEK

Description: 350 TB WIR PRO 180D SOL

In stock: 327367 pcs

RFQ



Manufacturers: Ohmite

T506

Description: SWITCH ROTARY 6POS 3A 120V In stock: 3565 pcs

RFQ















