

### **Panasonic**

**Panasonic** 



Image may be representation. See specifications for product details.

### **DK1A-12V**

Part Number:

Manufacturer/Brand:

Product description Datasheets:

Stock Condition

RoHs Status

Ship From Shipment Way DK1A-12V

Panasonic

RELAY GEN PURPOSE SPST 10A 12V

DK1A-12V.pdf

Hong Kong

Lead free / RoHS Compliant 4413 pcs stock

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Specifications of DK1A-12V

MANUFACTURER         Panasonic           DESCRIPTION         RELAY GEN PURPOSE SPST 10A 12V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         4113 pcs           DATA SHEET         60 KIA-12V.pdf           TURN ON VOLTAGE (MAX)         8.4 VDC           TURN OF FOUTAGE (MIN)         1.2 VDC           TERMINATION STYLE         PC Pin           SWITCHING VOLTAGE         250VAC, 125VDC - Max           SERIES         DK           RELAY TYPE         General Purpose           RELAY TYPE         General Purpose           PACKAGING         Tube           OTHER NAMES         255-1096           OPERATITIS TEMPERATURE         40°C ~ 65°C           OPERATE TIME         10ms           MOUNTING TYPE         Through Hole           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           FEATURES         Sealed - Fully           DETAILED DESCRIPTION         General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole           CONTACT RATING (CURRENT)         10A           CONTACT RATING (CURRENT)         5VST-NO (1 Form A)           COLI VOLTAGE         12VDC           CUIL VOLTAGE         12VDC		
DESCRIPTION         RELAY GEN PURPOSE SPST 10A 12V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         4413 pcs           DATA SHEET         DK 1A-12V.pdf           TURN ON VOLTAGE (MAX)         8.4 VDC           TURN OFF VOLTAGE (MIN)         1.2 VDC           TERMINATION STYLE         PC Pin           SWITCHING VOLTAGE         250VAC, 125VDC - Max           SERIES         DK           RELEASE TIME         8ms           RELAY TYPE         General Purpose           PACKAGING         Tube           OTHER NAMES         DK AGE           OPERATION TEMPERATURE         40° < 6° 5° C           OPERATION TEMPERATURE         10ms           MOUNTING TYPE         Through Hole           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           DETAILED DESCRIPTION         General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole           CONTACT RATING (CURRENT)         10A           CONTACT FORM         SPST-NO (1 Form A)           CONTACT FORM         SPST-NO (1 Form A)           COIL VOLTAGE         12VDC           COIL TYPE         Non Latching           COIL TYPE         Non Latching	PART NUMBER	DK1A-12V
LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         4413 pcs           DATA SHEET         □ DK1A-12V.pdf           TURN ON VOLTAGE (MAX)         8.4 VDC           TURN OFF VOLTAGE (MIN)         1.2 VDC           TERMINATION STYLE         PC PIn           SWITCHING VOLTAGE         250VAC, 125VDC - Max           SERIES         DK           RELEASE TIME         8ms           RELEAY TYPE         General Purpose           PACKAGISING         Tube           OTHER NAMES         255-1096 DK1AE-12V           OPERATE TIME         10ms           MOUNTING TYPE         10ms           MOUNTING TYPE         10ms           MOUNTING TYPE         10ms           EAT FLATURS (NOHS STATUS         Lead free / ROHS Compliant           EEAT PER STATUS / ROHS STATUS         Sealed - Fully           DETAILED DESCRIPTION         General Purpose Relay SPST-NO (1 Form A) 12VDC Coll Through Hole           CONTACT RATING (CURRENT)         10A           CONTACT FATURG (CURRENT)         SPST-NO (1 Form A)           CONTACT FORM         SPST-NO (1 Form A)           COLI VOLTAGE         12VDC           COLI TYPE         Non Latching           COLI	MANUFACTURER	Panasonic
QUANTITY AVAILABLE         4413 pcs           DATA SHEET         60 KIA-12V.pdf           TURN ON VOLTAGE (MAX)         8.4 VDC           TURN OFF VOLTAGE (MIN)         1.2 VDC           TERMINATION STYLE         PC PIN           SWITCHING VOLTAGE         250VAC, 125VDC - Max           SERIES         DK           RELEASE TIME         Bms           RELAY TYPE         General Purpose           PACKAGING         Tube           OTHER NAMES         DK18-12V           OPERATING TEMPERATURE         40°C ~ 65°C           OPERATING TEMPERATURE         10ms           MOUNTING TYPE         Through Hole           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           FEATURES         Sealed - Fully           DETAILED DESCRIPTION         General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole           CONTACT RATING (CURRENT)         10A           CONTACT FORM         SPST-NO (1 Form A)           CONTACT FORM         SPST-NO (1 Form A)           COLL VOLTAGE         12VDC           COLL VOLTAGE         12VDC           COLL TYPE         Non Latching           COLL RESISTANCE         200 mW	DESCRIPTION	RELAY GEN PURPOSE SPST 10A 12V
DATA SHEET         EN K1A-12V.pdf           TURN ON VOLTAGE (MAX)         8.4 VDC           TURN OFF VOLTAGE (MIN)         1.2 VDC           TERMINATION STYLE         PC PIN           SWITCHING VOLTAGE         250 VAC, 125 VDC - Max           SERLES         DK           RELEASE TIME         8ms           RELAY TYPE         General Purpose           PACKAGING         Tube           OTHER NAMES         255-1006           OPERATING TEMPERATURE         40°C ~ 65°C           OPERATING TYPE         Through Hole           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           FEATURES         Seeled - Fully           DETAILED DESCRIPTION         General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole           CONTACT RATING (CURRENT)         10A           CONTACT MATERIAL         Silver Tin Oxide (AgSnO)           CONTACT FORM         SPST-NO (1 Form A)           COLI VOLTAGE         12VDC           COLI LYDE         Non Latching           COLI LYDE         Non Latching           COLI RESISTANCE         220 Ohms	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN ON VOLTAGE (MAX)  1.2 VDC  TERMINATION STYLE  PC PIN  SWITCHING VOLTAGE (MIN)  SERIES  SWITCHING VOLTAGE  SERIES  DK  RELEASE TIME  Bms  RELAY TYPE  General Purpose  PACKAGING  OTHER NAMES  OFFERATING TEMPERATURE  A0°C ~ 65°C  OFFERAT TIME  MOUNTING TYPE  Through Hole  LEAD FREE STATUS / ROHS STATUS  LEAD free FAILUS  DETAILED DESCRIPTION  General Purpose Relay SPST-NO (1 Form A) 12VDC  COITACT HATERIAL  COITACT FORM  COITACT FORM  COIL VOLTAGE  COIL RESISTANCE  COIL MEXICAL  CESPONA  CESPONA  CESPONA  CESPONA  CESPONA  CESPONA  CESPONA  CONTACT RELIGIOUS  CONTACT RELIGIOUS  CONTACT FORM  COIL RESISTANCE  COIL RESISTANCE  COIL RESISTANCE  COIL RESISTANCE  COIL RESISTANCE  COIL POWER  COIL RESISTANCE  COIL POWER  CESPONA  CE	QUANTITY AVAILABLE	4413 pcs
TURN OFF VOLTAGE (MIN)         1.2 VDC           TERMINATION STYLE         PC Pin           SWITCHING VOLTAGE         250VAC, 125VDC - Max           SERIES         DK           RELEASE TIME         8ms           RELAY TYPE         General Purpose           PACKAGING         Tube           OTHER NAMES         255-1096 DKLAE-12V           OPERATING TEMPERATURE         40°C < 65°C	DATA SHEET	DK1A-12V.pdf
TERMINATION STYLE PC PIN  SWITCHING VOLTAGE 250VAC, 125VDC - Max  SERIES DK  RELEASE TIME 8MS  RELEASE TIME 8MS  RELEAY TYPE GENERAL TUBE  PACKAGING TUBE  OTHER NAMES DK1AE-12V  OPERATING TEMPERATURE 40°C C 65°C  OPERATING TEMPERATURE 10ms  MOUNTING TYPE 17mough Hole  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES Sealed - Fully  DETAILED DESCRIPTION GENERAL PURDOSE Relay SPST-NO (1 Form A) 12VDC COII Through Hole  CONTACT RATING (CURRENT) 10A  CONTACT FARM (CURRENT) SINDER TIME VIDE (AgSnO)  CONTACT FORM SPST-NO (1 Form A)  COLL VOLTAGE 11VDE NON Latching  COLL VOLTAGE 200 mW	TURN ON VOLTAGE (MAX)	8.4 VDC
SWITCHING VOLTAGE         250VAC, 125VDC - Max           SERIES         DK           RELEASE TIME         8ms           RELAY TYPE         General Purpose           PACKAGING         Tube           OTHER NAMES         255-1096 DK1AE-12V           OPERATING TEMPERATURE         40°C ~ 65°C           OPERATE TIME         10ms           MOUNTING TYPE         Through Hole           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           FEATURES         Sealed - Fully           DETAILED DESCRIPTION         General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole           CONTACT RATING (CURRENT)         10A           CONTACT MATERIAL         Silver Tin Oxide (AgSnO)           CONTACT FORM         SPST-NO (1 Form A)           COIL VOLTAGE         12VDC           COIL TYPE         Non Latching           COIL RESISTANCE         720 Ohms           COIL POWER         200 mW	TURN OFF VOLTAGE (MIN)	1.2 VDC
SERIES         DK           RELEASE TIME         8ms           RELAY TYPE         General Purpose           PACKAGING         Tube           OTHER NAMES         255-1096 DKLAF-12V           OPERATING TEMPERATURE         -40°C ~ 65°C           OPERATING TYPE         Through Hole           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           EFATURES         Sealed - Fully           DETAILED DESCRIPTION         General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole           CONTACT RATING (CURRENT)         10A           CONTACT MATERIAL         Silver Tin Oxide (AgSnO)           CONTACT FORM         SPST-NO (1 Form A)           COIL YOF         Non Latching           COIL TYPE         Non Latching           COIL TYPE         Non Latching           COIL RESISTANCE         20 Ohms	TERMINATION STYLE	PC Pin
RELAY TYPE General Purpose  PACKAGING Tube  OTHER NAMES  OPERATING TEMPERATURE  OPERATING TEMPERATURE  OPERATING TYPE  OPERATE TIME  IOMS  MOUNTING TYPE  Through Hole  LEAD FREE STATUS / ROHS STATUS  DETAILED DESCRIPTION  DETAILED DESCRIPTION  CONTACT RATING (CURRENT)  CONTACT RATING (CURRENT)  CONTACT PARM  CONTACT FORM  CONTACT FORM  CONTACT FORM  CONTACT FORM  CONTACT FORM  CONTACT FORM  COLL TYPE  NON Latching  COLL TYPE  COLL TYPE  COLL POWER  COLL POWER  TUBE  General Purpose  General Purpose Relay SPST-NO (1 Form A) 12VDC Coll Through Hole  CONTACT TRATING (CURRENT)  NON Latching  COLL TYPE  NON Latching  COLL POWER  200 mW	SWITCHING VOLTAGE	250VAC, 125VDC - Max
RELAY TYPE General Purpose  PACKAGING Tube  PACKAGING Tube  S55-196  DK1AE-12V  DPERATING TEMPERATURE -40°C ~65°C  OPERATE TIME 10ms  MOUNTING TYPE 1Through Hole  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES Sealed - Fully  DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL SIIVER SPST-NO (1 Form A)  CONTACT FORM SPST-NO (1 Form A)  COIL YOLTAGE 12VDC  COIL YOLTAGE 12VDC  COIL TYPE Non Latching  COIL RESISTANCE 720 Ohms  COIL POWER 12 DESCRIPTION 10 SERIAL 12VDC  COIL TYPE Non Latching 12VDC  COIL POWER 12 DESCRIPTION 10 SERIAL 12VDC  COIL POWER 12 DESCRIPTI	SERIES	DK
PACKAGING OTHER NAMES OTHER NAMES OPERATING TEMPERATURE -40°C ~ 65°C OPERATE TIME OPERATE TIME OPERATE TIME Through Hole LEAD FREE STATUS / ROHS STATUS LEAd Free / RoHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole CONTACT RATING (CURRENT) ONTACT MATERIAL SIIVER TIN Oxide (AgSnO) CONTACT FORM ONTACT FORM ONTACT FORM OND LEAD FORM ON	RELEASE TIME	8ms
OTHER NAMES  OTHER NAMES  OPERATING TEMPERATURE  -40°C ~ 65°C  OPERATE TIME  10ms  MOUNTING TYPE  Through Hole  LEAD FREE STATUS / ROHS STATUS  EATURES  Sealed - Fully  DETAILED DESCRIPTION  CONTACT RATING (CURRENT)  CONTACT MATERIAL  CONTACT FORM  CONTACT FORM  CONTACT FORM  COLL YOLTAGE  COLL YOLTAGE  COLL YOLTAGE  COLL YOLTAGE  COLL RESISTANCE  COLL POWER  ZESSION AUCC AGS°C  AUCC ~ 65°C  Through Hole  Lead Free / RoHS Compliant  Through Hole  Ceneral Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole  CONTACT MATERIAL  SIEVER TIN OXIDE (AgSNO)  CONTACT FORM  COLL YOLTAGE  COLL YOLTAGE  COLL YOLTAGE  COLL YOLTAGE  COLL RESISTANCE  COLL POWER  ZESSION AUCC AGS°C  AUCC ~ 65°C  CHOUGH HOLE  AUCC ~ 65°C  CHOUGH HOLE  COLL YOLTAGE  AUCC ~ 65°C  CHOUGH HOLE	RELAY TYPE	General Purpose
OFERATING TEMPERATURE -40°C ~ 65°C  OPERATE TIME 10ms  MOUNTING TYPE Through Hole  LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant  FEATURES Sealed - Fully  DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL Silver Tin Oxide (AgSnO)  CONTACT FORM SPST-NO (1 Form A)  COIL VOLTAGE 12VDC  COIL TYPE Non Latching  COIL RESISTANCE 720 Ohms  COIL POWER 200 MW	PACKAGING	Tube
OPERATE TIME 10ms  MOUNTING TYPE Through Hole  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES Sealed - Fully  DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL Silver Tin Oxide (AgSnO)  CONTACT FORM SPST-NO (1 Form A)  COIL VOLTAGE 12VDC  COIL TYPE Non Latching  COIL RESISTANCE 720 Ohms  COIL POWER 200 mW	OTHER NAMES	
MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Tin Oxide (AgSnO) CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE 720 Ohms COIL POWER 200 mW	OPERATING TEMPERATURE	-40°C ~ 65°C
LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  FEATURES  Sealed - Fully  General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole  CONTACT RATING (CURRENT)  CONTACT MATERIAL  CONTACT FORM  CONTACT FORM  COIL VOLTAGE  COIL TYPE  COIL TYPE  COIL TYPE  COIL POWER  COIL POWER  SEARCH SOMS  A GREE / ROHS Compliant  Lead free / RoHS Compliant  Sealed - Fully  General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole  Loud Form A) 12VDC Coil Through Hole  Loud Free / RoHS Compliant  Lead free / RoHS Compliant  Sealed - Fully  General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole  Loud Form A) 12VDC Coil Through Hole  Loud Free / RoHS Compliant  Lead free / RoHS Coil Form A) 12VDC Coil Through Hole  Lead free / RoHS Coil Through Hole	OPERATE TIME	10ms
FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Tin Oxide (AgSnO) CONTACT FORM SPST-NO (1 Form A) COIL VOLTAGE 12VDC COIL TYPE Non Latching COIL TYPE 720 Ohms COIL POWER 200 mW	MOUNTING TYPE	Through Hole
DETAILED DESCRIPTION General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole  CONTACT RATING (CURRENT) 10A  CONTACT MATERIAL Silver Tin Oxide (AgSnO)  CONTACT FORM SPST-NO (1 Form A)  COIL VOLTAGE 12VDC  COIL TYPE Non Latching  COIL RESISTANCE 720 Ohms  COIL POWER  ON THE STANCE 200 mW	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT)  CONTACT MATERIAL  CONTACT FORM  CONTACT FORM  COIL VOLTAGE  COIL TYPE  Non Latching  COIL RESISTANCE  COIL POWER  10A  Silver Tin Oxide (AgSnO)  SPST-NO (1 Form A)  12VDC  Non Latching  720 Ohms  200 mW	FEATURES	Sealed - Fully
CONTACT MATERIAL Silver Tin Oxide (AgSnO)  CONTACT FORM SPST-NO (1 Form A)  COIL VOLTAGE 12VDC  COIL TYPE Non Latching  COIL RESISTANCE 720 Ohms  COIL POWER 200 mW	DETAILED DESCRIPTION	General Purpose Relay SPST-NO (1 Form A) 12VDC Coil Through Hole
CONTACT FORM SPST-NO (1 Form A)  COIL VOLTAGE 12VDC  COIL TYPE Non Latching  COIL RESISTANCE 720 Ohms  COIL POWER 200 mW	CONTACT RATING (CURRENT)	10A
COIL VOLTAGE 12VDC COIL TYPE Non Latching COIL RESISTANCE 720 Ohms COIL POWER 200 mW	CONTACT MATERIAL	Silver Tin Oxide (AgSnO)
COIL TYPE Non Latching COIL RESISTANCE 720 Ohms COIL POWER 200 mW	CONTACT FORM	SPST-NO (1 Form A)
COIL RESISTANCE 720 Ohms COIL POWER 200 mW	COIL VOLTAGE	12VDC
COIL POWER 200 mW	COIL TYPE	Non Latching
	COIL RESISTANCE	720 Ohms
COIL CURRENT 16.7mA	COIL POWER	200 mW
	COIL CURRENT	16.7mA

Related Tags			
Panasonic DK1A-12V	DK1A-12V Distributor	DK1A-12V Supplier	
DK1A-12V Price	DK1A-12V Pictures	DK1A-12V Image	
DK1A-12V PDF Datasheet	DK1A-12V Download Datasheet	DK1A-12V Datasheet	
DK1A-12V Stock	Buy DK1A-12V	Buy Panasonic DK1A-12V	
Panasonic DK1A-12V	Panasonic Supplier	Panasonic Distributor	
Panasonic DK1A-12V	Panasonic - Consumer Division DK1A-12V	Panasonic - Consumer Electronics Corp. DK1A-12V	
Panasonic Battery Group DK1A-12V	Panasonic Electric Works - ACSD DK1A-12V	Panasonic Electronic Components - Semiconductor Pr DK1A-12V	
Panasonic - ATG DK1A-12V	Panasonic - BSG DK1A-12V	Panasonic - DTG DK1A-12V	
Panasonic Electric Works DK1A-12V	Panasonic Electronic Components DK1A-12V	Panasonic Industrial Automation Sales DK1A-12V	

# **Related Products**



Panasonic Semiconductor DK1A-12V

# **DK198-XEC**

Manufacturers: C-Ton Industries

Description: PROC METER/VOLTMETER LCD PNL MT In stock: 1437 pcs

**RFQ** 



### **DK1A-24V**

Manufacturers: Panasonic

Description: RELAY GEN PURPOSE SPST 10A 24V In stock: 4164 pcs

**RFQ** 



# **DK199-XEC**

Manufacturers: C-Ton Industries Description: PROC METER/VOLTMETER LCD PNL MT

In stock: 1488 pcs

**RFQ** 



### **DK198P**

Manufacturers: C-Ton Industries Description: PROC METER/VOLTMETER LCD PNL MT

In stock: 1649 pcs

**RFQ** 



#### DK1A-3V Manufacturers: Panasonic

Description: RELAY GEN PURPOSE SPST 10A 3V In stock: 2860 pcs

**RFQ** 



#### **DK199** Manufacturers: C-Ton Industries

Description: PROC METER/VOLTMETER LCD PNL MT In stock: 1807 pcs

**RFQ** 



#### **DK199P** Manufacturers: C-Ton Industries

Description: PROC METER/VOLTMETER LCD PNL MT In stock: 1811 pcs

**RFQ** 

Description: RELAY GEN PURPOSE SPST 10A 24V



### **DK1A-5V** Manufacturers: Panasonic

Description: RELAY GEN PURPOSE SPST 10A 5V In stock: 2811 pcs

**RFQ** 



# **DK1A-24V-F**

Manufacturers: Panasonic

In stock: 9373 pcs

**RFQ** 



**DK1A-12V-F** 

Manufacturers: Panasonic Description: RELAY GEN PURPOSE SPST 10A 12V


In stock: 11833 pcs **RFQ** 



### DK1A-3V-F Manufacturers: Panasonic

In stock: 9661 pcs

**RFQ** 





#### **DK198** Manufacturers: C-Ton Industries

In stock: 1818 pcs

**RFQ** 

Description: PROC METER/VOLTMETER LCD PNL MT

E-mail: Info@infinity-electronic.com Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong









