APEM



APEI

APEM Inc.

DHS10C

Part Number:

Manufacturer/Brand:

Product description Datasheets:

RoHs Status Stock Condition

Ship From Shipment Way DHS10C

APEM Inc.

SWITCH SLIDE DIP SPST 100MA 6V

DHS10C.pdf

Lead free / RoHS Compliant 25710 pcs stock

DHL/Fedex/TNT/UPS/EMS

Hong Kong

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER DHS10C MANUFACTURER APPM Inc. DESCRIPTION SWITCH SLIDE DIP SPST 100MA 6V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 25710 pcs DATA SHEET □ DHS10Cpdf WASHABLE Yes VOLTAGE RATING 6VDC TERMINATION STYLE Gull Wing SERIES DHS PITCH 0.050° (1.27mm), Half PACKAGING 79c & Red (TR) OPERATING TEMPERATURE 40°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MECHANICAL LIFE - LEENTH 0.568° (14.43mm) LEENTH ABOVE BOARD 0.087° (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Side (Standard) Actuator 100mA 6VOC CURRENT RATING 100mA CONTACT HATERIAL Beryllium Copper CUNTACT FINISH Guld GODY MATERIAL Polylphenylene		Specifications of DHS10C
MANUFACTURER APEM Inc. DESCRIPTION SWITCH SLIDE DIP SPST 100MA 6V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 25710 pcs DATA SHEET 530 DH510C.pdf WASHABLE Yes VOLTAGE RATING 6VDC SERIES DHS PITCH 0.050° (1.27mm), Half PACKAGING Tape & Real (TR) OPERATING TEMPERATURE 40°°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTION TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 2 (20mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.080° (2.2mm) FEATURES Tape Seal ELECTICAL LIFE 1,000 Cycles DETAILED DESCRIPTION 0.087° (2.2mm) CURRENT RATING 100mA CURRENT RATING 100mA CURRENT RATING 60d CONTACT FINISH		
DESCRIPTION SWITCH SLIDE DIP SPST 100MA 6V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 257.0 pcs DATA SHEET → DHS10C.pdf WASHABLE Yes VOLTAGE RATING 6VDC TERRIHATION STYLE Gull Wing SERIES DHS PITCH 0.050° (1.27mm), Half PACKAGING Tape & Reel (TR) OPERATING TEMPERATURE 40°C ~ 80°C NUMBER OF POSITIONS 0 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LENGTH 0.568° (14.43mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.087° (2.20mm) ELECTRICAL LIFE 1 pp Seal ELECTRICAL LIFE 1 pp Seal CELCETRICAL LIFE 1 pp Seal CURRENT BATTING 0 pp Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT BATTING 600M CURRENT BATTING 60d	PART NUMBER	DHS10C
LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 25710 pcs DATA SHEET ☑ DHSLOC.pdf WASHABLE Yes VOLTAGE RATING 6VDC TERNINATION STYLE Gull Wing SERIES DHS PITCH 0.050° (1.27mm), Half PACKAGING Tape & Reel (TR) OPBEATING TEMPERATURE 40°C ~ 80°C NUMBER OF POSITIONS 0 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0,087° (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles ELECTRICAL LIFE 1,000 Cycles CURRENT BATING 0,098° (2.20mm) CURRENT BATING 000°A CURRENT BATING 000°A CURRENT BATING 000°A CURRENT BATING Gold CONTACT MATERIAL Gold CONT	MANUFACTURER	APEM Inc.
QUANTITY AVAILABLE 25710 pcs DATA SHEET 10 HS10C-pdf WASHABLE Yes VOLTAGE RATING 6VDC TERMINATION STYLE Gull Wing SERIES DHS PITCH 0.505° (1.27mm), Half PACKAGING Tape & Reel (TR) OPERATING TEMPERATURE 40°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHADIAL LIFE - 568° (14.43mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES 1,000 Cycles ELECTRICAL LIFE 1,000 Cycles ELECTRICAL LIFE 1,000 Cycles ELECTRICAL LIFE 1,000 Cycles CURRENT RATING 100mA CONTACT MATERIAL Gold CONTACT FINISH Gold CONTACT FINISH Gold BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled BODY MATERIAL Side (Standard)	DESCRIPTION	SWITCH SLIDE DIP SPST 100MA 6V
DATA SHEFT WASHABLE VOLTAGE RATING VOLTAGE RATING VOLTAGE RATING VOLTAGE RATING FURMINATION STYLE GUIL Wing SERIES DHS PITCH 0.050° (1.27mm), Half PACKAGING Tepe & Reel (TR) OPERATING TEMPERATURE A0°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE SURFAGE MOUNTING TYPE WINGE MECHANICAL LIFE 1- LENGTH LENGTH LEAGT FRATURS HEIGHT ABOVE BOARD DEATH STATUS LEAGT FRATUS LEAGT FREE STATUS / ROHS STATUS LEAGT FREE STA	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
WASHABLE Yes VOLTAGE RATING 6VDC TERMINATION STYLE Gull Wing SERIES DHS PITCH 0.050" (1.27mm), Half" PACKAGING Tape & Red (TR) OPERATING TEMPERATURE -40°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.088" (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL Seryllium Copper CONTACT FINISH Gold CONTACT FINISH Gold BODY MATERIAL SPST BODY MATERIAL Slide (Standard) BODY MATERIAL Slide (Standard)	QUANTITY AVAILABLE	25710 pcs
VOLTAGE RATING 6VDC TERMINATION STYLE Gull Wing SERIES DHS PITCH 0.050" (1.27mm), Half PACKAGING Tape & Reel (TR) OPERATING TEMPERATURE -40°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant HEIGHT ABOVE BOARD 0.087" (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CURCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled BODY MATERIAL Slide (Standard)	DATA SHEET	DHS10C.pdf
EREMINATION STYLE Gull Wing SERIES DHS PITCH 0.050" (1.27mm), Half PACKAGING Tape & Reel (TR) OPERATING TEMPERATURE -40°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LENGTH 0.568" (14.43mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.087" (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL Gold CONTACT FINISH Gold CICKUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Slide (Standard)	WASHABLE	Yes
SERIES DHS PITCH 0.050" (1.27mm), Half PACKAGING Tape & Reel (TR) OPERATING TEMPERATURE -40°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LENGTH 0.568" (14.43mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.087" (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL Seryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Slide (Standard)	VOLTAGE RATING	6VDC
PACKAGING Tape & Reel (TR) OPERATING TEMPERATURE -40°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LENGTH 0.568" (14.43mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.087" (2.20mm) FEATURES 1,000 Cycles ELECTRICAL LIFE 1,000 Cycles ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP SWItch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 50dl CONTACT MATERIAL BERYLLIFE 50dl CONTACT FINISH 6.061 CIRCUIT SPST 6.01 SUSSE SUSSE SIBILED LEG (Standard) SUSSE SIBILED SUSSE SUSSE SIBILED SUSSE SUSSE SIBILED SUSSE SUSSE SIBILED SUSSE SUSSE SIBILED SUSSE SU	TERMINATION STYLE	Gull Wing
PACKAGINGTape & Reel (TR)OPERATING TEMPERATURE-40°C ~ 80°CNUMBER OF POSITIONS10MOUNTING TYPESurface MountMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE-LENGTH0.568" (14.43mm)LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantHEIGHT ABOVE BOARD0.087" (2.20mm)FEATURESTape SealELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDCCURRENT RATING100mACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCICILUISPSTBODY MATERIALPolyphenylene Sulfide (PPS), Glass FilledACTUATOR TYPESlide (Standard)	SERIES	DHS
OPERATING TEMPERATURE -40°C ~ 80°C NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LENGTH 0.568" (14.43mm) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant HEIGHT ABOVE BOARD 0.087" (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH GOId CIRCUIT SPST BODY MATERIAL SIIde (Standard) Slide (Standard)	PITCH	0.050" (1.27mm), Half
NUMBER OF POSITIONS 10 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE - LENGTH 0.568" (14.43mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.087" (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Slide (Standard)	PACKAGING	Tape & Reel (TR)
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE LENGTH LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEED FREE STATUS / ROHS STATUS LEEGHT ABOVE BOARD FEATURES ELECTRICAL LIFE LOW Cycles LECTRICAL LIFE Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING CONTACT FINISH CONTACT FINISH BODY MATERIAL BODY MATERIAL ACTUATOR TYPE Surface Mount Surface Mount Surface Mount Slide (Standard) Actuator 100mA 6VDC SPST BODY MATERIAL Silde (Standard)	OPERATING TEMPERATURE	-40°C ~ 80°C
MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE - LENGTH 0.568" (14.43mm) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant HEIGHT ABOVE BOARD 0.087" (2.20mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL DOLYMATERIAL FOLIAMOR SURFINED Slide (Standard) Slide (Standard) Slide (Standard) Slide (Standard) Slide (Standard) Slide (Standard)	NUMBER OF POSITIONS	10
MECHANICAL LIFE LENGTH LEAD FREE STATUS / ROHS STATUS LEAD	MOUNTING TYPE	Surface Mount
LENGTH0.568" (14.43mm)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.087" (2.20mm)FEATURESTape SealELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDCCURRENT RATING100mACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyphenylene Sulfide (PPS), Glass FilledACTUATOR TYPESlide (Standard)	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.087" (2.20mm)FEATURESTape SealELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDCCURRENT RATING100mACONTACT MATERIALBeryllium CopperCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALPolyphenylene Sulfide (PPS), Glass FilledACTUATOR TYPESlide (Standard)	MECHANICAL LIFE	-
HEIGHT ABOVE BOARD FEATURES Tape Seal LLECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE	LENGTH	0.568" (14.43mm)
FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Slide Seal	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Specifical 1,000 Cycles 1,000 Cy	HEIGHT ABOVE BOARD	0.087" (2.20mm)
DETAILED DESCRIPTION Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC CURRENT RATING 100mA CONTACT MATERIAL BODY MATERIAL ONA CIRCUIT BODY MATERIAL ACTUATOR TYPE Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC 100mA 100mA 6VDC 1	FEATURES	Tape Seal
CONTACT MATERIAL CONTACT FINISH CIRCUIT BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE 100mA Beryllium Copper Gold Gold Fryllium Copper Gold Gold Gold SPST SPST Slide (Standard)	ELECTRICAL LIFE	1,000 Cycles
CONTACT MATERIAL CONTACT FINISH CIRCUIT BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Beryllium Copper Gold Fold Gold Polyphenylene Sulfide (PPS), Glass Filled Slide (Standard)	DETAILED DESCRIPTION	Dip Switch SPST 10 Position Surface Mount Slide (Standard) Actuator 100mA 6VDC
CONTACT FINISH CIRCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Side (Standard)	CURRENT RATING	100mA
CIRCUIT SPST BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Slide (Standard)	CONTACT MATERIAL	Beryllium Copper
BODY MATERIAL Polyphenylene Sulfide (PPS), Glass Filled ACTUATOR TYPE Slide (Standard)	CONTACT FINISH	Gold
ACTUATOR TYPE Slide (Standard)	CIRCUIT	SPST
	BODY MATERIAL	Polyphenylene Sulfide (PPS), Glass Filled
ACTUATOR LEVEL Flush, Recessed	ACTUATOR TYPE	Slide (Standard)
	ACTUATOR LEVEL	Flush, Recessed

Related Tags

APEM Inc. DHS10C	DHS10C Distributor	DHS10C Supplier
DHS10C Price	DHS10C Pictures	DHS10C Image
DHS10C PDF Datasheet	DHS10C Download Datasheet	DHS10C Datasheet
DHS10C Stock	Buy DHS10C	Buy APEM Inc. DHS10C
APEM Inc. DHS10C	APEM Inc. Supplier	APEM Inc. Distributor
APEM Inc. DHS10C	APEM Components, LLC DHS10C	APEM Components, LLC DHS10C

Related Products



DHS100B24

Manufacturers: Cosel Description: DC DC CONVERTER 24V

In stock: 620 pcs

RFQ



DHS200A12-T

Manufacturers: Cosel Description: DC DC CONVERTER 12V

In stock: 468 pcs

RFQ



DHS100B28-T

Manufacturers: Cosel

Description: DC DC CONVERTER 28V In stock: 676 pcs

RFQ

DHS100B24-T

Manufacturers: Cosel Description: DC DC CONVERTER 24V

In stock: 774 pcs

RFQ



DHS10S

Manufacturers: APEM Inc. Description: SWITCH SLIDE DIP SPST 100MA 6V

In stock: 27633 pcs

RFQ



DHS200A05-T

Manufacturers: Cosel Description: DC DC CONVERTER 5V

In stock: 602 pcs

RFQ



DHS200A05 Manufacturers: Cosel

Description: DC DC CONVERTER 5V In stock: 463 pcs

RFQ



Manufacturers: Cosel

DHS100B15

Description: DC DC CONVERTER 15V In stock: 776 pcs

RFQ



DHS200A12 Manufacturers: Cosel

Description: DC DC CONVERTER 12V In stock: 530 pcs

RFQ



DHS100B15-T Manufacturers: Cosel

Description: DC DC CONVERTER 15V In stock: 706 pcs

RFQ



DHS100B28 Manufacturers: Cosel

Description: DC DC CONVERTER 28V In stock: 704 pcs

RFQ



DHS200A15

Manufacturers: Cosel Description: DC DC CONVERTER 15V In stock: 551 pcs

RFQ





Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong











