

The image shows a header section for a Honeywell product page. On the left, the Honeywell logo is displayed in red. To its right, the text "Honeywell Microelectronics & Precision Sensors" is written in black, with "Precision Sensors" on a separate line. Below this header is a large, empty rectangular area with a light gray background, which serves as a placeholder for a product image. At the bottom of this placeholder area, there is a line of text in a light gray font that reads: "Image may be representation. See specifications for product details."

HPB100RTTA

Part Number:	HPB100RTTA
Manufacturer/Brand:	Honeywell Microelectronics & Precision Sensors
Product description	BAROMETER
Datasheets:	 HPB100RTTA.pdf
RoHS Status	 Contains lead / RoHS non-compliant
Stock Condition	2820 pcs stock
Ship From	Hong Kong
Shipment Way	DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Specifications of HPB100RTTA

PART NUMBER	HPB100RTTA
MANUFACTURER	Honeywell Microelectronics & Precision Sensors
DESCRIPTION	BAROMETER
LEAD FREE STATUS / ROHS STATUS	Contains lead / RoHS non-compliant
QUANTITY AVAILABLE	2820 pcs
DATA SHEET	 HPB100RTTA.pdf
VOLTAGE - SUPPLY	6 V ~ 26 V
TERMINATION STYLE	Connector
SUPPLIER DEVICE PACKAGE	-
SERIES	-
PRESSURE TYPE	Absolute
PORT STYLE	Barbed
PORT SIZE	Male - 0.13" (3.18mm) Tube
PACKAGE / CASE	Module Cube
OUTPUT TYPE	TTL
OUTPUT	-
OPERATING TEMPERATURE	-40°C ~ 85°C
OPERATING PRESSURE	7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)
MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
MAXIMUM PRESSURE	-
LEAD FREE STATUS / ROHS STATUS	Contains lead / RoHS non-compliant
FEATURES	-
DETAILED DESCRIPTION	Pressure Sensor 7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa) Absolute Male - 0.13" (3.18mm) Tube Module Cube
ACCURACY	±0.012 PSI (±0.08 kPa)