product details.

## **linfinity-electronic**

## Specifications of WTT12L-B1533

PART NUMBER	WTT12L-B1533
MANUFACTURER	N/A
DESCRIPTION	PSH/PL LO 5-WIRE 2M CBL
LEAD FREE STATUS / ROHS STATUS	
QUANTITY AVAILABLE	263 pcs
DATA SHEET	
VOLTAGE - SUPPLY	10 V ~ 30 V
SERIES	PowerProx
SENSING METHOD	Proximity
SENSING DISTANCE	1.969" ~ 98.425" (50mm ~ 2.5m)
RESPONSE TIME	500µs
OUTPUT CONFIGURATION	NPN/PNP
OTHER NAMES	1072641
OPERATING TEMPERATURE	-35°C ~ 50°C (TA)
LIGHT SOURCE	Red Laser Diode (658nm)
INGRESS PROTECTION	IP67
CONNECTION METHOD	Cable
CABLE LENGTH	78.740" (2000.00mm)
ADJUSTMENT TYPE	Adjustable

## **Related Tags**

WTT12L-B1533	Supplier	Distributor
WTT12L-B1533 Stock	Buy WTT12L-B1533	Buy WTT12L-B1533
WTT12L-B1533 PDF Datasheet	WTT12L-B1533 Download Datasheet	WTT12L-B1533 Datasheet
WTT12L-B1533 Price	WTT12L-B1533 Pictures	WTT12L-B1533 Image
WTT12L-B1533	WTT12L-B1533 Distributor	WTT12L-B1533 Supplier

## **Related Products**



