Grayhill



Grayhill, Inc.

90GB03T

Part Number:

Datasheets:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Ship From Shipment Way 90GB03T

Grayhill, Inc.

SWITCH SLIDE DIP SPST 10MA 30V

90GB03T.pdf

Lead free / RoHS Compliant 29263 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

| PART NUMBER         90GB03T           MANUFACTURER         Grayhil, Inc.           DESCRIPTION         SWITCH SLIDE DIP SPST 10MA 30V           LEAD FREE STATU'S ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         29263 pcs           DATA SHEET         690803T.pdf           WASHABLE         NO           VOLTAGE RATING         30VDC           TERMINATION STYLE         PC Pin           SERIES         90CB           PITCH         0.100" (2.5-Inm), Full           PACKAGING         Tube           OPERATING THMERATURE         40°C ~ 85°C           NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LENGTH         0.370" (9.40mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           FEATURES         -           DETAILED DESCRIPTION         Dip Switch SPST 3 Position Through Hole Slide (Standard) Accustor 10mA 30VDC           CURRENT RATING         10mA           CONTACT HATERIAL         Copper Alloy   |                                  | Specifications of 90GB03T  |
|--|----------------------------------|--|
| MANUFACTURER         Grayhill, Inc.           DESCRIPTION         SWITCH SLIDE DIP SPST 10MA 30V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         39263 pcs           DATA SHEET         3906803T.pdf           WASHABLE         No           VOLTAGE RATING         30VDC           TERMINATION STYLE         P0 Pin           SERIES         90GB           PITCH         0.100° (2.54mm), Full           PACKAGING         Tube           OPERATING TEMPERATURE         -10°C ~ 85°C           NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.195" (4.95mm)           FEATURES         -           ELECTRICAL LIFE         2,000 Cycles           ELECTRICAL LIFE         2,000 Cycles           ELECTRICAL LIFE         2,000 Cycles           ELECTRICAL LIFE         1,000 Cycles           DETAILED DESCRIPTION   | •                                |  |
| DESCRIPTION         SWITCH SLIDE DIP SPST 10MA 30V           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           QUANTITY AVAILABLE         29263 pcs           DATA SHEET         ■ 906803T.pdf           WASHABLE         No           VOLTAGE RATING         30VIDC           TERMINATION STYLE         PC Pin           SERIES         90GB           PITCH         0.100° (2.54mm), Full           PACKAGING         Tube           OPERATING TEMPERATURE         40°C ~ 85°C           NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LENSTH         0.370° (9.40mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           HEIGHT ABOVE BOARD         0.195° (4.95mm)           FEATURES         -           ELECTRICAL LIFE         2,000 Cycles           LECETRICAL LIFE         2,000 Cycles           DETAILED DESCRIPTION         0.195° (4.95mm)           CONTACT MATERIAL         COPPER Alloy           CONTACT MATERIAL         COPPER Alloy           CONTACT MATERIAL         COPPER  | PART NUMBER                      | 90GB03T  |
| LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  QUANTITY AVAILABLE  29263 pcs  DATA SHEET  | MANUFACTURER                     | Grayhill, Inc.   |
| QUANTITYY AVAILABLE         29263 pcs           DATA SHEET         1906B03T.pdf           WASHABLE         No           VOLTAGE RATING         30VDC           TERMINATION STYLE         PC Pin           SERIES         90GB           PITCH         0.100" (2.54mm), Full           PACKAGING         Tube           OPERATING TEMPERATURE         -40°C ~ 85°C           NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LENGTH         0.370" (9.40mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           FEATURES         -           ELECTRICAL LIFE         2,000 Cycles           ELECTRICAL LIFE         2,000 Cycles           DETAILED DESCRIPTION         DIP Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC           CURRENT RATING         10mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           GOID         Thermoplastic           BODY MATERIAL         Thermoplastic  | DESCRIPTION                      | SWITCH SLIDE DIP SPST 10MA 30V   |
| DATA SHEET         SOBOST, pdf           WASHABLE         No           VOLTAGE RATING         30VDC           TERMINATION STYLE         PC Pin           SERIES         90GB           PITCH         0.100" (2.54mm), Full           PACKAGING         Tube           OPERATING TEMPERATURE         -40°C ~ 85°C           NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LENGTH         0.370" (9.40mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.195" (4.95mm)           FEATURES         -           ELECTRICAL LIFE         2,000 Cycles           DETAILED DESCRIPTION         Dip Switch SPST 3 Position Through Hole Silde (Standard) Actuator 10mA 30VDC           CURRENT RATING         10mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           CONTACT FINISH         Thermoplastic           BODY MATERIAL         Thermoplastic           BODY MATERIAL         Side (Standard)   | LEAD FREE STATUS / ROHS STATUS   | Lead free / RoHS Compliant   |
| WASHABLE         No           VOLTAGE RATING         30VDC           TERMINATION STYLE         PC PIn           SERIES         90GB           PITCH         0.100" (2.54mm), Full           PACKAGING         Tube           OPERATING TEMPERATURE         -40°C ~ 85°C           NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LENGTH         0.370" (9.40mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.195" (4.95mm)           FEATURES         -           ELECTRICAL LIFE         2,000 Cycles           DETAILED DESCRIPTION         Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC           CURRENT RATING         10mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           CICQUIT         SPST           BODY MATERIAL         Thermoplastic           BODY MATERIAL         Thermoplastic  | QUANTITY AVAILABLE               | 29263 pcs  |
| VOLTAGE RATING         30VDC           TERMINATION STYLE         PC Pin           SERIES         90GB           PITCH         0.100" (2.54mm), Full           PACKAGING         Tube           OPERATING TEMPERATURE         -40°C ~ 85°C           NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LENGTH         0.370" (9.40mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.195" (4.95mm)           FEATURES         -           ELECTRICAL LIFE         2,000 Cycles           DETAILED DESCRIPTION         Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC           CURRENT RATING         10mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           CIRCUIT         SPST           BODY MATERIAL         Thermoplastic           ACTUATOR TYPE         Slide (Standard)   | DATA SHEET                       | 90GB03T.pdf  |
| FERMINATION STYLE  PROPRIATION STYLE  PROPRIATION STYLE  PACKAGING  PITCH  PACKAGING  TUBE  POPERATING TEMPERATURE  A0°C ~ 85°C  NUMBER OF POSITIONS  3  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  MICHARICAL LIFE  2,000 Cycles  LENGTH  0.370° (9.40mm)  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEIGHT ABOVE BOARD  0.195° (4.95mm)  FEATURES  LEICITICAL LIFE  2,000 Cycles  ELECTICAL LIFE  2,000 Cycles  DETAILED DESCRIPTION  DIP SWITCH SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING  CONTACT MATERIAL  CONTACT MATERIAL  CONTACT FINISH  GOId  CIRCUIT  SPST  BODY MATERIAL  ACTUATOR TYPE  Slide (Standard)  Slide (Standard)  | WASHABLE                         | No   |
| SERIES         90GB           PITCH         0.100" (2.54mm), Full           PACKAGING         Tube           OPERATING TEMPERATURE         -40°C ~ 85°C           NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LENGTH         0.370" (9.40mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           HEIGHT ABOVE BOARD         0.195" (4.95mm)           FEATURES         -           ELECTRICAL LIFE         2,000 Cycles           DETAILED DESCRIPTION         Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC           CURRENT RATING         10mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           CIRCUIT         SPST           BODY MATERIAL         Thermoplastic           ACTUATOR TYPE         Slide (Standard)   | VOLTAGE RATING                   | 30VDC  |
| PTCH 0.100" (2.54mm), Full  PACKAGING Tube  PACKAGING Tube  OPERATING TEMPERATURE -40°C ~ 85°C  NUMBER OF POSITIONS 3  MOUNTING TYPE Through Hole  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  MECHANICAL LIFE 2,000 Cycles  LENGTH 0.370" (9.40mm)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  HEIGHT ABOVE BOARD 0.195" (4.95mm)  FEATURES -  ELECTRICAL LIFE 2,000 Cycles  ELECTRICAL LIFE 2,000 Cycles  CURRENT RATING 10mA  CONTACT MATERIAL Copper Alloy  CONTACT MATERIAL SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING 50d  CIRCUIT SPST 3  BODY MATERIAL Thermoplastic  ACTUATOR TYPE Slide (Standard) Slid | TERMINATION STYLE                | PC Pin   |
| PACKAGING  Tube  OPERATING TEMPERATURE  -40°C ~ 85°C  NUMBER OF POSITIONS  3  MOUNTING TYPE  Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  2,000 Cycles  LENGTH  0.370" (9.40mm)  LEAD FREE STATUS / ROHS STATUS  LEAd free / ROHS Compliant  HEIGHT ABOVE BOARD  0.195" (4.95mm)  FEATURES  - ELECTRICAL LIFE  2,000 Cycles  ELECTRICAL LIFE  2,000 Cycles  CURRENT RATING  Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING  CONTACT MATERIAL  CONTACT FINISH  Gold  CIRCUIT  SPST  BODY MATERIAL  ACTUATOR TYPE  Slide (Standard)  Side (Standard)   | SERIES                           | 90GB   |
| OPERATING TEMPERATURE  NUMBER OF POSITIONS  3  MOUNTING TYPE Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE 2,000 Cycles  LENGTH 0.370" (9.40mm)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  HEIGHT ABOVE BOARD 0.195" (4.95mm)  FEATURES - ELECTRICAL LIFE 2,000 Cycles  ELECTRICAL LIFE 2,000 Cycles  CURRENT RATING Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING CONTACT FINISH Gold  CIRCUIT SPST BODY MATERIAL ACTUATOR TYPE Slide (Standard) Slide (Standard) Slide (Standard) Slide (Standard) Slide (Standard)  | PITCH                            | 0.100" (2.54mm), Full  |
| NUMBER OF POSITIONS         3           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         2,000 Cycles           LENGTH         0.370" (9.40mm)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           HEIGHT ABOVE BOARD         0.195" (4.95mm)           FEATURES         -           ELECTRICAL LIFE         2,000 Cycles           DETAILED DESCRIPTION         Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC           CURRENT RATING         10mA           CONTACT MATERIAL         Copper Alloy           CONTACT FINISH         Gold           CIRCUIT         SPST           BODY MATERIAL         Thermoplastic           ACTUATOR TYPE         Slide (Standard)   | PACKAGING                        | Tube   |
| MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE  LENGTH  LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEED ROHS ON 1.95° (4.95mm)  ELEUT READ VE BOARD  DIPS WICH SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING CONTACT FINISH CONTACT FINISH CONTACT FINISH GOId CIRCUIT SPST BODY MATERIAL SIGN (Standard) SIGN (Standard) SIGN (Standard) SIGN (Standard) SIGN (Standard)  | OPERATING TEMPERATURE            | -40°C ∼ 85°C   |
| MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  2,000 Cycles  LENGTH  2,000 Planm  LEAD FREE STATUS / ROHS STATUS  LEAd free / ROHS Compliant  HEIGHT ABOVE BOARD  6.195" (4.95mm)  FEATURES  ELECTRICAL LIFE  2,000 Cycles  DETAILED DESCRIPTION  Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING  CONTACT FINISH  CONTACT FINISH  Gold  CIRCUIT  BODY MATERIAL  ACTUATOR TYPE  I (Unlimited)  1 (Unlimited)  2 (Unlimited)  2 (Unlimited)  2 (Unlimited)  2 (Unlimited)  2 (Unlimited)  2 (Unlimited)  3 (Unlimited)  4 (Unlimited)  4 (Unlimi | NUMBER OF POSITIONS              | 3  |
| MECHANICAL LIFE2,000 CyclesLENGTH0.370" (9.40mm)LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantHEIGHT ABOVE BOARD0.195" (4.95mm)FEATURES-ELECTRICAL LIFE2,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDCCURRENT RATING10mACONTACT MATERIALCopper AlloyCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALThermoplasticACTUATOR TYPESlide (Standard)  | MOUNTING TYPE                    | Through Hole   |
| LENGTH 0.370" (9.40mm)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  HEIGHT ABOVE BOARD 0.195" (4.95mm)  FEATURES -  ELECTRICAL LIFE 2,000 Cycles  DETAILED DESCRIPTION Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING 10mA  CONTACT MATERIAL Copper Alloy  CONTACT FINISH Gold  CIRCUIT SPST  BODY MATERIAL Thermoplastic  ACTUATOR TYPE SIIDE SCRIPTION SIIDE (Standard) SIIDE (STANDARD SIIDE SII | MOISTURE SENSITIVITY LEVEL (MSL) | 1 (Unlimited)  |
| LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  HEIGHT ABOVE BOARD  0.195" (4.95mm)  FEATURES  - ELECTRICAL LIFE  2,000 Cycles  DETAILED DESCRIPTION  Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING  10mA  CONTACT MATERIAL  CONTACT FINISH  Gold  CIRCUIT  SPST  BODY MATERIAL  Thermoplastic  ACTUATOR TYPE  SIde (Standard)  | MECHANICAL LIFE                  | 2,000 Cycles   |
| HEIGHT ABOVE BOARD  FEATURES  - ELECTRICAL LIFE  2,000 Cycles  DETAILED DESCRIPTION  Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC  CURRENT RATING  10mA  CONTACT MATERIAL  CONTACT FINISH  Gold  CIRCUIT  SPST  BODY MATERIAL  ACTUATOR TYPE  0.195" (4.95mm)  C-955mm)  Contact (Summan)  Contact (Standard) Actuator 10mA 30VDC  Copper Alloy  Copper Alloy  SPST  Thermoplastic  Slide (Standard)   | LENGTH                           | 0.370" (9.40mm)  |
| FEATURES - CONTACT FINISH Gold CIRCUIT SPST BODY MATERIAL ACTUATOR TYPE  - CONTACT MATERIAL - CONTACT MATERI | LEAD FREE STATUS / ROHS STATUS   | Lead free / RoHS Compliant   |
| ELECTRICAL LIFE2,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDCCURRENT RATING10mACONTACT MATERIALCopper AlloyCONTACT FINISHGoldCIRCUITSPSTBODY MATERIALThermoplasticACTUATOR TYPESlide (Standard)  | HEIGHT ABOVE BOARD               | 0.195" (4.95mm)  |
| DETAILED DESCRIPTION Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC CURRENT RATING 10mA CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT SPST  BODY MATERIAL Thermoplastic ACTUATOR TYPE Side (Standard) Actuator 10mA 30VDC  10mA COMA CONTACT FINISH COPPER Alloy Thermoplastic Side (Standard)  | FEATURES                         | -  |
| CONTACT MATERIAL Copper Alloy  CONTACT FINISH Gold  CIRCUIT SPST  BODY MATERIAL Thermoplastic  ACTUATOR TYPE Slide (Standard)  | ELECTRICAL LIFE                  | 2,000 Cycles   |
| CONTACT MATERIAL Copper Alloy  CONTACT FINISH Gold  CIRCUIT SPST  BODY MATERIAL Thermoplastic  ACTUATOR TYPE Slide (Standard)  | DETAILED DESCRIPTION             | Dip Switch SPST 3 Position Through Hole Slide (Standard) Actuator 10mA 30VDC |
| CONTACT FINISH  CIRCUIT  SPST  BODY MATERIAL  ACTUATOR TYPE  Gold  SPST  Thermoplastic  Slide (Standard)   | CURRENT RATING                   | 10mA   |
| CIRCUIT SPST  BODY MATERIAL Thermoplastic  ACTUATOR TYPE Slide (Standard)  | CONTACT MATERIAL                 | Copper Alloy   |
| BODY MATERIAL Thermoplastic  ACTUATOR TYPE Slide (Standard)  | CONTACT FINISH                   | Gold   |
| ACTUATOR TYPE Slide (Standard)   | CIRCUIT                          | SPST   |
|  | BODY MATERIAL                    | Thermoplastic  |
| ACTUATOR LEVEL Flush, Recessed   | ACTUATOR TYPE                    | Slide (Standard)   |
|  | ACTUATOR LEVEL                   | Flush, Recessed  |

## **Related Tags**

| Grayhill, Inc. 90GB03T | 90GB03T Distributor        | 90GB03T Supplier           |
|------------------------|----------------------------|----------------------------|
| 90GB03T Price          | 90GB03T Pictures           | 90GB03T Image              |
| 90GB03T PDF Datasheet  | 90GB03T Download Datasheet | 90GB03T Datasheet          |
| 90GB03T Stock          | Buy 90GB03T                | Buy Grayhill, Inc. 90GB03T |
| Grayhill, Inc. 90GB03T | Grayhill, Inc. Supplier    | Grayhill, Inc. Distributor |
| Grayhill, Inc. 90GB03T | Grayhill Inc. 90GB03T      |                            |

## **Related Products**



**90GB05ST** Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 10MA 30V In stock: 29286 pcs

**RFQ** 

Grayhill

Manufacturers: Grayhill, Inc. Description: SWITCH SLIDE DIP SPST 10MA 30V

In stock: 28187 pcs

**RFQ** 

90GB05T

90GB04ST



**90GB06LT** 

Manufacturers: Grayhill, Inc. Description: SWITCH SLIDE DIP SPST 10MA 30V

In stock: 25167 pcs

**RFQ** 



Manufacturers: Grayhill, Inc. Description: SWITCH SLIDE DIP SPST 10MA 30V

In stock: 25370 pcs

**RFQ** 



**90GB06ST** Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 10MA 30V In stock: 24577 pcs

**RFQ** 



**90GB06SLT** Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 10MA 30V In stock: 19732 pcs

RFQ



Manufacturers: Grayhill, Inc.

**90GB04LT** 

Description: SWITCH SLIDE DIP SPST 10MA 30V In stock: 28671 pcs

**RFQ** 



90GB04T Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 10MA 30V In stock: 28993 pcs

**RFQ** 



EasyBraid Co.

90GB05LT Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 10MA 30V In stock: 22088 pcs

**RFQ** 



**90GB05SLT** Manufacturers: Grayhill, Inc.

Description: SWITCH SLIDE DIP SPST 10MA 30V In stock: 25857 pcs

**RFQ** 



90G LARGE Manufacturers: EasyBraid Co. Description: GLOVES LARGE 1PAIR

In stock: 4184 pcs

**RFQ** 



**90GB04SLT** 

Manufacturers: Grayhill, Inc. Description: SWITCH SLIDE DIP SPST 10MA 30V

**RFQ** 

In stock: 24270 pcs



Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong











