Panasonic



Panasoni

Panasonic

JV1F-100V

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way JV1F-100V

Panasonic

RELAY GEN PURPOSE SPDT 10A 100V

JV1F-100V.pdf Lead free / RoHS Compliant

5414 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER MANUFACTURER Panasonic DESCRIPTION RELAY GEN PURPOSE SPDT 10A 100V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant QUANTITY AVAILABLE DATA SHEET TURN ON VOLTAGE (MAX) 70 VDC TURN OFF VOLTAGE (MIN) 5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 125VAC - Max SERIES JV RELEASE TIME 4ms RELAY TYPE General Purpose BACKAGING BUIK OPERATING TEMPERATURE -0°C ~ 70°C OPERATE TIME MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant FEATURES Sealed - Flux Protection General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) COIL YOFF COIL RESISTANCE COIL RESISTANCE COIL RESISTANCE COIL RESISTANCE COIL RESISTANCE COIL POWER 600 mW		Specifications of JV1F-100V
MANUFACTURER DESCRIPTION RELAY GEN PURPOSE SPDT 10A 100V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 5414 pcs DATA SHEET DATA SHEET TURN ON VOLTAGE (MAX) 70 VDC TURN OFF VOLTAGE (MIN) 5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 125VAC - Max SERIES JV RELEASE TIME 4ms RELAY TYPE General Purpose PACKAGING DEFAILING TEMPERATURE 40°C ~ 70°C OPERATE TIME MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES Seeled - Flux Protection General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) LOA CONTACT RATING (CURRENT) COIL YOLTAGE 100VDC COIL TYPE Non Latching COIL TYPE Non Latching COIL RESISTANCE 600 mW		
DESCRIPTION RELAY GEN PURPOSE SPDT 10A 100V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 5414 pcs DATA SHEET DATA SHEET TURN ON VOLTAGE (MAX) 70 VDC TURN OFF VOLTAGE (MIN) 5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 125VAC - Max SERIES JV RELEASE TIME 4ms RELAY TYPE General Purpose PACKAGING DEFAILING TEMPERATURE -40°C ~ 70°C OPERATING TEMPERATURE MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) LONTACT MATERIAL Silver Alloy CONTACT FATING (CURRENT) COIL YOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 10.6 KOhms 600 mW	PART NUMBER	JV1F-100V
Lead free / RoHS Compliant QUANTITY AVAILABLE 5414 pcs DATA SHEET TURN ON VOLTAGE (MAX) 70 VDC TURN OFF VOLTAGE (MIN) 5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 125VAC - Max SERIES JV RELEASE TIME 4ms RELAY TYPE General Purpose PACKAGING OPERATING TEMPERATURE 40°C ~ 70°C OPERATE TIME MOUNTING TYPE Through Hole LEAD free STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT FORM CONTACT FORM SPDT (1 Form C) COIL YOLTAGE COIL TYPE NON Latching COIL RESISTANCE Liead Free / ROHS Compliant FOR ALLOW SPDT (1 Form C) COIL RESISTANCE Los Kohns COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL RESISTANCE Los Kohns COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL RESISTANCE Los Kohns COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL RESISTANCE LOS HORS FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM SPDT (1 Form C) COIL POWER FOR WITH CONTACT FORM FOR WITH CO	MANUFACTURER	Panasonic
QUANTITY AVAILABLE DATA SHEET TURN ON VOLTAGE (MAX) 70 VDC TURN OFF VOLTAGE (MIN) 5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 125VAC - MAX SERIES JV RELEASE TIME RELAY TYPE General Purpose PACKAGING DEPARTING TEMPERATURE 40°C ~ 70°C OPERATE TIME MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant FEATURES DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coll Through Hole CONTACT MATERIAL CONTACT MATERIAL SINEY Alloy COLL YOLTAGE COLL YOLTAGE COLL TYPE NON LAtching COLL RESISTANCE LEAG ROWN SOM W	DESCRIPTION	RELAY GEN PURPOSE SPDT 10A 100V
DATA SHEET TURN ON VOLTAGE (MAX) 70 VDC TURN OFF VOLTAGE (MIN) 5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 125VAC - Max SERIES JV RELEASE TIME 4ms RELAY TYPE General Purpose PACKAGING DEFAILING TEMPERATURE 40°C ~ 70°C OPERATE TIME MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) COIL YOLTAGE OOL YOLTAGE OOL TYPE NO Latching COIL TYPE NO Latching COIL RESISTANCE 600 mW	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN ON YOLTAGE (MAX) TURN OFF VOLTAGE (MIN) 5 VDC TERMINATION STYLE PC PIN SWITCHING VOLTAGE SERIES JV RELEASE TIME Ams RELAY TYPE General Purpose PACKAGING OPERATING TEMPERATURE AV°C ~ 70°C OPERATE TIME MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION CONTACT RATING (CURRENT) LOA CONTACT MATERIAL SINVE Alloy CONTACT FORM SPDT (1 Form C) COIL YOLTAGE COIL YOLTAGE COIL FORM COIL TYPE NON LECKHING 600 mW	QUANTITY AVAILABLE	5414 pcs
TURN OFF VOLTAGE (MIN) TERMINATION STYLE PC PIN SWITCHING VOLTAGE 125VAC - Max SERIES JV RELEASE TIME 4mS RELAY TYPE General Purpose PACKAGING Bulk OPERATING TEMPERATURE 40°C ~ 70°C OPERATE TIME 5mS MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL TYPE Non Latching COIL FESISTANCE 600 mW	DATA SHEET	JV1F-100V.pdf
FERMINATION STYLE SWITCHING VOLTAGE SITCHING VOLTAGE 125VAC - Max JV RELEASE TIME 4ms RELAY TYPE General Purpose PACKAGING Bulk OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME 5ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) CONTACT FORM SPDT (1 Form C) COIL VOLTAGE NON Latching COIL TYPE NON Latching COIL RESISTANCE 600 mW	TURN ON VOLTAGE (MAX)	70 VDC
SERIES JV RELEASE TIME 4ms RELAY TYPE General Purpose PACKAGING BUIK OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME 5ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT FORM SPDT (1 Form C) COIL YOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER 600 mW	TURN OFF VOLTAGE (MIN)	5 VDC
SERIES RELASE TIME Ams RELAY TYPE General Purpose PACKAGING Bulk OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME Sms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE LOUVDC COIL TYPE Non Latching COIL RESISTANCE 16.6 KOhms 600 mW	TERMINATION STYLE	PC Pin
RELAY TYPE General Purpose PACKAGING Bulk OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME 5ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL TYPE Non Latching COIL RESISTANCE 600 mW	SWITCHING VOLTAGE	125VAC - Max
RELAY TYPE PACKAGING Bulk OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME 5ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) CONTACT MATERIAL CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 600 mW	SERIES	JV
PACKAGING OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME 5ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 KOhms COIL POWER	RELEASE TIME	4ms
OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME 5ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 KOhms 600 mW	RELAY TYPE	General Purpose
OPERATE TIME 5ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER 600 mW	PACKAGING	Bulk
MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER	OPERATING TEMPERATURE	-40°C ~ 70°C
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER	OPERATE TIME	5ms
Sealed - Flux Protection DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER	MOUNTING TYPE	Through Hole
DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER 600 mW	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER 600 mW	FEATURES	Sealed - Flux Protection
CONTACT MATERIAL CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER SPDT (1 Form C)	DETAILED DESCRIPTION	General Purpose Relay SPDT (1 Form C) 100VDC Coil Through Hole
CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER 600 mW	CONTACT RATING (CURRENT)	10A
COIL VOLTAGE 100VDC COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER 600 mW	CONTACT MATERIAL	Silver Alloy
COIL TYPE Non Latching COIL RESISTANCE 16.6 kOhms COIL POWER 600 mW	CONTACT FORM	SPDT (1 Form C)
COIL RESISTANCE 16.6 kOhms COIL POWER 600 mW	COIL VOLTAGE	100VDC
COIL POWER 600 mW	COIL TYPE	Non Latching
	COIL RESISTANCE	16.6 kOhms
COIL CURRENT 6.0mA	COIL POWER	600 mW
	COIL CURRENT	6.0mA

Related Tags

Panasonic JV1F-100V	JV1F-100V Distributor	JV1F-100V Supplier
JV1F-100V Price	JV1F-100V Pictures	JV1F-100V Image
JV1F-100V PDF Datasheet	JV1F-100V Download Datasheet	JV1F-100V Datasheet
JV1F-100V Stock	Buy JV1F-100V	Buy Panasonic JV1F-100V
Panasonic JV1F-100V	Panasonic Supplier	Panasonic Distributor
Panasonic JV1F-100V	Panasonic - Consumer Division JV1F-100V	Panasonic - Consumer Electronics Corp. JV1F-100V
Panasonic Battery Group JV1F-100V	Panasonic Electric Works - ACSD JV1F-100V	Panasonic Electronic Components - Semiconductor Pr JV1F-100V
Panasonic - ATG JV1F-100V	Panasonic - BSG JV1F-100V	Panasonic - DTG JV1F-100V
Panasonic Electric Works JV1F-100V	Panasonic Electronic Components JV1F-100V	Panasonic Industrial Automation Sales JV1F-100V
Panasonic Semiconductor JV1F-100V		

Related Products



JV1AS-5V

JV1F-6V

JV1F-18V

JV1F-12V

Manufacturers: Panasonic Description: RELAY GEN PURPOSE SPST 10A 5V

In stock: 5203 pcs

RFQ



JV1AS-6V

JV1F-24V

Manufacturers: Panasonic Description: RELAY GEN PURPOSE SPST 10A 6V

In stock: 6499 pcs

RFQ

Panasonic

Manufacturers: Panasonic Description: RELAY GEN PURPOSE SPDT 10A 6V

In stock: 4938 pcs

RFQ

Panasonic

Manufacturers: Panasonic

Description: RELAY GEN PURPOSE SPDT 10A 24V In stock: 18403 pcs

RFQ

Panasonic

Manufacturers: Panasonic Description: RELAY GEN PURPOSE SPDT 10A 18V

In stock: 5552 pcs

RFQ

Panasonic

JV1F-48V Manufacturers: Panasonic

Description: RELAY GEN PURPOSE SPDT 10A 48V In stock: 5465 pcs

RFQ

Manufacturers: Panasonic Description: RELAY GEN PURPOSE SPDT 10A 12V **Panasonic**

Panasonic In stock: 6156 pcs

RFQ

Manufacturers: Panasonic Description: RELAY GEN PURPOSE SPDT 10A 5V

JV1F-5V

In stock: 3239 pcs

RFQ




Manufacturers: Panasonic

JV1AS-18V

Description: RELAY GEN PURPOSE SPST 10A 18V In stock: 4552 pcs

RFQ



Description: RELAY GEN PURPOSE SPST 10A 24V

JV1AS-24V Manufacturers: Panasonic

RFQ

In stock: 4280 pcs



Manufacturers: Panasonic

JV1AS-12V

Description: RELAY GEN PURPOSE SPST 10A 12V In stock: 6126 pcs

RFQ





In stock: 5429 pcs

JV1AS-9V

Manufacturers: Panasonic Description: RELAY GEN PURPOSE SPST 10A 9V

E-mail: Info@infinity-electronic.com

Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong









