

WL12-3N2441

Part Number:

Manufacturer/Brand:

Product description Datasheets:

Shipment Way

Ship From

Stock Condition

WL12-3N2441

N/A

NPN RED M12 NON POLAR

507 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

PART NUMBER  WL12-3N2441  MANUFACTURER  N/A  DESCRIPTION  NPN RED M12 NON POLAR  LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  507 pcs  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  WL12-3  SENSING METHOD  Retroreflective  SENSING DISTANCE  275.591" (7m)  RESPONSE TIME  330µS  OUTPUT CONFIGURATION  NPN  OTHER NAMES  1041446	
MANUFACTURER  DESCRIPTION  NPN RED M12 NON POLAR  LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  507 pcs  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  WL12-3  SENSING METHOD  Retroreflective  SENSING DISTANCE  275.591" (7m)  RESPONSE TIME  330µS  OUTPUT CONFIGURATION  NPN  OTHER NAMES  1041446	
DESCRIPTION NPN RED M12 NON POLAR  LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE 507 pcs  DATA SHEET  VOLTAGE - SUPPLY 10 V ~ 30 V  SERIES WL12-3  SENSING METHOD Retroeflective  SENSING DISTANCE 275.591" (7m)  RESPONSE TIME 330µs  OUTPUT CONFIGURATION NPN  OTHER NAMES 1041446	
QUANTITY AVAILABLE 507 pcs  DATA SHEET  VOLTAGE - SUPPLY 10 V ~ 30 V  SERIES WL12-3  SENSING METHOD Retroreflective  SENSING DISTANCE 275.591" (7m)  RESPONSE TIME 330µs  OUTPUT CONFIGURATION NPN  OTHER NAMES 1041446	
QUANTITY AVAILABLE  DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  WL12-3  SENSING METHOD  Retroreflective  SENSING DISTANCE  275.591" (7m)  RESPONSE TIME  330µS  OUTPUT CONFIGURATION  NPN  OTHER NAMES  1041446	
DATA SHEET  VOLTAGE - SUPPLY  10 V ~ 30 V  SERIES  WL12-3  SENSING METHOD  Retroreflective  SENSING DISTANCE  275.591" (7m)  RESPONSE TIME  330µs  OUTPUT CONFIGURATION  NPN  OTHER NAMES  1041446	
VOLTAGE - SUPPLY  SERIES  WL12-3  SENSING METHOD  Retroreflective  SENSING DISTANCE  275.591" (7m)  RESPONSE TIME  330µS  OUTPUT CONFIGURATION  NPN  OTHER NAMES  1041446	
SERIES WL12-3 SENSING METHOD Retroreflective SENSING DISTANCE 275.591" (7m) RESPONSE TIME 330µs OUTPUT CONFIGURATION NPN OTHER NAMES 1041446	
SENSING METHOD Retroreflective  SENSING DISTANCE 275.591" (7m)  RESPONSE TIME 330µs  OUTPUT CONFIGURATION NPN  OTHER NAMES 1041446	
SENSING DISTANCE275.591" (7m)RESPONSE TIME330μsOUTPUT CONFIGURATIONNPNOTHER NAMES1041446	
RESPONSE TIME 330µs  OUTPUT CONFIGURATION NPN  OTHER NAMES 1041446	
OUTPUT CONFIGURATION NPN OTHER NAMES 1041446	
OTHER NAMES 1041446	
OPERATING TEMPERATURE -40°C ~ 60°C (TA)	
LIGHT SOURCE Red (640nm)	
INGRESS PROTECTION IP66	
CONNECTION METHOD Connector, M12	
CABLE LENGTH -	
ADJUSTMENT TYPE Adjustable, 5-Turn Potentiometer	

**Related Tags** 

WL12-3N2441	Supplier	Distributor
WL12-3N2441 Stock	Buy WL12-3N2441	Buy WL12-3N2441
WL12-3N2441 PDF Datasheet	WL12-3N2441 Download Datasheet	WL12-3N2441 Datasheet
WL12-3N2441 Price	WL12-3N2441 Pictures	WL12-3N2441 Image
WL12-3N2441	WL12-3N2441 Distributor	WL12-3N2441 Supplier

**Related Products** 

