



Image may be representation. See specifications for product details.

SDA09H0SB

Part Number:

Manufacturer/Brand: Product description

Datasheets: RoHs Status

Stock Condition

Ship From Shipment Way SDA09H0SB

C&K

SWITCH SLIDE DIP SPST 25MA 24V

Lead free / RoHS Compliant

SDA09H0SB.pdf

43509 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

Specifications of SDA09H0SR

REQUEST FOR QUOTATION

PART NUMBER SDA09H0SB MANUFACTURER CRK DESCRIPTION SWITCH SLIDE DIP SPST 25MA 24V LEAD FREE STATUS / ROHS STATUS SERIES SDA PITCH D.100" (2.54mm), Full PACKAGING Tube OTHER NAMES OTHER NAMES OFFRATING TEMPERATURE AUP"C 85"C NUMBER OF POSITIONS MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MICHANICAL LIFE 1,000 Cycles LENGTH LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STAT	
MANUFACTURER DESCRIPTION SWITCH SLIDE DIP SPST 25MA 24V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 43509 pcs DATA SHEET SDA09HOSB.pdf WASHABLE Yes VOLTAGE RATING 24VDC TEMMINATION STYLE Gull Wing SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING TUBE CXN6094 OPERATING TEMPERATURE 40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE MOUNTING TYPE SURface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LEAD FREE STATUS / ROHS STATUS HEIGHT ABOVE BOARD PLATE I 1,000 Cycles LEAD FREE STATUS / ROHS STATUS HEIGHT ABOVE BOARD PLATE I 1,000 Cycles DETAILED DESCRIPTION DIP SWITCH SPT 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT FINISH Gold	
DESCRIPTION SWITCH SLIDE DIP SPST 25MA 24V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant QUANTITY AVAILABLE 43509 pcs DATA SHEET WASHABLE Yes VOLTAGE RATING Z4VDC TERMINATION STYLE Gull Wing SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES CKN6094 OPERATING TEMPERATURE NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS Compilant LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS Compilant DIPS SWINCH SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT FINISH CONTACT FINISH SWITCH SURVEY SAMON STATUS ASSOCIATED ACTUAL STATUS LEAD FREE STATUS / ROHS COMPILATED ACTUAL STATUS SURVEY CONTACT FINISH SOLO STATUS STATUS LEAD FREE STATUS SURVEY SOLO STATUS SURVEY ASSOCIATED ACTUAL STATUS LEAD FREE STATUS SURVEY SOLO STATUS SURVEY ASSOCIATED ACTUAL STATUS LEAD FREE STATUS SURVEY SOLO STATUS SURVEY ASSOCIATED ACTUAL STATUS LEAD FREE STATUS SURVEY ASSOCIATED ACTUAL STATUS LEAD FREE STATUS SURVEY LEAD FREE STATUS SURVEY LEAD FREE STATUS SURVEY LEAD FREE STATUS SURVEY LEAD FREE SOLO SURVEY ASSOCIATED ACTUAL SURVEY LEAD F	
LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 43509 pcs DATA SHEET WASHABLE Yes VOLTAGE RATING 24VDC TERMINATION STYLE Gull Wing SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING OTHER NAMES CKN6094 OPERATING TEMPERATURE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) I (Unlimited) MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS LEAd FREE STATUS / ROHS STATUS HEIGHT ABOVE BOARD FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT FINISH Beryllium Copper CONTACT FINISH Gold	
QUANTITY AVAILABLE DATA SHEET WASHABLE YES VOLTAGE RATING 24VDC TERMINATION STYLE Gull Wing SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING TUBE OTHER NAMES CKN6094 OPERATING TEMPERATURE **SDA09HOSB CKN6094 OPERATING TEMPERATURE *40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP SWItch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT MATERIAL Beryllium Copper	
DATA SHEET WASHABLE Yes VOLTAGE RATING 24VDC TERMINATION STYLE Gull Wing SDA PITCH 0.100" (2.54mm), Full PACKAGING TUBE OTHER NAMES CKN6094 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000 Cycles LENGTH LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT MATERIAL Beryllium Copper	
WASHABLE VOLTAGE RATING 24VDC TERMINATION STYLE Gull Wing SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES OTHER NAMES OPERATING TEMPERATURE AU°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT MATERIAL Beryllium Copper	
VOLTAGE RATING TERMINATION STYLE Gull Wing SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING TUB OTHER NAMES CYMO994 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH	
SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES "SDA09H0SB CKN6094 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles CURRENT RATING 25mA CONTACT MATERIAL BEYLINGTON Gold CONTACT MATERIAL GOld CONTACT MATERIAL GOld	
SERIES SDA PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES SDA09H0SB CKN6094 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION DIP Switch SPST 9 Position Surface Mount Silde (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper	
PITCH 0.100" (2.54mm), Full PACKAGING Tube OTHER NAMES SDA09H05B CKN6094 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH GOID ACTUAL STATUS BERYLLING SIDE OF STATUS OF SIDE OF	
Tube OTHER NAMES CKN6094 OPERATING TEMPERATURE A0°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
CTHER NAMES *SDA09H0SB CKN6094 OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
OPERATING TEMPERATURE -40°C ~ 85°C NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles ELECTRICAL LIFE 1,000 Cycles CURRENT RATING 25mA CONTACT MATERIAL Gold	
NUMBER OF POSITIONS 9 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH	
MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
MECHANICAL LIFE 1,000 Cycles LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
LENGTH 0.978" (24.84mm) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
Lead free / RoHS Compliant HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
HEIGHT ABOVE BOARD 0.175" (4.45mm) FEATURES Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
Tape Seal ELECTRICAL LIFE 1,000 Cycles DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
ELECTRICAL LIFE1,000 CyclesDETAILED DESCRIPTIONDip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDCCURRENT RATING25mACONTACT MATERIALBeryllium CopperCONTACT FINISHGold	
DETAILED DESCRIPTION Dip Switch SPST 9 Position Surface Mount Slide (Standard) Actuator 25mA 24VDC CURRENT RATING CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
CURRENT RATING 25mA CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
CONTACT MATERIAL Beryllium Copper CONTACT FINISH Gold	
CONTACT FINISH Gold	
CIRCUIT	
3131	
BODY MATERIAL Polyphenylene Sulfide (PPS)	
ACTUATOR TYPE Slide (Standard)	

Related Tags

Flush, Recessed

C&K SDA09H0SB	SDA09H0SB Distributor	SDA09H0SB Supplier
SDA09H0SB Price	SDA09H0SB Pictures	SDA09H0SB Image
SDA09H0SB PDF Datasheet	SDA09H0SB Download Datasheet	SDA09H0SB Datasheet
SDA09H0SB Stock	Buy SDA09H0SB	Buy C&K SDA09H0SB
C&K SDA09H0SB	C&K Supplier	C&K Distributor
C&K SDA09H0SB	C&K Components SDA09H0SB	

Related Products



ACTUATOR LEVEL

SDA09H0BD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 53119 pcs

RFQ



SDA09H1KD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 6503 pcs

RFQ




SDA09H0SK

Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 5600 pcs

RFQ



SDA09H0SBR

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 51997 pcs

Manufacturers: C&K

RFQ



SDA09H0K Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 7060 pcs

RFQ



SDA09H0B Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 45258 pcs

RFQ



SDA09H0KD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 5666 pcs

RFQ



SDA09H1BD Manufacturers: C&K

In stock: 63095 pcs **RFQ**

Description: SWITCH SLIDE DIP SPST 25MA 24V



SDA08H1SKD Manufacturers: C&K

In stock: 5119 pcs

Description: SWITCH SLIDE DIP SPST 25MA 24V

RFQ



Manufacturers: C&K

SDA09H0SKD

Description: SWITCH SLIDE DIP SPST 25MA 24V

In stock: 5603 pcs **RFQ**



SDA08H1SBD Manufacturers: C&K

Description: SWITCH SLIDE DIP SPST 25MA 24V In stock: 51705 pcs

RFQ



Manufacturers: C&K

SDA09H0SBD



















