Grayhill





Grayhill, Inc.



44M45-05-1-03S

Part Number:

Product description

Manufacturer/Brand:

RoHs Status Stock Condition

Ship From Shipment Way

Datasheets:

44M45-05-1-03S

Grayhill, Inc.

SWITCH ROTARY 85 DEG;C, 45 DEG 5

K RoHS Compliant 943 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER 41M45-05-1-03S MANUFACTURER Grayhil, Inc. DESCRIPTION SWITCH ROTARY 85 DEG;C, 45 DEG 5 LEAD FREE STATUS / ROHS STATUS RoHS Compliant QUANTITY AVAILABLE 913 pcs DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 11SV TERMINATION STYLE SOIDER SERIES 44 ROHS Compliant PANEL QUTOUT DIMENSIONS - ROHS COMPLIANT PANEL QUTOUT DIMENSIONS - STATUS NUMBER OF POSITIONS 3 NUMBER OF POSITIONS 3 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS FEATURES - PEATURES - PEATURES - CONTACT MATERIAL GOLD SHOW MEBB CONTACT MATERIAL SINEY AND SON'S STATUS SON'S SHOW MEBB CONTACT MATERIAL SINEY AND ACQUARTED FOR DECK SPAT ANGLE OF THROW 45° ACTUATOR LENGTH 11.10mm		Specifications of 44M45-05-1-03S
MANUFACTURER Grayhill, Inc. DESCRIPTION SWITCH ROTARY 85 DEG;C, 45 DEG 5 LEAD FREE STATUS / ROHS STATUS RoHS Compliant QUANTITY AVAILABLE 943 pcs DATA SHEET WOLTAGE RATING - DC VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTAGY SWIRCH 3 Position SP3T SA (AC), IA (DC) 115VAC Panel Mount DETHIED BEHIND PANEL 61.19mm CURRENT RATING SA (AC), IA (DC) CONTACT TIMING Shorting (MBB) CONTACT TIMING Sh		
DESCRIPTION SWITCH ROTARY 85 DEG;C, 45 DEG 5 LEAD FREE STATUS / ROHS STATUS ROHS Compliant QUANTITY AVAILABLE 943 pxs DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS Compliant PANEL CUITOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF POSITIONS 3 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DETAILED DESCRIPTION Shorting (MBB) CONTACT TIMING Shorting (MBB) CONTACT TIMING	PART NUMBER	44M45-05-1-03S
ROHS Compliant QUANTITY AVAILABLE 943 pcs DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS COMPLIANT PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POLES PER DECK 1 NUMBER OF DOLES PER DECK 5 MOUNTING TYPE PANEL MOUNT PEATURES - DETAILED DESCRIPTION ROTAGE 61.19mm CURRENT RATING 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 61.19mm CURRENT RATING SA (AC), 1A (DC) CONTACT TIMING SHORT HOW CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 45° ACTUATOR TYPE Flatted (6.35mm Dia)	MANUFACTURER	Grayhill, Inc.
QUANTITY AVAILABLE 943 pcs DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS COMPILIAN PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed DETAILED DESCRIPTION ROTAGES - DETAILED DESCRIP	DESCRIPTION	SWITCH ROTARY 85 DEG;C, 45 DEG 5
DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS COMPliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS MOUNTING TYPE PANEL MOUNTING TYPE PANEL MOUNTING TYPE PAREL DESCRIPTION ROTATY SWITCH 3 POSITION SP3T 5A (AC), 1A (DC) 115VAC PANEL MOUNT CURRENT RATING CONTACT TIMING SONTACT TIMING CONTACT TIMING CONTACT TIMISH - CIRCUIT PER DECK ANGLE OF THROW 45° FLATUATOR TYPE Flatted (6.35mm Dia)	LEAD FREE STATUS / ROHS STATUS	RoHS Compliant
VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS ROHS COmpliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), IA (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 61.19mm CURRENT RATING 5A (AC), IA (DC) CONTACT TIMING Shorting (MBB) CONTACT TAINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° ACTUATOR TYPE Flatted (6.35mm Dia)	QUANTITY AVAILABLE	943 pcs
VOLTAGE RATING - AC 115V TERMINATION STYLE Solder Lug SERIES 44 ROHS STATUS RoHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DETH BEHIND PANEL 61.19mm CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° ACTUATOR TYPE Flatted (6.35mm Dia)	DATA SHEET	
FERMINATION STYLE SERIES 44 ROHS STATUS ROHS COMPIIANT PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF POLES PER DECK MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTATION ROTATION SOLITIONS OSTATION OF POLES PER MOUNT CURRENT RATING CONTACT TIMING Shorting (MBB) CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK ANGLE OF THROW 45° Fatted (6.35mm Dia)	VOLTAGE RATING - DC	28V
ROHS STATUS ROHS COMPILIANT ROHS STATUS ROHS COMPILIANT ROHS STATUS ROHS COMPILIANT ROHS COTTON RUMBER OF POSITIONS STATUS RUMBER OF POSITIONS STATUS RUMBER OF POLES PER DECK STATUS RUMBER OF DECKS STATUS ROUNTING TYPE ROUNTING SHORT ROUNTING SHORT ROUNTING SHORT ROUNTING ROTAGY SWITCH 3 POSITION SP3T 5A (AC), 1A (DC) 115VAC Panel Mount ROUNTENT RATING CONTACT TIMING CONTACT TIMING SHORTING CONTACT TIMING SHORTING CONTACT TIMING SHORTING CONTACT FINISH CIRCUIT PER DECK SP3T ANGLE OF THROW 45° ROUNTING HIELD (6.35mm Dia)	VOLTAGE RATING - AC	115V
ROHS STATUS ROHS Compliant PANEL CUTOUT DIMENSIONS - OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 61.19mm CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING CONTACT TIMING CONTACT FINISH CURCUIT PER DECK SP3T ANGLE OF THROW 45° Flatted (6.35mm Dia)	TERMINATION STYLE	Solder Lug
PANEL CUTOUT DIMENSIONS OPERATING FORCE 5.761 ~ 83gfm NUMBER OF POSITIONS 3 NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount CURRENT RATING CURRENT RATING SA (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° Flatted (6.35mm Dia)	SERIES	44
OPERATING FORCE NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES DETAILED DESCRIPTION ROTATY Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount CURRENT RATING CONTACT TIMING Shorting (MBB) CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	ROHS STATUS	RoHS Compliant
NUMBER OF POSITIONS 3 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 61.19mm CURRENT RATING CONTACT TIMING Shorting (MBB) CONTACT TIMISH - CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	PANEL CUTOUT DIMENSIONS	
NUMBER OF POLES PER DECK NUMBER OF DECKS 5 MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 61.19mm CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	OPERATING FORCE	5.761 ~ 83gfm
NUMBER OF DECKS MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 61.19mm CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° Flatted (6.35mm Dia)	NUMBER OF POSITIONS	3
MOUNTING TYPE Panel Mount INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 61.19mm CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT TIMING Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° Flatted (6.35mm Dia)	NUMBER OF POLES PER DECK	1
INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL 61.19mm CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° Flatted (6.35mm Dia)	NUMBER OF DECKS	5
FEATURES DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING CONTACT TIMING CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Flatted (6.35mm Dia)	MOUNTING TYPE	Panel Mount
DETAILED DESCRIPTION Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount 61.19mm CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° ACTUATOR TYPE Flatted (6.35mm Dia)	INDEX STOPS	Fixed
DEPTH BEHIND PANEL CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° ACTUATOR TYPE 61.19mm 61.1	FEATURES	-
CURRENT RATING 5A (AC), 1A (DC) CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° ACTUATOR TYPE Flatted (6.35mm Dia)	DETAILED DESCRIPTION	Rotary Switch 3 Position SP3T 5A (AC), 1A (DC) 115VAC Panel Mount
CONTACT TIMING Shorting (MBB) CONTACT MATERIAL Silver Alloy CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° ACTUATOR TYPE Flatted (6.35mm Dia)	DEPTH BEHIND PANEL	61.19mm
CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE Silver Alloy SP3T 45° Flatted (6.35mm Dia)	CURRENT RATING	5A (AC), 1A (DC)
CONTACT FINISH - CIRCUIT PER DECK SP3T ANGLE OF THROW 45° ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT TIMING	Shorting (MBB)
CIRCUIT PER DECK ANGLE OF THROW ACTUATOR TYPE SP3T 45° Flatted (6.35mm Dia)	CONTACT MATERIAL	Silver Alloy
ANGLE OF THROW 45° ACTUATOR TYPE Flatted (6.35mm Dia)	CONTACT FINISH	-
ACTUATOR TYPE Flatted (6.35mm Dia)	CIRCUIT PER DECK	SP3T
	ANGLE OF THROW	45°
ACTUATOR LENGTH 11.10mm	ACTUATOR TYPE	Flatted (6.35mm Dia)
	ACTUATOR LENGTH	11.10mm

Related Tags

Grayhill, Inc. 44M45-05-1-03S	44M45-05-1-03S Distributor	44M45-05-1-03S Supplier
44M45-05-1-03S Price	44M45-05-1-03S Pictures	44M45-05-1-03S Image
44M45-05-1-03S PDF Datasheet	44M45-05-1-03S Download Datasheet	44M45-05-1-03S Datasheet
44M45-05-1-03S Stock	Buy 44M45-05-1-03S	Buy Grayhill, Inc. 44M45-05-1-03S
Grayhill, Inc. 44M45-05-1-03S	Grayhill, Inc. Supplier	Grayhill, Inc. Distributor
Grayhill, Inc. 44M45-05-1-03S	Grayhill Inc. 44M45-05-1-03S	

Related Products



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 45 DEG 5 DECK,

In stock: 899 pcs

RFQ

44M45-05-1-03N

Grayhill

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 5

In stock: 1047 pcs

RFQ

44M45-05-1-04S



44M45-04B08S

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 4

In stock: 1018 pcs

RFQ



44M45-05-1-05S Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 5

In stock: 937 pcs **RFQ**



44M45-04-4-02N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 4 In stock: 766 pcs

RFQ



44M45-04-3-02N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 4 In stock: 840 pcs

RFQ



44M45-05-1-06N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 5 In stock: 984 pcs

RFQ



44M45-05-1-05N Manufacturers: Grayhill, Inc.

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 5 In stock: 1005 pcs

RFQ



Manufacturers: Grayhill, Inc.

44M45-05-1-02N

Description: SWITCH ROTARY 85 DEG;C, 45 DEG 5 In stock: 959 pcs

RFQ



Grayhill

Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 5

44M45-05-1-06S

In stock: 1019 pcs

RFQ





Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 5

44M45-05-1-04N

In stock: 862 pcs

RFQ



Manufacturers: Grayhill, Inc. Description: SWITCH ROTARY 85 DEG;C, 45 DEG 4

In stock: 828 pcs **RFQ**



Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong











