C&K



C&K

7108P3D9AQE

Part Number: Manufacturer/Brand:

Product description Datasheets: RoHs Status Stock Condition Ship From Shipment Way

7108P3D9AQE

C&K

SWITCH TOGGLE SPDT 5A 120V

7108P3D9AQE.pdf

Lead free / RoHS Compliant 13437 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

PART NUMBER         7108P3D9AQE           MANUFACTURER         C8K           DESCRIPTION         SWITCH TOGGLE SPOT \$A 120V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Comptiant           QUANTITY AVAILABLE         1347 pcs           DATA SHEET         28V           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           SERIES         700 Pon           SWITCH FUNCTION         0n-Mom           SERIES         700 Pon           PANCE CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOUNTING TYPE         1 Uniminated           IEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           LILUMINATION VOLTAGE (NOMINAL)         -           LILUMINATION VOLTAGE (NOMINAL)         -           LELUMINATION TYPE, COLOR         -           ELECTRICAL LIFE         40,000 Cycles           DETAILED DESCRIPTION         700 Cycles           DETAILED DESCRIPTION         700 Cycles           DETAILED DESCRIPTION         700 Cycles           DETAILED DESCRIPTION         700 Cycle		Specifications of 7108P3D9AQE
MANUFACTURER         C&K           DESCRIPTION         SWITCH TOGGLE SPDT SA 120V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         19437 pcs           DATA SHEET         500 710893D9AQE-pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         28V           SWITCH FUNCTION         0Pr. Po           SWITCH FUNCTION         0Pr. Mon           SERIES         7000           PACKAGING         BUIK           OPERATING TEMPERATURE         30°C ~ 85°C           MOUNTING TYPE         1 (Unlimited)           MOUNTING TYPE         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LILUMINATION VOLTAGE (NOMINAL)         -           LILUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         -           LILUMINATION TYPE, COLOR         -           LILUMINATION         Non-Illuminated           ELECTRICAL LIFE         50,000 Cycles           DETAILED DESCRIPTION         50,000 Cycles           CIRCRETT RATING         50,400 Cycles           CIRCRETT RATING         50,400 Cycles           CIRCRUT         5PDT		
DESCRIPTION         SWITCH TOGGLE SPDT SA 120V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         13437 pcs           DATA SHEET         2100 PROBE STATUS           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERRINATION STYLE         PC Pin           SWITCH FUNCTION         On-Mom           SERIES         7000           PACKAGING         Bulk           OPERATING TEMPERATURE         30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ILLUMINATION YOLTAGE (NOMINAL)         -           ILLUMINATION YOLTAGE (NOMINAL)         -           ILLUMINATION YPE, COLOR         PONO-Illuminated           ILLUMINATION YPE, COLOR         PONO-Illuminated           DECENTICAL LIFE         QUOO Cycles           DECENTICAL LIFE         QUOO Cycles           DECENTICAL LIFE         O (200 Cycles           DECENTICAL TYPE         SA (AC/PC)           CIRCUIT         SPOT           BUSHING THREAD         Unithreaded	PART NUMBER	7108P3D9AQE
LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         13437 pcs           DATA SHEET         17108P3D9AQE pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERNINATION STYLE         PC-PIN           SWITCH FUNCTION         On-Mom           SERIES         7000           PANEL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ILLUMINATION YDE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION STATUS         40,000 Cycles           DECENTIZED SECRIFITION         Toggle Switch SPOT Through Hole, Right Angle           CURRENT RATING         54 (AC/PC)           CURRENT RATING         54 (AC/PC)           CURRENT RATING         54 (AC/PC)           <	MANUFACTURER	C&K
QUANTITY AVAILABLE         13437 pcs           DATA SHEET         2708P3D9AQE.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC Pin           SWITCH FUNCTION         0m-Mom           SERIES         7000           PANEL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTING ESENSITUSTY LEVEL (MSL)         Lead free / RoHS Compliant           LEAD FREE STATUS / RONS TATUS         Lead free / RoHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         -           IELECTRICAL LIFE         40,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         SQ (AC/DC)           CIRCUIT         SPDT           BUSHING THREAD         Linthreaded           ACIUATOR TYPE         Flet Anti-Rotation           ACIVATOR MATERIAL         Flet Anti-Rotation	DESCRIPTION	SWITCH TOGGLE SPDT 5A 120V
DATA SHEET         € 7108P309AQE.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC Pin           SWITCH FUNCTION         On-Mom           SERIES         7000           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION         Non-Illuminated           FEATURES         Epoxy Sealed Terminals           ELECTRICAL LIFE         40,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         5A (AC/DC)           CURRENT RATING         5N (AC/DC)           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         A Rati-Rotation           ACTUATOR TYPE         A Rati-Rotation	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC PIN           SWITCH FUNCTION         On-Mom           SERIES         7000           PARL CUTOUT DIMENSIONS         -           PECKAGING         Bulk           OPERATING TEMPERATURE         30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         -           FEATURES         Epoxy Sealed Terminals           ELECTRICAL LIFE         40,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         5A (AC/DC)           CIRCUIT         SPDT           BUSHING THREAD         Unthreaded           ACTUATOR NATERIAL         Flet Anti-Rotation           ACTUATOR MATERIAL         Frass, Chrome Plated	QUANTITY AVAILABLE	13437 pcs
VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC Pin           SWITCH FUNCTION         On-Mom           SERIES         7000           PANEL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         FEATURES           ELECTRICAL LIFE         40,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         5A (AC/DC)           CURRENT RATING         5A (AC/DC)           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         Flat Anti-Rotation           ACTUATOR MATERIAL         Brass, Chrome Plated	DATA SHEET	7108P3D9AQE.pdf
ETEMINATION STYLE         PC Pin           SWITCH FUNCTION         On-Mom           SERIES         7000           PANEL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           POERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FEE STATUS / ROHS STATUS         Lead free / ROHS Compliant           LILUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         FOR-Illuminated           ELECTRICAL LIFE         40,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         5A (AC/OC)           CURRENT RATING         5A (AC/OC)           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         Flat Anti-Rotation           ACTUATOR MATERIAL         Flat Anti-Rotation	VOLTAGE RATING - DC	28V
SWITCH FUNCTION         On-Mom           SERIES         7000           PANEL CUTOUT DIMENSIONS         -           PACKAGIING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole, Right Angle           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         -           FEATURES         Epoxy Sealed Terminals           ELECTRICAL LIFE         40,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole, Right Angle           CURRENT RATING         SA (AC/DC)           CURCUIT         SD (CYCLE)           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         Flet Anti-Rotation           ACTUATOR MATERIAL         Brass, Chrome Plated	VOLTAGE RATING - AC	120V
PANEL CUTOUT DIMENSIONS PACKAGING PACKAGING BUIL  OPERATING TEMPERATURE 30°C ~ 85°C  MOUNTING TYPE MIDISTURES ENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEUMINATION VOLTAGE (NOMINAL) LILUMINATION YOLTAGE (NOMINAL) LILUMINATION LILUMINATION MON-Illuminated EECTRICAL LIFE DESAUGE DETAILED DESCRIPTION TORGIES SWICK SPOT Through Hole, Right Angle  LURRENT RATING SA (AC/DC)  SULUMINATION SHIPLED HOLE, RIGHT Angle  LURRENT RATING LURRENT RATING SA (AC/DC)  SULUMINATION SPOT BUSHING THREAD ACTUATOR MATERIAL Brass, Chrome Plated	TERMINATION STYLE	PC Pin
PACKAGING Bulk  OPERATING TEMPERATURE -30°C ~ 85°C  MOUNTING TYPE Through Hole, Right Angle  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  ILIUMINATION VOLTAGE (NOMINAL) -  ILLUMINATION TYPE, COLOR -  ILLUMINATION MON-Illuminated  FEATURES EDAYS Sealed Terminals  ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION TOGGLE SA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE  ACTUATOR TYPE  BLA ANTI-ROATION PLACE  BLA ANTI-ROATION SPDT  FLAT ANTI-ROATION SPORS, Chrone Plated  BLA ANTI-ROATION SPORS, Chrone Plated	SWITCH FUNCTION	On-Mom
PACKAGING Bulk  OPERATING TEMPERATURE -30°C ~ 85°C  MOUNTING TYPE Through Hole, Right Angle  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  ILLUMINATION VOLTAGE (NOMINAL) -  ILLUMINATION TYPE, COLOR -  ILLUMINATION TYPE, COLOR Non-Illuminated  FEATURES PROTECTION Sond Epoxy Sealed Terminals  ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION TOGGLE SWItch SPDT Through Hole, Right Angle  CURRENT RATING SA (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Brass, Chrome Plated  Brass, Chrome Plated	SERIES	7000
OPERATING TEMPERATURE  MOUNTING TYPE  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEUMINATION VOLTAGE (NOMINAL)  LLUMINATION YOLTAGE (NOMINAL)  LLUMINATION TYPE, COLOR  LLUMINATION  MON-Illuminated  FEATURES  Epoxy Sealed Terminals  ELECTRICAL LIFE  AU,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING  CURRENT RATING  BUSHING THREAD  MOTHERADE  ACTUATOR TYPE  FLA Anti-Rotation  FLA Anti-Rotation  Brass, Chrome Plated	PANEL CUTOUT DIMENSIONS	-
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LILUMINATION VOLTAGE (NOMINAL) LILUMINATION TYPE, COLOR LILUMINATION TYPE, COLOR LILUMINATION SPORY Sealed Terminals ELECTRICAL LIFE DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle CURRENT RATING SPORT SPORT BUSHING THREAD Unthreaded ACTUATOR TYPE ACTUATOR MATERIAL BRASS, Chrome Plated	PACKAGING	Bulk
MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAd free / ROHS Compliant  INGRESS PROTECTION  - ILLUMINATION VOLTAGE (NOMINAL)  LLUMINATION TYPE, COLOR  LLUMINATION  Non-Illuminated  FEATURES  Epoxy Sealed Terminals  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING  CURRENT RATING  SPDT  BUSHING THREAD  ACTUATOR TYPE  Flat Anti-Rotation  Brass, Chrome Plated	OPERATING TEMPERATURE	-30°C ~ 85°C
LEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-ILLUMINATIONNon-IlluminatedFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Through Hole, Right AngleCURRENT RATING5A (AC/DC)CIRCUITSPDTBUSHING THREADUnthreadedACTUATOR TYPEFlat Anti-RotationACTUATOR MATERIALBrass, Chrome Plated	MOUNTING TYPE	Through Hole, Right Angle
INGRESS PROTECTION - CLUMINATION VOLTAGE (NOMINAL) - CLUMINATION TYPE, COLOR - CLUMINATION TYPE, COLOR - CLUMINATION TYPE, COLOR - CLUMINATION Non-Illuminated - CLUMINATION - CLUMINATI	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  EATURES  Epoxy Sealed Terminals  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING  5A (AC/DC)  CIRCUIT  BUSHING THREAD  ACTUATOR TYPE  Flat Anti-Rotation  Brass, Chrome Plated	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  FEATURES  Epoxy Sealed Terminals  ELECTRICAL LIFE  40,000 Cycles  DETAILED DESCRIPTION  Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING  5A (AC/DC)  CIRCUIT  BUSHING THREAD  ACTUATOR TYPE  ACTUATOR MATERIAL  Brass, Chrome Plated	INGRESS PROTECTION	-
ILLUMINATIONNon-IlluminatedFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE40,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Through Hole, Right AngleCURRENT RATING5A (AC/DC)CIRCUITSPDTBUSHING THREADUnthreadedACTUATOR TYPEFlat Anti-RotationACTUATOR MATERIALBrass, Chrome Plated	ILLUMINATION VOLTAGE (NOMINAL)	-
ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION 70ggle Switch SPDT Through Hole, Right Angle  CURRENT RATING 5A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Flat Anti-Rotation  Brass, Chrome Plated	ILLUMINATION TYPE, COLOR	-
ELECTRICAL LIFE 40,000 Cycles  DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING 5A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Flat Anti-Rotation  Brass, Chrome Plated	ILLUMINATION	Non-Illuminated
DETAILED DESCRIPTION Toggle Switch SPDT Through Hole, Right Angle  CURRENT RATING 5A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Flat Anti-Rotation  ACTUATOR MATERIAL Brass, Chrome Plated	FEATURES	Epoxy Sealed Terminals
CURRENT RATING 5A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Flat Anti-Rotation  ACTUATOR MATERIAL Brass, Chrome Plated	ELECTRICAL LIFE	40,000 Cycles
CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Flat Anti-Rotation  ACTUATOR MATERIAL Brass, Chrome Plated	DETAILED DESCRIPTION	Toggle Switch SPDT Through Hole, Right Angle
BUSHING THREAD  ACTUATOR TYPE  ACTUATOR MATERIAL  Brass, Chrome Plated	CURRENT RATING	5A (AC/DC)
ACTUATOR TYPE Flat Anti-Rotation  ACTUATOR MATERIAL Brass, Chrome Plated	CIRCUIT	SPDT
ACTUATOR MATERIAL Brass, Chrome Plated	BUSHING THREAD	Unthreaded
	ACTUATOR TYPE	Flat Anti-Rotation
ACTUATOR LENGTH 13.21mm	ACTUATOR MATERIAL	Brass, Chrome Plated
	ACTUATOR LENGTH	13.21mm

# **Related Tags**

C&K 7108P3D9AQE	7108P3D9AQE Distributor	7108P3D9AQE Supplier
7108P3D9AQE Price	7108P3D9AQE Pictures	7108P3D9AQE Image
7108P3D9AQE PDF Datasheet	7108P3D9AQE Download Datasheet	7108P3D9AQE Datasheet
7108P3D9AQE Stock	Buy 7108P3D9AQE	Buy C&K 7108P3D9AQE
C&K 7108P3D9AQE	C&K Supplier	C&K Distributor
C&K 7108P3D9AQE	C&K Components 7108P3D9AQE	

## **Related Products**



#### **7108P3D9V4BES** Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: 11177 pcs

**RFQ** 



## **7108P3CWZQE2**

Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: 8020 pcs

**RFQ** 



## **7108P3CWZGE22**

Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: 7884 pcs

**RFQ** 

## 7108P3D9V4GE2

Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: 8580 pcs

**RFQ** 



## 7108P3D9A4QE2

Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: 9455 pcs

**RFQ** 

## 7108P3D9A2BE

Manufacturers: C&K Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: 12622 pcs

**RFQ** 



#### **7108P3CWZQE** Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: 12441 pcs

**RFQ** 



## 7108P3D9CBE

Manufacturers: C&K Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: 16904 pcs

**RFQ** 



#### 7108P3D9ABE Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: 12269 pcs

**RFQ** 

## Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 0.4VA 20V

7108P3D9V4BE2

In stock: 7121 pcs

**RFQ** 



#### 7108P3D9V4BE22 Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: 7333 pcs

**RFQ** 



## 7108P3D9V41ME22

Manufacturers: C&K

Description: SWITCH TOGGLE SPDT 5A 120V In stock: 14663 pcs **RFQ** 



Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong











