



Image may be representation. See specifications for product details.

TANGO41/1M/SMAM/S/S/32

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way TANGO41/1M/SMAM/S/S/32

Siretta

RF ANT 829MHZ/1.94GHZ WHIP STR

TANGO41/1M/SMAM/S/S/32.pdf Lead free / RoHS Compliant

1707 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER TANGO41/1M/SMAM/S/S/32 MANUFACTURER Siretta DESCRIPTION RF ANT 829MHZ/1.94GHZ WHIIP STR LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 1707 pcs DATA SHEET TANSO41/1M/SMAM/S/S/32.pdf VSWR 3 Connector, SMA Male SERIES TANGO 41 RETURN LOSS PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN FREQUENCY GROUP Wide Band FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz R 7 960MHz, 1.71GHz ~ 2.17GHz ~ 2.7GHz APPLICATIONS WLAN ANTENNA TYPE Whip, Straight WIAN ANTENNA TYPE Whip, Straight Winp, Straight		Specifications of TANGO41/1M/SMAM/S/S/32
MANUFACTURER DESCRIPTION RF ANT \$29MHZ/I.94CHZ WHIP 5TR LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DATA SHEET DATA SHEET DATA SHEET VSWR 3 TERMINATION Connector, SMA Male SERIES TANGO 41 RETURN LOSS PACKAGING BUIK NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) NOT Applicable LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE SPROTECTION HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP WIDE Band FREQUENCY GROUP WIDE Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FRATURES DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 0.00MHz, 1.71GHz ~ 0		
DESCRIPTION RF ANT 829MHz/1.94GHZ WHIP STR LEAD FREE STATUS / ROHS STATUS DATA SHEET TANGO41/1M/SMAM/S/S/32.pdf VSWR 3 TERMINATION Connector, SMA Male SERIES TANGO 41 RETURN LOSS PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Not Applicable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY GROUP Wide Band - FREQUENCY (CENTER/BAND) B29MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz NA Male Panel Mount APPLICATIONS WLAN	PART NUMBER	TANGO41/1M/SMAM/S/S/32
Lead free / RoHS Compliant QUANTITY AVAILABLE 1707 pcs DATA SHEET TANGO41/1M/SMAM/S/S/32.pdf VSWR 3 TERMINATION Connector, SMA Male SERIES TANGO 41 RETURN LOSS - PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Not Applicable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz (Connector, SMA Male Panel Mount APPLICATIONS WLAN	MANUFACTURER	Siretta
DATA SHEET DATA SHEET DATA SHEET VSWR 3 TERMINATION Connector, SMA Male SERIES TANGO 41 RETURN LOSS - PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Not Applicable LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067** (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz APPLICATIONS WLAN	DESCRIPTION	RF ANT 829MHZ/1.94GHZ WHIP STR
DATA SHEET WARN TERMINATION Connector, SMA Male TERMINATION Connector, SMA Male SERIES TANGO 41 RETURN LOSS - PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Not Applicable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz DETAILED DESCRIPTION WLAN	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TERMINATION Connector, SMA Male SERIES TANGO 41 RETURN LOSS PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Not Applicable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION HEIGHT (MAX) 3.067" (77.90mm) GAIN FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz RANTEN APPLICATIONS WLAN	QUANTITY AVAILABLE	1707 pcs
TERMINATION Connector, SMA Male SERIES TANGO 41 RETURN LOSS - PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz RATENNA FRANCENOR SAME PANEL MOUNT APPLICATIONS WLAN	DATA SHEET	TANGO41/1M/SMAM/S/S/32.pdf
TANGO 41 RETURN LOSS - PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Not Applicable LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES - DETAILED DESCRIPTION 821MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz WAN	VSWR	3
PACKAGING Bulk NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Not Applicable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ C.7GHz APPLICATIONS WLAN	TERMINATION	Connector, SMA Male
PACKAGING NUMBER OF BANDS 3 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE / ROHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz DETAILED DESCRIPTION APPLICATIONS WLAN	SERIES	TANGO 41
NUMBER OF BANDS3MOUNTING TYPEPanel MountMOISTURE SENSITIVITY LEVEL (MSL)Not ApplicableLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-HEIGHT (MAX)3.067" (77.90mm)GAIN-FREQUENCY RANGE698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHzFREQUENCY GROUPWide BandFREQUENCY (CENTER/BAND)829MHz, 1.94GHz, 2.5GHzFEATURES-DETAILED DESCRIPTION829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel MountAPPLICATIONSWLAN	RETURN LOSS	-
MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Not Applicable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz APPLICATIONS WLAN	PACKAGING	Bulk
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz WHAN APPLICATIONS WLAN	NUMBER OF BANDS	3
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINGRESS PROTECTION-HEIGHT (MAX)3.067" (77.90mm)GAIN-FREQUENCY RANGE698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHzFREQUENCY GROUPWide BandFREQUENCY (CENTER/BAND)829MHz, 1.94GHz, 2.5GHzFEATURES-DETAILED DESCRIPTION829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel MountAPPLICATIONSWLAN	MOUNTING TYPE	Panel Mount
INGRESS PROTECTION - HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES - DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount MUAN	MOISTURE SENSITIVITY LEVEL (MSL)	Not Applicable
HEIGHT (MAX) 3.067" (77.90mm) GAIN - FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES - DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount WLAN	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
FREQUENCY RANGE 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES - DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount WLAN	INGRESS PROTECTION	-
FREQUENCY GROUP Wide Band FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES - 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount APPLICATIONS WLAN	HEIGHT (MAX)	3.067" (77.90mm)
FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES - 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount APPLICATIONS WLAN	GAIN	-
FREQUENCY (CENTER/BAND) 829MHz, 1.94GHz, 2.5GHz FEATURES - 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount APPLICATIONS WLAN	FREQUENCY RANGE	698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz
FEATURES - 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount APPLICATIONS WLAN	FREQUENCY GROUP	Wide Band
DETAILED DESCRIPTION 829MHz, 1.94GHz, 2.5GHz WLAN Whip, Straight RF Antenna 698MHz ~ 960MHz, 1.71GHz ~ 2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount WLAN	FREQUENCY (CENTER/BAND)	829MHz, 1.94GHz, 2.5GHz
2.17GHz, 2.3GHz ~ 2.7GHz Connector, SMA Male Panel Mount APPLICATIONS WLAN	FEATURES	-
	DETAILED DESCRIPTION	
ANTENNA TYPE Whip, Straight	APPLICATIONS	WLAN
	ANTENNA TYPE	Whip, Straight

Related Tags

Siretta TANGO41/1M/SMAM/S/S/32	TANGO41/1M/SMAM/S/S/32 Distributor	TANGO41/1M/SMAM/S/S/32 Supplier
TANGO41/1M/SMAM/S/S/32 Price	TANGO41/1M/SMAM/S/S/32 Pictures	TANGO41/1M/SMAM/S/S/32 Image
TANGO41/1M/SMAM/S/S/32 PDF Datasheet	TANGO41/1M/SMAM/S/S/32 Download Datasheet	TANGO41/1M/SMAM/S/S/32 Datasheet
TANGO41/1M/SMAM/S/S/32 Stock	Buy TANGO41/1M/SMAM/S/S/32	Buy Siretta TANGO41/1M/SMAM/S/S/32
Siretta TANGO41/1M/SMAM/S/S/32	Siretta Supplier	Siretta Distributor
Siretta TANGO41/1M/SMAM/S/S/32	Siretta Ltd TANGO41/1M/SMAM/S/S/32	

Related Products



TANGO41/5M/SMAM/S/S/33

Manufacturers: Siretta

Description: RF ANT 829MHZ/1.94GHZ WHIP STR In stock: 1848 pcs

RFQ



TANGO43/0.5M/SMAM/SMAM/RP/S/S/17

Manufacturers: Siretta

Description: RF ANT DOME RP-SMA MALE PAN MT In stock: 2370 pcs

RFQ



TANGO3/1M/SMAM/S/S/31

Manufacturers: Siretta

Description: RF ANT 900MHZ/1.8GHZ WHIP STR In stock: 3645 pcs

RFQ



TANGO41/2.5M/SMAM/S/S/32

Manufacturers: Siretta

Description: RF ANT 829MHZ/1.94GHZ WHIP STR In stock: 1702 pcs

RFQ



TANGO44/2.5M/LL/SMAM/S/S/19

Manufacturers: Siretta

Description: RF ANT DOME SMA MALE PAN MT In stock: 2962 pcs

RFQ

TANGO30/0.1M/IPEX/S/S/35

Manufacturers: Siretta Description: 2.4GHZ 10.5MM HEIGHT X 19MM DIA

In stock: 8063 pcs

RFQ



TANGO44/1M/LL/SMAM/S/S/19 Manufacturers: Siretta

Description: RF ANT DOME SMA MALE PAN MT

In stock: 3041 pcs

RFQ



TANGO3/3M/FMEF/S/S/31

Manufacturers: Siretta Description: RF ANT 900MHZ/1.8GHZ WHIP STR

In stock: 5375 pcs

RFQ



TANGO33/0.67M/SMAM/S/S/17 Manufacturers: Siretta

Description: RF ANT 850MHZ/900MHZ WHIP TILT

In stock: 4433 pcs **RFQ**



TANGO43/2.5M/SMAM/SMAM/RP/S/S/17 Manufacturers: Siretta

Description: RF ANT DOME RP-SMA MALE PAN MT In stock: 2365 pcs

RFQ



TANGO40/X/NTYPEF/S/S/32 Manufacturers: Siretta

Description: RF ANT 829MHZ/1.94GHZ WHIP STR N In stock: 1899 pcs

RFQ



TANGO3/3M/SMAM/S/S/31 Manufacturers: Siretta

Description: RF ANT 900MHZ/1.8GHZ WHIP STR

In stock: 3836 pcs **RFQ**



Copyright © 2020 Reliable Distributor of Electronic Components











