

C&K C&K



KSC461G 70SH LFS PF

Part Number: KSC461G 70SH LFS PF

C&K Manufacturer/Brand:

TACT 6.2 X 6.2, 5.1 MM H, 6.25N, Product description KSC461G 70SH LFS PF.pdf Datasheets:

Lead free / RoHS Compliant RoHs Status 341391 pcs stock Stock Condition

Ship From Hong Kong Shipment Way DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

SWITCH TRAVEL SWITCH FUNCTION OFF-Mom SERIES SKC-PF PACKAGING Tape & Reel (TR) OUTLINE OUTLINE OPERATING TEMPERATURE OPERATING FORCE MOUNTING TYPE MOUNTING TYPE MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LILLIMINATION VOLTAGE (NOMINAL) ILLIMINATION TYPE, COLOR LILLIMINATION TYPE, COLOR DETAILIED DESCRIPTION TEATURES DETAILIED DESCRIPTION TO ACTUATOR TYPE STATUS / ROHS STATUS STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LILLIMINATION VOLTAGE (NOMINAL) TEATURES DETAILIED DESCRIPTION TO ACTUATOR TATING @ VOLTAGE TO SHAT WHEN THE SHATUS / ROHS STATUS TO SHATUS SHATUS / ROHS STATUS TO SHATUS SHATUS / ROHS STATUS TO SHATUS SHATUS / ROHS TIGHT, Waterproof THE MUNICATION TYPE, COLOR TO SHATUS SHATUS / ROHS STATUS / ROHS TIGHT, Waterproof THE MUNICATION TYPE, COLOR TO SHATUS SHATUS / ROHS SHATU		
MANUFACTURER C&K DESCRIPTION TACT 6.2 x 6.2 x 5.1 MM H, 6.25N, LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 31391 pcs DATA SHEET □ SC461G 70SH LFS PF.pdf TERMINATION STYLE Gull Wing SWITCH FRUNCTION Off-Morn SWITCH FRUNCTION Off-Morn SERIES KSC-PF PACKAGING Tape & Real (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR OPERATING TEMPERATURE -40°C ~ 85°C OPERATING TEMPERATURE -40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MICHAPITATION TYPE, COLOR 1 ILLUMINATION VOLTAGE (NOMINAL) 1 ILLUMINATION VOLTAGE (NOMINAL) 1 ILLUMINATION TYPE, COLOR 1 ILLUMINATION TYPE, COLOR 1 ILLUMINATION TYPE, COLOR 2 ILLUMINATION TYPE, COLOR 2 ILLUMINATION TYPE, COLOR <th></th> <th>Specifications of KSC461G 70SH LFS PF</th>		Specifications of KSC461G 70SH LFS PF
MANUFACTURER C&K DESCRIPTION TACT 6.2 x 6.2 x 5.1 MM H, 6.25N, LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 31331 pcs DATA SHET □ ISC4616 70SH LFS PP.pdf TERMINATION STYLE Gull Wing SWITCH FUNCTION Off-Mom SWITCH FUNCTION Off-Mom SERIES KSC-PF PACKAGING Taps & Reel (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR OPERATING TEMPERATURE 40PC ~ 85PC OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1067 - Dust Tight, Waterproof ILLUMINATION YOLTAGE (NOMINAL) 1 LILLUMINATION YOLTAGE (NOMINAL) 1 TEMPLATE OF DESCRIPTION ACTUAL SWITCH SPST-NO TOP ACTUALED Surface Mount CONTACT RATING @ VOLTAGE SPST-NO CIRCUIT <td>DADT NUMBER</td> <td>V00464 0 700U 4 F0 PF</td>	DADT NUMBER	V00464 0 700U 4 F0 PF
DESCRIPTION TACT 6,2 x 6,2,5,1 MM H, 6,25N, LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 341391 pcs DATA SHEET ■ SCAGIG 70SH LES PF.pdf TERMINATION STYLE Gull Wing SWITCH FRAVEL 1.00mm SWITCH FRUNCTION OFf-Hom SERIES KSC-PF PACKAGING Tape & Real (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR OPERATING TEMPERATURE 4.00c ~ 8SPC OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION 1967 - Dust Tight, Waterproof ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR - LELUMINATION TYPE, COLOR - DETAILED DESCRIPTION Tactile Swtch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCULT		
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 341391 pcs DATA SHEET ☑ SCC4G16 70SH LFS PF.pdf TERMINATION STYLE Gull Wing SWITCH TRAVEL 1.00mm SWITCH TRAVEL 1.00mm SWITCH FUNCTION Off-Mon SERIES KSC-PP PACKAGING Tape & Red (TR) OUTLINE 6.20mm OTHER NAMES CN11384TR KSC461G 70H LFS PF OPERATING TEMPERATURE 40°C ~ 85°C OPERATING FORCE 63°gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LINGRESS PROTECTION 1P67 - Dust Tight, Waterproof ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR - LILLUMINATION TYPE, COLOR - DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.054 @ 32VDC		
QUANTITY AVAILABLE 341391 pcs DATA SHEET ■ KSC461G 70SH LFS PF.pdf TERMINATION STYLE Gull Wing SWITCH FRAVEL 1.00mm SWITCH FUNCTION Off-Mom SERIES KSC-PF PACKAGING Tape & Reel (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR OPERATING TEMPERATURE 40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LILUMINATION VOLTAGE (NOMINAL) 1- LILUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR - IEATURES - DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05 & @ 32VDC CIRCUIT SPST-NO ACTUATOR ORIENTATION Top Actuated ACTUATOR ORIENTATION Top Actuated		
DATA SHEET EN SC461G 70SH LFS PF,pdf TERMINATION STYLE Gull Wing SWITCH FRAVEL 1.00mm SWITCH FUNCTION OFF-Mom SERIES KSC-PF PACKAGING Tape & Reel (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR OPERATING TEMPERATURE -40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RehS Compliant LILLIMINATION VOLTAGE (MOMINAL) - LILLIMINIATION VYPE, COLOR - LILLIMINIATION TYPE, COLOR - LILLIMINIATION TYPE, COLOR - LEATURES - DETAILED DESCRIPTION Tactle Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCUIT SPST-NO ACTUATOR TYPE Standard ACTUATOR ORIENTATION Top Actuated ACTUATOR MATERIAL<		
TERMINATION STYLE Gull Wing SWITCH TRAVEL 1.00mm SWITCH FUNCTION Off-Mon SERIES KSC-PF PACKAGING Tape & Reel (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CWN11994TR KSC4616 70H LFS PF OPERATING TEMPERATURE 40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MICHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LIAUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - LILLUMINATION TYPE, COLOR - DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCUIT SPST-NO ACTUATOR OXIENTATION Top Actuated ACTUATOR M	QUANTITY AVAILABLE	
SWITCH TRAVEL 1.00mm SWITCH FUNCTION Off-Mom SERIES KSC-PF PACKAGING Tape & Reel (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR KSC/616 TOH LES PF OPERATING TEMPERATURE 40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MECHANICAL LIFE 300,000 cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1P67 - Dust Tight, Waterproof ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VOC CIRCUIT SPST-NO ACTUATOR ORIENTATION Top Actuated ACTUATOR ORIENTATION Top Actuated ACTUATOR RATERIAL Silloon Rubber	DATA SHEET	KSC461G 70SH LFS PF.pdf
SYRIES SERIES SCS-PF PACKACING Tape & Reel (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR KSC46167 OH LES PF OPERATING TEMPERATURE 40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE MOUNTING TYPE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LILUMINATION VOLTAGE (NOMINAL) - LILUMINATION YOLTAGE (NOMINAL) - LILUMINATION TYPE, COLOR - BLILUMINATION TYPE, COLOR - BLILUMINATION OUTAGE (NOMINAL) - CEATURES CEATURES SCRIPTION TACKLES DETAILED DESCRIPTION TACKLES DETAILED DESCRIPTION TACKLES DETAILED DESCRIPTION TACKLES DETAILED ACKLES DETAILED DESCRIPTION TACKLES DETAILED ACKLES DETAILED ACKLES	TERMINATION STYLE	Gull Wing
SERIES KSC-PF Tape & Reel (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11994TR KSC4616 70H LFS PF OPERATING TEMPERATURE 40°C < 85°C OPERATING FORCE MOUNTING TYPE MOUNTING TYPE MOLITINE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS AND	SWITCH TRAVEL	1.00mm
PACKAGING Tape & Reel (TR) OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR KSC461G 70H LPS PF OPERATING TEMPERATURE 40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE SURFACE MOUNT MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1P67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR 1- ILLUMINATION TYPE, COLOR 1- ILLUMINATION TYPE, COLOR 1- ILLUMINATION SURFACE (NOMINAL) 1- ILLUMINATION	SWITCH FUNCTION	Off-Mom
OUTLINE 6.20mm x 6.20mm OTHER NAMES CKN11984TR KSC461G 70H LPS PF OPERATING TEMPERATURE -40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1P67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION Non-Illuminated FEATURES - DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCUIT SPST-NO ACTUATOR TYPE Standard ACTUATOR ORIENTATION Top Actuated ACTUATOR MATERIAL Silicon Rubber	SERIES	KSC-PF
CKN11984TR KSC461G 70H LFS PF OPERATING TEMPERATURE -40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION TYPE, COLOR 1- DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE (NOMINAL) SPST-NO ACTUATOR TYPE Standard Top Actuated Actuator Naterial Actuator Material Silicon Rubber Silicon R	PACKAGING	Tape & Reel (TR)
NOTITIES NAMES OPERATING TEMPERATURE -40°C ~ 85°C OPERATING FORCE 637gf MOUNTING TYPE MOUNTING TYPE MICHANICAL LIFE LEAD FREE STATUS / ROHS STATUS LILLUMINATION VOLTAGE (NOMINAL) 1- LILLUMINATION TYPE, COLOR 1- LILLUMINATION Non-Illuminated FEATURES DETAILED DESCRIPTION Tactile Switch SPST-NO TOP Actuated Surface Mount CONTACT RATING @ VOLTAGE CIRCUIT ACTUATOR TYPE ACTUATOR TYPE ACTUATOR ORIENTATION NON ACTUATOR MATERIAL SILICON RUBBER SILICON RUBBER 1- 1- 1- 1- 1- 1- 1- 1- 1- 1	OUTLINE	6.20mm x 6.20mm
OPERATING FORCE 637gf MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Mon-Illuminated FEATURES - DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCUIT SPST-NO ACTUATOR NYEE STANDA TOP Actuated ACTUATOR ORIENTATION TOP ACTUATED ACTUATOR ORIENTATION TOP ACTUATED SILICON RUBBER STANDA TOP ACTUATED ACTUATOR ORIENTATION TOP ACTUATED SILICON RUBBER STANDA TOP ACTUATED ACTUATOR ORIENTATION TOP ACTUATED SILICON RUBBER STANDA TOP ACTUATED ACTUATOR ORIENTATION TOP ACTUATED SILICON RUBBER STANDA TOP ACTUATED ACTUATOR ORIENTATION TOP ACTUATED SILICON RUBBER STANDA TOP ACTUATED ACTUATOR ORIENTATION SILICON RUBBER STANDA TOP ACTUATED ACTUATOR MATERIAL SILICON RUBBER STANDA TOP ACTUATOR MATERIAL SILICON RUBBER STANDA TOP ACTUATED ACTUATOR MATERIAL SILICON RUBBER STANDA TOP ACTUATOR MATERIAL SIL	OTHER NAMES	
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION YPE, COLOR ILLUMINATION TYPE, COLOR ILLUMINATION MON-Illuminated FEATURES DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE ACTUATOR ORIENTATION ACTUATOR ORIENTATION TOP Actuated ACTUATOR MATERIAL SURGESS PROTECTION 1. (Unlimited) 1. (Lead free / RoHS Compliant 1. (Lead free / RoHS Complia	OPERATING TEMPERATURE	-40°C ~ 85°C
MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) LLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE ACTUATOR RYIPE ACTUATOR RYIENTATION Top Actuated Silicon Rubber	OPERATING FORCE	637gf
MECHANICAL LIFE 300,000 Cycles LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION NON-Illuminated FEATURES - DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE CURCUIT ACTUATOR TYPE Standard ACTUATOR RIENTATION ACTUATOR MATERIAL 300,000 Cycles Lead free / ROHS Compliant Lead free / ROHS Compliant NOH-II Waterproof - 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	MOUNTING TYPE	Surface Mount
LEAD FREE STATUS / ROHS STATUS INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE CIRCUIT ACTUATOR TYPE ACTUATOR ORIENTATION Top Actuated Silicon Rubber	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
INGRESS PROTECTION IP67 - Dust Tight, Waterproof ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION Non-Illuminated FEATURES - DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCUIT SPST-NO ACTUATOR TYPE Standard ACTUATOR ORIENTATION Top Actuated Surface Mount Top Actuated Surface Mount Top Actuated Surface Mount SILICON Rubber	MECHANICAL LIFE	300,000 Cycles
ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE CIRCUIT ACTUATOR TYPE ACTUATOR ORIENTATION TOP ACtuated Silicon Rubber	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES - CACILIED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCUIT SPST-NO ACTUATOR TYPE Standard ACTUATOR ORIENTATION TOP ACTUATED ACTUATOR MATERIAL SIlicon Rubber	INGRESS PROTECTION	IP67 - Dust Tight, Waterproof
ILLUMINATION Non-Illuminated FEATURES - CAUTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCUIT SPST-NO ACTUATOR TYPE Standard ACTUATOR MATERIAL SIlicon Rubber	ILLUMINATION VOLTAGE (NOMINAL)	-
FEATURES DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE CIRCUIT SPST-NO ACTUATOR TYPE ACTUATOR ORIENTATION Top Actuated Silicon Rubber	ILLUMINATION TYPE, COLOR	-
DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Surface Mount CONTACT RATING @ VOLTAGE 0.05A @ 32VDC CIRCUIT SPST-NO ACTUATOR TYPE Standard ACTUATOR ORIENTATION Top Actuated Silicon Rubber	ILLUMINATION	Non-Illuminated
CONTACT RATING @ VOLTAGE 0.05A @ 32VDC SPST-NO ACTUATOR TYPE Standard Top Actuated ACTUATOR MATERIAL Silicon Rubber	FEATURES	-
CIRCUIT SPST-NO ACTUATOR TYPE Standard ACTUATOR ORIENTATION Top Actuated ACTUATOR MATERIAL Silicon Rubber	DETAILED DESCRIPTION	Tactile Switch SPST-NO Top Actuated Surface Mount
ACTUATOR TYPE Standard ACTUATOR ORIENTATION Top Actuated ACTUATOR MATERIAL Silicon Rubber	CONTACT RATING @ VOLTAGE	0.05A @ 32VDC
ACTUATOR ORIENTATION Top Actuated ACTUATOR MATERIAL Silicon Rubber	CIRCUIT	SPST-NO
ACTUATOR MATERIAL Silicon Rubber	ACTUATOR TYPE	Standard
	ACTUATOR ORIENTATION	Top Actuated
	ACTUATOR MATERIAL	Silicon Rubber
ACTUATOR LENGTH, RIGHT ANGLE -	ACTUATOR LENGTH, RIGHT ANGLE	-

Related Tags

5.20mm

C&K KSC461G 70SH LFS PF	KSC461G 70SH LFS PF Distributor	KSC461G 70SH LFS PF Supplier
KSC461G 70SH LFS PF Price	KSC461G 70SH LFS PF Pictures	KSC461G 70SH LFS PF Image
KSC461G 70SH LFS PF PDF Datasheet	KSC461G 70SH LFS PF Download Datasheet	KSC461G 70SH LFS PF Datasheet
KSC461G 70SH LFS PF Stock	Buy KSC461G 70SH LFS PF	Buy C&K KSC461G 70SH LFS PF
C&K KSC461G 70SH LFS PF	C&K Supplier	C&K Distributor
C&K KSC461G 70SH LFS PF	C&K Components KSC461G 70SH LFS PF	

Related Products



KSC463GST1LFG

ACTUATOR HEIGHT OFF PCB, VERTICAL

Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.01A 32V In stock: 214976 pcs

RFQ



KSC442J 70SH LFS PF

Manufacturers: C&K

Description: TACT 6.2 X 6.2, 5.1 MM H, 4.0N, In stock: 166638 pcs

RFQ



KSC443J 70 SH Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.01A 32V In stock: 4075 pcs

RFQ

KSC443J 70SH LFG Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.01A 32V In stock: 225323 pcs

RFQ



KSC461GST1LFS Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.05A 32V In stock: 335726 pcs

RFQ



KSC443G70SHLFG Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.01A 32V In stock: 120886 pcs

RFQ



KSC461JST1LFS Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.05A 32V

In stock: 369716 pcs

RFQ



KSC461JST2LFS Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.05A 32V In stock: 171614 pcs

RFQ



KSC461J 70SH LFS PF Manufacturers: C&K

Description: TACT 6.2 X 6.2, 5.1 MM H, 6.25N, In stock: 165010 pcs

RFQ



KSC442J 70SH LFS Manufacturers: C&K

Description: SWITCH TACTILE SPST-NO 0.05A 32V In stock: 359452 pcs

RFQ

KSC461GST2LFS



KSC442G 70SH LFS PF Manufacturers: C&K

Description: TACT 6.2 X 6.2, 5.1 MM H, 4.0N, In stock: 136266 pcs

RFQ





In stock: 335936 pcs **RFQ**











Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong