
C&K





C&K

Image may be representation. See specifications for product details.

MD00L2NZGD

Part Number:

Manufacturer/Brand:

Product description Datasheets:

RoHs Status Stock Condition

Ship From Shipment Way MD00L2NZGD

C&K

SWITCH ROTARY 6POS 250MA 125V

MD00L2NZGD.pdf

Lead free / RoHS Compliant 7986 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER MANUFACTURER C&K DESCRIPTION SWITCH ROTARY 6POS 250NA 125V LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 7986 pos MD000L2NZED.pdf VOLTAGE RATING - DC 28W VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING PORCE 2.880 ~ 5.041g/m NUMBER OF POLES PER DECK AUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS CONTINUOUS DETAILED DESCRIPTION ROTARY SWITCH 6 POSITION DETAILS LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS		Specifications of MD00L2NZGD
MANUFACTURER C&K DESCRIPTION SWITCH ROTARY 6POS 250MA 125V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 7986 pcs DATA SHEET MD00L2NZCD.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING POSTIONS 6 NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION ROTARY SWIICH 6 POSITION PORT 250MA (AC/DC) 125VAC Panel Mount CURRENT RATING CONTACT HIMING CONTACT HIMING CONTACT HIMING CONTACT HIMING CONTACT FINISH GOId CIRCUIT PER DECK DP6T ANGLE OF THROW 30°		Specifications of ModeleN2db
DESCRIPTION SWITCH ROTARY 6POS 250MA 125V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 7986 pcs DATA SHEET MMDDOL2NZGD.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION ROTARY SWINCH 6 POSITION DP6T 250mA (AC/DC) 125VAC Panel Mount CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL COPPER ABIG CIRCUIT PER DECK DP6T ANGLE OF THROW 30°	PART NUMBER	MD00L2NZGD
LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 7986 pcs DATA SHEET 28 MDDOLLANGED.pdf VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES M PANEL CUTOUT DIMENSIONS Croular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL COPPER Alloy CURRUIT PER DECK DP6T ANGLE OF THROW 30°	MANUFACTURER	C&K
QUANTITY AVAILABLE DATA SHEET WINDOULTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES DETAILED DESCRIPTION ROTAGE AND ROTAGE CURRENT RATING CONTACT TIMING NOn-Shorting (BBM) CONTACT MATERIAL COPPER ALIGN CIRCUIT PER DECK DP6T ANGLE OF THROW 30°	DESCRIPTION	SWITCH ROTARY 6POS 250MA 125V
DATA SHEET VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE SORIES M PANEL CUTOUT DIMENSIONS CIrcular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION ROLATY SWItch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL LIA.86mm CURRENT RATING CONTACT MATERIAL COPPER Alloy CONTACT MATERIAL COPPER Alloy CURCUIT PER DECK DP6T ANGLE OF THROW 30°	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE RATING - DC 28V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Copper Alloy CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW 30°	QUANTITY AVAILABLE	7986 pcs
VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES M PANEL CUTOUT DIMENSIONS Groular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Copper Alloy CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW 30°	DATA SHEET	MD00L2NZGD.pdf
FERMINATION STYLE SORIES M PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POSITIONS 6 NUMBER OF DECKS 1 MOUTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant INDEX STOPS Continuous FEATURES DETAILED DESCRIPTION ROTAT SWItch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount CURRENT RATING CONTACT TIMING NON-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW 30°	VOLTAGE RATING - DC	28V
SERIES M PANEL CUTOUT DIMENSIONS CIrcular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount CURRENT RATING 250mA (AC/DC) CONTACT TIMING NOn-Shorting (BBM) CONTACT MATERIAL COPER DECK DP6T ANGLE OF THROW 30°	VOLTAGE RATING - AC	125V
PANEL CUTOUT DIMENSIONS Circular - 6.60mm Dia OPERATING FORCE 2.880 ~ 5.041gfm NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES	TERMINATION STYLE	Solder Lug
OPERATING FORCE NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION ROTAGY Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL LA86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW 30°	SERIES	М
NUMBER OF POSITIONS 6 NUMBER OF POLES PER DECK 2 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH GOId CIRCUIT PER DECK DP6T ANGLE OF THROW 30°	PANEL CUTOUT DIMENSIONS	Circular - 6.60mm Dia
NUMBER OF POLES PER DECK NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW 30°	OPERATING FORCE	2.880 ~ 5.041gfm
NUMBER OF DECKS MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW 30°	NUMBER OF POSITIONS	6
MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW 30°	NUMBER OF POLES PER DECK	2
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW 1 (Unlimited) Lead free / RoHS Compliant Lead free / RoHS Compliant Andle OF THROW 1 (Unlimited) Lead free / RoHS Compliant Lead free / RoHS Compliant Lead free / RoHS Compliant Continuous Continuous	NUMBER OF DECKS	1
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Copper Alloy CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW 30°	MOUNTING TYPE	Panel Mount
INDEX STOPS Continuous FEATURES - DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW COntinuous Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount COPPORT JUSTIAN (AC/DC) 125VAC PANEL COP	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURES DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount DEPTH BEHIND PANEL 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount COPPER Mount COPPER MOUNT Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount COPPER MOUNT Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount COPPER MOUNT DEPTH BEHIND PANEL 14.86mm Copper Alloy Copper Alloy Copper Alloy Copper Alloy Copper Alloy CIRCUIT PER DECK DP6T	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount 14.86mm CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount 14.86mm Copper Alloy Copper Alloy Copper Alloy 30°	INDEX STOPS	Continuous
DEPTH BEHIND PANEL CURRENT RATING 250mA (AC/DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL COPPER Alloy CONTACT FINISH Gold CIRCUIT PER DECK ANGLE OF THROW 14.86mm 250mA (AC/DC) Non-Shorting (BBM) Copper Alloy Gold DP6T 30°	FEATURES	-
CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL COPPER Alloy CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW 250mA (AC/DC) Non-Shorting (BBM) Copper Alloy Copper Alloy 30°	DETAILED DESCRIPTION	Rotary Switch 6 Position DP6T 250mA (AC/DC) 125VAC Panel Mount
CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW Non-Shorting (BBM) Copper Alloy Sold Oper Alloy ANGLE OF THROW Non-Shorting (BBM) Oper Alloy Sold Oper Alloy	DEPTH BEHIND PANEL	14.86mm
CONTACT MATERIAL CONTACT FINISH Gold CIRCUIT PER DECK DP6T ANGLE OF THROW COPPER Alloy ANGLE OF THROW COPPER Alloy COPPER Alloy Gold DP6T	CURRENT RATING	250mA (AC/DC)
CONTACT FINISH CIRCUIT PER DECK DP6T ANGLE OF THROW 30°	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECK DP6T ANGLE OF THROW 30°	CONTACT MATERIAL	Copper Alloy
ANGLE OF THROW 30°	CONTACT FINISH	Gold
	CIRCUIT PER DECK	DP6T
ACTUATOR TYPE Screwdriver Slot	ANGLE OF THROW	30°
	ACTUATOR TYPE	Screwdriver Slot

Related Tags

Flush

C&K MD00L2NZGD	MD00L2NZGD Distributor	MD00L2NZGD Supplier
MD00L2NZGD Price	MD00L2NZGD Pictures	MD00L2NZGD Image
MD00L2NZGD PDF Datasheet	MD00L2NZGD Download Datasheet	MD00L2NZGD Datasheet
MD00L2NZGD Stock	Buy MD00L2NZGD	Buy C&K MD00L2NZGD
C&K MD00L2NZGD	C&K Supplier	C&K Distributor
C&K MD00L2NZGD	C&K Components MD00L2NZGD	

Related Products



ACTUATOR LENGTH

MD00S1NCGF

Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V In stock: 4568 pcs

RFQ



MD00L3NZGD

Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V In stock: 7696 pcs

RFQ



MD00L1NZGF

Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V In stock: 5508 pcs

RFQ



MD00L3NCGD

Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V In stock: 6400 pcs

RFQ





MD00L2NCGD

Manufacturers: C&K Description: SWITCH ROTARY 6POS 250MA 125V

In stock: 6208 pcs

RFQ



MD00L1NZQF

Manufacturers: C&K Description: SWITCH ROTARY 6POS 250MA 125V

In stock: 5491 pcs

RFQ



MD00S1NZGF Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V

In stock: 3558 pcs

RFQ



MD00L3NCQD Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V

In stock: 7655 pcs

RFQ



MD00L2NCGF Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V In stock: 5212 pcs

RFQ



MD00L1NZQD Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V In stock: 6738 pcs

RFQ



MD00L1NZGD Manufacturers: C&K

Description: SWITCH ROTARY 6POS 250MA 125V In stock: 6499 pcs

RFQ



MD00L3NCQF

Manufacturers: C&K Description: SWITCH ROTARY 6POS 250MA 125V

In stock: 5261 pcs **RFQ**



Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong











