

Image may be representation. See specifications for product details.

G2R-1Z4 AC24

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way G2R-1Z4 AC24

Omron

RELAY GEN PURPOSE SPDT 5A 24V

G2R-1Z4 AC24.pdf

Lead free / RoHS Compliant 9612 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER G2R-124 AC24 MANUFACTURER Omron RELAY GEN PURPOSE SPDT 5A 24V LEAD FREE STATUS / ROHS STATUS LEAD FREE STATU		Specifications of G2R-1Z4 AC24
MANUFACTURER Omron DESCRIPTION RELAY GEN PURPOSE SPDT 5A 24V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 9612 pcs DATA SHEET □ G2R-124 AC24.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERNINATION STYLE PC PIn SWITCHING VOLTAGE 380VAC, 125VDC - Max SERIES GZR RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Tray OTHER NAMES GZR.1Z4AC24 GZR.1Z4AC24 GZR.1Z		
DESCRIPTION RELAY GEN PURPOSE SPDT 5A 24W LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 9612 pcs DATA SHEET □ G2R-124 AC24.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE PC Pin SWITCHING VOLTAGE 380VAC, 125VDC - Max SERIES GER RELEASE TIME 10m General Purpose RELAY TYPE General Purpose PACKAGING Try OTHER NAMES G2R.124AC24 OPERATING TEMPERATURE 40m C ~ 70m C OPERATING TEMPERATURE 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5 CONTACT FORM SPDT (1 Form C) COLIVACE 24VAC COLI TYPE Non Labching COLI TYPE Non Labching <td>PART NUMBER</td> <td>G2R-1Z4 AC24</td>	PART NUMBER	G2R-1Z4 AC24
LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 9612 pcs DATA SHEET 2202-124 AC24.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE 800VAC, 125 VDC - Max SWITCHING VOLTAGE 380VAC, 125 VDC - Max SERLES G2R RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Tray OTHER NAMES G2R.124AC24 OPERATING TEMPERATURE 40°C ~ 70°C OPERATING TEMPERATURE 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5 CONTACT FORM SPDT (1 Form C) COLL VOLTAGE 24VAC COLL VOLTAGE Non Latching COLL VOLTAGE 260 Ohms	MANUFACTURER	Omron
QUANTITY AVAILABLE 9612 pcs DATA SHEET 262R-124 AC24.pdf TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 380VAC, 125VDC - Max SERIES GZR RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Tray OTHER NAMES GZR.124AC24 OPERATING TEMPERATURE 40°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Seeled - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5A CONTACT FORM SPDT (1 Form C) CONTACT FORM SPDT (1 Form C) COLI VOLTAGE 24VAC COLI LYPE Non Latching COLI LYPE So Ohms	DESCRIPTION	RELAY GEN PURPOSE SPDT 5A 24V
TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE 8CP PIN SWITCHING VOLTAGE 380VAC, 125VDC - Max SERIES 62R RELEASE TIME 10ms RELAY TYPE 6eneral Purpose PACKAGING OTHER NAMES OPERATING TEMPERATURE AUPC ~ 70°C OPERATE TIME MOUNTING TYPE 15ms MOUNTING TYPE THOUGH HOle LEAD FREE STATUS / ROHS STATUS Ead free / ROHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coll Through Hole CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT FORM CONTACT FORM CONTACT FORM COLL TYPE NON Latching 1912 VAC COLL TYPE PAC VAC COLL TYPE NON Latching COLL TYPE COLL T	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN ON VOLTAGE (MAX) 19.2 VAC TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE ROPIN SWITCHING VOLTAGE SWITCHING VOLTAGE SWITCHING VOLTAGE 380VAC, 125VDC - Max SERIES SERIES G2R RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Tray OTHER NAMES G2R-1274AC24 G2R.1274AC24 G2R.1274AC24 G2R.1274AC24 G2R.1274AC24 G2R.1274AC24 G2R.1274AC24 C2R.1274AC24 C2R.1274AC2	QUANTITY AVAILABLE	9612 pcs
TURN OFF VOLTAGE (MIN) 7.2 VAC TERMINATION STYLE PC PIN SWITCHING VOLTAGE 380VAC, 125VDC - Max SERLES G2R RELEASE TIME 10ms RELEAY TYPE General Purpose PACKAGING Tray OTHER NAMES G2R-174AC24 G2R1Z4AC24 G2R1Z4AC24 OPERATING TEMPERATURE 40°C ~ 70°C OPERATING TEMPERATURE 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COLL TYPE SO Ohms	DATA SHEET	G2R-1Z4 AC24.pdf
TERMINATION STYLE PC PIN SWITCHING VOLTAGE 380VAC, 125VDC - Max SERLES G2R RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Tray OTHER NAMES G2R-124AC24 G2R124AC24 G2R124AC24 OPERATING TEMPERATURE 40°C ~ 70°C OPERATING TEMPERATURE 15ms MOUNTING TYPE 15ms MOUNTING TYPE 15ms MOUNTING TYPE 5eeled - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5SPDT (1 Form C) CONTACT FORM 5PDT (1 Form C) COLL VOLTAGE 5LAVAC COLL VOLTAGE 5LOWED 50 Mnns SOND 1 SECONDAN ON Latching COLL LESISTANCE 5LOWED 50 Mnns	TURN ON VOLTAGE (MAX)	19.2 VAC
SERIES G2R RELEASE TIME 10ms RELAY TYPE 6eneral Purpose PACKAGING 7ray OTHER NAMES 62R-124AC24 62R124AC24 62R124AC24 OPERATING TEMPERATURE 40°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE 15ms ADEED STATUS / ROHS STATUS 15ms Eaded - Fully DETAILED DESCRIPTION 6eneral Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5M CONTACT PARTING (CURRENT) 5MPT (1 Form C) 24VAC Coil Through Hole CONTACT FORM 5MPT (2 HOW) 5MPT (1 Form C) 24VAC COIL TYPE NON Latching COIL VOLTAGE 260 Ohms	TURN OFF VOLTAGE (MIN)	7.2 VAC
SERIES G2R RELEASE TIME 10ms RELAY TYPE General Purpose PACKAGING Tray OTHER NAMES G2R-1.24AC.24 OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coll Through Hole CONTACT MATERIAL SINGER	TERMINATION STYLE	PC Pin
RELAY TYPE General Purpose PACKAGING Tray OTHER NAMES GZR-1Z4ACZ4 OPERATING TEMPERATURE 40°C ~ 70°C OPERATING TYPE 15ms MOUNTING TYPE 15ms LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Fully DETAILLED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5A CONTACT MATERIAL SILVE AND SPDT (1 Form C) COLI YOLTAGE 24VAC COIL TYPE Non Latching COLI LESISTANCE 56 OHMS	SWITCHING VOLTAGE	380VAC, 125VDC - Max
RELAY TYPE PACKAGING Tray OTHER NAMES G2R-124AC24 G2R1Z4AC24 OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATE TIME MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) SA CONTACT MATERIAL CONTACT FORM SPDT (1 Form C) COLL YOLTAGE COLL TYPE Non Latching COLL SIESISTANCE General Purpose AVAC COLL RESISTANCE General Purpose General Purpose SPDT (1 Form C) AVAC COLL RESISTANCE SOO OPMS COLL SIESISTANCE GENERAL PURPOSE GENERAL PURPOSE TRANS TR	SERIES	G2R
PACKAGING OTHER NAMES OGER-124AC24 G2R1Z4AC24 OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATING OPERATION OPER	RELEASE TIME	10ms
OTHER NAMES G2R-124AC24 G2R124AC24 OPERATING TEMPERATURE -40°C ~ 70°C OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COLL YOLTAGE 24VAC COLL TYPE Non Latching COLL RESISTANCE 260 Ohms	RELAY TYPE	General Purpose
OPERATING TEMPERATURE OPERATE TIME MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) CONTACT FORM SPDT (1 Form C) COIL YOLTAGE COIL TYPE NON LEACHING SEALED SEALED SO OPHING SEALED SEALE	PACKAGING	Tray
OPERATE TIME 15ms MOUNTING TYPE Through Hole LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COLI VOLTAGE 24VAC COIL TYPE Non Latching COONTACT RESISTANCE 15ms	OTHER NAMES	
MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS LEAd free / RoHS Compliant FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) SA CONTACT MATERIAL CONTACT FORM SPDT (1 Form C) COIL VOLTAGE COIL VOLTAGE COIL VOLTAGE COIL VOLTAGE COIL RESISTANCE SHOWS SHOWS SEALED - ROHS Sealed - Fully General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole Sealed - Fully Se	OPERATING TEMPERATURE	-40°C ∼ 70°C
LEAD FREE STATUS / ROHS STATUS FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE COIL VOLTAGE COIL TYPE Non Latching 260 Ohms	OPERATE TIME	15ms
FEATURES Sealed - Fully DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) Silver Alloy CONTACT FORM CONTACT FORM SPDT (1 Form C) COIL VOLTAGE COIL TYPE Non Latching COOL RESISTANCE Sealed - Fully General Purpose Relay SPDT (1 Form C) 24VAC Coil Form C) A COIL TYPE Sealed - Fully Sealed - Full	MOUNTING TYPE	Through Hole
DETAILED DESCRIPTION General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole CONTACT RATING (CURRENT) 5A CONTACT MATERIAL Silver Alloy CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE Seneral Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole SA AND Latching 260 Ohms	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) SA CONTACT MATERIAL Silver Alloy CONTACT FORM COIL VOLTAGE COIL VOLTAGE COIL TYPE Non Latching COIL RESISTANCE	FEATURES	Sealed - Fully
CONTACT MATERIAL CONTACT FORM COIL VOLTAGE COIL TYPE COIL RESISTANCE Silver Alloy SPDT (1 Form C) 24VAC AND Latching 260 Ohms	DETAILED DESCRIPTION	General Purpose Relay SPDT (1 Form C) 24VAC Coil Through Hole
CONTACT FORM SPDT (1 Form C) COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 260 Ohms	CONTACT RATING (CURRENT)	5A
COIL VOLTAGE 24VAC COIL TYPE Non Latching COIL RESISTANCE 260 Ohms	CONTACT MATERIAL	Silver Alloy
COIL TYPE Non Latching COIL RESISTANCE 260 Ohms	CONTACT FORM	SPDT (1 Form C)
COIL RESISTANCE 260 Ohms	COIL VOLTAGE	24VAC
	COIL TYPE	Non Latching
COIL POWER 0.9 VA	COIL RESISTANCE	260 Ohms
	COIL POWER	0.9 VA

Related Tags

37.5mA

Omron G2R-1Z4 AC24	G2R-1Z4 AC24 Distributor	G2R-1Z4 AC24 Supplier
G2R-1Z4 AC24 Price	G2R-1Z4 AC24 Pictures	G2R-1Z4 AC24 Image
G2R-1Z4 AC24 PDF Datasheet	G2R-1Z4 AC24 Download Datasheet	G2R-1Z4 AC24 Datasheet
G2R-1Z4 AC24 Stock	Buy G2R-1Z4 AC24	Buy Omron G2R-1Z4 AC24
Omron G2R-1Z4 AC24	Omron Supplier	Omron Distributor
Omron G2R-1Z4 AC24	Omron Electronics Inc-IA Div G2R-1Z4 AC24	Omron Electronics Inc-EMC Div G2R-1Z4 AC24
Omron Electronics LLC G2R-1Z4 AC24		

Related Products



COIL CURRENT

G2R-1Z4 DC12

Manufacturers: Omron

Description: RELAY GEN PURPOSE SPDT 5A 12V In stock: 12684 pcs

RFQ



G2R-2-AC110

Manufacturers: Omron

Description: RELAY GEN PURPOSE DPDT 5A 110V In stock: 7574 pcs

RFQ



G2R-1B-E AC24

Manufacturers: Omron Description: RELAY GEN PURPOSE SPST 16A 24V

In stock: 11780 pcs

RFQ



G2R-2 DC18

Manufacturers: Omron Description: RELAY GEN PURPOSE DPDT 5A 18V In stock: 14828 pcs

RFQ



G2R-1AZ4-DC24

Manufacturers: Omron Description: RELAY GEN PURPOSE SPST 5A 24V

In stock: 14405 pcs

RFQ



G2R-1S-ASI-DC12

Manufacturers: Omron Description: RELAY GEN PURPOSE SPDT 10A 12V

In stock: 4283 pcs

RFQ



G2R-1Z4 DC24

Manufacturers: Omron Description: RELAY GEN PURPOSE SPDT 5A 24V

In stock: 15685 pcs

RFQ

G2R-2 DC9

Manufacturers: Omron Description: RELAY GENERAL PURPOSE DPDT 5A 9V

In stock: 13894 pcs **RFQ**



Manufacturers: Omron

G2R-1B-EDC12

Description: RELAY GEN PURPOSE SPST 16A 12V In stock: 14013 pcs

RFQ



G2R-1Z-DC12 Manufacturers: Omron

Description: RELAY GEN PURPOSE SPDT 5A 12V In stock: 15302 pcs

RFQ



G2R-1B-E DC24

Description: RELAY GEN PURPOSE SPST 16A 24V In stock: 15086 pcs

Manufacturers: Omron

RFQ



G2R-1Z4-AC120 Manufacturers: Omron

Description: RELAY GEN PURPOSE SPDT 5A 120V In stock: 9513 pcs

RFQ















Copyright © 2020 Reliable Distributor of Electronic Components