



Image may be representation. See specifications for product details.

SI8234AB-D-IM

Part Number:

Manufacturer/Brand: Product description

Datasheets: RoHs Status

Stock Condition

Ship From Shipment Way SI8234AB-D-IM

Energy Micro (Silicon Labs)

DGTL ISO 2.5KV GATE DRIVER 14LGA

SI8234AB-D-IM.pdf

Lead free / RoHS Compliant

DHL/Fedex/TNT/UPS/EMS

34440 pcs stock Hong Kong

REQUEST FOR QUOTATION

PART NUMBER \$18234AB-D-IM MANUFACTURER Energy Micro (Silicon Labs) DESCRIPTION DGTI. ISO 2.5KV GATE DRIVER 14LGA LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 34440 pcs GLEAD FREE SUPPLY OUTAGE - FORWARD (VF) (TYP) - TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (SxS) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PACKAGEN PACKAGEN AUTOMOTIVE, AUTOMO	St	pecifications of SI8234AB-D-IM
MANUFACTURER Energy Micro (Silicon Labs) DESCRIPTION DGTL ISO 2.5KV GATE DRIVER 14LGA LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 34440 pcs DATA SHEET 158234AB-D-IM.pdf VOLTAGE - SUPPLY 6.5 V ~ 24 V VOLTAGE - ISOLATION 2500Vrms VOLTAGE - FORWARD (VF) (TYP) - TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (5x5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PRULSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 SIS234AB-D-IM-ND COPERATING TEMPERATURE 40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 3 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capaciti		Decineations of Sto25 the Diff
DETL ISO 2.5KY GATE DRIVER 14LGA LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE DATA SHEET DATA SHEET DATA SHEET DATA SHEET DATA SHEET VOLTAGE - SUPPLY OLTAGE - SUPPLY OLTAGE - SOLATION Z500Vrms VOLTAGE - FORWARD (VF) (TYP) TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (Sx5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PULSE WIDTH DISTORTION (MAX) S.6ns PROPAGATION DELAY TPLH / TPHL (MAX) FACKAGING Tube PACKAGING TUBE PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 518234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 14 Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (Sx5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	PART NUMBER	SI8234AB-D-IM
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 34440 pcs DATA SHEET □ \$18234AB-D-IM.pdf VOLTAGE - SUPPLY 6.5 V ~ 24 V VOLTAGE - FORWARD (VF) (TYP) - TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (5x5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PULSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGEING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 SIB234AB-D-1M-ND SIB234AB-D-1M-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 3 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500vrms 2 Channel 14-LGA (5x5) CURRENT - OUTPUT HIGH, LOW 2A, 4A	MANUFACTURER	Energy Micro (Silicon Labs)
QUANTITY AVAILABLE 34440 pcs DATA SHEET SI8234AB-D-IM.pdf VOLTAGE - SUPPLY 6.5 V ~ 24 V VOLTAGE - ISOLATION 2500Vms VOLTAGE - FORWARD (VF) (TYP) - TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (5x5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PULSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 S18234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 3 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	DESCRIPTION	DGTL ISO 2.5KV GATE DRIVER 14LGA
DATA SHEET SI8234AB-D-IM.pdf VOLTAGE - SUPPLY 6.5 V ~ 24 V VOLTAGE - ISOLATION 2500Vms VOLTAGE - FORWARD (VF) (TYP) - TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (5x5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PULSE WIDTH DISTORTION (MAX) 5.6ns PACRAGING Tube PACKAGEN / CASE 14-VFLGA OTHER NAMES 336-4688 S18234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOINTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 3 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE - SUPPLY 6.5 V ~ 24 V VOLTAGE - ISOLATION 2500Vrms VOLTAGE - FORWARD (VF) (TYP) - TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (Sx5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PUSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 S18234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTING TSNET SENSITIVITY LEVEL (MSL) 3 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (Sx5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	QUANTITY AVAILABLE	34440 pcs
VOLTAGE - ISOLATION 2500Vrms VOLTAGE - FORWARD (VF) (TYP) - TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (5x5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PULSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGING TUBE AUTOMARES OTHER NAMES 336-4688 518234AB-D-IM-ND OPERATING TEMPERATURE 40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 14 Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	DATA SHEET	SI8234AB-D-IM.pdf
VOLTAGE - FORWARD (VF) (TYP) TECHNOLOGY Capacitive Coupling SUPPLIER DEVICE PACKAGE 14-LGA (5x5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PULSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 \$18234AB-D-IM-ND OPERATING TEMPERATURE 40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 14 Get PROHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT HIGH, LOW 2A, 4A	VOLTAGE - SUPPLY	6.5 V ~ 24 V
TECHNOLOGY SUPPLIER DEVICE PACKAGE 14-LGA (5x5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PUSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 \$18234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 14-GB Hours) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT HIGH, LOW 2A, 4A	VOLTAGE - ISOLATION	2500Vrms
SUPPLIER DEVICE PACKAGE 14-LGA (5x5) SERIES Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PULSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES S18234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 14.68 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - PEAK OUTPUT HIGH, LOW 2A, 4A	VOLTAGE - FORWARD (VF) (TYP)	-
Automotive, AEC-Q100 RISE / FALL TIME (TYP) 12ns, 12ns (Max) PULSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 518234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 3 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	TECHNOLOGY	Capacitive Coupling
RISE / FALL TIME (TYP) PULSE WIDTH DISTORTION (MAX) 5.6ns PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 518234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 14. Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT HIGH, LOW 2A, 4A	SUPPLIER DEVICE PACKAGE	14-LGA (5x5)
PULSE WIDTH DISTORTION (MAX) PROPAGATION DELAY TPLH / TPHL (MAX) 60ns, 60ns Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 \$18234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 14-G8 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	SERIES	Automotive, AEC-Q100
PROPAGATION DELAY TPLH / TPHL (MAX) PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 SI8234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	RISE / FALL TIME (TYP)	12ns, 12ns (Max)
PACKAGING Tube PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 S18234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	PULSE WIDTH DISTORTION (MAX)	5.6ns
PACKAGE / CASE 14-VFLGA OTHER NAMES 336-4688 \$18234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	PROPAGATION DELAY TPLH / TPHL (MAX)	60ns, 60ns
OTHER NAMES 336-4688 \$SI8234AB-D-IM-ND OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) 13 (168 Hours) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	PACKAGING	Tube
OPERATING TEMPERATURE -40°C ~ 125°C NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	PACKAGE / CASE	14-VFLGA
NUMBER OF CHANNELS 2 MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	OTHER NAMES	
MOUNTING TYPE Surface Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	OPERATING TEMPERATURE	-40°C ~ 125°C
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	NUMBER OF CHANNELS	2
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	MOUNTING TYPE	Surface Mount
DETAILED DESCRIPTION 4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5) CURRENT - PEAK OUTPUT CURRENT - OUTPUT HIGH, LOW 2A, 4A	MOISTURE SENSITIVITY LEVEL (MSL)	3 (168 Hours)
CURRENT - PEAK OUTPUT 4A CURRENT - OUTPUT HIGH, LOW 2A, 4A	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CURRENT - OUTPUT HIGH, LOW 2A, 4A	DETAILED DESCRIPTION	4A Gate Driver Capacitive Coupling 2500Vrms 2 Channel 14-LGA (5x5)
	CURRENT - PEAK OUTPUT	4A
COMMON MODE TRANSIENT IMMUNITY (MIN) 20kV/µs	CURRENT - OUTPUT HIGH, LOW	2A, 4A
	COMMON MODE TRANSIENT IMMUNITY (MIN)	20kV/μs

Related Tags

CQC, CSA, UR, VDE

Energy Micro (Silicon Labs) SI8234AB-D-IM	SI8234AB-D-IM Distributor	SI8234AB-D-IM Supplier
SI8234AB-D-IM Price	SI8234AB-D-IM Pictures	SI8234AB-D-IM Image
SI8234AB-D-IM PDF Datasheet	SI8234AB-D-IM Download Datasheet	SI8234AB-D-IM Datasheet
SI8234AB-D-IM Stock	Buy SI8234AB-D-IM	Buy Energy Micro (Silicon Labs) SI8234AB-D-IM
Energy Micro (Silicon Labs) SI8234AB-D-IM	Energy Micro (Silicon Labs) Supplier	Energy Micro (Silicon Labs) Distributor
Energy Micro (Silicon Labs) SI8234AB-D-IM	Energy Micro SI8234AB-D-IM	Energy Micro (Silicon Labs) SI8234AB-D-IM
Silicon Laboratories SI8234AB-D-IM	Silicon Labs SI8234AB-D-IM	

Related Products



APPROVALS

SI8234AB-D-IS1

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV GATE DRVR 16SOIC

In stock: 41085 pcs


RFQ



SI8234AB-C-IS

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV GATE DRVR 16SOIC

In stock: 3673 pcs **RFQ**




SI8234AB-D-IM1R

Manufacturers: Energy Micro (Silicon Labs) Description: ISOLATED GATE DRIVER

In stock: 41041 pcs

RFQ



SI8234AB-C-IM

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV GATE DRIVER 14LGA

In stock: 2705 pcs

RFQ



SI8234AB-D-IS

Manufacturers: Energy Micro (Silicon Labs) Description: DGTL ISO 2.5KV GATE DRVR 16SOIC

In stock: 39640 pcs **RFQ**



SI8234AB-C-IS1 Manufacturers: Energy Micro (Silicon Labs)

Description: DGTL ISO 2.5KV GATE DRVR 16SOIC In stock: 6374 pcs

RFQ



SI8234AB-C-ISR Manufacturers: Energy Micro (Silicon Labs)

Description: DGTL ISO 2.5KV GATE DRVR 16SOIC In stock: 3838 pcs

RFQ




SI8234AB-D-IS1R

Description: DGTL ISO 2.5KV GATE DRVR 16SOIC In stock: 45501 pcs

Manufacturers: Energy Micro (Silicon Labs)

RFQ



SI8234AB-D-IMR Manufacturers: Energy Micro (Silicon Labs)

Description: DGTL ISO 2.5KV GATE DRIVER 14LGA In stock: 48931 pcs

RFQ




SI8234AB-C-IS1R Manufacturers: Energy Micro (Silicon Labs)

Description: DGTL ISO 2.5KV GATE DRVR 16SOIC In stock: 6411 pcs



RFQ



SI8234AB-D-IM1 Manufacturers: Energy Micro (Silicon Labs)

Description: ISOLATED GATE DRIVER In stock: 40759 pcs

RFQ



RFQ

Description: DGTL ISO 2.5KV GATE DRIVER 14LGA In stock: 4241 pcs













