



Image may be representation. See specifications for product details.

#### **ZR431LC02STOB**

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way ZR431LC02STOB

**Diodes Incorporated** 

IC VREF SHUNT ADJ TO92-3

ZR431LC02STOB.pdf

Lead free / RoHS Compliant 6597 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

| PART NUMBER         ZR431LC0ZSTOB           MANUFACTURER         Dodes Incorporated           DESCRIPTION         IC VREF SHUNT AD ITO92-3           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         6597 pc           BATA SHEET         6597 pc           VOLTAGE - OUTPUT (MINIFIXED)         10V           VOLTAGE - INPUT         - 10V           VOLTAGE - INPUT         2-2.5%           TEMPERATURE COEFFICIENT         50ppm/*C           SUPLIER DEVICE PACKAGE         10-92           SERIES         5-but           REFERENCE TYPE         Shunt           PACKAGING         Tape & Red (TR)           PACKAGE (ASS)         10-92-93 (T0-226AN) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING TEMPERATURE         40°C ~ 85°C (TA)           NOISE - 1.0HZ TO 10KHZ         - 40°C ~ 85°C (TA)           NOISE - 1.0HZ TO 10KHZ         1 Through Hole           MOUTTING TYPE         Through Hole           MOUTTING TYPE         Lead free / RoHS Compliant           MOUTTING TYPE         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS <td< th=""><th></th><th>Specifications of ZR431LC02STOB</th></td<>   |                                  | Specifications of ZR431LC02STOB                 |
|--|----------------------------------|---|
| MANUFACTURER         Diodes Incorporated           DESCRIPTION         IC VREF SHUNT ADJ TO92-3           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         6997 pcs           DATA SHEET         □ 2R431LC02STOB.pdf           VOLTAGE - OUTPUT (MIN/FIXED)         1.24V           VOLTAGE - INPUT            TOLERANCE         ±2.5%           TEMPERATURE COEFFICIENT         50ppm/*C           SUPPLIER DEVICE PACKAGE         TO-92           SERIES            PACKAGGING         To-92 -           PACKAGGING         To-92-3 (TO-92-4) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING EMPERATURE         - 0°C ~ 85°C (TA)           NOISE - 10HZ TO 10HZ         - 0°C ~ 85°C (TA)           NOISE - 10HZ TO 10HZ         - 10HZ           MOUNTING TYPE         Through Hole           MOUNTING TYPE         Through Hole           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92           CURRENT - OUTPUT  |                                  |   |
| DESCRIPTION         IC VREF SHUNT ADJ TO92-3           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         5997 pcs           DATA SHEET         278431LC02STOB.pdf           VOLTAGE - OUTPUT (MIN/FIXED)         1.24V           VOLTAGE - OUTPUT (MAX)         10V           VOLTAGE - INPUT   | PART NUMBER                      | ZR431LC02STOB                                   |
| LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           QUANTITY AVAILABLE         6597 pcs           DATA SHEET         248431LC025TOB.pdf           VOLTAGE - OUTPUT (MIN/FIXED)         1.24V           VOLTAGE - OUTPUT (MIN/FIXED)         10V           VOLTAGE - INPUT         -           TOLERANCE         ±2.5%           SUPPLIER DEVICE PACKAGE         50ppm/°C           SUPPLIER DEVICE PACKAGE         TO-92           SERIES         -           REFERENCE TYPE         Shunt           PACKAGING         Tape & Real (TR)           PACKAGE / CASE         TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING TEMPERATURE         -40°C ~ 85°C (TA)           NOISE - 10HZ TO 10KHZ         -           NOISE - 10HZ TO 10KHZ         Through Hole           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92           CURRENT - SUPPLY         25mA           CURRENT - CATHODE         100µA  | MANUFACTURER                     | Diodes Incorporated                             |
| QUANTITY AVAILABLE         6597 pcs           DATA SHEET         2R43LCQSTOB.pdf           VOLTAGE - OUTPUT (MIN/FIXED)         1.24V           VOLTAGE - OUTPUT (MAX)         10V           VOLTAGE - INPUT            TOLERANCE         ±2.5%           TEMPERATURE COEFFICIENT         509pm/°C           SUPPLIER DEVICE PACKAGE         TO-92           SERIES            PACKAGING         Tape & Reel (TR)           PACKAGING         TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING TEMPERATURE         40°C ~ 85°C (TA)           NOISE - 10HZ TO 10KHZ            NOISE - 10HZ TO 10KHZ         Through Hole           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ± 2.5% 25mA TO-92           CURRENT - SUPPLY         25mA           CURRENT - CATHODE         100µA  | DESCRIPTION                      | IC VREF SHUNT ADJ TO92-3                        |
| DATA SHEET         ZR43LLCQSTOB.pdf           VOLTAGE - OUTPUT (MIN/FIXED)         1.24V           VOLTAGE - OUTPUT (MAX)         10V           VOLTAGE - INPUT         -           TOLERANCE         ±2.5%           TEMPERATURE COEFFICIENT         50ppm/°C           SUPPLIER DEVICE PACKAGE         TO-92           SERIES         -           REFERENCE TYPE         Shuth           PACKAGING         To-226-3, TO-92-3 (TO-226AA) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING TEMPERATURE         -40°C ~ 85°C (TA)           NOISE - 10HZ TO 10HZ         -           NOISE - 0.1HZ TO 10HZ         -           MOUNTING TYPE         Through Hole           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compilant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ± 2.5% 25mA TO-92           CURENT - SUPPLY         -           CURENT - CUTPUT         25mA           CURENT - CATHODE         100µA  | LEAD FREE STATUS / ROHS STATUS   | Lead free / RoHS Compliant                      |
| VOLTAGE - OUTPUT (MIN/FIXED)         1.24V           VOLTAGE - OUTPUT (MAX)         10V           VOLTAGE - INPUT         -           TOLERANCE         ±2.5%           TEMPERATURE COEFFICIENT         50ppm/°C           SUPPLIER DEVICE PACKAGE         TO-92           SERIES         -           REFERENCE TYPE         Shunt           PACKAGING         Tape & Reel (TR)           PACKAGE/ CASE         TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING TEMPERATURE         -40°C ~ 85°C (TA)           NOISE - 10HZ TO 10KHZ         -           NOISE - 0.1HZ TO 10HZ         Through Hole           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ± 2.5% 25mA TO-92           CURRENT - SUPPLY         25mA           CURRENT - OUTPUT         25mA  | QUANTITY AVAILABLE               | 6597 pcs  |
| VOLTAGE - INPUT         -           YOLTAGE - INPUT         -           TOLERANCE         \$2.5%           TEMPERATURE COEFFICIENT         50ppm/°C           SUPPLIER DEVICE PACKAGE         TO-92           SERIES         -           REFERENCE TYPE         Shunt           PACKAGING         Tape & Reel (TR)           PACKAGING         TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING TEMPERATURE         -40°C ~ 85°C (TA)           NOISE - 10HZ TO 10KHZ         -           NOISE - 0.1HZ TO 10KHZ         -           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1. (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ± 2.5% 25mA TO-92           CURRENT - OUTPUT         25mA           CURRENT - CATHODE         100µA  | DATA SHEET                       | ZR431LC02STOB.pdf                               |
| VOLTAGE - INPUT         -           TOLERANCE         ±2.5%           TEMPERATURE COEFFICIENT         50ppm/°C           SUPPLIER DEVICE PACKAGE         TO-92           SERIES         -           REFERENCE TYPE         Shunt           PACKAGING         To-226-3, TO-92-3 (TO-226AA) (Formed Leads)           OLIPUT TYPE         Adjustable           OPERATING TEMPERATURE         -40°C ~ 85°C (TA)           NOISE - 10HZ TO 10KHZ         -           MOUNTING TYPE         Through Hole           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92           CURRENT - SUPPLY         25mA           CURRENT - OUTPUT         25mA  | VOLTAGE - OUTPUT (MIN/FIXED)     | 1.24V   |
| TOLERANCE         ±2.5%           TEMPERATURE COEFFICIENT         50ppm/°C           SUPPLIER DEVICE PACKAGE         TO-92           SERIES         -           REFERENCE TYPE         Shunt           PACKAGING         Tape & Reel (TR)           PACKAGE / CASE         TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING TEMPERATURE         40°C ~ 85°C (TA)           NOISE - 10HZ TO 10KHZ         -           NOISE - 0.1HZ TO 10KHZ         Through Hole           MOUNTING TYPE         Through Hole           MOINTING TYPE         Lead free / ROHS Compliant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92           CURRENT - SUPPLY         -           CURRENT - OUTPUT         25mA           CURRENT - OUTPUT         100µA  | VOLTAGE - OUTPUT (MAX)           | 10V   |
| SUPPLIER DEVICE PACKAGE  TO-92  SERIES  REFERENCE TYPE  Shunt  PACKAGING  Tape & Reel (TR)  PACKAGE / CASE  OUTPUT TYPE  Adjustable  OUTPUT TYPE  Adjustable  OPERATING TEMPERATURE  OPERATING TEMPERATURE  NOISE - 10HZ TO 10KHZ  NOISE - 0.1HZ TO 10KHZ  MOUNTING TYPE  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  DETAILED DESCRIPTION  CURRENT - SUPPLY  CURRENT - OUTPUT  CURRENT - OUTPUT  25mA  CURRENT - COUTPUT  SUPPLATED A SOPPORT A STATUS  DOUBLE - 10HZ TO 10KHZ  DETAILED DESCRIPTION  SHUNT VOISE REFERENCE TO 10V ± 2.5% 25mA TO-92  CURRENT - CUTPUT  100,µA  100,µA   | VOLTAGE - INPUT                  | -   |
| SUPPLIER DEVICE PACKAGE         TO-92           SERIES         -           REFERENCE TYPE         Shunt           PACKAGING         Tape & Reel (TR)           PACKAGE / CASE         TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)           OUTPUT TYPE         Adjustable           OPERATING TEMPERATURE         -40°C ~ 85°C (TA)           NOISE - 10HZ TO 10KLZ         -           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           DETAILED DESCRIPTION         Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92           CURRENT - SUPPLY         -           CURRENT - OUTPUT         25mA           CURRENT - CATHODE         100µA   | TOLERANCE                        | ±2.5%   |
| REFERENCE TYPE Shunt PACKAGING Tape & Reel (TR)  PACKAGE / CASE TO-22-6-3, TO-92-3 (TO-226AA) (Formed Leads)  OUTPUT TYPE Adjustable OPERATING TEMPERATURE 40°C ~ 85°C (TA)  NOISE - 1.0HZ TO 1.0HZ - 10HZ  MOUNTING TYPE Through Hole  MOISTURE SENSITIVITY LEVEL (MSL) 1(Ullimited)  LEAD FREE STATUS / ROHS STATUS Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92  CURRENT - 5UPPLY 55mA  CURRENT - OUTPUT (30) 400  LOURENT - OUTPUT (30) 400  Shunt Voltage Neference IC 10V ±2.5% 25mA TO-92  CURRENT - OUTPUT (30) 400  LOUPENT - OUTPUT (30)  | TEMPERATURE COEFFICIENT          | 50ppm/°C  |
| REFERENCE TYPE  PACKAGING  PACKAGING  PACKAGE / CASE  TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)  OUTPUT TYPE  Adjustable  OPERATING TEMPERATURE  AGO°C ~ 85°C (TA)  NOISE - 10HZ TO 10KHZ  NOISE - 0.1HZ TO 10HZ  MOUNTING TYPE  Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  DETAILED DESCRIPTION  DETAILED DESCRIPTION  CURRENT - SUPPLY  CURRENT - SUPPLY  CURRENT - OUTPUT  SHAME  TO 226-3, TO-92-3 (TO-226AA) (Formed Leads)  Adjustable  Adjustable  Adjustable  Adjustable  AGO°C ~ 85°C (TA)  FOR ASS°C (TA)  FOR | SUPPLIER DEVICE PACKAGE          | TO-92   |
| PACKAGING Tape & Reel (TR)  PACKAGE / CASE TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)  OUTPUT TYPE Adjustable  OPERATING TEMPERATURE -40°C ~ 85°C (TA)  NOISE - 10HZ TO 10KHZ -50.1HZ TO 10KHZ -50.1HZ TO 10HZ TO 10H | SERIES                           | -   |
| PACKAGE / CASE  TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)  OUTPUT TYPE  Adjustable  OPERATING TEMPERATURE  A0°C ~ 85°C (TA)  NOISE - 10HZ TO 10KHZ  NOISE - 0.1HZ TO 10KHZ  MOUNTING TYPE  MOUNTING TYPE  Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEad free / ROHS Compliant  DETAILED DESCRIPTION  CURRENT - SUPPLY  CURRENT - OUTPUT  25mA  CURRENT - CATHODE  TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)  Adjustable  Adjustable | REFERENCE TYPE                   | Shunt   |
| OUTPUT TYPE OPERATING TEMPERATURE A0°C ~ 85°C (TA)  NOISE - 10HZ TO 10KHZ NOISE - 0.1HZ TO 10HZ NOISE - 0.1HZ TO 10HZ MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAd FREE STATUS / ROHS STATUS DETAILED DESCRIPTION CURRENT - SUPPLY CURRENT - OUTPUT SEMA CURRENT - OUTPUT OUTPUT Adjustable Adjustable Advec ~ 85°C (TA) Avor ~ 85°C (TA) | PACKAGING                        | Tape & Reel (TR)                                |
| OPERATING TEMPERATURE -40°C ~ 85°C (TA)  NOISE - 10HZ TO 10KHZ  NOISE - 0.1HZ TO 10HZ  MOUNTING TYPE Through Hole  MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant  DETAILED DESCRIPTION Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92  CURRENT - SUPPLY 25mA  CURRENT - OUTPUT 25mA  CURRENT - CATHODE 100µA  | PACKAGE / CASE                   | TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)     |
| NOISE - 10HZ TO 10KHZ NOISE - 0.1HZ TO 10HZ NOISE - 0.1HZ TO 10HZ MOUNTING TYPE Through Hole MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS / ROHS STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS / ROHS STATUS / ROHS STATUS / RO | OUTPUT TYPE                      | Adjustable                                      |
| NOISE - 0.1HZ TO 10HZ  MOUNTING TYPE  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  DETAILED DESCRIPTION  CURRENT - SUPPLY  CURRENT - OUTPUT  CURRENT - OUTPUT  DOUA  100μA   | OPERATING TEMPERATURE            | -40°C ~ 85°C (TA)                               |
| MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS DETAILED DESCRIPTION Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92 CURRENT - SUPPLY CURRENT - OUTPUT 25mA CURRENT - CATHODE 100μA   | NOISE - 10HZ TO 10KHZ            | -   |
| MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  DETAILED DESCRIPTION  Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92  CURRENT - SUPPLY  CURRENT - OUTPUT  25mA  CURRENT - CATHODE   | NOISE - 0.1HZ TO 10HZ            | -   |
| LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantDETAILED DESCRIPTIONShunt Voltage Reference IC 10V ±2.5% 25mA TO-92CURRENT - SUPPLY-CURRENT - OUTPUT25mACURRENT - CATHODE100μA   | MOUNTING TYPE                    | Through Hole                                    |
| DETAILED DESCRIPTION  CURRENT - SUPPLY  CURRENT - OUTPUT  CURRENT - CATHODE  100μA  Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92  - CURRENT - OUTPUT  25mA  100μA   | MOISTURE SENSITIVITY LEVEL (MSL) | 1 (Unlimited)                                   |
| CURRENT - SUPPLY - CURRENT - OUTPUT 25mA  CURRENT - CATHODE 100µA  | LEAD FREE STATUS / ROHS STATUS   | Lead free / RoHS Compliant                      |
| CURRENT - OUTPUT 25mA<br>CURRENT - CATHODE 100μA   | DETAILED DESCRIPTION             | Shunt Voltage Reference IC 10V ±2.5% 25mA TO-92 |
| CURRENT - CATHODE 100μA  | CURRENT - SUPPLY                 | -   |
|  | CURRENT - OUTPUT                 | 25mA  |
| BASE PART NUMBER ZR431   | CURRENT - CATHODE                | 100μΑ   |
|  | BASE PART NUMBER                 | ZR431   |

### **Related Tags**

| Diodes Incorporated ZR431LC02STOB          | ZR431LC02STOB Distributor        | ZR431LC02STOB Supplier                |
|--|----------------------------------|---------------------------------------|
| ZR431LC02STOB Price                        | ZR431LC02STOB Pictures           | ZR431LC02STOB Image                   |
| ZR431LC02STOB PDF Datasheet                | ZR431LC02STOB Download Datasheet | ZR431LC02STOB Datasheet               |
| ZR431LC02STOB Stock                        | Buy ZR431LC02STOB                | Buy Diodes Incorporated ZR431LC02STOB |
| Diodes Incorporated ZR431LC02STOB          | Diodes Incorporated Supplier     | Diodes Incorporated Distributor       |
| Diodes Incorporated ZR431LC02STOB          | Diodes Inc ZR431LC02STOB         | Pericom Semiconductor ZR431LC02STOB   |
| Zetex Semiconductors (Diodes Incorporated) |                                  |                                       |

## **Related Products**

### **ZR431LC02L**

DIODES PERICOM INC.

ZR431LC02STOB

Manufacturers: Diodes Incorporated Description: IC VREF SHUNT ADJ TO92-3

In stock: 3546 pcs

RFQ



### **ZR431LF01TA**

Manufacturers: Diodes Incorporated Description: IC VREF SHUNT ADJ SOT23 In stock: 246174 pcs

**RFQ** 



## ZR431LC01STZ

Manufacturers: Diodes Incorporated Description: IC VREF SHUNT ADJ TO92-3

In stock: 5543 pcs

**RFQ** 



DIODES PERICOM THE

### ZR431LC01

Manufacturers: Diodes Incorporated Description: IC VREF SHUNT ADJ TO92-3

In stock: 98486 pcs

**RFQ** 



#### **ZR431N8TA** Manufacturers: Diodes Incorporated

Description: IC VREF SHUNT ADJ 8SO In stock: 7095 pcs

**RFQ** 



### **ZR431LF01TC**

Manufacturers: Diodes Incorporated Description: IC VREF SHUNT ADJ SOT23 In stock: 5375 pcs

**RFQ** 



#### **ZR431GTA** Manufacturers: Diodes Incorporated

Description: IC VREF SHUNT ADJ SOT223 In stock: 279221 pcs

**RFQ** 



#### ZR431LC01STOB Manufacturers: Diodes Incorporated

Description: IC VREF SHUNT ADJ TO92-3 In stock: 3744 pcs

**RFQ** 





## Manufacturers: Diodes Incorporated

**ZR431LF02TA** 

Description: IC VREF SHUNT ADJ SOT23-3 In stock: 129987 pcs

**RFQ** 



In stock: 6694 pcs

**RFQ** 



E-mail: Info@infinity-electronic.com

## ZR431LC02STZ

Description: IC VREF SHUNT ADJ TO92-3 In stock: 4417 pcs

Manufacturers: Diodes Incorporated

**RFQ** 



# ZR431LF02TC

In stock: 6941 pcs

Manufacturers: Diodes Incorporated Description: IC VREF SHUNT ADJ SOT23

**RFQ** 














**Copyright © 2020 Reliable Distributor of Electronic Components**