



Image may be representation. See specifications for product details.

82-4151.1214

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way 82-4151.1214

EAO

82-4151.1214.ILLUMINATED PUSHBUT

82-4151.1214.pdf

Lead free / RoHS Compliant 4919 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER 82-4151.1214 MANUFACTURER EAO DESCRIPTION 82-4151.1214.ILLUMINATED PUSHBUT LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 4919 pcs ADATA SHEET WOLTAGE RATING - DC VOLTAGE RATING - DC VOLTAGE RATING - AC 240V VOLTAGE RATING - AC 240V TYPE Slandard, Illuminated Selder, Qulck Connect - 0.110* (2.8mm) On-Mom SERIES 82 PANEL CUTOUT DIMENSIONS Groular - 16.00mm Dia Bulk OTHER NAMES 82-4151.1214-ND OPERATING THE FRATURE ADAR - 270C MOUNTING TYPE Panel Mount, Front MICHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS LEA		Specifications of 82-4151.1214	
MANUFACTURER BEAO BESCRIPTION B2-4151.1214.ILLUMINATED PUSHBUT LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 4919 pcs DATA SHEET 240V VOLTAGE RATING - DC 240V VOLTAGE RATING - AC 240V TYPE Standard, Illuminated TERMINATION STYLE Solder, Quick Connect - 0.110° (2.8mm) On-Mon SERIES 82 PARCE QUIC DIMENSIONS Circular - 16.00mm Dia PARCE AGING BUIK OTHER NAMES 3948-2215 82-4151.1214-ND OPERATING TYPE MOUNTING TYPE ADONO Cycles LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS			
DESCRIPTION 82-4151.1214.ILLUMINATED PUSHBUT LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 4919 pcs DATA SHEET 28-4151.1214.pdf VOLTAGE RATING - DC 240V VOLTAGE RATING - AC 240V TYPE Standard, Illuminated SWITCH FUNCTION On-Mon SERIES 82 PAREL CUTOUT DIMENSIONS Gircular - 16.00mm Dia PACKAGING Bulk OTHER NAMES 1948-2215 MOUNTING TYPE Panel Mount, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LIRON FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LILUMINATION VOLTAGE (NOMINAL) 24 VAC/DC ILLUMINATION TYPE, COLOR LED, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 34 (AC/DC)	PART NUMBER	82-4151.1214	
Lead free f NoHS Compliant QUANTITY AVAILABLE 4919 pcs DATA SHEET Col 82-4151.1214.pdf VOLTAGE RATING - DC 240V VOLTAGE RATING - AC 240V TYPE Standard, Illuminated TERMINATION STYLE Solder, Quick Connect - 0.110" (2.8mm) SWITCH FUNCTION On-Mom SERIES 82 PANEL CUTOUT DIMENSIONS Circular - 16.00mm Dia PACKAGING Bulk OTHER NAMES 1948-2215 82-2151.1214-ND OPERATING TEMPERATURE 30°C ~ 70°C MOUNTING TYPE PANEL STATUS / ROHS STATUS LEAD FREE STATUS / ROHS CONNEL LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS	MANUFACTURER	EAO	
QUANTITY AVAILABLE 4919 pcs DATA SHEET 240V VOLTAGE RATING - DC 240V VOLTAGE RATING - AC 240V TYPE Standard, Illuminated TERMINATION STYLE Solder, Quick Connect - 0.110" (2.8mm) SWITCH FUNCTION On-Mom SERIES 82 PANEL CUTOUT DIMENSIONS Gircular - 16.00mm Dia PACKAGING Bulk OTHER NAMES 82-4151.1214-ND OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount, Front MECHANICAL LIFE 1,000.000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant LINGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION YUFE, COLOR LED, Red FEATURES Stainless Steel ELECTICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	DESCRIPTION	82-4151.1214.ILLUMINATED PUSHBUT	
DATA SHEET \$\text{inition} 82-4151.1214.pdf \text{voltage Rating - DC} \text{voltage Rating - AC} \text{voltage Rating - AC} \text{voltage Rating - AC} \text{standard, Illuminated} \text{Standard, Illuminated Panel Mount, Front} \text{Indextandard, Illuminated Panel Mount, Front} Indextandard, Illuminated Pa	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
VOLTAGE RATING - DC 240V VOLTAGE RATING - AC 240V TYPE Standard, Illuminated TERMINATION STYLE Solder, Quick Connect - 0.110" (2.8mm) On-Mom SERIES 82 PANEL CUTOUT DIMENSIONS Circular - 16.00mm Dia Bulk OTHER NAMES Bulk OTHER NAMES 1948-215 82-4151.1214-ND OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LILUMINATION VOLTAGE (NOMINAL) 124 VAC/DC LILUMINATION TYPE, COLOR EET, RATINS Stanliess Steel ELECTRICAL LIFE 50,000 Cycles LECTRICAL LIFE 50,000 Cycles Stainless Steel ELECTRICAL LIFE 50,000 Cycles Stainless Steel Stainless Steel Stainless Steel DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATINS 34 (AC/DC)	QUANTITY AVAILABLE	4919 pcs	
TYPE Standard, Illuminated TERMINATION STYLE Solder, Quick Connect - 0.110" (2.8mm) SWITCH FUNCTION On-Mom SERIES 82 PANEL CUTOUT DIMENSIONS Circular - 16.00mm Dia BUIK OTHER NAMES 1948-2215 82-4151.1214-ND OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant LINGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof LILLUMINATION VOLTAGE (NOMINAL) 24 VAC/DC LILLUMINATION TYPE, COLOR LED, Red FEATURES STATUS Standard, Illuminated Panel Mount, Front LED, Red SOURCE STEEL STANDS STANDS LED, Red CERENT RATING SWITCH STANDARD SWITCH SWITC	DATA SHEET	82-4151.1214.pdf	
TYPE Standard, Illuminated TERMINATION STYLE Solder, Quick Connect - 0.110" (2.8mm) SWITCH FUNCTION On-Mom SERIES 82 PANEL CUTOUT DIMENSIONS Circular - 16.00mm Dia PACKAGING BUIK OTHER NAMES 1948-2215 82-4151.1214-ND OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE PANEL MOUNT, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION VOLTAGE (NOMINAL) 24 VAC/DC ILLUMINATION TYPE, COLOR LED, Red FEATURES STATUS Stales Steel ELECTRICAL LIFE 50,000 Cycles LECTRICAL LIFE 50,000 Cycles PUSHOULTH SWITCH SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	VOLTAGE RATING - DC	240V	
Solder, Quick Connect - 0.110" (2.8mm) SWITCH FUNCTION On-Mom On-Mom SERIES 82 PANEL CUTOUT DIMENSIONS Circular - 16.00mm Dia Bulk OTHER NAMES OTHER NAMES OPERATING TEMPERATURE A30°C ~ 70°C MOUNTING TYPE Panel Mount, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS LEAD FREE STA	VOLTAGE RATING - AC	240V	
SWITCH FUNCTION On-Mom SERIES 82 PANEL CUTOUT DIMENSIONS Circular - 16.00mm Dia PACKAGING Bulk OTHER NAMES 1948-2215 82-4151.1214-ND OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE PANEL MOUNT, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION VOLTAGE (NOMINAL) 24 VAC/DC ILLUMINATION TYPE, COLOR FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	TYPE	Standard, Illuminated	
SERIES PANEL CUTOUT DIMENSIONS Circular - 16.00mm Dia Bulk OTHER NAMES OTHER NAMES OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) LEU, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles LECTRICAL LIFE 50,000 Cycles LECTRICAL LIFE 50,000 Cycles LED, Red DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front A (AC/DC)	TERMINATION STYLE	Solder, Quick Connect - 0.110" (2.8mm)	
PANEL CUTOUT DIMENSIONS Circular - 16.00mm Dia Bulk OTHER NAMES OTHER NAMES OTHER NAMES OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE MECHANICAL LIFE MECHANICAL LIFE MECHANICAL LIFE LEAD FREE STATUS / ROHS STATUS LEED REGE STATUS / ROHS S	SWITCH FUNCTION	On-Mom	
PACKAGING DITHER NAMES DITHER NAMES DEFRATING TEMPERATURE DESCRIPTION DEFRATING TEMPERATURE DESCRIPTION DEFRATION DEFRATIO	SERIES	82	
1948-2215 82-4151.1214-ND OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION 1P65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION VOLTAGE (NOMINAL) 24 VAC/DC ILLUMINATION TYPE, COLOR ILLUMINATION TYPE, COLOR Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	PANEL CUTOUT DIMENSIONS	Circular - 16.00mm Dia	
82-4151.1214-ND OPERATING TEMPERATURE -30°C ~ 70°C MOUNTING TYPE Panel Mount, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION VOLTAGE (NOMINAL) LED, Red LED, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	PACKAGING	Bulk	
MOUNTING TYPE Panel Mount, Front MECHANICAL LIFE 1,000,000 Cycles LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION VOLTAGE (NOMINAL) 24 VAC/DC ILLUMINATION TYPE, COLOR LED, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	OTHER NAMES		
MECHANICAL LIFE 1,000,000 Cycles Lead free / RoHS Compliant INGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION VOLTAGE (NOMINAL) LED, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	OPERATING TEMPERATURE	-30°C ~ 70°C	
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION VOLTAGE (NOMINAL) LED, Red LED, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	MOUNTING TYPE	Panel Mount, Front	
INGRESS PROTECTION IP65/67 - Dust Tight, Water Resistant, Waterproof ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILED, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	MECHANICAL LIFE	1,000,000 Cycles	
ILLUMINATION VOLTAGE (NOMINAL) 24 VAC/DC ILLUMINATION TYPE, COLOR LED, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant	
LED, Red FEATURES Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	INGRESS PROTECTION	IP65/67 - Dust Tight, Water Resistant, Waterproof	
Stainless Steel ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	ILLUMINATION VOLTAGE (NOMINAL)	24 VAC/DC	
DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	ILLUMINATION TYPE, COLOR	LED, Red	
DETAILED DESCRIPTION Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front CURRENT RATING 3A (AC/DC)	FEATURES	Stainless Steel	
CURRENT RATING 3A (AC/DC)	ELECTRICAL LIFE	50,000 Cycles	
	DETAILED DESCRIPTION	Pushbutton Switch SPDT Standard, Illuminated Panel Mount, Front	
COLOR - ACTUATOR/CAP Silver	CURRENT RATING	3A (AC/DC)	
	COLOR - ACTUATOR/CAP	Silver	

Related Tags

SPDT

Round, Button, Flush

EAO 82-4151.1214	82-4151.1214 Distributor	82-4151.1214 Supplier
82-4151.1214 Price	82-4151.1214 Pictures	82-4151.1214 Image
82-4151.1214 PDF Datasheet	82-4151.1214 Download Datasheet	82-4151.1214 Datasheet
82-4151.1214 Stock	Buy 82-4151.1214	Buy EAO 82-4151.1214
EAO 82-4151.1214	EAO Supplier	EAO Distributor
EAO 82-4151.1214		

Related Products



CIRCUIT

ACTUATOR TYPE

82-4151.1223 Manufacturers: EAO

Description: 82-4151.1223.ILLUMINATED PUSHBUT

In stock: 5519 pcs

RFQ



82-4151.1243 Manufacturers: EAO

Description: 82-4151.1243.ILLUMINATED PUSHBUT In stock: 5291 pcs

RFQ



82-4151.1244

Manufacturers: EAO Description: 82-4151.1244.ILLUMINATED PUSHBUT

In stock: 5808 pcs

RFQ



82-4151.1144

Manufacturers: EAO

Description: 82-4151.1144.ILLUMINATED PUSHBUT In stock: 5253 pcs

RFQ



82-4151.1234 Manufacturers: EAO

Description: 82-4151.1234.ILLUMINATED PUSHBUT

In stock: 6291 pcs

RFQ



82-4151.1143 Manufacturers: EAO

Description: 82-4151.1143.ILLUMINATED PUSHBUT

In stock: 6497 pcs

RFQ



Manufacturers: EAO Description: 82-4151.1153.ILLUMINATED PUSHBUT

82-4151.1153

In stock: 6359 pcs

RFQ



82-4151.1134 Manufacturers: EAO

Description: 82-4151.1134.ILLUMINATED PUSHBUT In stock: 5432 pcs

RFQ



Manufacturers: EAO

82-4151.11A4

Description: 82-4151.11A4.ILLUMINATED PUSHBUT In stock: 4499 pcs

RFQ



Manufacturers: EAO Description: 82-4151.1233.ILLUMINATED PUSHBUT

82-4151.1233

In stock: 5707 pcs **RFQ**



82-4151.1154

Manufacturers: EAO Description: 82-4151.1154.ILLUMINATED PUSHBUT

In stock: 6076 pcs **RFQ**



82-4151.1254

Manufacturers: EAO

In stock: 4854 pcs **RFQ**

Description: 82-4151.1254.ILLUMINATED PUSHBUT













Copyright © 2020 Reliable Distributor of Electronic Components