

Honeywell **Honeywell Sensing and Productivity Solutions**

Image may be representation. See specifications for product details.

ASDX100A24R

Part Number:

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way ASDX100A24R

Honeywell Sensing and Productivity Solutions

SENSOR AMP 100PSI ABS .5-4.5 OUT

Lead free / RoHS Compliant

ASDX100A24R.pdf

3079 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

PART NUMBER ASDX100A24R MANUFACTURER Honeywell Sensing and Productivity Solutions DESCRIPTION SENSOR AMP 100PS1 ABS .5-4.5 OUT LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compiliant QUANTITY AVAILABLE 3079 pcs DATA SHEET VOLTAGE - SUPPLY 4.75 V ~ 5.25 V TERMINATION STYLE PCB SUPPLIER DEVICE PACKAGE - SERIES ASDX PRESSURE TYPE Absolute PORT STYLE Barbless PACKAGE / CASE OUTPUT TYPE Analog Voltage OUTPUT TYPE Analog Voltage OUTPUT TYPE Analog Voltage OUTPUT TYPE Analog Voltage OUTPUT TYPE OPERATING FRESSURE 100 PST (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 150 PST (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compiliant FEATURES AMPlified Output, Temperature Compensated DETAILED DESCRIPTION Module ACCURACY ± 296 DETAILED DESCRIPTION PORT STATUS / ROHS STATUS PRESSURE SENSITIVITY LEVEL (MSL) PRESSURE S		Specifications of ASDX100A24R
MANUFACTURER Honeywell Sensing and Productivity Solutions DESCRIPTION SENSOR AMP 100PSI ABS. 5-4.5 OUT LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 3079 pcs DATA SHEET ASDX100A24R.pdf VOLTAGE - SUPPLY 4.75 V ~ 5.25 V TERMINATION STYLE PCB SUPPLIER DEVICE PACKAGE SERIES ASDX PRESSURE TYPE Absolute PORT STYLE Barbless PORT STYLE Male - 0.09" (2.29mm) Tube PACKAGE / CASE OUTPUT TYPE Analog Voltage OUTPUT 1.57 V ~ 4.5 V OTHER NAMES 287-1917-ND 480-1917 OPERATING PRESSURE MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module DETAILLED DESCRIPTION		Specifications of ASDA100A2 IIC
DESCRIPTION SENSOR AMP 100PSI ABS .5-4.5 OUT LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant QUANTITY AVAILABLE 3079 pcs DATA SHEET IEM ASDX100A24R.pdf VOLTAGE - SUPPLY 4.75 V ~ 5.25 V TERMINATION STYLE PCB SUPPLIER DEVICE PACKAGE - SERIES ASDX PRESSURE TYPE Absolute PORT SIYLE Barbless PORT SIZE Male ~ 0.09" (2.29mm) Tube PACKAGE / CASE 8-DIP Module OUTPUT TYPE Analog Voltage OUTPUT 0.5 V ~ 4.5 V OTHER NAMES 287-1917 NO 480-1917 OPERATING TEMPERATURE -20°C ~ 105°C OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm)	PART NUMBER	ASDX100A24R
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant QUANTITY AVAILABLE 3079 pcs DATA SHEET ☑ ASDX100A24R.pdf VOLTAGE - SUPPLY 4.75 V ~ 5.25 V TERMINATION STYLE PCB SUPPLIER DEVICE PACKAGE - SERIES ASDX PRESSURE TYPE Absolute PORT STYLE Barbless PORT SIZE Male ~ 0.09" (2.29mm) Tube PACKAGE / CASE 8-DIP Module OUTPUT TYPE Analog Voltage OUTPUT 0.5 V ~ 4.5 V OTHER NAMES 287-1917 ND 480-1917 287-1917-ND 480-1917 290° C ~ 105°C OPERATING TEMPERATURE -20° C ~ 105°C OPERATING TEMPERATURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	MANUFACTURER	Honeywell Sensing and Productivity Solutions
QUANTITY AVAILABLE DATA SHEET DATA SADXIOA24R.pdf 4.75 V ~ 5.25 V TERMINATION STYLE PCB SUPPLIER DEVICE PACKAGE	DESCRIPTION	SENSOR AMP 100PSI ABS .5-4.5 OUT
DATA SHEET DOTATA STATUS DETAILED DESCRIPTION ASDX A.75 V ~ 5,25 V PCB B.75 V ~ 5,25 V A.75 V ~ 4,5 V A.75 V ~ 4,5 V DIT TYPE A.75 V ~ 4,5 V A.75 V ~ 4,5 V ~ 4,5 V ~ 4,5 V A.75 V ~ 4,5 V	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
VOLTAGE - SUPPLY 4.75 V ~ 5.25 V TERMINATION STYLE PCB SUPPLIER DEVICE PACKAGE - SERIES ASDX PRESSURE TYPE Absolute PORT STYLE Barbless PORT SIZE Male - 0.09" (2.29mm) Tube PACKAGE / CASE 8-DIP Module OUTPUT TYPE Analog Voltage OUTPUT 0.5 V ~ 4.5 V OTHER NAMES 287-1917 287-1917-ND 480-1917 OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	QUANTITY AVAILABLE	3079 pcs
FERMINATION STYLE SUPPLIER DEVICE PACKAGE SUPPLIER DEVICE PACKAGE SERIES ASDX RESSURE TYPE Absolute Barbless BORT STYLE Barbless PORT SIZE Male - 0.09" (2.29mm) Tube PACKAGE / CASE OUTPUT TYPE Analog Voltage OUTPUT OTHER NAMES 287-1917 287-1917-ND 480-1917 287-1917-ND 480-1917 OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATING PRESSURE MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION	DATA SHEET	ASDX100A24R.pdf
SUPPLIER DEVICE PACKAGE SERIES ASDX PRESSURE TYPE Absolute PORT STYLE Barbless Male - 0.09" (2.29mm) Tube PACKAGE / CASE OUTPUT TYPE Analog Voltage OUTPUT OTHER NAMES 287-1917 287-1917-AD 480-1917 287-1917-AD 480-1917 OPERATING TEMPERATURE OPERATING PRESSURE MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION	VOLTAGE - SUPPLY	4.75 V ~ 5.25 V
ASDX PRESSURE TYPE Absolute PORT STYLE Barbless PORT SIZE Male - 0.09" (2.29mm) Tube PACKAGE / CASE B-DIP Module OUTPUT TYPE Analog Voltage OUTPUT OTHER NAMES ASB7-1917-ND 480-1917 OPERATING TEMPERATURE OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES DETAILED DESCRIPTION PRESSURE SIND I TUBE (89.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	TERMINATION STYLE	PCB
PRESSURE TYPE Absolute PORT STYLE Barbless PORT SIZE Male - 0.09" (2.29mm) Tube PACKAGE / CASE 8-DIP Module OUTPUT TYPE Analog Voltage OUTPUT O1.5 V ~ 4.5 V OTHER NAMES 287-1917-ND 480-1917 OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS LEad free / ROHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION PROSED Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	SUPPLIER DEVICE PACKAGE	-
PORT STYLE PORT SIZE Male - 0.09" (2.29mm) Tube PACKAGE / CASE 8-DIP Module OUTPUT TYPE Analog Voltage OUTPUT OTHER NAMES 287-1917 287-1917-ND 480-1917 OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 100 PSI (689.48 kPa) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS PRESSURE Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	SERIES	ASDX
PORT SIZE Male - 0.09" (2.29mm) Tube PACKAGE / CASE 8-DIP Module OUTPUT TYPE Analog Voltage OUTPUT O.5 V ~ 4.5 V OTHER NAMES 287-1917 287-1917-ND 480-1917 OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Module	PRESSURE TYPE	Absolute
PACKAGE / CASE 8-DIP Module OUTPUT TYPE Analog Voltage OUTPUT 0.5 V ~ 4.5 V OTHER NAMES 287-1917 287-1917-ND 480-1917 OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	PORT STYLE	Barbless
OUTPUT TYPE OLTPUT O	PORT SIZE	Male - 0.09" (2.29mm) Tube
OUTPUT O.5 V ~ 4.5 V 287-1917 287-1917-ND 480-1917 OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES DETAILED DESCRIPTION O.5 V ~ 4.5 V 8-DIP Module	PACKAGE / CASE	8-DIP Module
287-1917 - ND 287-1917 - ND 480-1917 OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	OUTPUT TYPE	Analog Voltage
OPERATING TEMPERATURE -20°C ~ 105°C OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	OUTPUT	0.5 V ~ 4.5 V
OPERATING PRESSURE 100 PSI (689.48 kPa) MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	OTHER NAMES	287-1917-ND
MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) MAXIMUM PRESSURE 150 PSI (1034.21 kPa) Lead free / RoHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	OPERATING TEMPERATURE	-20°C ~ 105°C
MAXIMUM PRESSURE 150 PSI (1034.21 kPa) Lead free / RoHS Compliant FEATURES Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	OPERATING PRESSURE	100 PSI (689.48 kPa)
LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant Amplified Output, Temperature Compensated DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
Amplified Output, Temperature Compensated DETAILED DESCRIPTION Amplified Output, Temperature Compensated Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	MAXIMUM PRESSURE	150 PSI (1034.21 kPa)
DETAILED DESCRIPTION Pressure Sensor 100 PSI (689.48 kPa) Absolute Male - 0.09" (2.29mm) Tube 0.5 V ~ 4.5 V 8-DIP Module	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
Module Module	FEATURES	Amplified Output, Temperature Compensated
ACCURACY ±2%	DETAILED DESCRIPTION	
	ACCURACY	±2%

Related Tags

Honeywell Sensing and Productivity Solutions ASDX100A24R	ASDX100A24R Distributor	ASDX100A24R Supplier
ASDX100A24R Price	ASDX100A24R Pictures	ASDX100A24R Image
ASDX100A24R PDF Datasheet	ASDX100A24R Download Datasheet	ASDX100A24R Datasheet
ASDX100A24R Stock	Buy ASDX100A24R	Buy Honeywell Sensing and Productivity Solutions ASDX100A24R
Honeywell Sensing and Productivity Solutions ASDX100A24R	Honeywell Sensing and Productivity Solutions Supplier	Honeywell Sensing and Productivity Solutions Distributor
Honeywell Sensing and Productivity Solutions ASDX100A24R	HONEYWELL ASDX100A24R	Honeywell Sensing and Control EMEA ASDX100A24R
Honeywell Sensing and Productivity Solutions T&M ASDX100A24R		

Related Products



ASDX100D44R Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR AMP 100PSI DIF .5-4.5 OUT In stock: 3760 pcs

RFQ



ASDXACX015PA7A5 Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR 15 PSI ABS I2C 5V In stock: 1735 pcs

RFQ



ASDX030D44R-DO

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR PRESS 30PSI DIGITAL

In stock: 3892 pcs

RFQ



Honeywell

ASDX100G24R-D0

Description: SENSOR PRESS 100PSIG DIGITAL In stock: 2979 pcs

Manufacturers: Honeywell Sensing and Productivity Solutions

RFQ

Honeywell



ASDX030D44D Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR PRESS 30PSI ANALOG

In stock: 4936 pcs

RFQ



ASDX030G24R-DO

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR PRESS 30PSIG DIGITAL In stock: 5614 pcs

RFQ



ASDX100A24R-DO Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR PRESS 100PSIA DIGITAL In stock: 6599 pcs

RFQ



ASDX030D44R Manufacturers: Honeywell Sensing and Productivity Solutions

In stock: 6567 pcs

Description: SENSOR AMP 30PSI DIFF .5-4.5 OUT

RFQ

Honeywell

ASDX030A24R-DO Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR PRESS 30PSIA DIGITAL In stock: 5397 pcs

RFQ



ASDX030G24R Manufacturers: Honeywell Sensing and Productivity Solutions

Description: SENSOR AMP 30PSI GAUG .5-4.5 OUT In stock: 4073 pcs

RFQ



ASDXACX015PAAA5

Manufacturers: Honeywell Sensing and Productivity Solutions Description: SENSOR 15 PSI ABS 5V


In stock: 1501 pcs **RFQ**




ASDX100G24R

In stock: 5050 pcs

Description: SENSOR AMP 100PSI GAU .5-4.5 OUT







Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong











